



« - »

, 140091, . ,

, .30

/ . +7 (495) 632 0217

www.keb.ru

F5A

(V4.0)





« - »

, 140091, .
, .30

/ . +7 (495) 632 0217

www.keb.ru

,
COMBIVIS. F5M
V4.0 F5

()

(,)

dr.17
.11).

(.

3:1.

:

1.
2. 2. ST
()
3 3
3. 1- 2 (/
(), 1- 2 -
/ ()

dOH -
4.
5.





6. Проверить значение параметра ud02. В данном параметре необходимо установить значение, соответствующее режиму работы: F5M/4000об/мин (или F5M/8000об/мин) - в зависимости от максимальной скорости привода.

7.

Fr01 = -4

8.

9.

10.

cs00=4

11.

dr00 –
dr01 –
dr02 –
dr03 –
dr04 – cos
dr05 –

12.

ds04=249

13.

Fr10=2

14.

15.

dr49=5-20

i

Cs09=100-5

16.

ds02=1

17.

”:

uf18=3





« - »
 , 140091, .
 , .30
 / . +7 (495) 632 0217
www.keb.ru

18. uf15=0

19. :
 dr48=8

20. ST.

(dr17).

dr48/dr62

5 ,

ru00

dr00.
 "82"

(“

ru00
 ”),

”).
 “127” (“

ST.

21.

22.

cs25/cs26.





« - »

, 140091, . ,
, .30

/ . +7 (495) 632 0217

www.keb.ru

