

SIL2
Functional Safety
PLd

SIL3
Functional Safety
PLe

- Encoders for Functional Safety
- Safety Modules
- Safety Services
- Connection Technology
- Accessories

Our Pulses for Innovations



The Kübler Group belongs today to the leading specialists worldwide in the fields of position and motion sensors, functional safety, counting and process technology and transmission technology.

Founded in the year 1960 by Fritz Kübler, the family business is now led by the next generation of Gebhard and Lothar Kübler.

Nine international group members and distributors in more than 50 countries offer local product know-how, service and advice throughout the world.

Innovative product and sector solutions, as well as solutions for functional safety and a high level of service, are the reasons behind our global success.

The strict focus on quality ensures the highest levels of reliability and a long service life for our products in the field.

Over 400 dedicated people worldwide make this success possible and ensure that customers can continue to place their trust in our company.



Kübler Service for worldwide Planning Reliability



Sample and Repair Service

We manufacture samples of special designs or according to customer specification within shortest time. We carry out repair work reliably within a maximum of 5 days.



10 by 10

We will manufacture and deliver 10 encoders within 10 working days (365 days a year - with the exception of 24th Dec. until 2nd Jan.)



Kübler online – www.kuebler.com

- Up-to-date product and company information
- Product finder – the selection tool that helps you finding quickly the suitable product
- Download service for CAD data, software, operating instructions, certificates and catalogues
- You will find comprehensive information about the basic technical knowledge relating to our products on our homepage: www.kuebler.com/basics



48 h Express Service

We can process your order within 48 hours; we can ship stock items the same day.

- Simplified orders
- Calculable delivery
- Flexible use of small batch sizes



Safety Services

- Adapted service packages
- Individual customer solutions



Tailor-made Solutions – Kübler Design System (KDS) OEM Products and Systems (OPS)

We develop jointly with our customers product and engineering solutions for customer-specific products, integrated drive solutions, up to complete systems (sensors, electronics and mechanics).



Service-Center / Technical Hotline

Whatever your needs, advice, analysis or support for the installation, Kübler is present on site all over the world with its Service Center.

Kübler Germany	+49 7720 3903 952	Kübler Turkey	+90 216 999 9791
Kübler France	+33 3 89 53 45 45	Kübler China	+86 10 5134 8680
Kübler Italy	+39 026 423 345	Kübler India	+91 8600 147 280
Kübler Poland	+48 61 84 99 902	Kübler USA	+1 855 583 2537

Our Product Portfolio



Position and Motion Sensors

- Incremental and Absolute Encoders
- Linear Measuring Technology
- Inclinometers
- Connection Technology

Transmission Technology

- Slip Rings
- Optical Fibre Signal Transmission Modules
- Cables, Connectors and pre-assembled Cordsets

Functional Safety

- Encoders certified up to SIL3/PlE
- Modules for safe Drive Monitoring
- System Solutions for safe processing of Safety Sensors
- Adapted Service Packages

Counters and Process Devices

- Pulse Counters and Preset Counters
- Hour Meters and Timers
- Frequency Meters and Tachometers
- Combination Time and Energy Meters
- Position Displays
- Process Displays and Controllers for Temperature, Analogue Signals and Strain-Gauge
- Setpoint Adjuster


We offer Solutions for the following Industries:



The high performance level and reliability of the Kübler products are based on our long experience in these demanding application sectors. Learn more about our application-specific solutions under:

www.kuebler.com/industries

Table of contents	
Product Overview / Basics	5
Incremental Encoders	55
Absolute Encoders – Singleturn	75
Absolute Encoders – Multiturn	97
Safety Modules	119
Services	215
Connection Technology	225
Accessories	247
Addresses	275



Product overview		Page
Product overview	Incremental encoders	6
	Absolute encoders – Singleturn	7
	Absolute encoders – Multiturn	8
	Safety modules Safety-M compact	9
	Safety modules Safety-M modular	10
	Safety modules Safety-M	12
	Services	13
	Connection technology	14
	Accessories	15
Basics		Page
Encoders	Introduction	16
	Functional principle	17
	Incremental encoders	18
	Absolute encoders	20
	Electromagnetic compatibility	24
	Installing encoders	26
	Technologies	30
Connection technology	Introduction	32
	Cables and connectors	33
	Optical fibre signal transmission	35
Functional Safety	System solutions	36
	Encoders	40
	Safety functions for the drives technology	41
Glossary		44

















You will find comprehensive information about the basic technical knowledge relating to our products on our homepage, at the address

www.kuebler.com/basics







Product Overview

Incremental Encoders

	Ø Dimensions in mm [inch]	Optical (accuracy $\leq \pm 0.015^\circ$)	Resolution max. in PPR	SinCos interface	Power supply in V DC	Ø Hollow shaft max. in mm [inch]	Speed max. in RPM	Temperature range in °C [°F]	Protection max.	Type of connection	Pulse frequency max. in kHz	RoHS compliant	Approvals	Page
 <p>Standard, optical wave output, SIL2 / PLd Sendix SIL 5814FS2 (Shaft) Sendix SIL 5834FS2 (Hollow s.)</p>	58 [2.28]	•	1.024 and 2.048	•	5 10 ... 30	14 [0.55]	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M12 M23	400	•	  	56
 <p>Standard, optical sine wave output, SIL3 / PLe Sendix SIL 5814FS3 (Shaft) Sendix SIL 5834FS3 (Hollow s.)</p>	58 [2.28]	•	1.024 and 2.048	•	5 10 ... 30	14 [0.55]	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M12 M23	400	•	  	62
 <p>new Standard, optical ATEX / IECEx – Zone 1/21 SIL2 / PLd Sendix SIL 7014FS2 (Shaft)</p>	70 [2.76]	•	1.024 and 2.048	•	5 10 ... 30	–	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	400	•	  	68
 <p>new Standard, optical ATEX / IECEx – Zone 1/21 SIL3 / PLe Sendix SIL 7014FS3 (Shaft)</p>	70 [2.76]	•	1.024 and 2.048	•	5 10 ... 30	–	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	400	•	  	71

















Product Overview

Absolute Encoders Singleturn

		Ø Dimensions in mm [inch]	Optical (accuracy $\leq \pm 0.015^\circ$)	Resolution max. in bit	SSI interface	BiSS-C interface	Additional incremental track	Power supply in V DC	Speed max. in RPM	Temperature range in °C [°F]	Protection max.	Type of connection	RoHS compliant	Approvals	Page
	Standard, optical SIL2 / PLd Sendix SIL 5853FS2 (Shaft) Sendix SIL 5873FS2 (Hollow s.)	58 [2.28]	•	17	•	•	SinCos	5 10 ... 30	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M23	•	cUL ^{us} Ex ^{2/22} SIL2 PLd	76
	Standard, optical SIL3 / PLe Sendix SIL 5853FS3 (Shaft) Sendix SIL 5873FS3 (Hollow s.)	58 [2.28]	•	17	•	•	SinCos	5 10 ... 30	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M23	•	cUL ^{us} Ex ^{2/22} SIL3 PLe	82
	Standard, optical ATEX/IECEX – Zone 1/21 SIL2 / PLd Sendix SIL 7053FS2 (Shaft)	70 [2.76]	•	17	•	•	SinCos	10 ... 30	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	•	Ex IECEX SIL2 PLd	88
	Standard, optical ATEX/IECEX – Zone 1/21 SIL3 / PLe Sendix SIL 7053FS3 (Shaft)	70 [2.76]	•	17	•	•	SinCos	10 ... 30	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	•	Ex IECEX SIL3 PLe	92

Product Overview

Absolute Encoders Multiturn

		Ø Dimensions in mm [inch]	Optical (accuracy $\leq \pm 0.015^\circ$)	Resolution max. in bit ST+MT	SSI interface	BiSS-C interface	Additional incremental track	Power supply in V DC	Speed max. in RPM	Temperature range in °C [°F]	Protection max.	Type of connection	RoHS compliant	Approvals	Page
	Standard, optical mechanical Multiturn SIL2/PLd Sendix SIL 5863FS2 (Shaft) Sendix SIL 5883FS2 (Hollow s.)	58 [2.28]	•	17 + 12	•	•	SinCos	5 10 ... 30	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M23	•	  	98
	Standard, optical mechanical Multiturn SIL3/PLe Sendix SIL 5863FS3 (Shaft) Sendix SIL 5883FS3 (Hollow s.)	58 [2.28]	•	17 + 12	•	•	SinCos	5 10 ... 30	12.000 / 9.000	-40 ... +90 [-40 ... +194]	IP65	Cable M23	•	  	104
 new	Standard, optical mechanical Multiturn ATEX/IECEX – Zone 1/21 SIL2/PLd Sendix SIL 7063FS2 (Shaft)	70 [2.76]	•	17 + 12	•	•	SinCos	10 ... 30	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	•	  	110
 new	Standard, optical mechanical Multiturn ATEX/IECEX – Zone 1/21 SIL3/PLe Sendix SIL 7063FS3 (Shaft)	70 [2.76]	•	17 + 12	•	•	SinCos	10 ... 30	6.000	-40 ... +60 [-40 ... +140]	IP67	Cable	•	  	114

Product Overview

Safety Modules Safety-M compact Basic modules



new



	Monitoring - number of axes	Safe digital input lines	Analogue input lines	Relay output lines	Digitale output lines	Analogue output lines	Encoder interface	Max. number of expansion/ bus modules	Power supply in V DC	Module width in mm [inch]	RoHS compliant	Approvals	Page
Speed monitoring for 1 axis SMC1	1	4/2	–	1	4	1 opt.	HTL/TTL/ SinCos	0	24	50 [1.97]	• UL3 	120	

Product Overview





































Safety Modules Safety-M modular Basic modules

	Monitoring - number of axes	Digitale safe input lines	Analogue input lines	Relay output lines	Digital safe output lines	Safe cross communication	Communication interface	Encoder interface terminal	Max. number of expansion modules	Power supply in V DC	Module width in mm [inch]	RoHS compliant	Approvals	Page
 SMBD.420	• ¹⁾	8 / 4	• ¹⁾	• ¹⁾	2	–	–	HTL/ Proximity switch	31 safe slaves	24	22.5 [0.89]	•	 	124
 SMBD.32E	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	2	•	–	HTL/ Proximity switch	31 safe slaves	24	22.5 [0.89]	•	 	127
 SMBU.021	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	•	CANopen	–	31 safe slaves	24	100 [3.94]	•	 	130
 SMBU.031	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	•	PROFIBUS DP	–	31 safe slaves	24	100 [3.94]	•	 	133
 SMBU.0B1	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	•	EtherCAT	–	31 safe slaves	24	100 [3.94]	•	 	136
 SMBU.0C1	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	•	PROFINET IO	–	31 safe slaves	24	100 [3.94]	•	 	139
 SMBU.0D1	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	•	Ethernet / IP	–	31 safe slaves	24	100 [3.94]	•	 	142
 SMBS.S31	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	–	PROFIsafe PROFIBUS DP	–	31 safe slaves	24	100 [3.94]	•	 	145
 SMBS.SC1	• ¹⁾	6 / 3	• ¹⁾	• ¹⁾	6	–	PROFIsafe PROFINET IO	–	31 safe slaves	24	100 [3.94]	•	 	148

1) Via expansion module.









Product Overview

Safety Modules Safety-M modular Expansion modules

		Digital input lines	Analogue input lines	Digital output lines	Relay contacts	Encoder interface	Power supply in VDC	Module width in mm [inch]	RoHS compliant	Approvals	Page	
		Axis expansion, incremental EMAI.012	–	–	–	HTL	24	22.5 [0.89]	•	 	151	
		Axis expansion, incremental EMAI.022	–	–	–	SinCos	24	22.5 [0.89]	•	 	154	
		Axis expansion, absolute EMAA.032	–	–	2	SinCos SSI	24	22.5 [0.89]	•	 	157	
		I/O expansion, relay 1 x 4 contacts EMIO.SR.004	–	–	–	4	–	24	22.5 [0.89]	•		160
		I/O expansion, relay 2 x 4 contacts EMIO.SR.008	–	–	–	8	–	24	22.5 [0.89]	•		163
		I/O expansion, digital 8 + 8 / 4 EMIO.SIO.048	8	–	8 / 4	–	–	24	22.5 [0.89]	•		166
		I/O expansion, digital 16 / 8 + 1 EMIO.SIO.810	16 / 8	–	1	–	–	24	22.5 [0.89]	•		169
		I/O expansion, digital 8 / 4 + 4 / 2 EMIO.SIO.420	8 / 4	–	4 / 2	–	–	24	22.5 [0.89]	•		172
		I/O expansion, Digital 4 / 2 + 4 EMIO.SIO.204	4 / 2	–	4	–	–	24	22.5 [0.89]	•		175
		I/O expansion, digital 2 / 1 + 2 EMIO.SIO.10xP	2 / 1	–	2	–	–	45 [1.77]	•		178	
		I/O expansion, digital (non safe) 8 + 8 EMIO.IO.880	8	–	8	–	–	24	22.5 [0.89]	•		181

Product Overview

Safety Modules Safety-M Basic modules






		Monitoring - number of axes	Digital input lines	Analogue input lines	Relay contacts	Digital output lines	Encoder interface front (Sub-D)	Encoder interface terminal	Max. number of expansion/ bus modules	Power supply in V DC	Module width in mm [inch]	RoHS compliant	Approvals	Page
	Speed monitoring for 1 axis MS1	1	14 / 7	–	2 / 1	4 / 2	TTL/SinCos/SSI	HTL/ Proximity switch	2/1	24	45 [1.77]	•		184
	Speed and position monitoring for 1 axis MSP1	1	14 / 7	–	2 / 1	4 / 2	TTL/SinCos/SSI/ Resolver	HTL/ Proximity switch	2/1	24	67.5 [2.66]	•		188
	Speed monitoring for 2 axes MS2	2	14 / 7	4 optional	2 / 1	4 / 2	TTL/SinCos/SSI	HTL/ Proximity switch	2/1	24	67.5 [2.66]	•		192
	Speed and position monitoring for 2 axes MSP2	2	14 / 7	4 optional	2 / 1	4 / 2	TTL/SinCos/SSI/ Resolver	HTL/ Proximity switch	2/1	24	112.5 [4.43]	•		196

Safety Modules Safety-M Expansion modules

		Digital input lines	Digital input / output lines, configurable	Relay contacts	Digital output lines	Power supply in V DC	Module width in mm [inch]	RoHS compliant	Approvals	Page
	I/O expansion digital EM3	12 / 6	10 / 5	–	2	24	45 [1.77]	•		200
	I/O expansion relay EM4	12 / 6	2 / 1	8 / 4	2	24	90 [3.54]	•		202

Product Overview

Safety Modules Safety-M Bus modules

		Baud rate	Power supply in VDC	Module width in mm [inch]	Fieldbus interface	RoHS compliant	Page
	Communication module DeviceNet BM11	125 ... 500 kbit/s	From basic module	22.5 [0.89]	<i>DeviceNet</i>	•	204
	Communication module CANopen BM21	500 kbit/s	From basic module	22.5 [0.89]	<i>CANopen</i>	•	206
	Communication module PROFIBUS DP BM31	9.6 kBaud ... 12 MBaud	From basic module	22.5 [0.89]	<i>PROFIBUS</i>	•	208
	Communication module EtherCAT BMB1	100 Mbit/s, full-duplex	From basic module	22.5 [0.89]	<i>EtherCAT</i> Conformance tested	•	210
	Communication module PROFINET IO BMC1	100 Mbit/s, full-duplex	From basic module	22.5 [0.89]	<i>PROFINET</i>	•	212





Services

Advice, Safety services





		Page
	Risk Assessment	216
	Safety Concept	217
	Start-up / Validation	218
	Safety Retrofit	219

Product Overview

Connection Technology Cable, unprepared, cut to length





		PVC cable	PUR cable	TPE cable	Cross section in mm ² [AWG]	Cable diameter in mm	for incremental encoders	for absolute encoders	RoHS compliant	Approvals	Page
	8 core + shield	-	•	-	8 x 0.14 [AWG25] 3 x 2 x 0.14 [AWG25] + 2 x 0.5 [AWG20]	approx. 5.5 approx. 7.4	-	•	•	UL US	226
	10 core + shield	-	•	-	4 x 2 x 0.25 [AWG23] + 2 x 1 [AWG17]	approx. 7.9	•	•	•	-	226
	12 core + shield	•	-	-	10 x 0.14 [AWG25] + 2 x 0.5 [AWG20]	approx. 6.9	•	•	•	-	227
		-	•	-	12 x 0.14 [AWG25]	approx. 6.7	•	•	•	-	
		•	-	-	6 x 2 x 0.14 [AWG25]	approx. 7.5	•	•	•	UL US	
		-	-	•	5 x 2 x 0.14 [AWG25] + 2 x 0.5 [AWG20]	approx. 8.5	•	•	•	-	
		-	•	-	6 x 2 x 0.14 [AWG25]	approx. 7.3	•	•	•	-	
	PROFIBUS DP DeviceNet CANopen EtherCAT / PROFINET IO	•	-	-	2 x 0.34 [AWG25]	approx. 7.6	•	•	•	-	
		•	-	-	2 x 0.52 [AWG20] + 2 x 1.04 [AWG17]	approx. 8.4	•	•	•	-	
		-	•	-	3 x 2 x 0.25 [AWG23]	approx. 6.2	•	•	•	-	
		•	-	-	2 x 2 x 0.34 [AWG25]	approx. 4.8	•	•	•	-	

Connection Technology Connectors, self-assembly

		N° of pins	Housing	Connection technology	Cable diameter Ø in mm	Straight connector	Right angle connector	Wall/panel lead-through	for fieldbus	Page
	M12	4, 5, 8	Metal	Screw terminals	6 - 8	•	•	•	•	228
	M23	12	Metal	Solder pins	5.5 - 10.5	•	-	•	-	231
	Sub-D	9	ABS metallized	Solder pins	6 - 8	-	•	-	-	235
	RJ45	8	Plastic	Crimp connection	4.5 - 8	•	-	-	•	243

Product Overview

Connection Technology Cordsets, pre-assembled

	PVC cable	PUR cable	TPE cable	Straight connector	Right angle connector	for incremental encoders	for SSI / BiSS-C encoders	for fieldbus	for analogue interfaces	Page
 with M12 connector	•	•	–	•	•	•	•	•	•	229
 with M23 connector	•	•	•	•	–	•	•	–	•	233
 with Sub-D connector	–	•	–	–	•	–	–	•	–	236
 with RJ45 connector	–	•	–	•	–	–	–	•	–	244

Accessories

	Page
Encoder mounting attachments	248
LED displays	256
Optical fibre transmitter and receiver	262
Accessories for safety modules	264

Basics

Encoders

Introduction

Encoders can be used in applications, where length, positions, speed or an angular position are measured. They transform mechanical movements into electrical signals and can be divided into incremental and absolute measuring systems.


Incremental encoders generate pulses, where the number of pulses can be a measure of speed, length or position.

In absolute encoders, every position corresponds to a unique code pattern. No reference runs after starting-up are necessary as with incremental systems. Safety is increased and the time taken for reference runs is saved.

In principle we can supply all encoders, whether with a solid shaft or in a hollow shaft version.


Using a hollow shaft encoder saves up to 30 % of costs and up to 50 % of the required space compared to a shaft encoder. This is achieved by avoiding additional couplings, brackets and other assembly aids.

To mount a hollow shaft encoder it just needs to be pushed onto the shaft, clamped, and in the simplest case prevented from rotating by using a cylinder pin. Moreover, in principle, hollow shaft encoders require less installation depth.




Application examples


Angular measurement




Positioning




Detecting of fork's position




Detecting of position



Angular measurement



Velocity measurement



Encoders Functional Principle

Assembly and function

Optical scanning (incremental)

A disc fitted with a grating, having a code pattern of slits and bars, is mounted so that it can rotate between an LED and a receiver.


The light emitted by the LED is modulated by the mask and grating and then strikes the receiver, which produces a signal proportional to the luminosity.

When the disc rotates this signal has a shape that approximates to a sine wave.

Optical scanning (absolut)

The light that is emitted by an LED is modulated by a code pattern, which is applied to a rotating disc; this is scanned by a special Kübler Opto ASIC. A unique bit pattern is assigned to each position and this is generally available as Gray Code.

The advantage, compared with incremental encoders, lies in the fact that any movement of the shaft whilst voltage is not applied is immediately detected when power is re-applied, ensuring the correct position is always available.



Basics

Encoders Incremental Encoders

Processing of the signals (optical, incremental encoders)

The sine wave signals are then processed in a specially designed electronic circuitry. Most controllers require square-wave signals on their input.

The signals are therefore pre-processed accordingly in the encoder and made available using various output circuits depending on the application.

Inverted signals

When used in environments, with a lot of electrical noise and/or if very long cable distances are required, we recommend using encoders with inverted (complementary) signals.

These signals are always available with output circuits of the RS422 type and sine wave outputs or optionally with push-pull outputs.

Resolution

The required angular or linear resolution of a application determines the number of pulses per revolution. Linear movements must first be converted into rotary, for example by means of a spindle.

given:

- Circumference of the measuring wheel = 200 mm
- Accuracy of the system = 0.1 mm

wanted:

- Resolution of the encoder [ppr] ¹⁾

Example:

An encoder is equipped with a measuring wheel. Every revolution corresponds to a distance of 200 mm (circumference). The accuracy should be 0.1 mm. What is the required resolution (ppr)?

$$\text{Resolution} = \frac{\text{Circumference}}{\text{Accuracy}}$$

The required resolution would be 2000 ppr ¹⁾.

Pulse frequency

The required pulse frequency can be calculated as a result of the number of pulses per revolution (PPR) and the maximum speed (RPM). The maximum pulse frequency is shown in the data sheet specifications for each encoder.

Example:

given:

- Speed = 3000 min⁻¹
- Resolution of the encoder = 1000 ppr ¹⁾

wanted:


- Required pulse frequency of the encoder

Generally this is 300 KHz, but can be up to 800 KHz with high-resolution encoders.

$$\text{Pulse frequency} = \frac{\text{Speed} \times \text{Resolution}}{60}$$

The required pulse frequency is thus 50 KHz. This can now be compared with the maximum possible pulse frequency of the desired encoder.

This diagram can be used to estimate the required pulse frequency. ¹⁾



1) ppr = Pulses per revolution

Encoders


Incremental Encoders

Sine wave outputs


The sine wave signals are available as voltage signals. They can be further processed in the evaluation electronics. Due to the interpolation of the two signals, which are 90° out of phase, a very high resolution can be achieved.

Further they are very suitable for digital drives with a very slow movement, e.g. for grinding machines or lifts and elevators.

- Shaft turning clockwise, top view of shaft
- 0 pulse is generated once per turn (only with 5804 / 5824)



Output circuit and recommended input circuit for sine wave voltage signals



$R_a = 10 \Omega$
 $C_1 = 150 \text{ pF}$
 $C_2 = 10 \text{ pF}$
 $R_1 = 10 \text{ k}\Omega$
 $R_2 = 33 \text{ k}\Omega$
 $U_0 = 2,5 \text{ V} \pm 0,5 \text{ V}$

$Z = 120 \Omega$
 $U_1 = U_0$

operation amplifier:
 e.g. MC33074

Encoders Absolute Encoders

Versions

Singleturn encoders

Depending on the number of divisions they generate unique positions per revolution. After one complete revolution the process re-commences at the start position.

They are suitable for angular measurement over a maximum of one turn of the shaft (=360°), for example in robotics, with cam controllers and in other controlled rotary motion.

Multiturn encoders

Up to 17 bit unique angular positions per revolution are provided. In addition the number of revolutions is detected. Up to 4096 (12 bit) unique revolutions can be made available on the output.


Multiturn encoders are suitable for angular measurement over more than one turn of a shaft, for example with longer traverse paths, such as high rack storage areas, cranes or machine tools.

Code types

Binary Code

The Binary Code can be processed very easily by computer systems. When using optical read-out, errors may occur, because the change from one bit to another on the different concentric tracks

(LSB, LSB+1...) is not exactly synchronized. Due to this, without any correction of the code, the position information could be wrong.



Gray Code


The Gray Code is a single-step code, which guarantees that from one position to the next only 1 bit changes.

This leads to reliable scanning of the code and consequently of the positions.

Symmetrically capped Gray Code (Gray-Excess):

If a particular section of the complete Gray Code is extracted, this results in the so-called Gray Excess Code

This permits even-numbered divisions, such as 360, 720, 1000, and 1440.



Reversion of the Gray Code

The code values increase when the shaft is turning clockwise.

The Gray Code is reversible, i.e. if the most significant bit (MSB) is inverted, the code values decrease when the shaft is turning clockwise.

Encoders

The mechanical Sendix Multiturn stage with gear



Absolute Encoders

- Multiturn gear with purely optical scanning technology. Completely resistant to magnetic fields.
- First stage with double bearing layer.
- Special materials ensure temperature stability and long service life.
- Through hollow shaft diameter up to 14 mm
- up to 15 mm as blind hollow shaft.
- Specially developed gear teeth allow for very high rotational speeds and eliminate wear.



Outputs

To transfer the position data to a controller, different interfaces are available.


Synchronous Serial Interface (SSI)

Compared to the parallel interface, the SSI interface needs less components and the EMC characteristics are much better.


In addition less lines are needed for transmission and the possible cable length is much longer.

Output circuit and recommended input circuit

5862, 5882, 9081



Data transmission SSI



- $t_1 = T / 2$
- $t_2 < 1 / (4 \times f_{max})$
- $t_3 = \text{Monoflop time (see below)}$
- $n = \text{Resolution in bit}$
- $1 / f_{max} \leq T \leq 1 / f_{min}$
- $f_{min} = \text{min. clock rate (see data sheet)}$
- $f_{max} = \text{max. clock rate (see data sheet)}$

At rest, the clock and data lines are at a high level. With the first falling clock-pulse edge, the current encoder data are stored in the buffer ready to be sent. With the next rising clock-pulse edge, the data are transmitted bit by bit, starting with the MSB. The transfer of a complete data word requires $n+1$ rising clock-pulse edges (n =resolution in bit), e.g. 14 clock signals for a complete readout of a 13 bit encoder.

After the last positive-going clock-pulse edge the data line will remain for the duration of the monoflop time t_3 at a low level, until the encoder is ready for a new data word. The clock line must stay high for at least as long, and then can begin a new read-out sequence again with the next falling edge.

Please note!

Only for type 5850, 5870, 5862, 5882 and 9081:

The updating of the data occurs synchronously with the read-out cycle. So, the data are as up-to-date as the interval time between two read-outs.

A periodic read-out of the encoder in the application is therefore recommended, using appropriately short cycle times, so that current position values are constantly maintained. It is not possible to read out the same data word several times.

Monoflop time of the encoder: $t_3 = \text{max. } 40\mu\text{s}$

Only for the new Sendix absolute encoders:

The updating of the data occurs immediately with the first falling edge of the clock signal. The data are thus always up-to-date. If a repeated read-out of the same data word is desired, then a new clock sequence must be started within the time interval t_3 . If the clock sequence is terminated before the necessary number of clock pulses, needed for a complete readout of the data word, has been transmitted, then after a further time interval t_3 the data line will go high again and signal that the last read-out sequence has been aborted. It will also indicate that it is ready for a new data word to be sent. Monoflop time of the encoder: $t_3 = \text{see data sheet}$.

Encoders Absolute Encoders


BiSS-C Interface

Point-to-point communication

- Bidirectional isochronous connection between drive, converter and sensor.
- Purely digital link for maximum performance, reliability and safety in transmission.
- Reduction of hardware, installation and maintenance work.

Advantages at a glance

- Flexible.
- Fast and safe.
- Cost-effective and non proprietary / Open source.
- Fully digital and bidirectional.
- Suitable for motor feedback systems.
- Plug and Play.



Extended possibilities with BiSS-C

- Motor data and maintenance information can be stored and read out easily in the encoder.
- Condition monitoring through register communication.

Easy supplementing of the BiSS-C master function

- The existing standard control hardware can mostly be used also for BiSS-C.
- Extension by firmware update is in most cases possible.
- BiSS-C as a real alternative to existing, RS422 or RS485-based interfaces.
- Fast and simple BiSS-C master implementation with free-of-charge BiSS-C IPs on processors and FPGAs.

Details about our BiSS-C interface can be found on our website at: www.kuebler.com/service/biss_en.pdf.

EMC compliant installation

EMC = Electromagnetic compatibility

Safety modules monitor the signals from sensors and in particular from encoders very intensively. This is necessary, as an encoder signal contains positioning or rotational speed regulation information. EMC is considered as one of the main causes of malfunctions in plants and machines during installation and commissioning. Generally, EMC problems translate into sporadically occurring errors or phenomena.

Therefore, one of the main tasks of Safety-M safety modules is to detect and display such signal changes. What is sometimes wrongly described as availability problems is nothing but the effects of insufficient EMC measures.

Several guidelines are to be observed in order to maintain the best signal quality possible:


1) Cable routing

Cable routing strongly contributes to the EMC of a plant. The cables must be classified in four groups I, II, III and IV:


- | | |
|--|--|
| <p>Group I: Very sensitive to interference (analogue signals, measuring lines).</p> | <p>Group III: Source of interference (control cables for inductive loads, unswitched power cables, motor brakes, contactors).</p> |
| <p>Group II: Sensitive to interference (digital signals, sensor cables, 24 VDC switching signals, communication signals such as e.g. fieldbuses).</p> | <p>Group IV: Strong source of interference (frequency converter output cables, welding plant power supply cables, switched power cables).</p> |

Lines should always be routed so that the signal lines are separated from the power supply lines:


Cross lines of groups I, II and of groups III, IV at right angles.



Ideally: route the lines in different cable channels.



Alternative: separate the lines using a metal separator.



2) Shielding


Signal lines should be shielded.

For long signal lines, the cable should be grounded at several locations along the line.

Screwed cable fittings should not interrupt the shield, but take it on (see chapter connection technology).

The shield should be applied on a large surface on the functional earth.

If possible, no compensation currents should flow through the shield. These currents appear when the mass does not have the same reference potential.




1 - Conductor
2 - Isolation
3 - Shield
4 - Sheath


3) Cabinet layout

The products should be arranged in functional groups in a cabinet.


The cabinet itself should be equipped with a functional earth applied on large surfaces. The cabinet elements should be connected by means of high-frequency, low-impedance connections.



According to VDE 0100, the functional earth is not identical with the protective earth!
Protection against dangerous contact voltage is only a secondary task of the grounding connections.



Typical connections for proper potential equalisation, with the largest contact surface and cross-section possible.



Source: ZVEI

Encoders

Installing Encoders

Introduction

Encoders shafts and in turn their bearings are subjected to loads for a variety of reasons:

- Installation tolerances when mounting the encoders (radial and angular displacement).
- Thermal changes, e.g. linear expansion of the drive shaft.
- Effects of wear, e.g. radial runout of the drive shaft or vibrations.

These load factors have a direct effect on the life expectancy of the shaft bearings and on the quality of the signal.

Facilities must therefore be provided during installation to compensate for these forces. For encoders having a solid shaft this is generally done by using shaft couplings between the drive shaft and the encoder shaft. The solution with hollow shaft encoders is to use stator couplings, fixing brackets or torque stops between the encoder flange and the mounting surface.

Not making use of a coupling but instead rigidly mounting the shaft and the encoder housing generally leads to unacceptably high loads on the bearings; the ensuing wear will cause the encoder to fail prematurely.


In order to avoid permanent damage of the encoder, certain bearing loads should not be exceeded. If hollow shaft encoders are correctly installed and the torque stops or stator couplings that are available from Kübler are used, then no problems should occur. For solid shaft encoders the maximum permitted axial and radial loads are shown in the appropriate technical data.

Mounting options for hollow shaft encoders


Hollow shaft encoder with torque stop and pin

(easiest and fastest mounting)


Standard hollow shaft encoders are equipped with the torque stop (cylindrical pin not supplied).



Extended torque stop and long pin



Stator coupling




Encoders


Installing Encoders

Mounting examples for shaft encoders with synchronous flange

Fastening eccentrics + coupling
(to reduce shaft overload)




Assembly bell, fastening eccentrics + coupling
(to prevent shaft overload and to isolate the encoder thermally and electrically)




Product overview
Basics

Mounting examples for shaft encoders with clamping bracket

Angular bracket + coupling
(to reduce shaft overload)



Clamping device + coupling
(to reduce shaft overload)



Encoders Installing Encoders

Loading of encoder shaft bearings using coupling forces

With all spring couplings (shaft coupling, stator coupling, fixing bracket), alignment and axial errors are converted to a force that corresponds to the spring constant of the coupling.

This force has to be absorbed by the encoder shaft bearings. When installing an encoder, this should be done with as little force as possible, i.e. without any unnecessary initial tension on the coupling. If this is adhered to, then with all Kübler couplings adequate tolerance compensation is guaranteed for the whole service life of the encoder bearings.

This force does not occur with torque stops for hollow shaft encoders, where the encoder is prevented from turning also by means of a pin or rod.

Although the encoder is prevented from rotating due to a rigid interlock, the encoder is still free to move in any other direction. This is of course dependent on it being mounted in such a way that it has freedom to move radially and especially axially (thermal linear expansion of the drive shaft!).

Possible errors in accuracy due to couplings

1. Deviations in accuracy caused by torsion of a spring coupling (in particular shaft couplings).

This deviation in accuracy is defined by the torque to be transmitted (bearing friction and mass moment of inertia) and by the torsional spring constant of the torque stop.

The following applies:

$$\text{Max. error (degree)} = \frac{\text{max. torque [Ncm]}}{\text{torsional spring constant [Ncm/Grad]}}$$

The following table serves to estimate the ratio between such an error and the smallest increment of an encoder:

Relationship between the resolution of an encoder in bit and the smallest increment in angular degrees:

Resolution	binary	10 bit	11 bit	12 bit	13 bit	14 bit	17 bit
	ppr		1024	2048	4096	8192	16384
Increment	degrees	0.352	0.176	0.088	0.044	0.022	0.0028
	degrees:min:sec	0:21:06	0:10:33	0:05:16	0:02:38	0:01:19	0:00:10
	sec	1266	633	316	158	79	10


2. Deviations in accuracy caused by radial play in the drive shaft with asymmetrical mounting of the couplings.

Here one has to differentiate between couplings that are mounted in an axially symmetrical manner round the shaft (all shaft couplings, many stator couplings) and asymmetrically mounted couplings (many stator couplings, all mounting brackets and pin-based torque stops).

With asymmetrical couplings deviations in accuracy can arise due to radial movements of the drive shaft (radial runout/play); this is determined by the system. These deviations are dependent on the amount of the radial play and the distance of the torque stop locating point from the drive shaft.

The relationship is shown in the following diagram:

Maximum permissible radial runout to achieve an accuracy <1/2 LSB when using an asymmetrical 1 point torque stop.



Encoders	Installing Encoders	
-----------------	----------------------------	--

Particular shaft loading due to toothed-wheels, gear-pulleys and similar elements

Measuring wheels, toothed wheels or gear pulleys, which are mounted directly on the encoder shaft, exert radial forces on the latter, dependent on prestressing and angular acceleration. Kübler encoders are designed so that they can absorb these forces to a great extent. The maximum permissible load capacity of the shaft is shown in the technical data for the encoder.

If these load values may be exceeded in a particular application, then the encoder shaft must be isolated from the radial load by interposing an appropriate shaft with its own bearings that can absorb the forces. Kübler offers suitable bearing blocks and bearing boxes for this purpose (please refer to the 'Accessories' section in the catalogue).

Encoders	Technologies	
-----------------	---------------------	--

Safety-Lock™



All Kübler encoders are equipped with the Safety-Lock™ bearing structure.

Safety-Lock™

Interlocked bearings, large bearing span and extra strong outer bearings ensure stability when subjected to vibration and tolerance of installation errors. Machine downtime and repairs are eliminated.

Safety-Lockplus™

The proven Safety-Lock™ construction with additional mechanically protected shaft seal.

HD-Safety-Lock™ = Safety-Lock™ + additional engineering

Floating bearing on the cover-side eliminates internal stress ¹⁾

- Mechanically decoupled sensor unit ensures constant signal quality with large temperature fluctuations and other adverse environmental influences. ¹⁾
- Dual seals on the shaft-side – friction seal against humidity, labyrinth seal against dust and water jet ingress.
- Very large, highly-robust flange bearings.
- Even greater bearing clearance.
- Extremely robust flange mounting due to screw-on housing.
- Bearing design incorporates integrated isolation (isolating inserts not required), tested up to 2.5 kV for high running accuracy; metal to metal connection for slip free mounting. ²⁾

Benefits:

The resistance against adverse environmental conditions is greatly increased – especially against high bearing loads and high temperatures.

¹⁾ for Sendix H100 ²⁾ for Sendix H120

	Safety-Lock™	HD-Safety-Lock™
Stability with vibration	+	++
Robustness against installation errors	++	++
Radial load	80 N	400 N
Axial load	40 N	300 N
Elimination of internal stresses	0	++
Constant signal quality with extended temperatures	+	++
Mechanical protection of the seal	0	++



Encoders	Technologies	
----------	--------------	--

Ageing compensation (optical encoders)

Every LED loses some of its luminosity over time. Without ageing compensation the excellent quality of the output signals would suffer. The phase shift of 90° necessary to detect the direction of rotation would be lost. This effect however is prevented by means of special electronic circuitry.

Benefit:

The ageing compensation circuit ensures the same signal, even after many years of operating time. The downtime of machines will be reduced dramatically and the reliability is increased.



Product overview
Basics

Temperature compensation

This circuit ensures that the signal will remain the same over the whole working temperature range.

Benefit:

The positioning accuracy of a machine will not be affected by temperature changes.

Current consumption

The typical values for current consumption given in the catalogue apply for ambient temperature (23°C). Because of the temperature compensation, the current consumption of the encoder rises with the temperature.

This increase in current is taken into consideration when giving the figure for maximum current consumption. The output currents are dependent on the user's input circuit and are therefore not included in the figures given; these should therefore be calculated and added in.

Short-circuit protection

The outputs of all the encoders are short-circuit protected, provided that the supply voltage is correctly wired. If an output is connected by mistake to 0 V or +U_B or with another output, the device will not be damaged. As soon as the error is corrected, the encoder is ready for use again.

Benefit:

Wiring circuit errors during installation that often occur in the hectic of day-to-day industrial environments do not lead to the encoder being permanently damaged.

Environmental conditions



The environmental conditions in which the encoder operates can have a significant influence on its service life, for example

- The ambient temperature.
- The expected shaft load.
- Soiling and humidity.
- Noise interference.

Thanks especially to the high-quality technology employed in our encoders, they are particularly suitable for use in harsh environments.

Numerous references from our customers, including Bosch, Siemens, Bombardier and from suppliers to the automotive industry, are proof of this.

Bearing life

All Kübler encoders are designed to ensure that their bearings give a long service life. This is subject of course to correct installation and to the load limits for the shaft (shaft encoders) being complied with or, in the case of hollow shaft encoders, being mounted with the appropriate stator couplings or torque stops.

The following diagrams show the expected service life of the shaft encoder bearings depending on the bearing load. The calculations are based on a mixed load, where the axial force components are always half of the radial shaft load.

The use of the torque stops and stator couplings that are offered ensure that the shaft load with the hollow shaft encoders as supplied from the factory is kept very small.

Connection Technology Introduction

Introduction

All products of chapter connection technology have been tested and released in relation with the corresponding compatible Kübler sensors.

They ensure the full functionality and high signal quality of our sensors - this guarantee is supported by our competent customer service.

Your advantage:



- Prevents from misconnections
- No time-consuming search for errors.
- Optimal shielding
- Prevents from EMC problems.
- Shorter mounting times
- Time- and thus cost-savings.
- No time-consuming search for the suitable connector or cable
- Time-savings and error prevention.

Pre-assembled cordsets for the Functional Safety technology

Kübler offers pre-assembled cordsets to connect an encoder with a Safety-M safety module.

Pre-assembled cordsets are divided into encoder cables and adapter and split cables.

- **Standard encoder cables** are intended to connect the encoder in the application to the cabinet. These cables are available in various materials to cover different environmental conditions and areas of application.
- **Adapter or split cables** are intended to split the signals for different devices / interfaces or to adapt connectors inside of the cabinet.



Connection Technology

Cables and Connectors

Material information - cables

PVC

- Suitable for average mechanical stresses in the area of packaging machines and assembly and production lines.
- Good resistance against acids and alkalis and thus predestined for use in the food and beverage industry.
- Limited friction resistance and partial resistance to oils and chemicals.

PUR

- Flexible, PVC, silicone and halogen-free control cable with PUR cable jacket and polypropylene wire insulation.
- The cable is oil-resistant and non-flammable according to VDE 0472, and it is resistant to chemicals, hydrolysis and microbes.
- Temperature resistance from -30°C to +90°C.
- Use is possible in trailing cable carriers with a bending radius equal at least to 10 x D.
- Thanks to its resistance to welding sparks, this cable is very well adapted for flexible use in the area of robotics, machine tools and metal cutting production.

Material information - connectors

Two material groups are used for the connectors described in the catalogue:

Metals for contacts and housings

- Contacts:
Metal, CuZn, gilded.
- Connecting nut /compression screw:
Metal, CuZn, nickel-plated.

Plastics for insulator and housing

- Contact carrier:
Plastic, TPU, black.
- Body:
Plastic, TPU, black.
- Seal:
Plastic, fluorine rubber (FKM/FPM) FPM/FKM or nitrile-butadiene rubber (NBR).

Coding of the M12 x 1 connectors


The connectors are coded to guarantee protection against polarity reversal. This coding is achieved by means of a peg or a notch in the contact carrier.

Kübler connectors make a distinction between A, B or D coding.

A-coding

Female connector with coupling nut:
Male connector with external thread:
Use:


Coding notch
Coding peg
CANopen and
8-pin connector



B-coding

Female connector with coupling nut:
Male connector with external thread:
Use:


Coding peg
Coding notch
Profibus



D-coding

Female connector with coupling nut:
Male connector with external thread:
Use:

Coding peg and
Coding notch
Coding peg and
Coding notch
Profinet and
EtherCAT



Connection Technology

Cables and Connectors

Shielding

With round connectors, care must be taken to connect carefully the shielding braid of the cable to the shield connection of the connector.

An all-round contact (360°) is optimal. Good (in practice often sufficient) shielding values are also reached by connecting the shielding braid firmly to the electrically conductive housing. Connectors purely out of plastic, without metal sleeve, providing no contact for the shielding braid, are not sufficient.

Furthermore, a proper contact with the mating connector is also important, as well as a good contact of the mating connector with the chassis of the equipment.



"Allround" shielding with Kübler cordsets


Counting direction cw/ccw

The counting direction of the connectors is indicated by cw for a clockwise arrangement and ccw for a counter-clockwise arrangement. The connector is always viewed from the mating side.

Top view of mating side



Counting direction cw (e.g. female connector)



Counting direction ccw (e.g. male connector)

Connection Technology	Optical Fibre Signal Transmission	
-----------------------	-----------------------------------	--

Description	<p>The system is made up of an optical fibre transmitter and an optical fibre receiver.</p> <p>The optical fibre transmitter converts the electrical signals of an encoder into optical fibre signals. A simple glass fibre allows reliable transmission up to distances of 1500 m.</p> <p>The receiver module converts the optical signals back into electrical signals.</p> <p>The modules are available in various level and power supply voltage variants.</p>	<p>Main advantages of an optical fibre transmission:</p> <ul style="list-style-type: none"> • Insensitivity to electromagnetic interferences and to leakage effects between lines routed parallel. • Significantly higher transmission speeds. • The optical fibre cable can be routed through explosive atmospheres. • Cost and weight savings thanks to reduced cabling work, especially for important cable lengths.
Mounting of optical fibre modules	<p>The optical fibre modules can be mounted directly on a TS35 DIN rail (top-hat rail) according to EN 50022.</p> <p>The installation width for every module is only 22.5 mm.</p>	
Laying and connection of glass fibre cables	<p>Laying the cable is generally easy.</p> <p>Care must nevertheless be taken to make sure that the bending radius does not become smaller than 30 mm for static laying and 60 mm for dynamic laying.</p>	<p>When connecting the cable, make sure that the bayonet catch is locked and remove the dust protection caps only just before connecting the cable.</p>
Glass fibre cables	<p>The modules can be connected together using 50/125 µm or 62.5/125 µm multimode glass fibre cables with ST/PC type connectors with bayonet catch. Single-mode Simplex patch cables are not suitable.</p>	<p>Kübler offers finished confectioned patch cables adapted to the optical fibre modules as accessories.</p> <p>They ensure the full functionality and high signal quality of our sensors.</p>

Product overview
Basics

Functional Safety

Kübler's extensive product portfolio of rotary and linear position and motion sensors, with the matching safe encoder evaluation devices, provides the basis for safe application-specific drive solutions. However, safe single components alone do not ensure a safe global application.

Legally compliant safety already begins when planning the machine, and this is why the Kübler service technicians and engineers offer a wide


System Solutions

range of supports both for the plant manufacturer and for the operator.

The matter Functional Safety technology is simplified by the certified encoders of the Sendix SIL family, which includes both incremental, absolute and ATEX / IECEx encoders. The safe encoder evaluation devices of the Safety-M family include single compact standalone devices for simple applications as well as modular extendable

compact controllers that can be connected via a gateway to any higher-level control system.

This allows realizing flexible safety release circuits integrating a safe speed and position monitoring to achieve simple machine safety. Kübler's technical safety solutions meet all high safety and reliability requirements.



1 Standard encoders

- Incremental and absolute encoders
- Fieldbus and Industrial Ethernet encoders
- Encoders with ATEX / IECEx approval



2 Safe encoders

- Incremental and absolute encoders
- Encoders with ATEX / IECEx approval



3 Safety modules

- **Safety-M modular** with fieldbus and Industrial Ethernet protocols, with safe protocols such as Profisafe, with safe cross communication
- **Safety-M compact** with integrated signal splitting, with internal signal conversion into RS422 or analogue signals




4 Extension modules

- Emergency stop with several release circuits
- Inputs (OSSD, analogue)
- Outputs (semiconductor, relays)
- Stop categories
- Rotary speed, position monitoring



Functional Safety has become an integral part of mechanical engineering.

With a view to machinery Directive 2006/42/EC, Kübler also provides MTTF values for its standard encoders. This allows the user to perform his own calculations in compliance with standard EN ISO 13849-1.



8 Connection technology

- M12, M23, RJ45 connectors
- Pre-assembled cordsets
- Adapter cable

9 Encoder signal splitting

- Different solutions: in the cable, as a module, fully integrated
- Easy installation
- EMC compliant

5 Decentralised input/output extensions

- With high IP67 protection level, for remote field installation
- Safe inputs and outputs

6 Safety services

- Preparation of risk analyses
- Elaboration of safety concepts
- On-site commissioning and acceptance
- Retrofit of existing machines

7 PC software

- SafeConfig
- SafeMonitor
- SafePLC
- SafePMT

10 Linear encoder systems

- Incremental and absolute linear systems

Functional Safety	System Solutions	
--------------------------	-------------------------	--

Competence for SIL-compliant encoder projects

Integrated: safety is achieved by the intelligent combination of encoder, controller and actuator.
Efficient: adapted to the requirements of the Functional Safety technology.

Machinery Directive 2006/42/EC of the European Parliament applies to all manufacturers of machines, plants or separately sold safety components.


In order to keep both the extent of the work and the costs relating to new tests and approvals manageable, Kübler offers – as your partner for the implementation of your safety concept – its application know-how for safe position and motion sensors.

Procedure to determine the right components for your safety project:

1. Definition of the safety concept, including the drive.
2. Realisation of the safety structure: division into safety-related subsystems.
3. Implementation of a FMEA (failure effect analysis) for every subsystem.
4. Differentiation between "dangerous failures" and "safe failures".
5. The error rate of the whole system including the encoder must lie below a specific threshold.

Relevant standards

Standard IEC 61508 with its parts 1 up to 7 is known as an "umbrella standard".
 Many various industry-specific standards have been derived from it.



Functional Safety	System Solutions
--------------------------	-------------------------

Connection possibilities for safe motion monitoring

Graphic	Components
	1 x certified Sendix SIL encoder 1 x certified Safety-M safety module
	2 x encoders 1 x certified Safety-M safety module
	1 x certified absolute Sendix SIL encoder 1 x certified Safety-M safety module
	1 x encoder 1 x proximity switch 1 x certified Safety-M safety module
	2 x proximity switches 1 x certified Safety-M safety module

Product overview
Basics


Functional Safety	Encoders	
Incremental encoders for the Functional Safety technology	<p>In order to achieve safe information with the incremental encoder, the controller must monitor the validity of the analogue, 90° phase-shifted sine/cosine signals with the help of the function $\sin^2 + \cos^2 = 1$. If this check takes place continuously, a very high diagnostic coverage can be achieved.</p>	<p>In addition, the encoder manufacturer must certify that the information has been assessed from a safety-related point of view, from its generation, through its conditioning, up to its transmission. Only this allows assuming that sine and cosine are independent from each other and are therefore considered as two channels.</p>
Absolute encoders for the Functional Safety technology	<p>Achieving safe absolute position information requires either transmitting a safe position via a safe channel (e.g. safe fieldbus), or transmitting two independent pieces of information via standard interfaces.</p> <p>Safe positioning using an absolute encoder with additional incremental tracks (such as e.g. Sendix SIL) is a particularly smart and cost-effective variant.</p>	<p>In this case, the controller reads the absolute value when initializing and can then set immediately the incremental value internally. From now on, the controller counts the incremental pulses and compares the result with the absolute positions that are also provided by the encoder. This way, relative counting is applied to the first channel and absolute counting to the second.</p>
Safe mechanical connection between encoders and the applications	<p>A 100% reliable mechanical connection is required for a safe function in the applications. Otherwise, no application with a certified encoder will be possible.</p> <p>For hollow shaft encoders, exclusion of faults is achieved with suitably dimensioned mounting attachments. This is the case for all Sendix SIL encoders.</p>	<p>With shaft encoders, a shaft with a feather key or with a flat offers the possibility of safe connection for the application. Also special safety-oriented couplings offer here simple solutions.</p>

According to DIN EN 13849-1 and DIN EN 61800-5-2 up to SIL3/PLe/Cat.4 the following safety functions can be implemented with the encoder:

Safe Switch-Off


STO – Safe Torque OFF

Safe disabling of the torque on the drive by means of an immediate switching off of the energy supply.



SBC – Safe Brake Control


Safe de-energizing of the brake. This allows generating a braking torque.



Safe Standstill


SS1 – Safe Stop 1

Safe monitored standstill followed by the disabling of the torque on the drive.




SS2 – Safe Stop 2

Safe monitored standstill followed by standstill monitoring, while the torque remains enabled.



SOS – Safe Operating Stop


The drive is maintained in its position electrically.



Safe Motion


SLS – Safely-Limited Speed

Safe monitoring of a reduced drive speed.




SSR – Safe Speed Range

The safely monitored speed must be within a corridor.




SDI – Safe Direction

Safe monitoring of the direction of movement of the drive.




SLA – Safely-Limited Acceleration

Monitoring of the maximum acceleration of the drive.



SAR – Safe Acceleration Range

The safely monitored acceleration must be within a corridor.




Functional Safety Safety Functions for the Drives Technology

Safe Monitoring


SSM – Safe Speed Monitor

Safe monitoring of a speed range.




SCA – Safe Cam

Safe monitoring of a defined position range.




SLT – Safely-Limited Torque

Safe monitoring of a maximum torque.



SMT – Safe Motor Temperature


Safe monitoring of a maximum motor temperature.



Safe Positioning


SLP – Safely-Limited Position

Safe monitoring of limit positions = safe software limit switches.



SLI – Safely-Limited Increment

Safe monitoring of an increment for the jog mode.



Glossary

Actuator

The word actuator relates to controlling or driving elements, e.g. motors, relays, frequency converters, valves, signal lights, etc., which convert electrical signals into mechanical movement (or other physical quantities, e.g. pressure, temperature).

American National Standards Institute (ANSI)

Comparable with the German DIN. ANSI is the US American standardization agency and is a member of the International Organization for Standardization (ISO).

Antivalence

Describes two different signals, e.g., for switching contacts, a normally closed and a normally open contact.

AS-Interface (AS-i)

Standard according to IEC 62026-2 for an actuator-sensor interface since 1999.

AS-i Safe

Safety-oriented communication through the standard AS interface (AS Interface Safety at Work).

Austrian Standards Institute (ASI)

Austrian member of the International Organization for Standardization (ISO).

Average Diagnostic Coverage (DCavg)

Describes the total diagnostic coverage to be achieved for a system, contrary to the diagnostic coverage, which is defined for every channel.

B10


The B10 value for components affected by wear is expressed in the number of switching cycles: this is the number of switching cycles for which 10% of the samples failed during an endurance test (or: number of operating cycles after which 10% of the devices failed). The B10 value and the operating cycle allow calculating the failure rate for electromechanical components.

B10d

In contrast to the B10 value, this value describes exclusively the dangerous failures.

Bathtub Curve / Failure Distribution

The failure distribution describes the distribution in time of the failures of materials, electronic or mechanical components. In the safety technology, the used components must lie in the flat area of the failure rate curve. Early failures and failures due to wear are prevented by stating a service life. Early failures and failures due to wear are prevented by stating a service life.



Source: BGIA Report 2/2008

Bit (Binary Digit)

Smallest discrete piece of information. A bit can be allocated the value 0 or 1.

Cable Color Coding

Code according to DIN IEC 757

abbreviation	color
BK	black
BN	brown
RD	red
OG	orange
YE	yellow
GN	green
BU	blue
VT	violet
GY	grey
WH	white
PK	pink
GD	gold
TQ	turquoise
SR	silver


Glossary

Categories (Cat.)

The categories of EN ISO 13849-1 (B, 1, 2, 3 and 4) allow evaluating the performance of safety-relevant parts of a control when failures occur. They describe and classify the system architecture e.g. with redundancies or testing equipment.

Category B:

The control must be designed so that it can withstand the expected influences. System behavior: A failure can lead to the loss of the safety function.




Category 1:

The requirement of B must be met; use of tried and tested safety-relevant components and principles. System behavior: as system behavior B, but with higher safety-related reliability.


Category 2:

The requirement of B must be met; additional safety function check at appropriate intervals. System behavior: the occurrence of a failure can lead to the loss of the safety function between the checks.



Category 3:


The requirement of B must be met, a single failure shall not lead to the loss of the safety function; single failures must be detected. The failure safety is increased by redundancy. System behavior: the safety function always is maintained in case of occurrence of single failures.



Category 4:

The requirement of B must be met; the single failure must be detected prior to or during the following request for the safety function.

The failure safety is increased by redundancy. System behavior: when failures occur, the safety function always remains maintained; the failures are detected in time.



ccw (counter clockwise)

Turning the encoder shaft in counterclockwise direction (in view of the shaft side of the encoder).

cw (clockwise)

Turning the encoder shaft in clockwise direction (in view of the shaft side of the encoder).

CIPsafety

Safe Common Industrial Protocol

Safety-oriented communication via standard EtherNet/IP or Sercos III.

Clock Output / Pulse Output

When wired accordingly, these special outputs apply defined clock signals/clock patterns to the inputs. This allows detecting cross-short-cuts.

Common Cause Failure (CCF)

Failure of several subassemblies due to a common cause (e.g. short-circuit). The CCF allows evaluating whether a system having e.g. a redundant structure withstands sufficiently such failures.

In standard EN ISO 13849-1, measures must be taken against these failures. Points can be scored for various measures, the sum of which must be >60 to demonstrate that the system is resistant enough.

Conformité Européenne (CE) (European Conformity)

The machine manufacturer is to mark his products with the CE mark if he wants to market his machine (Machinery Directive, "Protection against arbitrariness").

Remark: the CE marking for the Low-Voltage Directive is not comparable with the CE marking for the Machinery Directive.

Glossary

Cross Comparison

Cross comparison is the direct comparison of two events, values. In safety technology, this is used e.g. for redundant systems that monitor each other. Every system detects the faulty operation of the other system thanks to the different result of the same operation.

Cross-Short-Cut

Can only occur in case of multichannel device control and is a short-circuit between channels (e.g. in a two-channel sensor circuit).

Cyclic Redundancy Check (CRC)

The cyclic redundancy check, generally called CRC, is a method for determining a test value for data in order to detect errors during transmission or storage. A CRC is calculated prior to the transmission, and the receiver checks the data and calculates a second CRC after the transmission. If both CRCs are identical, the data has not been altered during transmission.

Danger Zone

Area in or around a machine in which a person is exposed to the risk of an injury or damage to health.

Demand Rate

Operating modes are subdivided in so-called demand rates. This allows displaying how frequently the safety function is requested.

A distinction is made between:

- **Low Demand:**
Operating mode with low demand rate, in which the safety function is only carried out upon request to place the system in a defined safe state, with a request frequency that does not exceed once a year.
- **High Demand:**
Operating mode with high demand rate, in which the safety function is only carried out upon request to place the system in a defined safe state, with a request frequency exceeding once a year.
- **Continuous Demand:**
Operating mode with continuous demand, in which the safety function maintains the system in a safe state as a part of the normal operation.

Declaration of Conformity

Certificate issued by the manufacturer of the machine, certifying that the machine meets all relevant Machinery Directive provisions and can therefore be marketed. This is shown to the user by the CE mark.

Deutsches Institut Für Normung (DIN)

German member of the International Organization for Standardization (ISO).

Deutsche Kommission Elektrotechnik Elektronik Informationstechnik (DKE)

Deutsche Kommission Elektrotechnik Elektronik Informationstechnik, a body of the Deutsche Institut für Normung (DIN) and of the Verband der Elektrotechnik, Elektronik und Informationstechnik (VDE).

Diagnostic Coverage (DC)

Diagnostic coverage $\lambda_{dd}/\lambda_{total}$, with

- λ_{dd} , Rate of the detected dangerous failures.
- λ_{total} , Rate of all dangerous failures in total ($\lambda_{dd} + \lambda_{du}$).

$$DC = \frac{\sum \lambda_{dd}}{\sum \lambda_{dd} + \sum \lambda_{du}} = \frac{\sum \lambda_{dd}}{\sum \lambda_d}$$

The diagnostic coverage is subdivided in various classes in standard EN ISO 13849-1:

DC (diagnostic coverage)	
Designation	Range
small	DC < 60 %
low	60 % < DC < 90 %
medium	90 % < DC < 99 %
high	99 % < DC

Diversity

Describes the variety of something. Used in relation with redundancy to describe a redundancy created using different paths, i.e. using different means to realize a required function. It is understood as a strategy for increasing failure safety.

Emergency Stop

Emergency action intended to stop a process or movement that is becoming dangerous.

Endangering

Endangering (due to an event) represents a danger for the user and can lead to injury (potential source of harm).

Failure

Describes the condition of a device that is not able to carry out a requested function, with the exception of the inability during maintenance work, other scheduled actions or the lack of external means.

Failure Behavior

Describes the possibilities for a system to fail.

Failure Exclusion

Ability to resist failures. For certain components, defined failures can be excluded for the time of SRP/CS operation. A short-circuit can e.g. be excluded by safe cable routing. The justification of a failure exclusion must be documented!

Failure In Time (FIT)

Error measure describing the number of failures in 109 hours

$$1Fit = 10^{-9} \text{ 1/h}$$

Glossary

Failure Mode Effect Analysis (FMEA)

Failure mode and effects analysis (failure effects analysis).

Analytic method for the systematic and complete registration of potential failures and failure conditions of components of a system and of their effect.

Failure Modes, Effects and Diagnostic Coverage Analysis (FMEDA)

In addition to the FMEA, the FMEDA determines the Safe Failure Fraction (SFF) as an evaluation parameter for the Functional Safety Management according to IEC 61508.

Failure Probability

A statistical value for the failure of the component/of the system. The failure safety describes the safety achieved.

Failure Safety

Failure safety is the defined safety against a failure. The Performance Level (PL) or the Safety Integrity Level (SIL) describe a measure for failure safety in functional safety technology.

Failure Tolerance

Describes the resistance of a system against failures.

Feedback Loop

Electrical circuit for monitoring the controlled contactors/relays.

The function of the contactors/relays can be monitored by having an evaluation device read back the positively guided auxiliary contacts. If contactor/relay contacts are welded, the evaluation device prevents from re-starting.

Functional Safety (FS)

The part of the safety of an installation (e.g. machine, plant) that depends of the correct operation.

Institut Für Arbeitsschutz (IFA)

The Institute for Occupational Safety and Health of the German statutory accident insurance, former Berufsgenossenschaftliches Institut für Arbeitsschutz (BGIA) is a research and testing institute based in Sankt Augustin near Bonn.

[<http://www.dguv.de/ifa>]

International Electrotechnical Commission (IEC)

The International Electrotechnical Commission is an international standardization organization based in Geneva for standards in the electrotechnical and electronic field. Some standards have been developed jointly with the ISO.

International Standard Organisation (ISO)

International Organization for Standardization.

Harmonized Standard

The type A (basic standards), type B (group standards) and type C (product standards) allow applying the presumption of conformity ("compliance" with the Machinery Directive).

Low Voltage Directive (LVD)

Official designation: Directive 2006/95/EC of the European Parliament and of the Council of 12 December 2006 on the harmonization of the laws of Member States relating to electrical equipment designed for use within certain voltage limits. It is used for the safety of electrically powered devices.

Mean Time Between Failures (MTBF)

Mean time between device failures.

Sum of MTTF (mean time to failure) and MTTR (mean time to repair). The mean time between failures is the time that elapses in normal device or plant operation before a new failure occurs.

Mean Time To Failure (MTTF)

Period of time between the first start-up and a failure.

The MTTF can be determined for components by means of the analysis of field data or predictions. With a constant failure rate, the average value of the failure-free operating time $MTTF = 1/\lambda$, λ being the failure rate of the device (from a statistical point of view, it can be assumed that, after the expiration of the MTTF, 63.2 % of the concerned components have failed).

Mean Time To Dangerous Failure (MTTFd)

Period of time between the first start-up and a dangerous failure.

$$MTTFd = 1/\lambda_d$$

$$MTTFd = 2x MTTF$$

$$MTTFd = B10d/0.1xnop$$

Mean Time To Repair (MTTR)

Mean time necessary for repairing a device.

MTTR is always significantly smaller than MTTF.

Mission Time TM

Identical to the service life.

Muting

Is a bypass function. Neutralization of the safety function with additional sensors, limited in time and in accordance with the intended purpose (EN ISO 13849-1:2006: temporary automatic bypass of a safety function).

National Fire Protection Association (NFPA)

The US-american National Fire Protection Association edits a comprehensive rule book about fire protection (National Fire Codes) that applies mainly in the USA. The NFPA corresponds approximately to the German Vereinigung zur Förderung des Deutschen Brandschutzes.

Glossary

Nationally Recognized Testing Laboratory (NRTL)

This laboratory can test products for use in the USE in compliance with NFPA79. An NRTL listing is equivalent to a certification.

Occupational Safety And Health Administration (OSHA)

US American federal authority in charge of safety issues in the industry. It can be compared with the German Institut für Arbeitsschutz of the German statutory accident insurances. The goal of this organizations is to reduce the number and consequences of accidents at work.

Operating Mode

The operating modes are various predictable conditions of a machine. The machine must be safe in any operating mode. A distinction is e.g. made between automatic operation, manual mode, set-up mode, maintenance mode.

Performance Level (PL)

Ability of safety-related parts to perform a safety function under foreseeable conditions (that should be taken into consideration), in order to achieve the expected risk reduction: from PLa PLe.

Performance Level Required (PLr)

Required Performance Level (see PL).

Probability Of Dangerous Failure Per Hour (PFH)

A failure probability measure of IEC 61508.

Probability Of Dangerous Failure On Demand (PFD)

A failure probability measure of IEC 61508.

Proof Test / Proof Test Interval

Proof test: periodic repeat inspection performed to detect failures in a SRECS so that, if necessary, the system can be reset to or as close as practically possible to an "as-new-condition" (derived from IEC 61508-4).

Presumption of Conformity

When the requirements of the harmonized standards of the Machinery Directive are met, it can be presumed that the requirements of the Machinery Directive are also met.

PUR - Polyurethanes

Polyurethanes are generally soft and elastic plastics or synthetic resins used in cable manufacturing. Used generally here as external sheathing.

PVC – Polyvinyl Chloride

Polyvinyl chloride is a plastic made soft and elastic by the addition of plasticizers and stabilizers, used in cable manufacturing. Used generally here as sheathing or cable insulation.

Qualification

Means the assessment of capabilities (qualifications) that are necessary for a determined task or requirement.

The verification that the capabilities are sufficient to meet the requirements in a reproducible way in practice is the content of the so-called validation.

Quantification

A quantification describes a result statement in the form of a numerical value, in which one or several characteristics of an object or the nature of a situation are reformulated as measurable quantities and numerical values.

Reaction Time

Time between the detection of the hazardous event and the restoration of the safe condition.

Redundancy / Two-Channel Design

Presence of more means than those basically necessary for performing the intended tasks.

Reset

Reset is a switch-on function (ON) that brings a system back to a defined initialization status, it represents a restart interlock.

This may become necessary if the system does not operate correctly after a failure and does not react properly to inputs any more.

Response Time

Time that elapses between the powering of the device and its readiness for operation.

Risk

Combination of the probability of occurrence of damage and of the the extent of damage.

Risk Analysis

The risk analysis is a part of the risk assessment. It identifies the dangers in a machine.

Risk Assessment

Standard ISO 14121 includes procedures that are required for carrying out a risk assessment. The risk assessment includes a risk analysis followed by a risk evaluation.

Risk Evaluation

The risk analysis is a part of the risk assessment. It classifies the dangers in a machine.

Safe State

The safe state is the state in which a machine does not represent any danger for men, machines or the environment.

Glossary

Safety Arrangement

Is required wherever danger for men, machines and environment may occur. It can be achieved e.g. in the form of safety circuits with electronic components.

Safety Component

Component used for ensuring a safety function whose failure and/or malfunction endangers the safety of persons and that is not necessary for machine operation or that may be replaced with components usual for machine operation. Safety components are listed in Annex IV of Machinery Directive 2006/42/EC and receive a CE mark. Examples of safety components:

Sensor-controlled protective equipment (light barriers, safety mats, electromagnetic detectors), automatic mobile protective equipment on machines in compliance with Letter A Number 9, 10 and 11, two-hand circuits, roll-over protection structures and falling-object protective structures.

Safety Integrity Level (SIL)

Safety Integrity Level, a requirement classification according to EN 61508 / EN 61511 / EN 62061. It is used for evaluating electrical/electronic/programmable electronic (E/E/PE) systems in terms of reliability of the safety functions.

Safety Function

Function (e.g. of a machine or control) whose failure (or breakdown) can increase the risk/the risks.

Safety-M

Family name of the safety modules of the Kübler company.

This family today includes several series:

- Safety-M compact
- Safety-M modular
- Safety-M

Safety-M compact is a compact safety controller suitable especially for the drive safety functions. It has limited extension possibilities and is characterized by a very compact design.



Safety-M modular is a compact safety controller suitable especially for the drive safety functions. It is characterized by its freely selectable and modularly extensible functionality.



Safety Related Control Function (SRCF)

Safety-related control function performed by the SRECS with a defined Integrity Level, intended for maintaining the safe state of a machine or preventing an immediate increase of the risks.

Safety Related Electrical Control System (SRECS)

Safety-related electrical control system of a machine whose failure leads to an immediate increase of risks.

Safety Related Parts Of Control Systems (SRP/CS)

Safety-related part of a control system that reacts to safety-related input signals and generates safety-related output signals.

Schweizerische Normen-Vereinigung (SNV)

Swiss member of the International Organization for Standardization (ISO).

Service Life

Describes the maximum time a component may be operated from a safety technology point of view.

Short-Circuit

A practically unopposed conductive connection between two live electrical lines.

Shut-Off Path

Designs the section of the safety system used for shutting down the machine. This often also allows achieving the safe state, and this is why the function of the shut-off paths must be tested during validation.

Single-Failure-Proof

Describes a system that does not lose its safety in spite of a failure. This is classically achieved for systems as from category 3.

SIL Claim Limit (SIL CL)

Safety Integrity Level, a requirement classification according to EN 62061 [refer also to Safety Integrity Level (SIL)].

Sistema

Free software for the evaluation of the safety of controls within the framework of DIN EN ISO 13849-1. Issued by the IFA. The Windows tool simulates the structure of the safety-related control elements on the basis of the so-called planned architectures and calculates reliability values on various levels of detail including the attained performance level.

Glossary

Soiling and Humidity

The IP classification according to EN 60529 describes how the encoder is protected against particles and water. It is described as an abbreviation "IP" followed by two numbers.

These two tables summarise the most used IP ratings.

Protection against particles (first digit)

The higher the number the smaller the particles.

0	Not protected
1	Protected against particles 50 mm and larger
2	Protected against particles 12.5 mm and larger
3	Protected against particles 2.5 mm and larger
4	Protected against particles 1.0 mm and larger
5	Protected against dust
6	Dust proof

Our encoders have a protection up to IP69k.

Protection against water (second digit)

The higher the number, the higher the water pressure can be.

0	Not protected
1	Protected against vertically falling drops of water
2	Protected against vertically falling drops of water when enclosure is tilted up to 15°
3	Protected against spraying water
4	Protected against splashing water
5	Protected against water jets
6	Protected against powerful water jets
7	Protected against the effects of temporary immersion in water
8	Protected against the effects of continuous immersion in water

9k	Acc. to DIN 40050 / Part 9: protected against high-pressure water / steam jet cleaning
----	---

Speed Monitoring

Monitoring of the rotary speed of a mechanical movement (e.g. drive) in a defined speed window. This can be achieved without sensor (current, frequency) or by means of a (generally incremental) encoder.

Start Interlock / Restart

After having triggered a safety function or restored the power supply, the machine / plant must restart. Automatic restarting is only allowed for well-defined exceptions. Automatic restarting is prevented by a safety control device.

Stop Category

Term used in EN 60204-1 to define three different shutdown functions.

Refer to Safety Functions.

Temperature

Working temperature:

Is defined as the environmental temperature, in which the encoder will produce the signals defined in the data sheets.

Operating temperature:

Is defined as the environmental temperature, in which the encoder can be operated without incurring damage.

TPE – Thermoplastic Elastomers

Thermoplastic elastomers are plastics that are soft, as all classical elastomers. The material loses these rubber-elastic properties at high temperatures; it can then be formed.

Two-Hand Operation / Two-Hand Control

Two-hand operation is a safety concept/control unit for working on machines in which a crushing or shearing hazard is possible for the hands and therefore requires two-hand operation.

Working in the hazardous area is required to place or remove parts in presses, punching machines, casting machines and similar machines. The working stroke may only be triggered (started) when both hands have left the hazardous area. This is achieved thanks to a simultaneous and separate actuation of switches or levers. The distance between the operating elements is chosen so as to make one-hand operation impossible.

The rule is standard DIN EN 574.

User Information

The user information includes all indications, instructions, descriptions required for the safe and intended operation of the machine, e.g.: pictograms on the machine, operating instructions, maintenance instructions etc.

Validation

Proof of the reproducibility of a result from a described procedure under defined conditions.

Verification


Proof that suspected or alleged circumstances are true.

Verband der Elektrotechnik, Elektronik und Informationstechnik (VDE)

The Verband der Elektrotechnik, Elektronik und Informationstechnik is a technical-scientific association in Germany. The VDE is committed to a better innovation climate, safety standards, modern engineering education and better public acceptance for technology.

Zero Signal

The zero signal is emitted once per revolution, it can be used e.g. as a reference signal during the first revolution after power on.



Incremental Encoders

Series	Type	Output circuit	Page
Standard, optical	Sine wave output, SIL2/PLd	Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)	56
	Sine wave output, SIL3/PLe	Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)	62
	ATEX/IECEX – Zone 1/21, SIL2/PLd	Sendix SIL 7014FS2 (Shaft)	68
	ATEX/IECEX – Zone 1/21, SIL3/PLe	Sendix SIL 7014FS3 (Shaft)	71



Further incremental encoders you will find in our catalogue "Position and Motion Sensors" or under:
www.kuebler.com/incremental




Incremental Encoders

Standard

Sine wave output, SIL2/PLd, optical

Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)

SinCos



The incremental encoders 5814FS2 and 5834FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 according to EN 61800-5-2 or PLd according to EN ISO 13849-1.

These encoders are particularly suited for applications in the field of safe drive technology.



Safety-Lock™



High rotational speed



Temperature range



High protection level



High shaft load capacity




Shock / vibration resistant



Magnetic field proof



Reverse polarity protection



SinCos



Optical sensor

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- With incremental SinCos tracks.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code Shaft version

8.5814FS2 . 1 X X X . X X X X
Type a b c d e

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"], with feather key

c Output circuit / Power supply

1 = SinCos / 5 V DC

2 = SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

5 = M12 connector, 8 pin, axial

6 = M12 connector, 8 pin, radial

e Pulse rate

1024, 2048

optional on request

- special cable length

- Ex 2/22

Order code Hollow shaft

8.5834FS2 . X X X X . X X X X
Type a b c d e

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"], tapered shaft

c Output circuit / Power supply

1 = SinCos / 5 V DC

2 = SinCos / 10 ... 30 V DC

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

6 = M12 connector, 8 pin, radial

e Pulse rate

1024, 2048

optional on request

- special cable length

- Ex 2/22

Incremental Encoders

Standard Sine wave output, SIL2/PLd, optical		Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)	SinCos
Accessory			Order No.
EMC shield terminal	for top-hat rail mounting		8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml		8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
Connection technology			Order No.
Cordset, pre-assembled	M12 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾		05.00.6041.8211.002M
	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾		8.0000.6901.0002
Connector, self-assembly (straight)	M12 female connector with coupling nut		05.CMB 8181-0
	M23 female connector with coupling nut		8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22		8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.	
Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value ²⁾	2.16 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Power consumption (no load)	5 V DC max. 70 mA 10 ... 30 V DC max. 45 mA
Reverse polarity protection of the power supply (+V)	yes
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics		
Max. speed, shaft version	up to 70°C [158°F]	12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous)
	up to T _{max}	8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F]	9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous)
	up to T _{max}	6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque – at 20°C [68°F]	shaft version	< 0.01 Nm
	hollow shaft version	< 0.03 Nm
Moment of inertia	shaft version	4.0 x 10 ⁻⁶ kgm ²
	hollow shaft version	7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version	min. 34 mm [1.34"]
Load capacity of shaft	radial	80 N
	axial	40 N
Weight		approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529		IP65
EX approval for hazardous areas		optional zone 2 and 22
Working temperature range		-40°C ... +90°C [-40°F ... +194°F] ³⁾
Materials	shaft / hollow shaft	stainless steel
	flange	aluminium
	housing	zinc die-cast housing
	cable	PVC
Shock resistance acc. EN 60068-2-27		500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6		200 m/s ² , 10 ... 150 Hz

- 1) Other lengths available.
- 2) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL2.
- 3) Cable version: -30°C ... +90°C [-22°F ... +194°F] fixed installation.

Incremental Encoders

Standard	Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)	SinCos
Sine wave output, SIL2/PLd, optical		

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes ¹⁾
Pulse rate	1024 / 2048 ppr

Terminal assignment


Output circuit	Type of connection	Cable (isolate unused wires individually before initial start-up)							
1, 2	1, 2, E	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Cable colour:	WH	BN	GN	YE	GY	PK	shield
Output circuit	Type of connection	M23 connector, 12-pin							
1, 2	3, 4	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Pin:	10	12	5	6	8	1	PH ²⁾
Output circuit	Type of connection	M12 connector, 8-pin							
1, 2	5, 6	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Pin:	1	2	3	4	5	6	PH ²⁾

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

Top view of mating side, male contact base



M12 connector, 8-pin



M23 connector, 12-pin

1) Short circuit to 0 V or to output, one channel at a time, supply voltage correctly applied
 2) PH = shield is attached to connector housing

Incremental Encoders


Standard Sine wave output, SIL2/PLd, optical	Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)	SinCos
---	--	---------------

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type 2 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{f7} [0.39]




Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type A (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{h7} [0.39]



(Drawing with M12 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 mm ^{h7} [0.39]



Incremental Encoders

Standard
Sine wave output, SIL2/PLd, optical

Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)

SinCos

Dimensions hollow shaft version

Dimensions in mm [inch]



Flange with torque stop set, rigid

Flange type A

(Drawing with cable)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm



D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]




(Drawing with M12 connector)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible

Flange type 9

(Drawing with M23 connector)

- 1 recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Incremental Encoders

Standard Sine wave output, SIL2/PLd, optical	Sendix SIL 5814FS2 / 5834FS2 (Shaft / Hollow shaft)	SinCos
--	--	---------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with stator coupling, $\varnothing 63$ [2.48] and hollow shaft Flange type B

(Drawing with M23 connector)


- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

- 2 for (4x) M3 screw

D = $\varnothing 10^{H7}$ [0.39]

$\varnothing 12^{H7}$ [0.47]

$\varnothing 14^{H7}$ [0.55]



Incremental Encoders

Flange with stator coupling, $\varnothing 63$ [2.48] and tapered shaft Flange type B


(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button

- 4 SW 4




Incremental Encoders

Standard

Sine wave output, SIL3/PLe, optical

Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)

SinCos



The incremental encoders 5814FS3 and 5834FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 according to EN 61800-5-2 or PLe to EN ISO 13849-1.

These encoders are particularly suited for applications in the field of safe drive technology.



Safety-Lock™



High rotational speed



Temperature range
-40°...+90°C



High protection level



High shaft load capacity




Shock / vibration resistant



Magnetic field proof



Reverse polarity protection



SinCos



Optical sensor

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- With incremental SinCos tracks.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code Shaft version

8.5814FS3 . 1 X X X . X X X X
Type a b c d e

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"], with feather key

c Output circuit / Power supply

1 = SinCos / 5 V DC

2 = SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

5 = M12 connector, 8 pin, axial

6 = M12 connector, 8 pin, radial

e Pulse rate

1024, 2048

optional on request

- special cable length

- Ex 2/22

Order code Hollow shaft

8.5834FS3 . X X X X . X X X X
Type a b c d e

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"], tapered shaft

c Output circuit / Power supply

1 = SinCos / 5 V DC

2 = SinCos / 10 ... 30 V DC

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

6 = M12 connector, 8 pin, radial

e Pulse rate

1024, 2048

optional on request

- special cable length

- Ex 2/22

Incremental Encoders

Standard Sine wave output, SIL3/PLe, optical		Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)	SinCos
Accessory			Order No.
EMC shield terminal	for top-hat rail mounting		8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml		8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
Connection technology			Order No.
Cordset, pre-assembled	M12 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾		05.00.6041.8211.002M
	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾		8.0000.6901.0002
Connector, self-assembly (straight)	M12 female connector with coupling nut		05.CMB 8181-0
	M23 female connector with coupling nut		8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22		8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.	
Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value ²⁾	1.09 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Power consumption (no load)	5 V DC max. 70 mA 10 ... 30 V DC max. 45 mA
Reverse polarity protection of the power supply (+V)	yes
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics		
Max. speed, shaft version	up to 70°C [158°F]	12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous)
	up to T _{max}	8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F]	9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous)
	up to T _{max}	6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque – at 20°C [68°F]	shaft version	< 0.01 Nm
	hollow shaft version	< 0.03 Nm
Moment of inertia	shaft version	4.0 x 10 ⁻⁶ kgm ²
	hollow shaft version	7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version	min. 34 mm [1.34"]
Load capacity of shaft	radial	80 N
	axial	40 N
Weight		approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529		IP65
EX approval for hazardous areas		optional zone 2 and 22
Working temperature range		-40°C ... +90°C [-40°F ... +194°F] ³⁾
Materials	shaft / hollow shaft	stainless steel
	flange	aluminium
	housing	zinc die-cast housing
	cable	PVC
Shock resistance acc. EN 60068-2-27		500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6		200 m/s ² , 10 ... 150 Hz

- 1) Other lengths available.
- 2) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL3.
- 3) Cable version: -30°C ... +90°C [-22°F ... +194°F] fixed installation.

Incremental Encoders

Standard
Sine wave output, SIL3/PLe, optical

Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)

SinCos

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes ¹⁾
Pulse rate	1024 / 2048 ppr

Terminal assignment


Output circuit	Type of connection	Cable (isolate unused wires individually before initial start-up)							
1, 2	1, 2, E	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Cable colour:	WH	BN	GN	YE	GY	PK	shield
Output circuit	Type of connection	M23 connector, 12-pin							
1, 2	3, 4	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Pin:	10	12	5	6	8	1	PH ²⁾
Output circuit	Type of connection	M12 connector, 8-pin							
1, 2	5, 6	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Pin:	1	2	3	4	5	6	PH ²⁾

+V: Encoder power supply +V DC
 0 V: Encoder power supply ground GND (0 V)
 A, \bar{A} : Cosine signal
 B, \bar{B} : Sine signal
 PH \perp : Plug connector housing (Shield)

Top view of mating side, male contact base



M12 connector, 8-pin



M23 connector, 12-pin

1) Short circuit to 0 V or to output, one channel at a time, supply voltage correctly applied
 2) PH = shield is attached to connector housing

Incremental Encoders


Standard Sine wave output, SIL3/PLe, optical	Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)	SinCos
---	--	---------------

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, ϕ 58 [2.28]
Flange type 1 with shaft type 2
 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{f7} [0.39]




Clamping flange, ϕ 58 [2.28]
Flange type 1 with shaft type A
 (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{h7} [0.39]



(Drawing with M12 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 mm ^{h7} [0.39]



Incremental Encoders

Standard
Sine wave output, SIL3/PLe, optical

Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft) SinCos

Dimensions hollow shaft version



Dimensions in mm [inch]

Flange with torque stop set, rigid Flange type A

(Drawing with cable)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm



D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]




(Drawing with M12 connector)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible Flange type 9

(Drawing with M23 connector)

- 1 recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Incremental Encoders

Standard Sine wave output, SIL3/PLe, optical	Sendix SIL 5814FS3 / 5834FS3 (Shaft / Hollow shaft)	SinCos
---	--	---------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with stator coupling, $\varnothing 63$ [2.48] and hollow shaft Flange type B

(Drawing with M23 connector)


- 1 SW 3,
recommended torque for the
clamping ring 2.5 Nm

- 2 for (4x) M3 screw

D = $\varnothing 10^{H7}$ [0.39]

$\varnothing 12^{H7}$ [0.47]

$\varnothing 14^{H7}$ [0.55]



Incremental Encoders

Flange with stator coupling, $\varnothing 63$ [2.48] and tapered shaft Flange type B


(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button

- 4 SW 4



Incremental Encoders

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, optical	Sendix SIL 7014FS2 (Shaft)	SinCos
--	-----------------------------------	---------------



Ex protection and Functional Safety in one device.

The incremental encoders 7014FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 acc. to EN 61800-5-2 or PLd to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- With incremental SinCos tracks.
- Certified mechanical mounting + electronic.

Explosion protection

- "Flameproof-enclosure" version.
- ATEX with EC type examination certificate.
- IECEx with Certificate of Conformity (CoC).

Order code	8.7014 FS2 . 1 XXX . XXXX . XXXX
Shaft version	Type a b c d e f

a Flange 1 = clamping-synchronous flange, IP67 ø 70 mm [2.76"]	c Output circuit / Power supply 1 = SinCos / 5 V DC 2 = SinCos / 10 ... 30 V DC	e Pulse rate 1024, 2048 <i>optional on request - special cable length</i>
b Shaft (ø x L) 2 = 10 x 20 mm [0.39 x 0.79"], with flat 1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key	d Type of connection 1 = axial cable, 2 m [6.56'] PUR 2 = radial cable, 2 m [6.56'] PUR A = axial cable, length > 2 m [6.56'] B = radial cable, length > 2 m [6.56']	f Cable length in dm ¹⁾ 0050 = 5 m [16.40'] 0100 = 10 m [32.81'] 0150 = 15 m [49.21']

Accessory		Order No.
EMC shield terminal	for top-hat rail mounting	8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .	
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .	

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

1) Not applicable with connection types 1 and 2

Incremental Encoders

Standard ATEX / IECEx – Zone 1 / 21, SIL2/PLd, optical	Sendix SIL 7014FS2 (Shaft)	SinCos
--	-----------------------------------	---------------

Technical data

Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009

Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEx PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008

Notes regarding "Functional Safety"

These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.

Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 45 mA
Reverse polarity protection for power supply (+V)	yes
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value¹⁾	2.16 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Mechanical characteristics		
Max. speed		continuous 6 000 min ⁻¹
Starting torque – at 20°C [68°F]		< 0.05 Nm
Moment of inertia		4.0 x 10 ⁻⁶ kgm ²
Load capacity of shaft	radial axial	80 N 40 N
Weight		approx. 1.3 kg [45.86 oz]
Protection acc. to EN 60529		IP67
Working temperature range		-40°C ... +60°C [-40 ... +140°F]
Materials	shaft flange / housing cable	stainless steel seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on request) PUR
Shock resistance acc. EN 60068-2-27		500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6		200 m/s ² , 10 ... 150 Hz

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes ²⁾
Pulse rate	1024 / 2048 ppr

Terminal assignment

Output circuit	Type of connection	Cable (isolate unused wires individually before initial start-up)							
1, 2	1, 2, A, B	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Cable marking:	6	1	7	8	9	10	shield

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- \perp : Plug connector housing (Shield)

1) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL2.

2) Short-circuit with 0 V or output, only one channel at a time, supply voltage correctly applied.

Incremental Encoders

Standard
ATEX/IECEX – Zone 1/21, SIL2/PLd, optical

Sendix SIL 7014FS2 (Shaft)


SinCos

Dimensions

Dimensions in mm [inch]


Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet

- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep



Incremental Encoders

Standard ATEX / IECEx – Zone 1 / 21, SIL3/PLe, optical	Sendix SIL 7014FS3 (Shaft)	SinCos
--	-----------------------------------	---------------



Ex protection and Functional Safety in one device.

The incremental encoders 7014FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 acc. to EN 61800-5-2 or PLe to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Incremental Encoders



Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- With incremental SinCos tracks.
- Certified mechanical mounting + electronic.

Explosion protection

- “Flameproof-enclosure” version.
- ATEX with EC type examination certificate.
- IECEx with Certificate of Conformity (CoC).

Order code 8.7014 FS3 . 1 XXX . XXXX . XXXX
Shaft version Type

<p>a Flange</p> <p>1 = clamping-synchronous flange, IP67 ø 70 mm [2.76"]</p> <p>b Shaft (ø x L)</p> <p>2 = 10 x 20 mm [0.39 x 0.79"], with flat 1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key</p>	<p>c Output circuit / Power supply</p> <p>1 = SinCos / 5 V DC 2 = SinCos / 10 ... 30 V DC</p> <p>d Type of connection</p> <p>1 = axial cable, 2 m [6.56'] PUR 2 = radial cable, 2 m [6.56'] PUR A = axial cable, length > 2 m [6.56'] B = radial cable, length > 2 m [6.56']</p>	<p>e Pulse rate</p> <p>1024, 2048</p> <p><i>optional on request - special cable length</i></p> <p>f Cable length in dm ¹⁾</p> <p>0050 = 5 m [16.40'] 0100 = 10 m [32.81'] 0150 = 15 m [49.21']</p>
--	--	---

Accessory	Order No.
EMC shield terminal for top-hat rail mounting	8.0000.4G06.0000
Screw retention Loctite 243, 5 ml	8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

1) Not applicable with connection types 1 and 2.

Incremental Encoders

Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, optical	Sendix SIL 7014FS3 (Shaft)	SinCos
--	-----------------------------------	---------------

Technical data

Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009

Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEX PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008

Notes regarding "Functional Safety"
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.

Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 45 mA
Reverse polarity protection for power supply (+V)	yes
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value ¹⁾	1.09 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Mechanical characteristics		
Max. speed	continuous 6 000 min ⁻¹	
Starting torque – at 20°C [68°F]	< 0.05 Nm	
Moment of inertia	4.0 x 10 ⁻⁶ kgm ²	
Load capacity of shaft	radial	80 N
	axial	40 N
Weight	approx. 1.3 kg [45.86 oz]	
Protection acc. to EN 60529	IP67	
Working temperature range	-40°C ... +60°C [-40 ... +140°F]	
Materials	shaft	stainless steel
	flange / housing	seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on request)
	cable	PUR
Shock resistance acc. EN 60068-2-27	500 m/s ² , 11 ms	
Vibration resistance acc. EN 60068-2-6	200 m/s ² , 10 ... 150 Hz	

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes ²⁾
Pulse rate	1024 / 2048 ppr

Terminal assignment

Output circuit	Type of connection	Cable (isolate unused wires individually before initial start-up)							
1, 2	1, 2, A, B	Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
		Cable marking:	6	1	7	8	9	10	shield

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- \perp : Plug connector housing (Shield)

1) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL3.
2) Short-circuit with 0 V or output, only one channel at a time, supply voltage correctly applied.

Incremental Encoders


Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, optical	Sendix SIL 7014FS3 (Shaft)	SinCos
---	-----------------------------------	---------------

Dimensions

Dimensions in mm [inch]


Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet

- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep





TYPE: S-MH
S. 7083-12X12-XXXX
1018

REV	DATE	DESCRIPTION
1		
2		
3		
4		
5		
6		
7		
8		
9		
10		

Absolute Encoders - Singleturn

Series	Type	Interface	Page
Standard, optical	SIL2/PLd	Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)	SSI / BiSS-C + SinCos 76
	SIL3/PLe	Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)	SSI / BiSS-C + SinCos 82
	ATEX/IECEX – Zone 1/21, SIL2/PLd	Sendix SIL 7053FS2 (Shaft)	SSI / BiSS-C + SinCos 88
	ATEX/IECEX – Zone 1/21, SIL3/PLe	Sendix SIL 7053FS3 (Shaft)	SSI / BiSS-C + SinCos 92



Further absolute encoders you will find in our catalogue "Position and Motion Sensors" or under:
www.kuebler.com/absolute




Absolute Encoders - Singleturn

Standard
SIL2/PLd, optical


Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)

SSI/BiSS-C + SinCos



The absolute singleturn encoders 5853FS2 and 5873FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 according to EN 61800-5-2 or PLd to EN ISO 13849-1.

The extra strong Safety-Lock™ Design interlocked bearings, the high integration density of the components based on OptoASIC technology and the rugged die-cast housing make these devices ideal also for demanding applications outdoors up to IP65.



Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code
Shaft version

8.5853FS2 . 1 X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"] , with feather key

c Interface / Power supply

3 = SSI or BiSS-C + 2048 ppr SinCos / 5 V DC

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

Order code
Hollow shaft

8.5873FS2 . X X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"] , tapered shaft

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

1) Resolution, preset value and count direction are factory-programmable.

Absolute Encoders - Singleturn

Standard SIL2/PLd, optical	Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
Accessory		Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .	
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .	
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .	
Connection technology		Order No.
Cordset, pre-assembled	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾	8.0000.6901.0002.0031
	M23 female connector with coupling nut, 10 m [32.81'] PVC cable ¹⁾	8.0000.6901.0002.0032
Connector, self-assembly (straight)	M23 female connector with coupling nut	8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22	8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.	
Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value ²⁾	2.16 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Current consumption (no load)	5 V DC max. 70 mA 10 ... 30 V DC max. 45 mA
Reverse polarity protection of the power supply (+V)	yes
Short circuit proof outputs	yes ⁴⁾
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed, shaft version	up to 70°C [158°F] 12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous) up to T _{max} 8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F] 9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous) up to T _{max} 6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque - at 20°C [68°F]	shaft version < 0.01 Nm hollow shaft version < 0.03 Nm
Moment of inertia	shaft version 4.0 x 10 ⁻⁶ kgm ² hollow shaft version 7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version min. 34 mm [1.34"]
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529	IP65
EX approval for hazardous areas	optional zone 2 and 22
Working temperature range	-40°C ... +90°C ³⁾ [-40°F ... +194°F] ³⁾
Material	shaft / hollow shaft stainless steel flange aluminium housing zinc die-cast housing cable PVC
Shock resistance acc. EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

1) Other lengths available.

2) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL2.

3) Cable version: -30°C ... +90°C [-22°F ... +194°F].

4) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders - Singleturn

Standard SIL2/PLd, optical	Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---------------------------------------	--	----------------------------

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at I _{Load} = 20 mA typ 1.3 V
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Code	Binary or gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: If the clock starts cycling within the monoflop time, a second data transfer starts with the same data. If the clock starts cycling after the monoflop time, the data transfer starts with the new values. The update rate is dependent on the clock speed, data length and monoflop-time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Resolution singleturn	10 ... 14 bit and 17 bit ¹⁾
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	<ul style="list-style-type: none"> - Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings - CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input or SET button	
Input	active HIGH
Input type	comparator
Signal level	HIGH min: 60 % of +V, max: +V LOW max: 25 % of +V (Power supply)
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms
Reaction time (DIR input)	1 ms
The encoder can be set to zero at any position by means of a HIGH signal on the SET input or by pressing the optional SET button (with a pencil, ball-point pen or similar). Other preset values can be factory-programmed. The SET input has a signal delay time of approx. 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approx. 15 ms before the new position data can be read. During this time the LED is ON.	

DIR input	
A HIGH signal switches the direction of rotation from the default CW to CCW. This function can also be factory-programmed to be inverted. If DIR is changed when the device is already switched on, then this will be interpreted as an error. The LED will come ON and the status output will switch to LOW.	

Power-on delay	
After Power-ON the encoder requires a time of approx. 150 ms before valid data can be read.	

LED	
The optional LED (red) serves to display various alarm or error messages. In normal operation the LED is OFF.	
If the LED is ON (status output LOW) this indicates:	
<ul style="list-style-type: none"> - Sensor error, singleturn or multeturn (soiling, glass breakage etc.) - LED error, failure or ageing - Over- or under-temperature 	
In the SSI mode, the fault indication can only be reset by switching off the power supply to the device.	


Terminal assignment

Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	1, 2, E	Cable colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	shield

Interface	Type of connection	M23 connector, 12-pin													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	3, 4	Pin:	1	2	3	4	5	6	7	8	9	10	11	12	PH

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- SET: Set input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : cosine signal
- B, \bar{B} : sine signal
- PH \perp : Plug connector housing (shield)

Top view of mating side, male contact base



M23 connector, 12-pin

1) Other options on request.

Absolute Encoders - Singleturn


Standard SIL2/PLd, optical	Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---------------------------------------	--	----------------------------

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type 2 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{h7} [0.39]



Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type A (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{h7} [0.39]



Absolute Encoders
Singleturn

Absolute Encoders - Singleturn

Standard
SIL2/PLd, optical

Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)

SSI/BiSS-C + SinCos

Dimensions hollow shaft version

Dimensions in mm [inch]



Flange with torque stop set, rigid

Flange type A


(Drawing with cable)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible

Flange type 9

(Drawing with M23 connector)

- 1 recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Absolute Encoders - Singleturn

Standard SIL2/PLd, optical	Sendix SIL 5853FS2 / 5873FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---------------------------------------	--	----------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with stator coupling, \varnothing 63 [2.48]

and hollow shaft


Flange type B

(Drawing with M23 connector)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

- 2 for (4x) M3 screw

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Flange with stator coupling, \varnothing 63 [2.48]

and tapered shaft

Flange type B


(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button

- 4 SW 4




Absolute Encoders
Singleturn

Absolute Encoders - Singleturn

Standard
SIL3/PLe, optical


Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)

SSI/BiSS-C + SinCos



The absolute singleturn encoders 5853FS3 and 5873FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 according to EN 61800-5-2 or PLe to EN ISO 13849-1.

The extra strong Safety-Lock™ Design interlocked bearings, the high integration density of the components based on OptoASIC technology and the rugged die-cast housing make these devices ideal also for demanding applications outdoors up to IP65.



Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code
Shaft version

8.5853FS3 . 1 X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"], with feather key

c Interface / Power supply

3 = SSI or BiSS-C + 2048 ppr SinCos / 5 V DC

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Input/output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

Order code
Hollow shaft

8.5873FS3 . X X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"], tapered shaft

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Input/output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

1) Resolution, preset value and count direction are factory-programmable.

Absolute Encoders - Singleturn

Standard SIL3/PLe, optical	Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
Accessory		Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .	
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .	
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .	
Connection technology		Order No.
Cordset, pre-assembled	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾	8.0000.6901.0002.0031
	M23 female connector with coupling nut, 10 m [32.81'] PVC cable ¹⁾	8.0000.6901.0002.0032
Connector, self-assembly (straight)	M23 female connector with coupling nut	8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22	8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.	
Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value ²⁾	1.09 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Current consumption (no load)	5 V DC max. 70 mA 10 ... 30 V DC max. 45 mA
Reverse polarity protection of the power supply (+V)	yes
Short circuit proof outputs	yes ⁴⁾
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed, shaft version	up to 70°C [158°F] [158°F] 12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous) up to T _{max} 8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F] [158°F] 9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous) up to T _{max} 6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque - at 20°C [68°F]	shaft version < 0.01 Nm hollow shaft version < 0.03 Nm
Moment of inertia	shaft version 4.0 x 10 ⁻⁶ kgm ² hollow shaft version 7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version min. 34 mm [1.34"]
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529	IP65
EX approval for hazardous areas	optional zone 2 and 22
Working temperature range	-40°C ... +90°C ³⁾ [-40°F ... +194°F] ³⁾
Material	shaft / hollow shaft stainless steel flange aluminium housing zinc die-cast housing cable PVC
Shock resistance acc. EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

1) Other lengths available.

2) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL3.

3) Cable version: -30°C ... +90°C [-22°F ... +194°F].

4) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders - Singleturn

Standard SIL3/PLe, optical	Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---------------------------------------	--	----------------------------

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at $I_{Load} = 20\text{ mA}$ typ 1.3 V
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Code	Binary or gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	$\leq 15\ \mu\text{s}$
Note: If the clock starts cycling within the monoflop time, a second data transfer starts with the same data. If the clock starts cycling after the monoflop time, the data transfer starts with the new values. The update rate is dependent on the clock speed, data length and monoflop-time.	
Data refresh rate	resolution ≤ 14 bit $\leq 1\ \mu\text{s}$ resolution ≥ 15 bit $4\ \mu\text{s}$
Status and parity bit	on request

BiSS-C interface	
Resolution singleturn	10 ... 14 bit and 17 bit ¹⁾
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	$< 10\ \mu\text{s}$, depends on the clock rate and the data length
Data refresh rate	$\leq 1\ \mu\text{s}$
Note:	<ul style="list-style-type: none"> - Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings - CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} ($\pm 10\%$)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input or SET button	
Input	active HIGH
Input type	comparator
Signal level	HIGH min: 60 % of +V, max: +V LOW max: 25 % of +V (Power supply)
Input current	$< 0.5\text{ mA}$
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms
Reaction time (DIR input)	1 ms
The encoder can be set to zero at any position by means of a HIGH signal on the SET input or by pressing the optional SET button (with a pencil, ball-point pen or similar). Other preset values can be factory-programmed. The SET input has a signal delay time of approx. 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approx. 15 ms before the new position data can be read. During this time the LED is ON.	

DIR input	
A HIGH signal switches the direction of rotation from the default CW to CCW. This function can also be factory-programmed to be inverted. If DIR is changed when the device is already switched on, then this will be interpreted as an error. The LED will come ON and the status output will switch to LOW.	

Power-on delay	
After Power-ON the encoder requires a time of approx. 150 ms before valid data can be read.	

LED	
The optional LED (red) serves to display various alarm or error messages. In normal operation the LED is OFF.	
If the LED is ON (status output LOW) this indicates:	
<ul style="list-style-type: none"> - Sensor error, singleturn or multeturn (soiling, glass breakage etc.) - LED error, failure or ageing - Over- or under-temperature 	
In the SSI mode, the fault indication can only be reset by switching off the power supply to the device.	


Terminal assignment

Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	1, 2, E	Cable colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	shield

Interface	Type of connection	M23 connector, 12-pin													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	3, 4	Pin:	1	2	3	4	5	6	7	8	9	10	11	12	PH

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- SET: Set input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : cosine signal
- B, \bar{B} : sine signal
- PH \perp : Plug connector housing (shield)

Top view of mating side, male contact base



M23 connector, 12-pin

1) Other options on request.

Absolute Encoders - Singleturn


Standard SIL3/PLe, optical	Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---------------------------------------	--	----------------------------

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type 2 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{h7} [0.39]



Clamping flange, $\varnothing 58$ [2.28] Flange type 1 with shaft type A (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{h7} [0.39]



Absolute Encoders
Singleturn

Absolute Encoders - Singleturn

Standard
SIL3/PLe, optical

Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)

SSI/BiSS-C + SinCos

Dimensions hollow shaft version

Dimensions in mm [inch]



Flange with torque stop set, rigid

Flange type A


(Drawing with cable)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible

Flange type 9

(Drawing with M23 connector)

- 1 recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Absolute Encoders - Singleturn

Standard SIL3/PLe, optical	Sendix SIL 5853FS3 / 5873FS3 (Shaft / Hollow shaft)	SSI / BiSS-C + SinCos
---------------------------------------	--	------------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]


Flange with stator coupling, $\varnothing 63$ [2.48] and hollow shaft

Flange type B
(Drawing with M23 connector)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

- 2 for (4x) M3 screw

$D = \varnothing 10^{H7}$ [0.39]
 $\varnothing 12^{H7}$ [0.47]
 $\varnothing 14^{H7}$ [0.55]



Flange with stator coupling, $\varnothing 63$ [2.48] and tapered shaft


Flange type B
(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button

- 4 SW 4



Absolute Encoders - Singleturn

Standard

ATEX/IECEX – Zone 1/21, SIL2/PLd, optical

Sendix SIL 7053FS2 (Shaft)

SSI/BiSS-C + SinCos




Ex protection and Functional Safety in one device.

The absolute singleturn encoders 7053FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 acc. to EN 61800-5-2 or PLd to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Ex approval



Safety-Lock™



High rotational speed



High protection level



High shaft load capacity



Shock / vibration resistant



Magnetic field proof



Short-circuit proof



Reverse polarity protection



Optical sensor



Seawater-resistant

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Explosion protection

- “Flameproof-enclosure” version.
- ATEX with EC type examination certificate.
- IECEx with Certificate of Conformity (CoC).

Order code Shaft version

8.7053FS2 . 1 X 4 X . X X 2 1 . XXXX
Type a b c d e f g h i 1)

a Flange

1 = clamping-synchronous flange, IP67, ø 70 mm [2.76"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key

c Interface / Power supply

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 2 m [6.56'] PUR

2 = radial cable, 2 m [6.56'] PUR

A = axial cable, length > 2 m [6.56']

B = radial cable, length > 2 m [6.56']

preferred length see i, e. g.: 0100 = 10 m [32.81']

e Code

B = SSI, Binary
C = BiSS-C, Binary
G = SSI, Gray

f Resolution 2)

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Inputs / Outputs 2)

2 = SET input

h Options

1 = no option

i Cable length in dm 1)

0050 = 5 m [16.40']

0100 = 10 m [32.81']

0150 = 15 m [49.21']

optional on request
- special cable length

1) Not applicable with connection types 1 and 2.

2) Resolution, preset value and counting direction factory-programmable.

Absolute Encoders - Singleturn

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, optical		Sendix SIL 7053FS2 (Shaft)	SSI/BiSS-C + SinCos
Accessory			Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000	
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000	
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .		

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009

Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEX PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value ¹⁾	2.16 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 45 mA
Reverse polarity protection for power supply (+V)	yes
Short circuit proof outputs	yes ²⁾
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed	continuous 6 000 min ⁻¹
Starting torque – at 20°C [68°F]	< 0.05 Nm
Moment of inertia	4.0 x 10 ⁻⁶ kgm ²
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 1.3 kg [45.86 oz]
Protection acc. to EN 60529	IP67
Working temperature range	-40°C ... +60°C [-40 ... +140°F]
Material	shaft stainless steel flange / housing seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on req.) cable PUR
Shock resistance acc. to EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. to EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

1) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL2.
2) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders - Singleturn

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, optical	Sendix SIL 7053FS2 (Shaft)	SSI/BiSS-C + SinCos
---	-----------------------------------	----------------------------

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at $I_{Load} = 20\text{ mA}$ typ 1.3 V
Singleturn resolution	10...14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or Gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: if clock starts cycling within monoflop time a second data transfer starts with the same data. If clock starts cycling after monoflop time, the data transfer starts with updated values. The update rate depends on clock speed, data length and monoflop time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	<ul style="list-style-type: none"> – Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings – CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input	
Input	HIGH active
Input type	comparator
Signal level (+V = Power supply)	HIGH min. 60 % of +V max. +V LOW max. 25 % of +V
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms

The encoder can be set to zero at any position by means of a High signal on the SET input. Other preset values can be factory-programmed. The SET input has a signal delay time of approximately 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approximately 15 ms before the new position data can be read.

Power-ON delay	
After Power-ON, the device requires a time of approximately 150 ms before valid data can be read.	

Terminal assignment

Interface	Type of connection	Features	Cable (isolate unused wires individually before initial start-up)												
			Signal:	0 V	+V	C+	C-	D+	D-	SET	A	\bar{A}	B	\bar{B}	\perp
4	1, 2, A, B	SET	Cable marking:	6	1	2	3	4	5	11	7	8	9	10	shield

+V: Encoder power supply +V DC

0 V: Encoder power supply ground GND (0 V)

C+, C-: Clock signal

D+, D-: Data signal

SET: SET input. The current position becomes defined as position zero.

A, \bar{A} : Cosine signal

B, \bar{B} : Sine signal

\perp : Protective earth

1) Other options on request.

Absolute Encoders - Singleturn


Standard ATEX / IECEx – Zone 1/21, SIL2/PLd, optical	Sendix SIL 7053FS2 (Shaft)	SSI / BiSS-C + SinCos
---	-----------------------------------	------------------------------

Dimensions

Dimensions in mm [inch]


Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet

- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep



Absolute Encoders - Singleturn

Standard

ATEX/IECEX – Zone 1/21, SIL3/PLe, optical

Sendix SIL 7053FS3 (Shaft)

SSI/BiSS-C + SinCos




Ex protection and Functional Safety in one device.

The absolute singleturn encoders 7053FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 acc. to EN 61800-5-2 or PLe to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Ex approval



Safety-Lock™



High rotational speed



High protection level



High shaft load capacity




Shock / vibration resistant



Magnetic field proof



Short-circuit proof



Reverse polarity protection



Optical sensor



Seawater-resistant

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Explosion protection

- “Flameproof-enclosure” version.
- ATEX with EC type examination certificate.
- IECEx with Certificate of Conformity (CoC).

Order code Shaft version

8.7053FS3 . 1 X 4 X . X X 2 1 . XXXX
Type a b c d e f g h i 1)

a Flange

1 = clamping-synchronous flange, IP67, ø 70 mm [2.76"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key

c Interface / Power supply

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 2 m [6.56'] PUR

2 = radial cable, 2 m [6.56'] PUR

A = axial cable, length > 2 m [6.56']

B = radial cable, length > 2 m [6.56']

preferred length see i, e. g.: 0100 = 10 m [32.81']

e Code

B = SSI, Binary
C = BiSS-C, Binary
G = SSI, Gray

f Resolution 2)

A = 10 bit ST

1 = 11 bit ST

2 = 12 bit ST

3 = 13 bit ST

4 = 14 bit ST

7 = 17 bit ST

g Inputs / Outputs 2)

2 = SET input

h Options

1 = no option

i Cable length in dm 1)

0050 = 5 m [16.40']

0100 = 10 m [32.81']

0150 = 15 m [49.21']

optional on request
- special cable length

1) Not applicable with connection types 1 and 2.

2) Resolution, preset value and counting direction factory-programmable.

Absolute Encoders - Singleturn

Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, optical		Sendix SIL 7053FS3 (Shaft)	SSI/BiSS-C + SinCos
Accessory			Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000	
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000	
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .		

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009

Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEX PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008

Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.	

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value ¹⁾	1.09 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 45 mA
Reverse polarity protection for power supply (+V)	yes
Short circuit proof outputs	yes ²⁾
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed	continuous 6 000 min ⁻¹
Starting torque – at 20°C [68°F]	< 0.05 Nm
Moment of inertia	4.0 x 10 ⁻⁶ kgm ²
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 1.3 kg [45.86 oz]
Protection acc. to EN 60529	IP67
Working temperature range	-40°C ... +60°C [-40 ... +140°F]
Material	shaft stainless steel flange / housing seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on req.) cable PUR
Shock resistance acc. to EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. to EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

- 1) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit. The encoder evaluation unit must meet at least the requirements for SIL3.
- 2) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders - Singleturn

Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, optical	Sendix SIL 7053FS3 (Shaft)	SSI/BiSS-C + SinCos
---	-----------------------------------	----------------------------

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at $I_{Load} = 20\text{ mA}$ typ 1.3 V
Singleturn resolution	10...14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or Gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: if clock starts cycling within monoflop time a second data transfer starts with the same data. If clock starts cycling after monoflop time, the data transfer starts with updated values. The update rate depends on clock speed, data length and monoflop time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	<ul style="list-style-type: none"> – Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings – CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input	
Input	HIGH active
Input type	comparator
Signal level (+V = Power supply)	HIGH min. 60 % of +V max. +V LOW max. 25 % of +V
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms

The encoder can be set to zero at any position by means of a High signal on the SET input. Other preset values can be factory-programmed. The SET input has a signal delay time of approximately 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approximately 15 ms before the new position data can be read.

Power-ON delay	
After Power-ON, the device requires a time of approximately 150 ms before valid data can be read.	

Terminal assignment

Interface	Type of connection	Features	Cable (isolate unused wires individually before initial start-up)												
			Signal:	0 V	+V	C+	C-	D+	D-	SET	A	\bar{A}	B	\bar{B}	\perp
4	1, 2, A, B	SET	Cable marking:	6	1	2	3	4	5	11	7	8	9	10	shield

+V: Encoder power supply +V DC

0 V: Encoder power supply ground GND (0 V)

C+, C-: Clock signal

D+, D-: Data signal

SET: SET input. The current position becomes defined as position zero.

A, \bar{A} : Cosine signal

B, \bar{B} : Sine signal

\perp : Protective earth

1) Other options on request.

Absolute Encoders - Singleturn


Standard ATEX / IECEx – Zone 1 / 21, SIL3/PLe, optical	Sendix SIL 7053FS3 (Shaft)	SSI / BiSS-C + SinCos
---	-----------------------------------	------------------------------

Dimensions

Dimensions in mm [inch]

Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet


- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Absolute Encoders
Singleturn

Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep





Absolute Encoders – Multiturn

Series	Type	Interface	Page
Standard, optical	SIL2/PLd, mechanical Multiturn	Sendix SIL 5863FS2 / 5883FS2 (Shaft/Hollow s.)	SSI / BiSS-C + SinCos 98
	SIL3/PLe, mechanical Multiturn	Sendix SIL 5863FS3 / 5883FS3 (Shaft/Hollow s.)	SSI / BiSS-C + SinCos 104
	ATEX/IECEX – Zone 1/21, SIL2/PLd, mech. MT	Sendix SIL 7063FS2 (Shaft)	SSI / BiSS-C + SinCos 110
	ATEX/IECEX – Zone 1/21, SIL3/PLe, mech. MT	Sendix SIL 7063FS3 (Shaft)	SSI / BiSS-C + SinCos 114




Further absolute encoders you will find in our catalogue "Position and Motion Sensors" or under:
www.kuebler.com/absolute



Absolute Encoders – Multiturn

Standard
SIL2/PLd, mech. Multiturn, optical

Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos



The absolute multiturn encoders 5863FS2 and 5883FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 according to EN 61800-5-2 or PLd to EN ISO 13849-1.

The extra strong Safety-Lock™ Design interlocked bearings, the high integration density of the components based on OptoASIC technology and the rugged die-cast housing make these devices ideal also for demanding applications outdoors up to IP65.




Mechanical drive



Safety-Lock™



High rotational speed



Temperature range
-40°...+90°C



High protection level
IP



High shaft load capacity



Shock / vibration resistant



Magnetic field proof



Reverse polarity protection



SinCos



Optical sensor

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code
Shaft version

8.5863FS2 . 1 X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"], with feather key

c Interface / Power supply

3 = SSI or BiSS-C + 2048 ppr SinCos / 5 V DC

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

Order code
Hollow shaft

8.5883FS2 . X X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces. Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.



a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"], tapered shaft

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

1) Resolution, preset value and count direction are factory-programmable.

Absolute Encoders – Multiturn

Standard SIL2/PLd, mech. Multiturn, optical	Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
--	--	----------------------------

Accessory		Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000

Bellows coupling, safety-oriented You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories.

Safety modules Safety-M compact / modular You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety.

LED SSI display 570 / 575 Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display.

Connection technology		Order No.
Cordset, pre-assembled	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾	8.0000.6901.0002.0031
	M23 female connector with coupling nut, 10 m [32.81'] PVC cable ¹⁾	8.0000.6901.0002.0032
Connector, self-assembly (straight)	M23 female connector with coupling nut	8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22	8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"
These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.
Additional functions can be found in the operating manual.

Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value ²⁾	2.16 x 10 ⁻⁹ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Current consumption (no load)	5 V DC max. 80 mA 10 ... 30 V DC max. 50 mA
Reverse polarity protection of the power supply (+V)	yes
Short circuit proof outputs	yes ⁴⁾
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed, shaft version	up to 70°C [158°F] [158°F] 12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous) up to T _{max} 8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F] [158°F] 9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous) up to T _{max} 6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque - at 20°C [68°F]	shaft version < 0.01 Nm hollow shaft version < 0.03 Nm
Moment of inertia	shaft version 4.0 x 10 ⁻⁶ kgm ² hollow shaft version 7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version min. 34 mm [1.34"]
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529	IP65
EX approval for hazardous areas	optional zone 2 and 22
Working temperature range	-40°C ... +90°C ³⁾ [-40°F ... +194°F] ³⁾
Material	shaft / hollow shaft stainless steel flange aluminium housing zinc die-cast housing cable PVC
Shock resistance acc. EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

- 1) Other lengths available.
- 2) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL2.
- 3) Cable version: -30°C ... +90°C [-22°F ... +194°F].
- 4) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders – Multiturn

Standard
SIL2/PLd, mech. Multiturn, optical

Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at I _{Load} = 20 mA typ 1.3 V
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: If the clock starts cycling within the monoflop time, a second data transfer starts with the same data. If the clock starts cycling after the monoflop time, the data transfer starts with the new values. The update rate is dependent on the clock speed, data length and monoflop-time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Resolution singleturn	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	<ul style="list-style-type: none"> – Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings – CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input or SET button	
Input	HIGH active
Input type	comparator
Signal level	HIGH min: 60 % of +V, max: +V LOW max: 25 % of +V (Power supply)
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms
Reaction time (DIR input)	1 ms
The encoder can be set to zero at any position by means of a HIGH signal on the SET input or by pressing the optional SET button (with a pencil, ball-point pen or similar). Other preset values can be factory-programmed. The SET input has a signal delay time of approx. 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approx. 15 ms before the new position data can be read. During this time the LED is ON.	

DIR input
A HIGH signal switches the direction of rotation from the default CW to CCW. This function can also be factory-programmed to be inverted. If DIR is changed when the device is already switched on, then this will be interpreted as an error. The LED will come ON and the status output will switch to LOW.

Power-on delay
After Power-ON the encoder requires a time of approx. 150 ms before valid data can be read.

LED
The optional LED (red) serves to display various alarm or error messages. In normal operation the LED is OFF.
If the LED is ON (status output LOW) this indicates:

- Sensor error, singleturn or multiturn (soiling, glass breakage etc.)
- LED error, failure or ageing
- Over- or under-temperature

In the SSI mode, the fault indication can only be reset by switching off the power supply to the device.


Terminal assignment

Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	1, 2, E	Cable colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	shield
Interface	Type of connection	M23 connector, 12-pin													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	3, 4	Pin:	1	2	3	4	5	6	7	8	9	10	11	12	PH

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- SET: Set input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : cosine signal
- B, \bar{B} : sine signal
- PH \perp : Plug connector housing (shield)

1) Other options on request.

Top view of mating side, male contact base



M23 connector, 12-pin

Absolute Encoders – Multiturn


Standard
SIL2/PLd, mech. Multiturn, optical **Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos**

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, ø 58 [2.28]
Flange type 1 with shaft type 2
 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{h7} [0.39]



Clamping flange, ø 58 [2.28]
Flange type 1 with shaft type A
 (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{h7} [0.39]



Absolute Encoders
Multiturn

Absolute Encoders – Multiturn

Standard
SIL2/PLd, mech. Multiturn, optical

Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos

Dimensions hollow shaft version

Dimensions in mm [inch]



Flange with torque stop set, rigid

Flange type A


(Drawing with cable)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible

Flange type 9

(Drawing with M23 connector)

- 1 recommended torque for the clamping ring 2.5 Nm

D = \varnothing 10^{H7} [0.39]
 \varnothing 12^{H7} [0.47]
 \varnothing 14^{H7} [0.55]



Absolute Encoders – Multiturn

Standard SIL2/PLd, mech. Multiturn, optical	Sendix SIL 5863FS2 / 5883FS2 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
--	--	----------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with stator coupling, $\varnothing 63$ [2.48]

and hollow shaft

Flange type B

(Drawing with M23 connector)


- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

- 2 for (4x) M3 screw

$D = \varnothing 10^{H7}$ [0.39]

$\varnothing 12^{H7}$ [0.47]

$\varnothing 14^{H7}$ [0.55]



Flange with stator coupling, $\varnothing 63$ [2.48]

and tapered shaft

Flange type B


(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button


- 4 SW 4



Absolute Encoders – Multiturn

Standard
SIL3/PLe, mech. Multiturn, optical

Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos



The absolute multiturn encoders 5863FS3 and 5883FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 according to EN 61800-5-2 or PLe to EN ISO 13849-1.

The extra strong Safety-Lock™ Design interlocked bearings, the high integration density of the components based on OptoASIC technology and the rugged die-cast housing make these devices ideal also for demanding applications outdoors up to IP65.



Mechanical drive



Safety-Lock™




High rotational speed



Temperature range
-40°...+90°C



High protection level
IP



High shaft load capacity




Shock / vibration resistant



Magnetic field proof



Reverse polarity protection



SinCos



Optical sensor

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Flexible

- Shaft and hollow shaft versions.
- Cable and connector variants.
- Various mounting options available.

Order code
Shaft version

8.5863FS3 . 1 X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces.



Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.

a Flange

1 = clamping flange, IP65, ø 58 mm [2.28"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

A = 10 x 20 mm [0.39 x 0.79"], with feather key

c Interface / Power supply

3 = SSI or BiSS-C + 2048 ppr SinCos / 5 V DC

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 1 m [3.28'] PVC

2 = radial cable, 1 m [3.28'] PVC

3 = M23 connector, 12 pin, axial

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

Order code
Hollow shaft

8.5883FS3 . X X X X . X X 2 X
Type a b c d e f g h

If for each parameter of an encoder the underlined preferred option is selected, then the delivery time will be 10 working days for a maximum of 10 pieces.



Qts. up to 50 pcs. of these types generally have a delivery time of 15 working days.

a Flange

9 = with torque stop, flexible, IP65

A = with torque stop set, rigid, IP65

B = with stator coupling, IP65, ø 63 mm [2.48"]

b Hollow shaft

3 = ø 10 mm [0.39"]

4 = ø 12 mm [0.47"]

5 = ø 14 mm [0.55"]

K = ø 10 mm [0.39"], tapered shaft

d Type of connection

2 = radial cable, 1 m [3.28'] PVC

E = tangential cable, 1 m [3.28'] PVC

4 = M23 connector, 12 pin, radial

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ¹⁾

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Input / output ¹⁾

2 = SET, DIR input

h Options (Service)

1 = no option

2 = Status LED

3 = SET button and status LED

optional on request

- special cable length

- Ex 2/22

1) Resolution, preset value and count direction are factory-programmable.

Absolute Encoders – Multiturn

Standard SIL3/PLe, mech. Multiturn, optical	Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
---	--	----------------------------

Accessory		Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000

Bellows coupling, safety-oriented You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories.

Safety modules Safety-M compact / modular You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety.

LED SSI display 570 / 575 Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display.

Connection technology		Order No.
Cordset, pre-assembled	M23 female connector with coupling nut, 2 m [6.56'] PVC cable ¹⁾	8.0000.6901.0002.0031
	M23 female connector with coupling nut, 10 m [32.81'] PVC cable ¹⁾	8.0000.6901.0002.0032
Connector, self-assembly (straight)	M23 female connector with coupling nut	8.0000.5012.0000
	M23 female connector with coupling nut, Ex zone 2/22	8.0000.5012.0000.Ex

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data

Notes regarding "Functional Safety"
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality.
Additional functions can be found in the operating manual.

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value ²⁾	1.09 x 10 ⁻⁹ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007

Electrical characteristics	
Power supply	5 V DC ±5 % or 10 ... 30 V DC
Current consumption (no load)	5 V DC max. 80 mA 10 ... 30 V DC max. 50 mA
Reverse polarity protection of the power supply (+V)	yes
Short circuit proof outputs	yes ⁴⁾
UL approval	File 224618
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU

EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005

Mechanical characteristics	
Max. speed, shaft version	up to 70°C [158°F] [158°F] 12 000 min ⁻¹ , 10 000 min ⁻¹ (continuous) up to T _{max} 8 000 min ⁻¹ , 5 000 min ⁻¹ (continuous)
Max. speed, hollow shaft version	up to 70°C [158°F] [158°F] 9 000 min ⁻¹ , 6 000 min ⁻¹ (continuous) up to T _{max} 6 000 min ⁻¹ , 3 000 min ⁻¹ (continuous)
Starting torque - at 20°C [68°F]	shaft version < 0.01 Nm hollow shaft version < 0.03 Nm
Moment of inertia	shaft version 4.0 x 10 ⁻⁶ kgm ² hollow shaft version 7.0 x 10 ⁻⁶ kgm ²
Insertion depth for shaft	hollow shaft version min. 34 mm [1.34"]
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 0.45 kg [15.87 oz]
Protection acc. to EN 60529	IP65
EX approval for hazardous areas	optional zone 2 and 22
Working temperature range	-40°C ... +90°C ³⁾ [-40°F ... +194°F] ³⁾
Material	shaft / hollow shaft stainless steel flange aluminium housing zinc die-cast housing cable PVC
Shock resistance acc. EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

- 1) Other lengths available.
- 2) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL3.
- 3) Cable version: -30°C ... +90°C [-22°F ... +194°F].
- 4) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders – Multiturn

Standard
SIL3/PLe, mech. Multiturn, optical

Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at $I_{Load} = 20\text{ mA}$ typ 1.3 V
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: If the clock starts cycling within the monoflop time, a second data transfer starts with the same data. If the clock starts cycling after the monoflop time, the data transfer starts with the new values. The update rate is dependent on the clock speed, data length and monoflop-time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Resolution singleturn	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	<ul style="list-style-type: none"> - Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings - CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input or SET button	
Input	HIGH active
Input type	comparator
Signal level	HIGH min: 60 % of +V, max: +V LOW max: 25 % of +V (Power supply)
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms
Reaction time (DIR input)	1 ms
The encoder can be set to zero at any position by means of a HIGH signal on the SET input or by pressing the optional SET button (with a pencil, ball-point pen or similar). Other preset values can be factory-programmed. The SET input has a signal delay time of approx. 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approx. 15 ms before the new position data can be read. During this time the LED is ON.	

DIR input
A HIGH signal switches the direction of rotation from the default CW to CCW. This function can also be factory-programmed to be inverted. If DIR is changed when the device is already switched on, then this will be interpreted as an error. The LED will come ON and the status output will switch to LOW.

Power-on delay
After Power-ON the encoder requires a time of approx. 150 ms before valid data can be read.

LED
The optional LED (red) serves to display various alarm or error messages. In normal operation the LED is OFF.
If the LED is ON (status output LOW) this indicates:
- Sensor error, singleturn or multiturn (soiling, glass breakage etc.)
- LED error, failure or ageing
- Over- or under-temperature
In the SSI mode, the fault indication can only be reset by switching off the power supply to the device.


Terminal assignment

Interface	Type of connection	Cable (isolate unused wires individually before initial start-up)													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	1, 2, E	Cable colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	shield
Interface	Type of connection	M23 connector, 12-pin													
		Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
3, 4	3, 4	Pin:	1	2	3	4	5	6	7	8	9	10	11	12	PH

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- SET: Set input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : cosine signal
- B, \bar{B} : sine signal
- PH \perp : Plug connector housing (shield)

1) Other options on request.

Top view of mating side, male contact base



M23 connector, 12-pin

Absolute Encoders – Multiturn


Standard
SIL3/PLe, mech. Multiturn, optical **Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos**

Dimensions shaft version

Dimensions in mm [inch]


Clamping flange, ø 58 [2.28]
Flange type 1 with shaft type 2
 (Drawing with cable)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- D = 10 ^{H7} [0.39]



Clamping flange, ø 58 [2.28]
Flange type 1 with shaft type A
 (Drawing with M23 connector)

- 1 3 x M3, 6 [0.24] deep
- 2 3 x M4, 8 [0.32] deep
- 3 Feather key DIN 6885 - A - 3x3x6
- D = 10 ^{H7} [0.39]



Absolute Encoders
Multiturn

Absolute Encoders – Multiturn

Standard
SIL3/PLe, mech. Multiturn, optical

Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft) SSI/BiSS-C + SinCos

Dimensions hollow shaft version

Dimensions in mm [inch]



Flange with torque stop set, rigid

Flange type A


(Drawing with cable)

1 SW 3, recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Torque pin with rectangular sleeve with M4 thread





Flange with torque stop, flexible

Flange type 9

(Drawing with M23 connector)

1 recommended torque for the clamping ring 2.5 Nm

D = \emptyset 10^{H7} [0.39]
 \emptyset 12^{H7} [0.47]
 \emptyset 14^{H7} [0.55]



Absolute Encoders – Multiturn

Standard SIL3/PLe, mech. Multiturn, optical	Sendix SIL 5863FS3 / 5883FS3 (Shaft / Hollow shaft)	SSI/BiSS-C + SinCos
--	--	----------------------------

Dimensions hollow shaft version

Dimensions in mm [inch]

Flange with stator coupling, $\varnothing 63$ [2.48]

and hollow shaft


Flange type B

(Drawing with M23 connector)

- 1 SW 3, recommended torque for the clamping ring 2.5 Nm

- 2 for (4x) M3 screw

D = $\varnothing 10^{H7}$ [0.39]
 $\varnothing 12^{H7}$ [0.47]
 $\varnothing 14^{H7}$ [0.55]



Flange with stator coupling, $\varnothing 63$ [2.48]

and tapered shaft

Flange type B


(Drawing with tangential cable outlet)

- 1 for (4x) M3 screw

- 2 Status LED

- 3 SET button

- 4 SW 4



Absolute Encoders – Multiturn

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, mech. Multiturn, optical	Sendix SIL 7063FS2 (Shaft)	SSI / BiSS-C + SinCos
--	-----------------------------------	------------------------------




Ex protection and Functional Safety in one device.

The absolute multiturn encoders 7063FS2 of the Sendix SIL family are suited for use in safety-related applications up to SIL2 acc. to EN 61800-5-2 or PLd to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Ex approval



Safety-Lock™



High rotational speed



High protection level



High shaft load capacity



Shock / vibration resistant



Magnetic field proof



Short-circuit proof



Reverse polarity protection



Optical sensor



Seawater-resistant

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL2 acc. to EN 61800-5-2.
- Suitable for applications up to PLd acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Explosion protection

- “Flameproof-enclosure” version.
- ATEX with EC type examination certificate.
- IECEx with Certificate of Conformity (CoC).

Order code	8.7063FS2	.1	X	4	X	.X	X	X	2	1	.XXXX
Shaft version	Type	a	b	c	d	e	f	g	h	i ¹⁾	

a Flange

1 = clamping-synchronous flange, IP67, ø 70 mm [2.76"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key

c Interface / Power supply

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 2 m [6.56'] PUR

2 = radial cable, 2 m [6.56'] PUR

A = axial cable, length > 2 m [6.56']

B = radial cable, length > 2 m [6.56']

preferred length see **i**, e. g.: 0100 = 10 m [32.81']

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution ²⁾

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Inputs / Outputs ²⁾

2 = SET input

h Options

1 = no option

i Cable length in dm ¹⁾

0050 = 5 m [16.40']

0100 = 10 m [32.81']

0150 = 15 m [49.21']

*optional on request
- special cable length*

1) Not applicable with connection types 1 and 2.

2) Resolution, preset value and counting direction factory-programmable.

Absolute Encoders – Multiturn

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, mech. Multiturn, optical		Sendix SIL7063FS2 (Shaft)	SSI/BiSS-C + SinCos
Accessory			Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000	
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000	
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .		

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data	
Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009
Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEX PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008
Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL2 acc. to EN 61800-5-2 and PLd to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.	
Safety characteristics	
Classification	PLd / SIL2
System structure	2 channel (Cat. 3 / HFT = 1)
PFH_d value ¹⁾	2.16 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007
Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 50 mA
Reverse polarity protection for power supply (+V)	yes
Short circuit proof outputs	yes ²⁾
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU
EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005
Mechanical characteristics	
Max. speed	continuous 6 000 min ⁻¹
Starting torque – at 20°C [68°F]	< 0.05 Nm
Moment of inertia	4.0 x 10 ⁻⁶ kgm ²
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 1.3 kg [45.86 oz]
Protection acc. to EN 60529	IP67
Working temperature range	-40°C ... +60°C [-40 ... +140°F]
Material	shaft stainless steel flange / housing seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on req.) cable PUR
Shock resistance acc. to EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. to EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

1) The specified value is based on a diagnostic coverage of 90 %, that must be achieved with an encoder evaluation unit.

The encoder evaluation unit must meet at least the requirements for SIL2.

2) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders – Multiturn

Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, mech. Multiturn, optical	Sendix SIL 7063FS2 (Shaft)	SSI/BiSS-C + SinCos
--	-----------------------------------	----------------------------

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at I _{Load} = 20 mA typ 1.3 V
Singleturn resolution	10...14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or Gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: if clock starts cycling within monoflop time a second data transfer starts with the same data. If clock starts cycling after monoflop time, the data transfer starts with updated values. The update rate depends on clock speed, data length and monoflop time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	– Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings – CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input	
Input	HIGH active
Input type	comparator
Signal level (+V = Power supply)	HIGH min. 60 % of +V max. +V LOW max. 25 % of +V
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms

The encoder can be set to zero at any position by means of a High signal on the SET input. Other preset values can be factory-programmed. The SET input has a signal delay time of approximately 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approximately 15 ms before the new position data can be read.

Power-ON delay	
After Power-ON, the device requires a time of approximately 150 ms before valid data can be read.	

Terminal assignment

Interface	Type of connection	Features	Cable (isolate unused wires individually before initial start-up)												
			Signal:	0 V	+V	C+	C-	D+	D-	SET	A	\bar{A}	B	\bar{B}	\perp
4	1, 2, A, B	SET	Cable marking:	6	1	2	3	4	5	11	7	8	9	10	shield

+V: Encoder power supply +V DC

0 V: Encoder power supply ground GND (0 V)

C+, C-: Clock signal

D+, D-: Data signal

SET: SET input. The current position becomes defined as position zero.

A, \bar{A} : Cosine signal

B, \bar{B} : Sine signal

\perp : Protective earth

1) Other options on request.

Absolute Encoders – Multiturn


Standard ATEX/IECEX – Zone 1/21, SIL2/PLd, mech. Multiturn, optical	Sendix SIL7063FS2 (Shaft)	SSI/BiSS-C + SinCos
--	----------------------------------	----------------------------

Dimensions

Dimensions in mm [inch]


Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet

- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep



Absolute Encoders
Multiturn

Absolute Encoders – Multiturn

Standard

ATEX/IECEX – Zone 1/21, SIL3/PLe, mech. Multiturn, optical

Sendix SIL 7063FS3 (Shaft)

SSI / BiSS-C + SinCos




Ex protection and Functional Safety in one device.

The absolute multiturn encoders 7063FS3 of the Sendix SIL family are suited for use in safety-related applications up to SIL3 acc. to EN 61800-5-2 or PLe to EN ISO 13849-1.

In addition, these devices ensure Ex protection in a compact 70 mm housing out of seawater-resistant aluminium.



Ex approval



Safety-Lock™



High rotational speed



High protection level



High shaft load capacity



Shock / vibration resistant



Magnetic field proof



Short-circuit proof



Reverse polarity protection



Optical sensor



Seawater-resistant

Functional Safety

- Encoder with individual certificate from IFA / TÜV.
- Suitable for applications up to SIL3 acc. to EN 61800-5-2.
- Suitable for applications up to PLe acc. to EN ISO 13849-1.
- SSI or BiSS-C interface with incremental SinCos tracks with 2048 ppr.
- Certified mechanical mounting + electronic.

Explosion protection

- “Flameproof-enclosure” version.
- ATEX with EC type examination certificate.
- IECEX with Certificate of Conformity (CoC).

Order code Shaft version

8.7063FS3 . 1 X 4 X . X X 2 1 . XXXX
Type a b c d e f g h i 1)

a Flange

1 = clamping-synchronous flange, IP67, ø 70 mm [2.76"]

b Shaft (ø x L)

2 = 10 x 20 mm [0.39 x 0.79"], with flat

1 = 12 x 25 mm [0.47 x 0.98"], with keyway for 4 x 4 mm [0.16 x 0.16"] key

c Interface / Power supply

4 = SSI or BiSS-C + 2048 ppr SinCos / 10 ... 30 V DC

d Type of connection

1 = axial cable, 2 m [6.56'] PUR

2 = radial cable, 2 m [6.56'] PUR

A = axial cable, length > 2 m [6.56']

B = radial cable, length > 2 m [6.56']

preferred length see i, e. g.: 0100 = 10 m [32.81']

e Code

B = SSI, Binary

C = BiSS-C, Binary

G = SSI, Gray

f Resolution 2)

A = 10 bit ST + 12 bit MT

1 = 11 bit ST + 12 bit MT

2 = 12 bit ST + 12 bit MT

3 = 13 bit ST + 12 bit MT

4 = 14 bit ST + 12 bit MT

7 = 17 bit ST + 12 bit MT

g Inputs / Outputs 2)

2 = SET input

h Options

1 = no option

i Cable length in dm 1)

0050 = 5 m [16.40']

0100 = 10 m [32.81']

0150 = 15 m [49.21']

optional on request
- special cable length

1) Not applicable with connection types 1 and 2.

2) Resolution, preset value and counting direction factory-programmable.

Absolute Encoders – Multiturn

Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, mech. Multiturn, optical		Sendix SIL7063FS3 (Shaft)	SSI/BiSS-C + SinCos
Accessory			Order No.
EMC shield terminal	For top-hat rail mounting	8.0000.4G06.0000	
Screw retention	Loctite 243, 5 ml	8.0000.4G05.0000	
Bellows coupling, safety-oriented	You will find an overview of our couplings for Sendix SIL shaft encoders in the accessories section or under www.kuebler.com/accessories .		
Safety modules Safety-M compact / modular	You will find an overview of our systems and components for Functional Safety and the corresponding software in the safety technology section or under www.kuebler.com/safety .		
LED SSI display 570 / 575	Electronic position display up to 32 bit. You will find an overview in the accessories section or under www.kuebler.com/position_display .		

Further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

Technical data	
Explosion protection ATEX	
EC type-examination certificate	PTB09 ATEX 1106 X
Category (gas)	II 2 G Ex d IIC T4 - T6 Gb
Category (dust)	II 2D Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	EN 60079-0: 2009; EN 60079-1: 2007; EN 60079-31: 2009
Explosion protection IECEx	
Certificate of Conformity (CoC)	IECEX PTB 13.0026 X
Category (gas)	Ex d IIC T4 - T6 Gb
Category (dust)	Ex tb IIIC T135°C - T85°C Db IP6x
Relevant standards	IEC 60079-0:2007; IEC 60079-1:2007; IEC 60079-31:2008
Notes regarding "Functional Safety"	
These encoders are suitable for use in safety-related systems up to SIL3 acc. to EN 61800-5-2 and PLe to EN ISO 13849-1 in conjunction with controllers or evaluation units, which possess the necessary functionality. Additional functions can be found in the operating manual.	
Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value ¹⁾	1.09 x 10 ⁻⁸ h ⁻¹
Proof-test interval	20 years
Relevant standards	EN ISO 13849-1:2008; EN ISO 13849-2:2013; EN 61800-5-2:2007
Electrical characteristics	
Power supply	10 ... 30 V DC
Current consumption (no load)	max. 50 mA
Reverse polarity protection for power supply (+V)	yes
Short circuit proof outputs	yes ²⁾
CE compliant acc. to	EMC guideline 2004/108/EC ATEX guideline 94/9/EC Machinery directive 2006/42/EC
RoHS compliant acc. to	guideline 2011/65/EU
EMC	
Relevant standards	EN 55011 Class B :2009 / A1:2010 EN 61000-6-3 :2007 / A1:2011 EN 61000-6-2 :2005
Mechanical characteristics	
Max. speed	continuous 6 000 min ⁻¹
Starting torque – at 20°C [68°F]	< 0.05 Nm
Moment of inertia	4.0 x 10 ⁻⁶ kgm ²
Load capacity of shaft	radial 80 N axial 40 N
Weight	approx. 1.3 kg [45.86 oz]
Protection acc. to EN 60529	IP67
Working temperature range	-40°C ... +60°C [-40 ... +140°F]
Material	shaft stainless steel flange / housing seawater-resistant Al, type AISiMgMn (EN AW-6082) (stainless steel on request) cable PUR
Shock resistance acc. to EN 60068-2-27	500 m/s ² , 11 ms
Vibration resistance acc. to EN 60068-2-6	200 m/s ² , 10 ... 150 Hz

1) The specified value is based on a diagnostic coverage of 99 %, that must be achieved with an encoder evaluation unit.
The encoder evaluation unit must meet at least the requirements for SIL3.
2) Short circuit to 0 V or to output, one channel at a time, power supply correctly applied.

Absolute Encoders – Multiturn

Standard	Sendix SIL 7063FS3 (Shaft)	SSI / BiSS-C + SinCos
ATEX / IECEx – Zone 1/21, SIL3/PLe, mech. Multiturn, optical		

SSI interface	
Output driver	RS485 transceiver type
Permissible load / channel	max. 20 mA
Signal level	HIGH typ 3.8 V LOW at I _{Load} = 20 mA typ 1.3 V
Singleturn resolution	10...14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary or Gray
SSI clock rate	50 kHz ... 2 MHz
Monoflop time	≤ 15 μs
Note: if clock starts cycling within monoflop time a second data transfer starts with the same data. If clock starts cycling after monoflop time, the data transfer starts with updated values. The update rate depends on clock speed, data length and monoflop time.	
Data refresh rate	resolution ≤ 14 bit ≤ 1 μs resolution ≥ 15 bit 4 μs
Status and parity bit	on request

BiSS-C interface	
Singleturn resolution	10 ... 14 bit and 17 bit ¹⁾
Number of revolutions	4096 (12 bit)
Code	Binary
Clock rate	up to 10 MHz
Max. update rate	< 10 μs, depends on the clock rate and the data length
Data refresh rate	≤ 1 μs
Note:	– Bidirectional, factory programmable parameters are: resolution, code, direction, alarms and warnings – CRC data verification

SinCos interface	
Max. frequency -3dB	400 kHz
Signal level	1 V _{pp} (±10 %)
Short circuit proof	yes
Pulse rate	2048 ppr

SET input	
Input	HIGH active
Input type	comparator
Signal level (+V = Power supply)	HIGH min. 60 % of +V max. +V LOW max. 25 % of +V
Input current	< 0.5 mA
Min. pulse duration (SET)	10 ms
Timeout after SET signal	14 ms

The encoder can be set to zero at any position by means of a High signal on the SET input. Other preset values can be factory-programmed. The SET input has a signal delay time of approximately 1 ms. Once the SET function has been triggered, the encoder requires an internal processing time of approximately 15 ms before the new position data can be read.

Power-ON delay	
After Power-ON, the device requires a time of approximately 150 ms before valid data can be read.	

Terminal assignment

Interface	Type of connection	Features	Cable (isolate unused wires individually before initial start-up)												
			Signal:	0 V	+V	C+	C-	D+	D-	SET	A	\bar{A}	B	\bar{B}	\perp
4	1, 2, A, B	SET	Cable marking:	6	1	2	3	4	5	11	7	8	9	10	shield

+V: Encoder power supply +V DC

0 V: Encoder power supply ground GND (0 V)

C+, C-: Clock signal

D+, D-: Data signal

SET: SET input. The current position becomes defined as position zero.

A, \bar{A} : Cosine signal

B, \bar{B} : Sine signal

\perp : Protective earth

1) Other options on request.

Absolute Encoders – Multiturn


Standard ATEX/IECEX – Zone 1/21, SIL3/PLe, mech. Multiturn, optical	Sendix SIL7063FS3 (Shaft)	SSI/BiSS-C + SinCos
--	----------------------------------	----------------------------

Dimensions

Dimensions in mm [inch]


Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 1 with axial cable outlet


- 1 6 x M4, 10 [0.39] deep
- 2 Keyway for DIN 6885-A-4x4x25 key



Clamping-synchronous flange, \varnothing 70 [2.76]
Shaft type 2 with radial cable outlet

- 1 6 x M4, 10 [0.39] deep





Kubler
Safety-M
SMBS

PROFINET
PROFIsafe

ESC
Service

↑
Mode

Set
↓

OK

+ASI 1-

+ASI 1-

+ASI 1-

ASI
+PWR-

Power
Profinet

Config Error

U ASI

ASI Active

Prog Enable

Prog Mode

AUX


1 2
3 4
5 6
SI - Safe Input


1 2
3 4
5 6
SO - Safe Output


X31

X41

Safety Modules

Safety-M compact			Type	Page
Basic module 	Speed monitoring	1 axis	SMC1	120

Safety-M modular			Type	Page
Basic modules 	Digital	With USB diagnostic interface	SMBD.420	124
	Digital	With Ethernet diagnostic interface	SMBD.32E	127
	Gateway, universal	CANopen	SMBU.021	130
	Gateway, universal	PROFIBUS DP	SMBU.031	133
	Gateway, universal	EtherCAT	SMBU.0B1	136
	Gateway, universal	PROFINET IO	SMBU.0C1	139
	Gateway, universal	Ethernet / IP	SMBU.0D1	142
	Gateway, safe	PROFIsafe over PROFIBUS DP	SMBS.S31	145
	Gateway, safe	PROFIsafe over PROFINET IO	SMBS.SC1	148

Expansion modules 	Axis expansion	Incremental, HTL / Push-pull	EMAI.012	151
	Axis expansion	Incremental, SinCos	EMAI.022	154
	Axis expansion	Absolute, SSI, SinCos, TTL / RS422	EMAA.032	157
	I/O expansion	Relay 1 x 4 contacts	EMIO.SR.004	160
	I/O expansion	Relay 2 x 4 contacts	EMIO.SR.008	163
	I/O expansion	Digital 8 + 8 / 4	EMIO.SIO.048	166
	I/O expansion	Digital 16 / 8 + 1	EMIO.SIO.810	169
	I/O expansion	Digital 8 / 4 + 4 / 2	EMIO.SIO.420	172
	I/O expansion	Digital 4 / 2 + 4	EMIO.SIO.204	175
	I/O expansion	Digital 2 / 1 + 2	EMIO.SIO.10xP	178
	I/O expansion	Digital (non safe) 8 + 8	EMIO.IO.880	181

Safety-M			Type	Page
Basic modules	Speed monitoring	1 axis	MS1	184
	Speed and position monitoring	1 axis	MSP1	188
	Speed monitoring	2 axes	MS2	192
	Speed and position monitoring	2 axes	MSP2	196

Expansion modules	I/O expansion	Digital	EM3	200
	I/O expansion	Relay	EM4	202

Bus modules	Communication module	DeviceNet	BM11	204
	Communication module	CANopen	BM21	206
	Communication module	PROFIBUS DP	BM31	208
	Communication module	EtherCAT	BMB1	210
	Communication module	PROFINET IO	BMC1	212

Safety Modules

Safety-M compact Basic module	Speed monitoring – SMC1	1 axis
--------------------------------------	--------------------------------	---------------



SMC1 is a compact safety module of the Safety-M family with integrated drive monitoring for one axis.

For optimal integration in existing safety circuits or for upgrading old machines.

Parameterizable by means of a removable control unit or a simple PC software.



1- and 2-encoder solutions (HTL/proximity switch, TTL/RS422, SinCos) are supported for the safe speed detection.

- Extensive library of pre-configured safe sensors and command devices.
- Complete range of speed-related safe drive monitoring functions equivalent to EN 61800-5-2 already integrated in firmware (e.g. SS1, SS2, SOS, SLS, SDI, SSM).
- Different encoder interfaces for TTL / RS422, SinCos and HTL / Push-Pull / proximity switch.
- Integrated signal splitter for encoder signal forwarding (optional).
- Snap-on installation on 35 mm C profile rail.

- LED on the front side indicates operating state.
- Removable control and diagnosis display (optional).
- 4/2 safe input lines, 8/4 safe shut-off channels.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- 1 analogue output 4 ... 20 mA (optional).

Order code	8 . SMC1 . XXX 241	Available end of 2014
a Encoder interface	b Internal signal splitting	c Analogue output
1 = 1 x Sub-D SinCos 2 = 2 x Sub-D SinCos	0 = without S = with	0 = without A = 4 ... 20 mA

Accessory	Order No.
Control and diagnostic display, OLED touch screen	8.SMCB.000
Programming cable, Multi-USB Adapter	05.C162RK1
Shield terminal for encoder cable, C profile rail	8.0000.4G06.0000
Connection technology	Order No.
Cordset, pre-assembled 2 m ¹⁾	
for Sendix SIL encoders	
cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6V00.0002.0085
cable with 1 x M12 / 1 x Sub-D, 9-pin	8.0000.6V00.0002.0084
cable, single-ended / 1 x Sub-D, 9-pin, male connector	8.0000.6V00.0002.0087
cable, single-ended / 1 x Sub-D, 9-pin, female connector	8.0000.6V00.0002.0086

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

¹⁾ Other lengths available

Safety Modules

Safety-M compact Basic module	Speed monitoring – SMC1	1 axis
--	--------------------------------	---------------

Technical data

General data	
Digital input lines	4 / 2
Digital output lines	8 / 4
Safe relay outputs	1
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Drive monitoring - number of axis	1 axis

Electrical characteristics	
Power supply	24 V DC / 2 A
Tolerance	±20 %
Power consumption (no load)	max. 150 mA
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA
Rated data digital outputs	24 V DC / 250 mA
Rated data relay	24 V DC / 5 A

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +70°C [-13°F ...+158°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178
CE compliant acc. to	EMC guideline 2004/108/EC Machinery directive 2006/42/EC Low voltage guideline 2006/95/EC
RoHS compliant acc. to	guideline 2011/65/EU

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 3 / HFT = 1)
PFH _d value	6.0 x 10 ⁻⁸ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1:2008 EN 62061:2005

EMC	
Relevant standards	EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	50 x 100 x 165 mm [1.97 x 3.94 x 6.50"]
Weight	390 g [13.76 oz]
Mounting	snap-on mounting on standard head rail

SinCos interface (IN) X6, X7	
Type of connection	Sub-D, 9-pin
Signal	SinCos
Frequency	max. 500 kHz
Signal level	1 V _{pp} (±20 %)

Incremental interface (IN) X8, X9	
Type of connection	pluggable terminals, 7-pin
Signal	RS422 / TTL
Frequency	max. 500 kHz

Incremental interface (IN) X10	
Type of connection	pluggable terminals, 5-pin
Signal	proximity switch / HTL
Frequency	max. 250 kHz
Signal level	PNP (24 V DC)

Incremental interface (OUT) X2	
Type of connection	pluggable terminals, 8-pin
Signal	HTL / Push-Pull
Frequency	max. 250 kHz


Incremental interface (OUT) X4	
Type of connection	pluggable terminals, 7-pin
Signal	RS422 / TTL, analogue
Frequency	max. 500 kHz, 4 ... 20 mA

SinCos interface (OUT) X5	
Type of connection	Sub-D, 9-pin
Signal	SinCos
Frequency	max. 500 kHz

USB interface X12	
Type	USB-B female connector
Standard	USB 1.0

LED display		
ERROR (yellow)	steadily on	error
	flashing	peripheral alarm
ON (green)		power on

DIP switch S1



ON		
OFF	1	Factory setting
	2	Self-test report
	3	Programming mode




Safety Modules

**Safety-M compact
Basic module**

Speed monitoring – SMC1

1 axis

Terminal assignment





Interface	Sub-D female connector										
Terminal X6 / X7	Signal: SinCos	A	\bar{B}	B	+V	0 V	-	-	-	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

Interface	Sub-D male connector										
Terminal X5	Signal: SinCos	A	\bar{B}	B	-	0 V	-	-	-	\bar{A}	\perp
	Pin:	1	2	3	4	5	6	7	8	9	PH

- +V: Power supply encoder +V DC
- 0 V: Encoder power supply ground GND (0V)
- A, \bar{A} : Cosine signal / Incremental channel A
- B, \bar{B} : Sine signal / Incremental channel B
- PH \perp : Plug connector housing (Shield)

Sub-D female connector, 9-pin Sub-D male connector, 9-pin




Safety Modules

Safety-M compact Basic module	Speed monitoring – SMC1	1 axis
--	--------------------------------	---------------


Dimensions

Dimensions in mm [inch]

Basic module



Control and diagnostic display



Safety Modules

**Safety-M modular
Basic module**

With USB diagnostic interface – SMBD.420

Digital



SMBD is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 8 / 4 safe inputs and 2 safe shut-off channels.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Speed-related safe drive monitoring functions via counting inputs (e.g. SS1, SOS, SLS, SSM).
- Extended drive monitoring via axis expansion module EMAX (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Basic unit comes with 4 safe input lines and 2 safe shut-off channels. The 4 safe inputs can also be used as 8 standard inputs.

- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Parameterizable inputs for HTL/Push-Pull sensors for direct speed monitoring up to 4 kHz, also as e.g. proximity switch.
- AS-i master functionality with up to 31 safe slaves.
- Reduced module width and therefore costs saving at cabinet level.
- Easy, fast and comfortable wiring, without topological restrictions.

Order No.

SMBD Basic module

8.SMBD.420

Accessory

		Order No.
Memory chip card	replacement (10 pieces), 32 kB / 256 kbits	8.SMCC.032
USB-Programming cable	2 m length	05.68784.002M
SafeMonitor license	single user software license	8.SMSW.000

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI

Axis expansion for incremental encoders.

EMAA

Axis expansion for absolute encoders.

EMIO

Input / output expansion.



Safety Modules

Safety-M modular Basic module	With USB diagnostic interface – SMBD.420	Digital
--------------------------------------	---	----------------

Technical data

General data	
Safe digital input lines	8 / 4, OSSD compatible
Safe digital output lines	2
Type of connection	pluggable terminals, Spring-loaded
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC / 4 A
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.08 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 / AC:2009 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service			
S11 ... S18	LED yellow	OFF	contact (S11 ... S18) open
		BLINK 1Hz	cross short-cut
		ON	contact (S11 ... S18) closed
SM	LED green	OFF	AS-i voltage faulty
		BLINK 1Hz	protection mode and SafeMonitor active
		ON	protection mode active
	LED yellow	BLINK 1Hz	service button, status 'Teach error'
		ON	service button, status 'Ready'
	LED red	BLINK 1Hz	configuration mode and SafeMonitor active
	ON	configuration mode active	
ASI M	LED green	OFF	offline, monitor mode
		BLINK 1Hz	master: programming mode, no error
		ON	master: protected mode, no error
	LED red	BLINK 1Hz	peripheral error without config error
		ON	config. error, auto addressing impossible
	S01 ... S02	LED yellow	OFF
		BLINK 1Hz	restart interlock
		ON	output (S01 ... S02) on
	LED red	ON	AUX voltage missing

Encoder interface terminal X31 / X41		
Signal	HTL/proximity switch	
Frequency	max. 4 kHz, resolution 0.1 Hz	
Axes	2 x 2 channel PLd, SIL2 – speed + standstill 2 x 1 channel PLc, SIL1 – speed	
Inputs status	yellow	
Speed monitoring	1 channel	X31: S52 input 1 S61 input 2 X41: S72 input 3 S81 input 4
	2 channel	X31: S52 input 1.1 S61 input 1.2 X41: S72 input 2.1 S81 input 2.2

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

Safety Modules


Safety-M modular Basic module

With USB diagnostic interface – SMBD.420

Digital

Terminal assignment


X11		X21		X31	
1	2	1	2	1	2
Terminal S11	Terminal S12	Terminal S31	Terminal S32	Terminal S51	Terminal S52
Test / Clock / Signalling output	Input (NO), OSSD compatible / Proxi	Test / Clock / Signalling output	Input (NO), OSSD compatible / Proxi	Test / Clock / Signalling output	Input (NO), OSSD compatible / Proxi
Input (NO), OSSD compatible / Proxi	Input (NO), OSSD compatible / Proxi	Input (NO), OSSD compatible / Proxi	Input (NO), OSSD compatible / Proxi	Input (NO), OSSD compatible / Proxi	Input (NO), OSSD compatible / Proxi
Input (NO / NC), OSSD compatible / Proxi	Test / Signalling output	Input (NO / NC), OSSD compatible / Proxi	Test / Signalling output	Input (NO / NC), OSSD compatible / Proxi	Test / Signalling output
Test / Signalling output		Input (NO / NC), OSSD compatible / Proxi		Input (NO / NC), OSSD compatible / Proxi	
		Test / Signalling output		Test / Signalling output	



X41		X51		X61	
1	2	1	2	1	2
Terminal S71	Terminal S72	Terminal I.14	Terminal 0 V	Terminal ASI+	Terminal ASI-
Test / Clock / Signalling output	Input (NO), OSSD compatible / Proxi	Semiconductor output 1	Ground connection for semiconductor output	External power supply connection	External power supply connection
Input (NO), OSSD compatible / Proxi	Input (NO / NC), OSSD compatible / Proxi	Ground connection for semiconductor output 2	Terminal 2.14		
Input (NO / NC), OSSD compatible / Proxi	Test / Signalling output	Ground connection for semiconductor output	Terminal 0 V		
Test / Signalling output					

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module	With Ethernet diagnostic interface – SMBD.32E	Digital
--------------------------------------	--	----------------



SMBD is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 2 safe shut-off channels.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Speed-related safe drive monitoring functions via counting inputs (e.g. SS1, SOS, SLS, SSM).
- Extended drive monitoring via axis expansion module EMAX (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Basic unit comes with 3 safe input lines and 2 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Parameterizable inputs for HTL/Push-Pull sensors for direct speed monitoring up to 4 kHz, also as e.g. proximity switch.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Reduced module width and therefore costs saving at cabinet level.
- Easy, fast and comfortable wiring, without topological restrictions.

Safety Modules

Order No.	
SMBD	Basic module
	8.SMBD.32E

Accessory		Order No.
Memory chip card	replacement (10 pieces), 32 kB / 256 kbits	8.SMCC.032
SafeMonitor license	single user software license	8.SMSW.000
Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI Axis expansion for incremental encoders.
EMAA Axis expansion for absolute encoders.
EMIO Input / output expansion.



Safety Modules

Safety-M modular Basic module	With Ethernet diagnostic interface – SMBD.32E	Digital
--------------------------------------	--	----------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	2
Type of connection	pluggable terminals, spring-loaded
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC / 4 A
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ... +131°F]
Storage temperature	-25°C ... +85°C [-13°F ... +185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.08 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 / AC:2009 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service			
SI1 ... SI8	LED yellow	OFF	contact (SI1 ... SI8) open
		BLINK 1Hz	cross short-cut
		ON	contact (SI1 ... SI8) closed
SM	LED green	OFF	AS-i voltage faulty
		BLINK 1Hz	protection mode and SafeMonitor active
		ON	protection mode active
	LED yellow	BLINK 1Hz	service button, status 'Teach error'
		ON	service button, status 'Ready'
	LED red	BLINK 1Hz	configuration mode and SafeMonitor active
		ON	configuration mode active
ASI M	LED green	OFF	offline, monitor mode
		BLINK 1Hz	master: programming mode, no error
		ON	master: protected mode, no error
	LED red	BLINK 1Hz	peripheral error without config error
		ON	config error, auto addressing impossible
S01 ... S02	LED yellow	OFF	output (S01 ... S02) off
		BLINK 1Hz	restart interlock
		ON	output (S01 ... S02) on
	LED red	ON	AUX voltage missing

Encoder interface terminal X31	
Signal	HTL/proximity switch
Frequency	max. 4 kHz, 0.1 Hz
Axes	2 x 2 channel PLd, SIL2 – speed + standstill 2 x 1 channel PLc, SIL1 – speed
Inputs status	yellow
Speed monitoring	1 channel X31: S52 input 1 S61 input 2 2 channel X31: S52 input 1.1 S61 input 1.2


AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

Safety Modules

Safety-M modular Basic module	With Ethernet diagnostic interface – SMBD.32E	Digital
--	--	----------------

Terminal assignment


X11				X21				X31			
Test / Clock / Signalling output	Terminal S11	1	⊗	Test / Clock / Signalling output	Terminal S31	1	⊗	Test / Clock / Signalling output	Terminal S51	1	⊗
Input (NO), OSSD compatible / Proxi	Terminal S12	2	⊗	Input (NO), OSSD compatible / Proxi	Terminal S32	2	⊗	Input (NO), OSSD compatible / Proxi	Terminal S52	2	⊗
Input (NO / NC), OSSD compatible / Proxi	Terminal S21	3	⊗	Input (NO / NC), OSSD compatible / Proxi	Terminal S41	3	⊗	Input (NO / NC), OSSD compatible / Proxi	Terminal S61	3	⊗
Test / Signalling output	Terminal S22	4	⊗	Test / Signalling output	Terminal S42	4	⊗	Test / Signalling output	Terminal S62	4	⊗



X51				X61			
Semiconductor output 1	Terminal 1.14	1	⊗	AS-i Bus connection	Terminal ASI+	1	⊗
Ground connection for semiconductor output	Terminal 0 V	2	⊗	AS-i Bus connection	Terminal ASI-	2	⊗
Semiconductor output 2	Terminal 2.14	3	⊗	External power supply connection	Terminal AUX+	3	⊗
Ground connection for semiconductor output	Terminal 0 V	4	⊗	External power supply connection	Terminal AUX-	4	⊗

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module

Gateway, universal – SMBU.021

CANopen



SMBU is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

CANopen Gateway.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMax (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.

- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Order No.

SMBU Basic module **8.SMBU.021.330**

Accessory

		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000
Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI

Axis expansion for incremental encoders.

EMAA

Axis expansion for absolute encoders.

EMIO

Input / output expansion.



Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.021	CANopen
--------------------------------------	--------------------------------------	----------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service	
LCD	menu, AS-i slave address display, plain text error messages
LED power	voltage ON
LED CAN	CAN Master detected
LED config error	configuration error
LED U AS-i	AS-i voltage o.k.
LED AS-i active	AS-i operation normal
LED prg enable	automatic slave programming possible
LED prj mode	programming mode active
LED AUX	auxiliary energy available
LEDs SI1 ... SI6 (Input status)	off open on closed
LEDs SO1 ... SO6 (Output status)	off open on closed

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

CANopen interface	
Interface	CAN acc. to ISO 11898
Protocol	CANopen profile DS301
Baud rate	10 ... 1000 kbit/s
Type of connection	Combicon connector
Functions	extended boot-up, minimum boot-up, life guarding
PDOs	up to 35 Rx, 35 Tx
PDO Modi	async, cyclic, acyclic

Safety Modules

**Safety-M modular
Basic module**


Gateway, universal – SMBU.021

CANopen

Terminal assignment

X11	
1	2
Pulse output 2	T2
Safe input 2	S12
Safe input 4	S14
Safe input 6	S16

X21	
1	2
Pulse output 1	T1
Safe input 1	S11
Safe input 3	S13
Safe input 5	S15




X31	
1	2
Safe output 5	SD5
Power supply local 1 / 0	24 V DC
Power supply local 1 / 0	0 V
Safe output 6	SD6

X41	
1	2
Safe output 1	SD1
Safe output 2	SD2
Safe output 3	SD3
Safe output 4	SD4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.031	PROFIBUS DP
--------------------------------------	--------------------------------------	--------------------



SMBU is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

Profibus Gateway.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMAX (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.
- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Safety Modules

Order No.	
SMBU Basic module	8.SMBU.031.330

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000

Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56"]	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs and axis monitoring.



Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.031	PROFIBUS DP
--------------------------------------	--------------------------------------	--------------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service					
LCD	menu, AS-i slave address display, plain text error messages				
LED power	voltage ON				
LED Profibus	PROFIBUS Master detected				
LED config error	configuration error				
LED U AS-i	AS-i voltage o.k.				
LED AS-i active	AS-i operation normal				
LED prg enable	automatic slave programming possible				
LED prj mode	programming mode active				
LED AUX	auxiliary energy available				
LEDs S11 ... S16 (Input status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				
LEDs S01 ... S06 (Output status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

PROFIBUS DP interface	
Interface	Specification acc. to PROFIBUS DP 2.0 IEC 61158 / IEC 61784
Baud rate	9.6 kBaud ... 12 MBaud automatic detection
Type of connection	Sub-D, 9-pin
DP functions	Representation of the expansion modules as I/O process data in the PROFIBUS. Comprehensive diagnostics and configuration via Profibus Master.


Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.031	PROFIBUS DP
--	--------------------------------------	--------------------

Terminal assignment

X11			
Pulse output 2	T2	Safe input 2	S12
Safe input 4	S14	Safe input 6	S16

X21			
Pulse output 1	T1	Safe input 1	S11
Safe input 3	S13	Safe input 5	S15




X31			
Safe output 5	SO5	24 V DC	Power supply local I / O
Power supply local I / O		0 V	Power supply local I / O
Safe output 6	SO6		

X41			
Safe output 1	SO1	Safe output 2	SO2
Safe output 3	SO3	Safe output 4	SO4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0B1	EtherCAT
--------------------------------------	--------------------------------------	-----------------



SMBU is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

EtherCAT Gateway.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMax (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.
- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Order No.	
SMBU Basic module	8.SMBU.0B1.330

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000
Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI


Axis expansion for incremental encoders.

EMAA

Axis expansion for absolute encoders.

EMIO

Input / output expansion.



Safety-M modular Basic module	Gateway, universal – SMBU.0B1	EtherCAT
--------------------------------------	--------------------------------------	-----------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service	
LCD	menu, AS-i slave address display, plain text error messages
LED power	voltage ON
LED EtherCAT	EtherCAT Master detected
LED config error	configuration error
LED U AS-i	AS-i voltage o.k.
LED AS-i active	AS-i operation normal
LED prg enable	automatic slave programming possible
LED prj mode	programming mode active
LED AUX	auxiliary energy available
LEDs SI1 ... SI6 (Input status)	off open on closed
LEDs SO1 ... SO6 (Output status)	off open on closed

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

EtherCAT interface	
Interface	EtherCAT
Baud rate	10 / 100 MBaud
Type of connection	2 x RJ45, IN / OUT

Safety Modules


**Safety-M modular
Basic module**

Gateway, universal – SMBU.0B1

EtherCAT

Terminal assignment


X11				X21			
1	2	3	4	1	2	3	4
Pulse output 2	S2	S4	S6	T1	S11	S13	S15
Safe input 2	S12	S14	S16	Safe input 1	Safe input 1	Safe input 3	Safe input 5



X31				X41			
1	2	3	4	1	2	3	4
Safe output 5	Power supply local 1 / 0	Power supply local 1 / 0	Safe output 6	Safe output 1	Safe output 2	Safe output 3	Safe output 4
SD5	24 V DC	0 V	SD6	SD1	SD2	SD3	SD4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0C1	PROFINET IO
--------------------------------------	--------------------------------------	--------------------



SMBU is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

PROFINET Gateway.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMAX (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.
- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Safety Modules

Order No.	
SMBU Basic module	8.SMBU.0C1.330

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000

Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs and axis monitoring.



Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0C1	PROFINET IO
--------------------------------------	--------------------------------------	--------------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service	
LCD	menu, AS-i slave address display, plain text error messages
LED power	voltage ON
LED PROFINET	green PROFINET Master detected red PROFINET Master not detected
LED config error	configuration error
LED U AS-i	AS-i voltage o.k.
LED AS-i active	AS-i operation normal
LED prg enable	automatic slave programming possible
LED prj mode	programming mode active
LED AUX	auxiliary energy available
LEDs SI1 ... SI6 (Input status)	off open on closed
LEDs SO1 ... SO6 (Output status)	off open on closed

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA


PROFINET IO interface	
Interface	PROFINET IO
Baud rate	100 MBaud
Type of connection	2 x RJ45, 2-port switch
Conformance class	B

Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0C1	PROFINET IO
--	--------------------------------------	--------------------

Terminal assignment


X11				X21			
1	2	3	4	1	2	3	4
T2	S12	S14	S16	T1	S11	S13	S15
Pulse output 2	Safe input 2	Safe input 4	Safe input 6	Pulse output 1	Safe input 1	Safe input 3	Safe input 5



X31				X41			
1	2	3	4	1	2	3	4
S05	24 V DC	0 V	S06	S01	S02	S03	S04
Safe output 5	Power supply local I / O	Power supply local I / O	Safe output 6	Safe output 1	Safe output 2	Safe output 3	Safe output 4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0D1	Ethernet / IP
--------------------------------------	--------------------------------------	----------------------



SMBU is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

Ethernet IP Gateway.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMax (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.
- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Safe cross communication with other SMBx modules.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Order No.	
SMBU Basic module	8.SMBU.0D1.330

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000
Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI


Axis expansion for incremental encoders.

EMAA

Axis expansion for absolute encoders.

EMIO

Input / output expansion.



Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0D1	Ethernet / IP
--------------------------------------	--------------------------------------	----------------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service					
LCD	menu, AS-i slave address display, plain text error messages				
LED power	voltage ON				
LED Ethernet / IP	Ethernet / IP Master detected				
LED config error	configuration error				
LED U AS-i	AS-i voltage o.k.				
LED AS-i active	AS-i operation normal				
LED prg enable	automatic slave programming possible				
LED prj mode	programming mode active				
LED AUX	auxiliary energy available				
LEDs SI1 ... SI6 (Input status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				
LEDs SO1 ... SO6 (Output status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

Ethernet IP interface	
Interface	Ethernet / IP acc. to IEEE 802.3
Baud rate	10 / 100 MBaud
Type of connection	2 x RJ45, 2-port switch


Safety Modules

Safety-M modular Basic module	Gateway, universal – SMBU.0D1	Ethernet / IP
--------------------------------------	--------------------------------------	----------------------

Terminal assignment

X11			
1	2	3	4
T2	S2	S4	S6
Pulse output 2	Safe input 2	Safe input 4	Safe input 6

X21			
1	2	3	4
T1	S1	S3	S5
Pulse output 1	Safe input 1	Safe input 3	Safe input 5




X31			
1	2	3	4
SD5	24 V DC	0 V	SD6
Safe output 5	Power supply local 1 / 0	Power supply local 1 / 0	Safe output 6

X41			
1	2	3	4
SD1	SD2	SD3	SD4
Safe output 1	Safe output 2	Safe output 3	Safe output 4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module	Gateway, safe – SMBS.S31	PROFIsafe over PROFIBUS DP
--------------------------------------	---------------------------------	-----------------------------------



SMBS is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

Profisafe Gateway over PROFIBUS DP.



- | | |
|---|--|
| <ul style="list-style-type: none"> • Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs. • Extensive library of pre-configured safe sensors and command devices. • Extended drive monitoring via axis expansion module EMAX (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...). • Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads. • Programming with SafeMonitor software. • Status LED on the front side. • Plain text display with 5 different languages. • Gateway functionality with access to all data of the basic and extension modules. • Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server. | <ul style="list-style-type: none"> • Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs. • Cross-short-cut monitoring functionality (EDM). • Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts. • Extensive diagnostic functionality integrated in FW. • Integrated chip card for saving configuration data, ensuring easy device replacement. • AS-i master functionality with up to 31 safe slaves. • Easy, fast and comfortable wiring, without topological restrictions. |
|---|--|

Safety Modules

Order No.	
SMBS Basic module	8.SMBS.S31.330

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000

Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56"]	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs and axis monitoring.



Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Basic module	Gateway, safe – SMBS.S31	PROFIsafe over PROFIBUS DP
--------------------------------------	---------------------------------	-----------------------------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ... +131°F]
Storage temperature	-25°C ... +85°C [-13°F ... +185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service					
LCD	menu, AS-i slave address display, plain text error messages				
LED power	voltage ON				
LED Profibus	PROFIBUS Master detected				
LED config error	configuration error				
LED U AS-i	AS-i voltage o.k.				
LED AS-i active	AS-i operation normal				
LED prg enable	automatic slave programming possible				
LED prj mode	programming mode active				
LED AUX	auxiliary energy available				
LEDs S11 ... S16 (Input status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				
LEDs S01 ... S06 (Output status)	<table border="0"> <tr> <td>off</td> <td>open</td> </tr> <tr> <td>on</td> <td>closed</td> </tr> </table>	off	open	on	closed
off	open				
on	closed				

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA


PROFIBUS DP interface	
Interface	specification acc. to PROFIBUS DP 2.0 IEC 61158 / IEC 61784
Baud rate	9.6 kBaud ... 12 MBaud automatic detection
Type of connection	Sub-D, 9-pin
DP functions	Representation of the expansion modules as I/O process data in the PROFIBUS. Comprehensive diagnostics and configuration via Profibus Master.
PROFIsafe functions	signal safe inputs via PROFIsafe write safe outputs via PROFIsafe

Safety Modules

Safety-M modular Basic module	Gateway, safe – SMBS.S31	PROFIsafe over PROFIBUS DP
--	---------------------------------	-----------------------------------

Terminal assignment


X11				X21			
1	2	3	4	1	2	3	4
T2	S12	S14	S16	T1	S11	S13	S15
Pulse output 2	Safe input 2	Safe input 4	Safe input 6	Pulse output 1	Safe input 1	Safe input 3	Safe input 5



X31				X41			
1	2	3	4	1	2	3	4
S05	24 V DC	0 V	S06	S01	S02	S03	S04
Safe output 5	Power supply local I / O	Power supply local I / O	Safe output 6	Safe output 1	Safe output 2	Safe output 3	Safe output 4

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Basic module

Gateway, safe – SMBS.SC1

PROFIsafe over PROFINET IO



SMBS is a compact and modular safety control of the Safety-M modular product family with integrated drive monitoring. This device is freely programmable for safe processing of drive-related safety functions and of EMERGENCY STOP switches, two-hand controls, light barriers, operating mode selectors, etc.

The basic device offers 6 / 3 safe inputs and 6 safe shut-off channels.

Profisafe Gateway over PROFINET IO.



- Basic module for setting up a monitoring system for safe speed and/or position measurement with configurable inputs and outputs.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring via axis expansion module EMax (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Safe brake control "SBC" via output expansion modules EMIO e.g. for suspended loads.
- Programming with SafeMonitor software.
- Status LED on the front side.
- Plain text display with 5 different languages.
- Gateway functionality with access to all data of the basic and extension modules.
- Gateway parameter file (GSD, GSDML, ESI, etc.) integrated in the device-internal web server.
- Basic unit comes with 3 safe input lines and 6 safe shut-off channels. The 3 safe inputs can also be used as 6 standard inputs or as messaging outputs.
- Cross-short-cut monitoring functionality (EDM).
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- AS-i master functionality with up to 31 safe slaves.
- Easy, fast and comfortable wiring, without topological restrictions.

Order No.

SMBS Basic module **8.SMBS.SC1.330**

Accessory		Order No.
Memory chip card	replacement (10 pieces), 128 kB / 1024 kbit	8.SMCC.128
SafeMonitor license	single user software license	8.SMSW.000
Connection technology		Order No.
Cordset, pre-assembled, 2 m [6.56']	Ethernet programming cable	05.00.60A1.7272.002M
Crossover adapter	Ethernet adapter	05.CA.RJ45
USB Fast Ethernet Port	USB <-> Ethernet adapter	05.UA0144

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs and axis monitoring.

Expansion modules

EMAI Axis expansion for incremental encoders.
EMAA Axis expansion for absolute encoders.
EMIO Input / output expansion.



Safety-M modular Basic module	Gateway, safe – SMBS.SC1	PROFIsafe over PROFINET IO
--------------------------------------	---------------------------------	-----------------------------------

Technical data

General data	
Safe digital input lines	6 / 3, OSSD compatible
Safe digital output lines	6
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Interface for expansion modules	AS-i

Electrical characteristics	
Power supply	24 V DC
Tolerance	-15 %, +25 %
Power consumption	4.8 W
Fuse on power supply	max. 4 A
Rated data digital inputs	24 V DC / 15 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 100 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2012 EN 62061 :2005 / A1:2013

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	100 x 120 x 106 mm [3.94 x 4.72x 4.17"]
Weight	800 g [28.22 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service	
LCD	menu, AS-i slave address display, plain text error messages
LED power	voltage ON
LED PROFINET	green PROFINET Master detected red PROFINET Master nor detected
LED config error	configuration error
LED U AS-i	AS-i voltage o.k.
LED AS-i active	AS-i operation normal
LED prg enable	automatic slave programming possible
LED prj mode	programming mode active
LED AUX	auxiliary energy available
LEDs S11 ... S16 (Input status)	off open on closed
LEDs S01 ... S06 (Output status)	off open on closed

AS-i interface	
Type	AS-i 3.0 Master
Voltage	18 ... 31.6 V
Power consumption	max. 200 mA

PROFINET IO interface	
Interface	PROFINET IO
Baud rate	100 MBaud
Type of connection	2 x RJ45, 2-port switch
Conformance class	B
PROFIsafe functions	signal safe inputs via PROFIsafe write safe outputs via PROFIsafe

Safety Modules

Safety Modules


Safety-M modular Basic module

Gateway, safe – SMBS.SC1

PROFIsafe over PROFINET IO

Terminal assignment


X11				X21			
1	2	3	4	1	2	3	4
Pulse output 2	Safe input 2	Safe input 4	Safe input 6	Pulse output 1	Safe input 1	Safe input 3	Safe input 5
T2	S2	S4	S6	T1	S1	S3	S5



X31				X41			
1	2	3	4	1	2	3	4
Safe output 5	Power supply local I / 0	Power supply local I / 0	Safe output 6	Safe output 1	Safe output 2	Safe output 3	Safe output 4
S05	24 V DC	0 V	S06	S01	S02	S03	S04

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAI.012	Incremental HTL / Push-pull
--	----------------------------------	------------------------------------



Expansion module for the basic modules of the Safety-M modular product family.

Incremental axis expansion for safe motion monitoring with HTL encoders.



- For the safe speed detection.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring acc. to EN 61800-5-2 (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Programming with SafeMonitor software.
- Status LED on the front side.
- In-depth encoder monitoring.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- AS-i slave.
- Rotary speed teach-in possible via front-side key.

Order No.	
EMAI	Expansion module 8.EMAI.012.000

Accessory		Order No.
Encoder connection box	adapter module for splitting encoder signals	8.EMAS.000
EMC terminal	for encoder cable shield, top hat rail installation	8.0000.4G06.0000
Memory chip card	replacement (10 pieces), 32 kB / 256 kBit	8.SMCC.032
Connection technology		Order No.
Connection cable 5 m [16.40']	for encoder connection, Mini-IO – wire	8.SMAS.C01.005M

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	Axis expansion – EMA1.012	Incremental HTL / Push-pull
--	----------------------------------	------------------------------------

Technical data

General data	
Safe digital input lines	0
Safe digital output lines	0
Type of connection	plugable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
Power supply	24 V DC
Tolerance	± 25 %
Power consumption	3.6 W
Fuse on power supply	max. 2 A
Memory	chip card 32 k

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ... +131°F]
Storage temperature	-25°C ... +85°C [-13°F ... +185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 / AC:2009 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service		
LED 1 ASI	green	AS-i voltage active
LED 2 FLT	red	offline
LED 3 AUX	green	24 V DC AUX active
LED 4 CONF	yellow	AUS = normal operation
LED 5 ST1	yellow	status encoder 1 (ENC 1)
LED 6 F1	yellow	safe, low frequency or stand still axis 1
LED 7 F2	yellow	safe, low frequency or stand still axis 2
LED 8 ST2	yellow	status encoder 2 (ENC 2)

Encoder interface front ENC1 / ENC2	
Type of connection	Mini-IO
Number of interfaces	2 (software configurable)
Interface	HTL/Push-Pull
Processing	1 encoder – 2 axes 2 encoder – 1 axis



HTL interface	
Singal level	HTL
Max. pulse frequency	200 kHz
Reverse polarity protection	yes
Pulse rate	adjustable

AS-i interface	
Type	AS-i slave
Voltage	18 ... 31.6 V
Power consumption	max. 150 mA

Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAI.012	Incremental HTL / Push-pull
--	----------------------------------	------------------------------------

Terminal assignment




	Terminal ASI+	Terminal ASI-	Terminal AUX+	Terminal AUX-
	AS+ Bus connection	AS- Bus connection	External power supply connection	External power supply connection
	X65			
	1	2	3	4
	⊗	⊗	⊗	⊗

Terminal encoder 1 and 2

ENC1 / ENC2 – Mini IO female connector										
Signal:	HTL	\bar{B}	B	nc	nc	A	\bar{A}	+V	0 V	\perp
Pin:		1	2	3	4	5	6	7	8	PH


- +V: Power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Incremental channel A
- B, \bar{B} : Incremental channel B
- PH \perp : Plug connector housing (Shield)

Female connector, Mini-IO



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAI.022	Incremental SinCos
--	----------------------------------	---------------------------



Expansion module for the basic modules of the Safety-M modular product family.

Incremental axis expansion for safe motion monitoring with SinCos encoders.



- For the safe speed detection.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring acc. to EN 61800-5-2 (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, ...).
- Programming with SafeMonitor software.
- Status LED on the front side.
- In-depth encoder monitoring.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- AS-i slave.
- Rotary speed teach-in possible via front-side key.

Order No.		
EMAI	Expansion module	8.EMAI.022.000

Accessory		Order No.
Encoder connection box	adapter module for splitting encoder signals	8.EMAS.000
EMC terminal	for encoder cable shield, top hat rail installation	8.0000.4G06.0000
Memory chip card	replacement (10 pieces), 32 kB / 256 kBit	8.SMCC.032
Connection technology		Order No.
Connection cable 5 m [16.40']	for encoder connection, Mini-IO – wire	8.SMAS.C01.005M

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.


Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAI.022	Incremental SinCos
--	----------------------------------	---------------------------

Technical data

General data	
Safe digital input lines	0
Safe digital output lines	0
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
Power supply	24 V DC
Tolerance	±25 %
Power consumption	3.6 W
Fuse on power supply	max. 2 A
Memory	chip card 32 k

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 / AC:2009 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service		
LED 1 ASI	green	AS-i voltage active
LED 2 FLT	red	offline
LED 3 AUX	green	24 V DC AUX active
LED 4 CONF	yellow	AUS = normal operation
LED 5 ST1	yellow	status encoder 1 (ENC 1)
LED 6 F1	yellow	safe, low frequency or stand still axis 1
LED 7 F2	yellow	safe, low frequency or stand still axis 2
LED 8 ST2	yellow	status encoder 2 (ENC 2)

Encoder interface front ENC1 / ENC2	
Type of connection	Mini-IO
Number of interfaces	2 (software configurable)
Interface	SinCos
Processing	1 encoder – 2 axes 2 encoder – 1 axis

SinCos interface	
Singal level	RS485
Max. pulse frequency	200 kHz
Reverse polarity protection	yes
Pulse rate	adjustable

AS-i interface	
Type	AS-i slave
Voltage	18 ... 31.6 V
Power consumption	max. 150 mA



Safety Modules

**Safety-M modular
Expansion module**

Axis expansion – EMAI.022

**Incremental
SinCos**

Terminal assignment




	Terminal ASI+	Terminal ASI-	Terminal AUX+	Terminal AUX-
	AS-i Bus connection	AS-i Bus connection	External power supply connection	External power supply connection
	X65			
	1	2	3	4

Terminal encoder 1 and 2

ENC1 / ENC2 – Mini IO female connector										
Signal:	SinCos	\bar{B}	B	nc	nc	A	\bar{A}	+V	0 V	\perp
Pin:		1	2	3	4	5	6	7	8	PH


- +V: Power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / Incremental channel A
- B, \bar{B} : Sine signal / Incremental channel B
- PH \perp : Plug connector housing (Shield)

Female connector, Mini-IO



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAA.032	Absolute SSI, SinCos
--	----------------------------------	-----------------------------



Expansion module for the basic modules of the Safety-M modular product family.

Absolute and incremental axis expansion for safe position and motion monitoring with SinCos and/or SSI encoders.



- For the safe speed detection.
- Extensive library of pre-configured safe sensors and command devices.
- Extended drive monitoring acc. to EN 61800-5-2 (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, SLI, SLP, ...).
- Programming with SafeMonitor software.
- Status LED on the front side.
- In-depth encoder monitoring.
- Fast local shut-off via safe semiconductor outputs.
- Integrated chip card for saving configuration data, ensuring easy device replacement.
- Two safe outputs for fast direct shut-off.
- AS-i slave.
- Rotary speed teach-in possible via front-side key.

Order No.	Available end of 2014
EMAI Expansion module	8.EMAA.032.010

Accessory		Order No.
Encoder connection box	adapter module for splitting encoder signals	8.EMAS.000
EMC terminal	for encoder cable shield, top hat rail installation	8.0000.4G06.0000
Memory chip card	replacement (10 pieces), 32 kB / 256 kBit	8.SMCC.032
Connection technology		Order No.
Connection cable 1 m [3.28']	for encoder connection box, RJ45 – RJ45	8.SMAS.C22.001M

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs and axis monitoring.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAA.032	Absolute SSI, SinCos
--	----------------------------------	-----------------------------

Technical data

General data	
Safe digital input lines	0
Safe digital output lines	2 / 1
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
Power supply	24 V DC
Tolerance	± 25 %
Power consumption	3.6 W
Fuse on power supply	max. 2 A
Memory	chip card 32 k

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	5.36 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Max. response time	< 40 ms
Max. mission time	12 months
Relevant standards	EN ISO 13849-1 :2008 / AC:2009 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail

Display LEDs – for other statuses please contact the Kübler Service		
LED 1 ASI	green	AS-i voltage active
LED 2 FLT	red	offline
LED 3 AUX	green	24 V DC AUX active
LED 4 CONF	yellow	AUS = normal operation
LED 5 ST1	yellow	status encoder 1 (ENC 1)
LED 6 F1	yellow	safe, low frequency or stand still axis 1
LED 7 F2	yellow	safe, low frequency or stand still axis 2
LED 8 ST2	yellow	status encoder 2 (ENC 2)
LED 01	yellow	status output 1
LED 02	yellow	status output 2

Encoder interface front ENC1 / ENC2	
Type of connection	RJ45
Number of interfaces	2 (software configurable)
Interface	SSI, SinCos
Processing	1 encoder – 2 axes 2 encoder – 1 axis

SSI interface	
Singal level	RS485
Pulse frequency	mastermode 150 kHz slavemode max. 250 kHz
Code	Binary or Gray
Monoflop time	< 1 µs
Data length	10 ... 32 bit



SinCos interface	
Singal level	1 Vpp (± 15 %)
Max. Frequency ~ 3dB	200 kHz
Reverse polarity protection	yes
Pulse rate	adjustable

AS-i interface	
Type	AS-i slave
Voltage	18 ... 31.6 V
Power consumption	max. 150 mA

Safety Modules

Safety-M modular Expansion module	Axis expansion – EMAA.032	Absolute SSI, SinCos
--	----------------------------------	-----------------------------

Terminal assignment



				Terminal 1, 14
				Terminal 0 V
				Terminal 2, 14
				Terminal 0 V
				Terminal ASI+
				Terminal ASI-
				Terminal AUX+
				Terminal AUX-


				X55
1	2	3	4	
⊗	⊗	⊗	⊗	

				X65
1	2	3	4	
⊗	⊗	⊗	⊗	

Terminal encoder 1 and 2

RJ45 female connector										
Signal:	SinCos	\bar{B}	B	-	-	A	\bar{A}	+V	0 V	\perp
	SSI	C-	C+	D+	D-	-	-	+V	0 V	\perp
Pin:		5	4	3	6	7	8	1	2	PH


RJ45 female connector



- +V: Power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / Incremental channel A
- B, \bar{B} : Sine signal / Incremental channel B
- C+, C-: Clock signal
- D+, D-: Data signal
- PH \perp : Plug connector housing (Shield)

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SR.004

Relay 1 x 4 contacts



I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped a safe relay with four contact sets.

The expansion module allows signal duplication on potential-free contacts (contact expansion).



- Safe contact expansion, undelayed.
- 1 x 4 potential-free normally open contacts (NO).
- 1 EDM feedback channel.

Order No.

EMIO I/O expansion, relay contacts

8.EMIO.SR.004

Modular construction

Basic module

Modular safety control system.

SMBx

Expansion modules

For additional inputs and outputs.

EMxx

Basic modules

SMBD Basic module digital.

SMBU Basic module with universal gateway functionality.

SMBS Basic module with safe gateway functionality.

Expansion modules

EMAI Axis expansion for incremental encoders.

EMAA Axis expansion for absolute encoders.

EMIO Input / output expansion.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SR.004	Relay 1 x 4 contacts
--	------------------------------------	-----------------------------

Technical data

General data	
Safe relays	1
Contacts per relay	4
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
Input	
Signal level	0 signal < 2.4 V DC 1 signal 18 ... 26.5 V DC
Permissible test pulse duration	max. 1.5 ms
Rated current	60 mA per channel
Output	
Contact type	positively driven
Output circuits short-circuit protection (external)	3 A fast-acting; 2 A delayed
Closing / opening delay	< 20 ms / < 20 ms
Switching frequency	max. 15Hz
Max. switch-on current	6 A for 20 ms
Rating surge voltage	4 kV
Switching current	5 mA ... 3 A
Total current (per channel)	12 A
Utilization category (DIN EN 60347-4-1/EN 60947-5-1)	AC1 230 V/3 A (appr. 150 x 10 ³ cycles) AC15 230 V/3 A (appr. 80 x 10 ³ cycles) DC1 24 V/3 A (appr. 500 x 10 ³ cycles) DC13 24 V/3 A/0.1 Hz (appr. 50 x 10 ³ cycles)
Switching voltage AC	10 ... 230 V
Switching voltage DC	10 ... 230 V
Input circuit isolation	X23 reinforced insulation (6 kV) X53 basic insulation (4 kV)
Contact load EDM	
Switching current	max. 20 mA

Environmental data	
Operating temperature	-20°C ... +50°C [-4°F ...+122°F]
Storage temperature	-40°C ... +70°C [-40°F ...+158°F]
Humidity	non-condensing
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178

Safety characteristics	
B10d (AC15)	1.96 x 10 ⁶ cycles
B10d (DC13)	780 x 10 ³ cycles

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	190 g [6.70 oz]
Mounting	snap-on mounting on standard head rail

EMC	
Relevant standards	EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 60947-1 :2007 / A1:2011 EN 60947-5-1 :2004 / AC:2005

LED display	
LED 1 (CH 1)	safe input 1
LED 3 (EDM 1)	EDM channel 1

Safety Modules


Safety-M modular Expansion module

I/O expansion – EMIO.SR.004

Relay 1 x 4 contacts


Terminal assignment

X23		X33	
1	2	1	2
Output channel 1.1	Terminal 1.13	NC	NC
Output channel 1.1	Terminal 1.14	NC	NC
Output channel 1.2	Terminal 1.23	EDM (feedback loop) channel 1	Terminal 1.52
Output channel 1.2	Terminal 1.24	EDM (feedback loop) channel 1	Terminal 1.51




X43		X53	
1	2	1	2
Normally open contacts channel 1	Terminal 1.A1	Output channel 1.4	Terminal 1.43
Normally open contacts channel 1	Terminal 1.A2	Output channel 1.4	Terminal 1.44
NC	NC	Output channel 1.3	Terminal 1.33
NC	NC	Output channel 1.3	Terminal 1.34

Output relay



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SR.008	Relay 2 x 4 contacts
--	------------------------------------	-----------------------------



I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with two safe relays, each with four contact sets.

The expansion module allows signal duplication on potential-free contacts (contact expansion).



- Safe contact expansion, undelayed.
- 2 x 4 potential-free normally open contacts (NO).
- 2 EDM feedback channels.

Order No.		
EMIO	I/O expansion, relay contacts	8.EMIO.SR.008

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SR.008

Relay 2 x 4 contacts

Technical data

General data

Safe relays	2
Contacts per relay	4
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics

Input

Signal level	0 signal	< 2.4 V DC
	1 signal	18 ... 26.5 V DC

Permissible test pulse duration	max. 1.5 ms
---------------------------------	-------------

Rated current	60 mA per channel
---------------	-------------------

Output

Contact type	positively driven
--------------	-------------------

Output circuits short-circuit protection (external)	3 A fast-acting; 2 A delayed
---	------------------------------

Closing / opening delay	< 20 ms / < 20 ms
-------------------------	-------------------

Switching frequency	max. 15Hz
---------------------	-----------

Max. switch-on current	6 A for 20 ms
------------------------	---------------

Rating surge voltage	4 kV
----------------------	------

Switching current	5 mA ... 3 A
-------------------	--------------

Total current (per channel)	12 A
-----------------------------	------

Utilization category (DIN EN 60347-4-1 / EN 60947-5-1)	AC1	230 V/3 A (appr. 150 x 10 ³ cycles)
	AC15	230 V/3 A (appr. 80 x 10 ³ cycles)
	DC1	24 V/3 A (appr. 500 x 10 ³ cycles)
	DC13	24 V/3 A/0.1 Hz (appr. 50 x 10 ³ cycles)

Switching voltage AC	10 ... 230 V
----------------------	--------------

Switching voltage DC	10 ... 230 V
----------------------	--------------

Input circuit isolation	X13, X23	reinforced insulation (6 kV)
	X53, X63	basic insulation (4 kV)

Contact load EDM

Switching current	max. 20 mA
-------------------	------------

Environmental data

Operating temperature	-20°C ... +50°C [-4°F ... +122°F]
-----------------------	-----------------------------------

Storage temperature	-40°C ... +70°C [-40°F ... +158°F]
---------------------	------------------------------------

Humidity	non-condensing
----------	----------------

Protection acc. to EN 60529	IP20
-----------------------------	------

Climate class	3 acc. to DIN 50178
---------------	---------------------

Safety characteristics

B10d (AC15)	1.96 x 10 ⁶ cycles
-------------	-------------------------------

B10d (DC13)	780 x 10 ³ cycles
-------------	------------------------------

Mechanical characteristics

Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
----------------	--

Weight	280 g [9.88 oz]
--------	-----------------

Mounting	snap-on mounting on standard head rail
----------	--

EMC

Relevant standards	EN 61000-6-2 :2005 / AC:2005
	EN 61000-6-4 :2007 / A1:2011
	EN 60947-1 :2007 / A1:2011
	EN 60947-5-1 :2004 / AC:2005

LED display

LED 1 (CH 1)	safe input 1
--------------	--------------

LED 2 (CH 2)	safe input 2
--------------	--------------

LED 3 (EDM 1)	EDM channel 1
---------------	---------------


LED 4 (EDM 2)	EDM channel 2
---------------	---------------

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SR.008	Relay 2 x 4 contacts
--	------------------------------------	-----------------------------


Terminal assignment

X13		X23		X33							
1	2	3	4	1	2	3	4	1	2	3	4
Output channel 2.1		Terminal 2.13		Output channel 1.1		Terminal 1.13		EDM (feedback loop) channel 2		Terminal 2.52	
Output channel 2.1		Terminal 2.14		Output channel 1.1		Terminal 1.14		EDM (feedback loop) channel 2		Terminal 2.51	
Output channel 2.2		Terminal 2.23		Output channel 1.2		Terminal 1.23		EDM (feedback loop) channel 1		Terminal 1.52	
Output channel 2.2		Terminal 2.24		Output channel 1.2		Terminal 1.24		EDM (feedback loop) channel 1		Terminal 1.51	



X43		X53		X63							
1	2	3	4	1	2	3	4	1	2	3	4
Normally open contacts channel 1		Terminal 1.A1		Output channel 1.4		Terminal 1.43		Output channel 2.4		Terminal 2.43	
Normally open contacts channel 1		Terminal 1.A2		Output channel 1.4		Terminal 1.44		Output channel 2.4		Terminal 2.44	
Normally open contacts channel 2		Terminal 2.A1		Output channel 1.3		Terminal 1.33		Output channel 2.3		Terminal 2.33	
Normally open contacts channel 2		Terminal 2.A2		Output channel 1.3		Terminal 1.34		Output channel 2.3		Terminal 2.34	


Output relay



X: 1 = relay 1
2 = relay 2

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SIO.048

Digital 8 + 8 / 4



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with 8 digital inputs, 8 / 4 safe outputs and 1 messaging output.



- 8 digital input lines.
- 8 / 4 safe output lines.
- 1 messaging output.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.

EMIO I/O expansion, digital

8.EMIO.SIO.048

Modular construction

Basic module

Modular safety control system.

SMBx

Expansion modules

For additional inputs and outputs.

EMxx

Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.048	Digital 8 + 8 / 4
--	-------------------------------------	--------------------------

Technical data

General data	
Digital input lines	8
Safe digital output lines	8 / 4
Messaging outputs	1
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
AUX	
Power supply	18 ... 30 V DC (PELV)
Power consumption	max. 1 A
Isolation voltage AS-i / AUX	500 V

Input	
Power supply	from AUX
Input level	10 mA, R < 150 Ω
Singal level	0 signal < 5 V DC 1 signal > 15 V DC
Rated data digital inputs	24 V DC / 20 mA
Output	
Power supply	from AUX
Contact load	0.7 A, DC-13 at 30 V
Rated data digital outputs	24 V DC / 250 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Humidity	non-condensing

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.21 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2008 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	190 g [6.70 oz]
Mounting	snap-on mounting on standard head rail

LED display	
LEDs SI1 ... SI8 (yellow)	status of inputs SI1 ... SI8
LEDs SO1 ... SO8 (yellow)	status of outputs SO1 ... SO8
LED PWR (green)	AS-i voltage active
LED FLT (red)	AS-i error LED
LED AUX (red)	24 V DC AUX active
LED O1 (yellow)	messaging output has switched

AS-i interface		
Type		AS-i slave
Profile	configuration slave	S-7.A.5
	4I / 4O slave	S-7.A.7
	safe output slaves	S-7.F
	diagnostic slaves	S-7.A.E
Voltage		18 ... 31.6 V
Power consumption		max. 200 mA

Safety Modules


Safety-M modular Expansion module

I/O expansion – EMIO.SIO.048

Digital 8 + 8 / 4

Terminal assignment



X22				X32			
1	2	3	4	1	2	3	4
Safe input terminal, input 1	Terminal 1			Terminal 5			
Safe input terminal, input 2	Terminal 2			Terminal 6			
Safe input terminal, input 3	Terminal 3			Terminal 7			
Safe input terminal, input 4	Terminal 4			Terminal 8			



Terminal S01	Safe output terminal, output 1	1	2	3	4
Terminal S02	Safe output terminal, output 2				
Terminal S03	Safe output terminal, output 3				
Terminal S04	Safe output terminal, output 4				
Terminal S05	Safe output terminal, output 5	1	2	3	4
Terminal S06	Safe output terminal, output 6				
Terminal S07	Safe output terminal, output 7				
Terminal S08	Safe output terminal, output 8				
ASI+	AS+ Bus connection	1	2	3	4
ASI-	AS+ Bus connection				
AUX+	Power supply input line				
AUX-	Power supply input line				

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.810	Digital 16 / 8 + 1
--	-------------------------------------	---------------------------



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with 16 / 8 safe inputs and 1 messaging output.



- 16 / 8 safe input lines.
- 1 messaging output.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.	
EMIO I/O expansion, digital	8.EMIO.SIO.810

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.810	Digital 16 / 8 + 1
--	-------------------------------------	---------------------------

Technical data

General data	
Safe digital input lines	16 / 8
Digital output lines	1
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
AUX	
Power supply	18 ... 30 V DC (PELV)
Power consumption	max. 1 A
Isolating voltage AS-i/AUX	500 V
Input	
Power supply	from AUX
Input level	10 mA, R < 150 Ω
Singal level	0 signal < 5 V DC 1 signal > 15 V DC
Rated data digital inputs	24 V DC / 20 mA
Output	
Power supply	from AUX
Contact load	0.7 A, DC-13 at 30 V
Rated data digital outputs	24 V DC / 250 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Humidity	non-condensing

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.08 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2008 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	180 g [6.35 oz]
Mounting	snap-on mounting on standard head rail

LED display	
LEDs S11 ... S116 (yellow)	status of inputs S11 ... S116
LED PWR (green)	AS-i voltage active
LED FLT (red)	AS-i error LED
LED AUX (red)	24 V DC AUX active
LED O1 (yellow)	messaging output has switched


AS-i interface		
Type	AS-i slave	
Profile	safe input slaves	S-0.B.F.0
	diagnostic slaves	S-7.A.5.E
Voltage	18 ... 31.6 V	
Power consumption	max. 200 mA	

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.810	Digital 16 / 8 + 1
--	-------------------------------------	---------------------------

Terminal assignment


X12				X22				X32			
Safe input terminal, input 4	Terminal S4	1	⊗	Safe input terminal, input 8	Terminal S8	1	⊗	Safe input terminal, input 12	Terminal S12	1	⊗
Safe input terminal, input 3	Terminal S3	2	⊗	Safe input terminal, input 7	Terminal S7	2	⊗	Safe input terminal, input 11	Terminal S11	2	⊗
Safe input terminal, input 2	Terminal S2	3	⊗	Safe input terminal, input 6	Terminal S6	3	⊗	Safe input terminal, input 10	Terminal S10	3	⊗
Safe input terminal, input 1	Terminal S1	4	⊗	Safe input terminal, input 5	Terminal S5	4	⊗	Safe input terminal, input 9	Terminal S9	4	⊗



X42				X52				X62			
Safe input terminal, input 13	Terminal S13	1	⊗	Semiconductor output 1	Terminal 1, 14	1	⊗	AS+ Bus connection	1	⊗	
Safe input terminal, input 14	Terminal S14	2	⊗	Ground connection for semiconductor output	Terminal 0 V	2	⊗	AS- Bus connection	2	⊗	
Safe input terminal, input 15	Terminal S15	3	⊗	Pulse 1 (S1, S3, S5, S7, S9, S11, S13, S15)	Terminal T1	3	⊗	Power supply input line	3	⊗	
Safe input terminal, input 16	Terminal S16	4	⊗	Pulse 1 (S2, S4, S6, S8, S10, S12, S14, S16)	Terminal T2	4	⊗	Power supply input line	4	⊗	

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SIO.420

Digital 8 / 4 + 4 / 2



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with 8 / 4 safe inputs and 4 / 2 safe outputs.



- 8 / 4 safe input lines.
- 4 / 2 safe output lines.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.

EMIO I/O expansion, digital

8.EMIO.SIO.420

Modular construction

Basic module

Modular safety control system.

SMBx

Expansion modules

For additional inputs and outputs.

EMxx

Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.420	Digital 8 / 4 + 4 / 2
--	-------------------------------------	------------------------------

Technical data

General data	
Safe digital input lines	8 / 4
Safe digital output lines	4 / 2
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
AUX	
Voltage	20 ... 30 V DC (PELV)
Power consumption	max. 4 A
Isolation voltage AS-i / AUX	500 V
Input	
Power supply	from AUX
Input level	10 mA, R < 150 Ω
Switching current	static 4 mA for 24 V DC dynamic 15 mA for 24 V DC (T = 100 μs)
Output	
Power supply	from AUX
Contact load	max. 0.7 A, DC-13 for 30 V
Max. output current	1.4 A

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Humidity	non-condensing

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.08 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2008 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	180 g [6.35 oz]
Mounting	snap-on mounting on standard head rail

LED display	
LEDs SI1 ... SI8 (yellow)	status of inputs SI1 ... SI8
LED PWR (green)	AS-i voltage active
LED FLT (red)	AS-i error LED
LEDs SO1 ... SO2	status of outputs SO1 ... SO2

AS-i interface		
Type	AS-i slave	
Profile	safe input slaves	S-0.B.F.0
	diagnostic slaves	S-7.A.5.E
Voltage	18 ... 31.6 V	
Power consumption	max. 200 mA	

Safety Modules


Safety-M modular Expansion module

I/O expansion – EMIO.SIO.420

Digital 8 / 4 + 4 / 2

Terminal assignment


X12		X22		X32											
1	2	3	4	1	2	3	4	1	2	3	4				
Safe input terminal, input 1	Terminal S22	Safe input terminal, input 1	Terminal S21	Safe input terminal, input 1	Terminal S12	Safe input terminal, input 1	Terminal S11	Safe input terminal, input 2	Terminal S42	Safe input terminal, input 2	Terminal S41	Safe input terminal, input 2	Terminal S32	Safe input terminal, input 2	Terminal S31
Safe input terminal, input 2	Terminal S62	Safe input terminal, input 3	Terminal S61	Safe input terminal, input 3	Terminal S52	Safe input terminal, input 3	Terminal S51	Safe input terminal, input 3	Terminal S51	Safe input terminal, input 3	Terminal S51	Safe input terminal, input 3	Terminal S51	Safe input terminal, input 3	Terminal S51



X42		X52		X62											
1	2	3	4	1	2	3	4	1	2	3	4				
Safe input terminal, input 4	Terminal S71	Safe input terminal, input 4	Terminal S72	Safe input terminal, input 4	Terminal S81	Safe input terminal, input 4	Terminal S82	Semiconductor output 1	Terminal I.14	Ground connection for semiconductor output	Terminal O V1	Semiconductor output 1	Terminal 2.14	Ground connection for semiconductor output	Terminal O V2
AS+ Bus connection	AS+ Bus connection	Power supply input line	Power supply input line	AS+ Bus connection	AS+ Bus connection	Power supply input line	Power supply input line	AS+ Bus connection	AS+ Bus connection	Power supply input line	Power supply input line	AS+ Bus connection	AS+ Bus connection	Power supply input line	Power supply input line

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.204	Digital 4 / 2 + 4
--	-------------------------------------	--------------------------



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with 4 / 2 safe inputs and 4 messaging outputs.



- 4 / 2 safe input lines.
- 4 messaging outputs.

Order No.		
EMIO	I/O expansion, digital	8.EMIO.SIO.204

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.204	Digital 4 / 2 + 4
--	-------------------------------------	--------------------------

Technical data

General data	
Safe digital input lines	4 / 2
Messaging outputs	4
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
AUX	
Power supply	24 V DC (20 ... 30 V DC)
Power consumption	max. 4 A
Input	
Power supply	from AUX
Switching current	static 4 mA at 24 V DC dynamic 15 mA at 24 V DC (T = 100 µs)
Input level	10 mA, R < 150 Ω
Output	
Power supply	from AUX
Max. output current	1 A per output
Total current	3 A

Environmental data	
Operating temperature	0°C ... +70°C [+32°F ...+158°F]
Storage temperature	-40°C ... +85°C [-40°F ...+185°F]
Protection acc. to EN 60529	IP20
Humidity	non-condensing

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.18 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2008 EN 62061 :2005 / A1:2010

EMC	
Relevant standards	EN 61326-3-1 :2008 EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	120 g [4.23 oz]
Mounting	snap-on mounting on standard head rail

LED display	
LEDs S11 ... S14 (yellow)	status of inputs S11 ... S14
LEDs O1 ... O4 (yellow)	status of outputs O1 ... O4
LED ASI/FLT1 (red/green)	green slave online red no data exchange yellow/red blinking address 0 red/green blinking peripheral error
LED ASI/FLT2 (red/green)	green slave online red no data exchange yellow/red blinking address 0 red/green blinking peripheral error red blinking slave switched off, while slave 1 has address 0
LED AUX (green)	24 V DC AUX on
LED CC (red)	input circuit cross short cut, peripheral error


AS-i interface	
Type	AS-i slave
Profile	slave 1 S-7.B.0, ID1 = F slave 2 S-7.B.0, ID1 = E
Address	2 single slaves
Voltage	22 ... 31.6 V
Power consumption	max. 60 mA

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.204	Digital 4 / 2 + 4
--	-------------------------------------	--------------------------

Terminal assignment

X12				X22			
1	2	3	4	1	2	3	4
Terminal S11	Terminal S12	Terminal S21	Terminal S22	Terminal S31	Terminal S32	Terminal S41	Terminal S42
Safe input terminal, input 1	Safe input terminal, input 1	Safe input terminal, input 2	Safe input terminal, input 2	Safe input terminal, input 3	Safe input terminal, input 3	Safe input terminal, input 4	Safe input terminal, input 4




X42				X52			
1	2	3	4	1	2	3	4
Semiconductor output 1	Semiconductor output 2	Semiconductor output 3	Semiconductor output 4	Terminal O1	Terminal O2	Terminal O3	Terminal O4
AS+ Bus connection	AS+ Bus connection	Power supply input line	Power supply input line	ASI+	ASI-	AUX+	AUX-

ADDR1 = Addressing socket 1
 ADDR2 = Addressing socket 2

Dimensions

Dimensions in mm [inch]




Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SIO.10xP

Digital 2 / 1 + 2



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The decentralized expansion module with high protection level is equipped with 2 / 1 safe inputs and 2 messaging outputs.



- 2 / 1 safe inputs.
- 2 messaging outputs.

- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.

Available end of 2014

EMIO	2 / 1 digital inputs (OSSD compatible)	8.EMIO.SIO.101P
	2 / 1 digital inputs	8.EMIO.SIO.102P

Modular construction

Basic module

Modular safety control system.

Expansion modules

For additional inputs and outputs.

SMBx

EMxx

Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Connection technology		Order No.
Connector, self-assembly	M12 male connector with external thread, 5 pin	05.BS-8151-0/9
	M12 female connector with coupling nut, 4 pin	05.B8141-0
Cordset, pre-assembled	With M12 male connector with external thread, 5 pin, single-ended, 2 m [6.56'] PVC cable	05.00.6091.A411.002M
	With M12 female connector with coupling nut, 4 pin, single-ended, 2 m [6.56'] PUR cable	05.00.6061.6211.002M

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.SIO.10xP	Digital 2 / 1 + 2
--	--------------------------------------	--------------------------

Technical data

General data	
Safe digital input lines	2 / 1
Messaging outputs	2
Type of connection	M12 connector

Mechanical characteristics	
Size w x h x d	116.5 x 45 x 47.5 mm [4.59 x 1.77 x 1.87"]
Weight	120 g [4.23 oz]

Electrical characteristics	
AUX	
Power supply	24 V DC (20 ... 30 V DC), PELV
Power consumption	max. 3 A
Input	
Safety signal	potential-free contact
static switching current	4 mA
dynamic switching current	15 mA for 24 V DC (T = 100 µs)
Power supply	from AS-i
Switching threshold	10 mA, R < 150 Ω
Output	
Power supply	from AUX
Max. output current	1 A
Total current	max. 3 A, O1 ... O2

LED display	
2 x LED (yellow)	status of input SI1 ... SI2
2 x LED (yellow)	status of output O1 ... O2
LED AUX (green)	24 V DC AUX active
LED ASI (green)	AS-i power supply active
LED FLT (red)	LED on AS-i communication error, slave is not in normal data transfer
	LED blinks peripheral error

AS-i interface	
Type	AS-i slave
Profile	S-7.B.=, ID1 = F
Voltage	22 ... 31.6 V
Power consumption	max. 80 mA

Environmental data	
Operating temperature	0°C ... +55°C [+32°F ... +131°F]
Storage temperature	-40°C ... +85°C [-40°F ... +185°F]
Protection acc. to EN 60529	IP67
Shock and vibration resistance	≤ 15 g, T ≤ 11 ms 10 ... 55 Hz, 0.5 mm amplitude
Humidity	non-condensing

Safety characteristics	
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	5.18 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years
Relevant standards	EN ISO 13849-1 :2008 EN ISO 13849-2 :2008 EN 62061 :2005

EMC	
Relevant standards	EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 60947-1 :2007 / A1:2011 EN 60947-5-1 :2004 / AC:2005

Safety Modules

Safety-M modular Expansion module

I/O expansion – EMIO.SIO.10xP

Digital 2 / 1 + 2

Terminal assignment


M12 connector, A coded, terminal S1					
Signal EMIO.SIO.101P	24 V ext. out	OSSD2	0 V ext. out	OSSD1	Shield
Signal EMIO.SIO.102P	S11+	S11-	S2+	S2-	-
Pin	1	2	3	4	5

M12 connector, A coded, terminal S2					
Signal EMIO.SIO.101P	24 V ext. out	-	0 V ext. out	24 V ext. out	Shield
Signal EMIO.SIO.102P	S12+	S12-	-	-	-
Pin	1	2	3	4	5

M12 connector, A coded, terminal O1					
Signal EMIO.SIO.101P	-	Out2	0 V ext. out	Out1	-
Signal EMIO.SIO.102P	-	Out2	0 V ext. out	Out1	-
Pin	1	2	3	4	5


M12 connector, A coded, terminal O2					
Signal EMIO.SIO.101P	-	-	0 V ext. out	Out1	-
Signal EMIO.SIO.102P	-	-	0 V ext. out	Out2	-
Pin	1	2	3	4	5

M12 connector, A coded, terminal ASI / AUX					
Signal EMIO.SIO.101P	AS-i+	0 V ext. in	AS-i-	24 V ext. in	-
Signal EMIO.SIO.102P	AS-i+	0 V ext. in	AS-i-	24 V ext. in	-
Pin	1	2	3	4	5



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.IO.880	Digital (non safe) 8 + 8
--	------------------------------------	---------------------------------



Digital I/O expansion for the basic modules of the Safety-M modular product family.

The expansion module is equipped with 8 standard inputs and 8 standard outputs.



- 8 input lines.
- 8 output lines.

Order No.	
EMIO I/O expansion, digital	8.EMIO.IO.880

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.



Basic modules

- SMBD** Basic module digital.
- SMBU** Basic module with universal gateway functionality.
- SMBS** Basic module with safe gateway functionality.

Expansion modules

- EMAI** Axis expansion for incremental encoders.
- EMAA** Axis expansion for absolute encoders.
- EMIO** Input / output expansion.

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.IO.880	Digital (non safe) 8 + 8
--	------------------------------------	---------------------------------

Technical data

General data	
Digital inputs	8
Digital outputs	8
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]

Electrical characteristics	
AUX	
Power supply	18 ... 30 V DC
Power consumption	8 A
Input	
Number of inputs	8
Signal level	0 signal < 5 V DC 1 signal > 15 V DC
Rated data digital inputs	24 V DC / 20 mA
Output	
Number of outputs	8 x electronic
Power supply	from AUX
Rated data digital outputs	1000 mA
Max. output current	1 A
Total current (per terminal)	max. 3 A, X44 (01 ... 04) max. 3 A, X54 (05 ... 08)

Environmental data	
Operating temperature	-25°C ... +70°C [-13°F ... +158°F]
Storage temperature	-25°C ... +85°C [-13°F ... +185°F]
Protection acc. to EN 60529	IP20
Humidity	non-condensing

EMC	
Relevant standards	EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011 EN 62026-2 :2013 EN 61131-2 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm
Weight	140 g [4.94 oz]
Mounting	snap-on mounting on standard head rail

LED display		
LED AS-i/FLT1 (red / green)	green red yellow/red blinking red/green blinking	slave online slave offline address 0 peripheral error
LED AS-i/FLT2 (red / green)	green red yellow/red blinking red/green blinking red blinking	slave online slave offline address 0 peripheral error slave 2 is switched off, while slave 1 is offline
LEDs I1 ... I8 (yellow)		status of inputs I1 ... I8
LEDs O1 ... O8 (yellow)		status of outputs O1 ... O8
LED AUX (green)	on off	24 V DC AUX no 24 V DC AUX


AS-i interface	
Type	AS-i slave
Profile	slave 1 S-7.0.E, ID1 = F (default) slave 2 S-7.0.E, ID1 = E (default)
AS-i Address	2 single slaves
Voltage	18 ... 31.6 V
Power consumption	max. 60 mA

Safety Modules

Safety-M modular Expansion module	I/O expansion – EMIO.IO.880	Digital (non safe) 8 + 8
--	------------------------------------	---------------------------------

Terminal assignment


	X14				X24				X34			
	1	2	3	4	1	2	3	4	1	2	3	4
Sensor supply	I-	I+	0-	0-	I8	I7	I6	I5	I4	I3	I2	I1
Sensor supply												
Ground reference for outputs												
Ground reference for outputs												



	01	02	03	04	05	06	07	08	AS+	AS-	AUX+	AUX-
Output 1												
Output 2												
Output 3												
Output 4												
Output 5												
Output 6												
Output 7												
Output 8												
AS+ Bus connection												
AS- Bus connection												
Power supply input line												
Power supply input line												

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety Modules

Safety-M Basic module	Speed monitoring – MS1	1 axis
----------------------------------	-------------------------------	---------------



MS1 is a compact and modular safety control of the Safety-M family with integrated drive monitoring for one axis. This device is freely programmable for the safe processing of drive-related safety functions as well as of EMERGENCY STOP switches, two-hand operator controls, light barriers, operating mode selectors, etc.

The basic version allows 1 safe encoder connection to be implemented. 14 safe inputs and 3 safe shut-off channels are available.



1-encoder solutions (TTL/HTL, SinCos, proximity switch) and to a limited extent also 2-encoder solutions (a combination of any encoder technologies) are supported for the safe speed and/or position detection.

- Extensive library of pre-configured safe sensors and command devices
- Complete range of speed- and position-related safe drive monitoring functions as per DIN EN 61800 already integrated (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, SBC, EDM)
- Parameterizable encoder interface for TTL / SinCos / SSI on the front and proximity switch / HTL via terminal connection
- Graphical programming interface by SafePLC software

- Basic unit comes with 14 safe input lines and 3 safe shut-off channels, comprising 1 safe relay output and 2 messaging outputs
- Cross-short-cut monitoring functionality
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts
- Extensive diagnostic functionality integrated in FW
- Status monitoring by coded 7-segment-display and status LED's
- Quit- / Start- / Reset-button on the front display
- Extendable up to max. 65 safe I/O lines by means of an integrated backplane bus (connector for top hat rail mount)
- Optional field bus interface (bus modules for PROFIBUS DP, PROFINET IO, CANopen, EtherCAT, DeviceNet)

Order No.	The programming software SafePLC and the programming cable are required for programming. T-BUS connectors are required for connecting a BUS module or an expansion module.	
MS1	Speed monitoring for 1 axis	8.MS1.000

Accessory		Order No.
T-bus connector		05.TBMS.000
Programming adapter		8.0010.9000.0020
Licence key SafePLC		05.SPLC.001
Connection technology		Order No.
Cordset, pre-assembled 1 m	for incremental encoders	8.0000.6900.0001.0081
	for SSI signals, X31/X32	8.0000.6900.0001.0068

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety

Safety Modules

Safety-M Basic module	Speed monitoring – MS1	1 axis
----------------------------------	-------------------------------	---------------

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.

Bus modules
For standard field bus / Ethernet interface.



Overview inputs / outputs

14 x	safe digital inputs
2 x	relays outputs (safe due to redundant operation)
2 x	digital outputs LOSIDE / HISIDE (safe due to redundant operation)
2 x	messaging outputs

Technical data

General data	
Max. number of expansion modules	2 x EM, 1 x BM
Interface for expansion modules	T-bus connector for top hat rail mount
Safe digital input lines	14 incl. 8 OSSD
Safe digital output lines	2
Safe relay outputs	1
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]
Drive monitoring - number of axis	1 axis

Electrical characteristics	
Power supply	24 V DC / 2 A
Tolerance	-15 %, +20 %
Power consumption	2.4 W
Fuse on power supply	max. 2 A
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Rated data relay	24 V DC / 2 A or 230 V AC / 2 A
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Mechanical characteristics	
Size w x h x d	45 x 99 x 114.5 mm [1.77 x 3.90 x 4.51"]
Weight	310 g [10.94 oz]
Mounting	snap-on mounting on standard head rail

Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	2.3 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Encoder interface front X31 / X32	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL
Frequency SinCos, TTL	max. 200 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 250 kHz
Data length SSI	10-28 bit

Encoder interface terminal X23	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 10 kHz

Safety Modules


Safety-M Basic module

Speed monitoring – MS1

1 axis

Terminal assignment

X11		X12		X13		X14	
1	2	1	2	1	2	1	2
Power supply module +24 V DC	U24 extern	Digital IN 13	DI 13 / E 0.13	Power supply encoder interface X31	U_ENC_1	Digital IN 01 (OSSD compatible)	DI 01 / E 0.1
Power supply module +24 V DC	U24 extern	Digital IN 14	DI 14 / E 0.14	Power supply encoder interface X31	GND_ENC_1	Digital IN 02 (OSSD compatible)	DI 02 / E 0.2
Power supply module 0 V DC	GND extern	Pulse output P1	P1	Messaging and auxiliary output DO 0.1	DO 0.1 / A 0.1	Digital IN 03 (OSSD compatible)	DI 03 / E 0.3
Power supply module 0 V DC	GND extern	Pulse output P2	P2	Messaging and auxiliary output DO 0.2	DO 0.2 / A 0.2	Digital IN 04 (OSSD compatible)	DI 04 / E 0.4



X21		X22		X23		X24	
1	2	1	2	1	2	1	2
HISIDE output 0	DO 0-HI / AD 0.0P	Relay output 1	K1.1 / AK 0.1	Digital IN 05 / Proximity switch 1	DI 05 / E 0.5	Digital IN 09 (OSSD compatible)	DI 09 / E 0.9
LOSIDE output 0	DO 0-LO / AD 0.0M	Relay output 1	K1.2 / AK 0.1	Digital IN 06 / Proximity switch 1	DI 06 / E 0.6	Digital IN 10 (OSSD compatible)	DI 10 / E 0.10
HISIDE output 1	DO 1-HI / AD 0.1P	Relay output 2	K1.1 / AK 0.2	Digital IN 07 / Proximity switch 2	DI 07 / E 0.7	Digital IN 11 (OSSD compatible)	DI 11 / E 0.11
LOSIDE output 1	DO 1-LO / AD 0.1M	Relay output 2	K1.2 / AK 0.2	Digital IN 08 / Proximity switch 2	DI 08 / E 0.8	Digital IN 12 (OSSD compatible)	DI 12 / E 0.12


Safety Modules

Safety-M Basic module	Speed monitoring – MS1	1 axis
----------------------------------	-------------------------------	---------------

Terminal assignment

Interface	Sub-D female connector											
Terminal X31/X32	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	-	C-	D+	D-	-	C+	+V	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH

Sub-D female connector, 9-pin




- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / incremental output channel A
- B, \bar{B} : Sine signal / incremental output channel B

- C+, C- : Clock signal
- D+, D- : Data signal
- PH \perp : Plug connector housing (Shield)

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M Basic module

Speed and position monitoring – MSP1

1 axis



MSP1 is a compact and modular safety control of the Safety-M family with integrated drive monitoring for one axis and extended encoder interface. This device is freely programmable for the safe processing of drive-related safety functions as well as of EMERGENCY STOP switches, two-hand operator controls, light barriers, operating mode selectors, etc.

The basic version allows 2 safe encoder connections to be implemented. 14 safe inputs and 3 safe shut-off channels are available.

1-encoder solutions (TTL/HTL, resolver, SinCos, proximity switch) and to a limited extent also 2-encoder solutions (a combination of any encoder technologies) are supported for the safe speed and/or position detection.

- Extensive library of pre-configured safe sensors and command devices.
- Complete range of speed- and position-related safe drive monitoring functions as per DIN EN 61800 already integrated (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, SBC, EDM, SLI, SLP).
- Parameterizable encoder interface for TTL / SinCos / SSI / Resolver on the front and proximity switch / HTL via terminal connection.
- Graphical programming interface by SafePLC software.

- Basic unit comes with 14 safe input lines and 3 safe shut-off channels, comprising 1 safe relay output and 2 messaging outputs.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Status monitoring by coded 7-segment-display and status LED's.
- Quit- / Start- / Reset-button on the front display.
- Extendable up to max. 65 safe I/O lines by means of an integrated backplane bus (connector for top hat rail mount).
- Optional field bus interface (bus modules for PROFIBUS DP, PROFINET IO, CANopen, EtherCAT, DeviceNet).

Order No.

The programming software SafePLC and the programming cable are required for programming. T-BUS connectors are required for connecting a BUS module or an expansion module.

MSP1 Speed and position monitoring for 1 axis **8.MSP1.000**

Accessory		Order No.	
T-bus connector		05.TBMS.000	
Programming adapter		8.0010.9000.0020	
Licence key SafePLC		05.SPLC.001	
Connection technology		Order No.	
Cordset, pre-assembled 1 m	for incremental encoders	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0081
	for SSI signals, X31/X32	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0068
	for SSI signals, X33/X34	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0072
	for SinCos+SSI signals	cable with 1 x M23 / 2 x Sub-D, 9-pin	8.0000.6900.0001.0070
	for SinCos+SSI signals, SET/DIR separate	cable with 1 x M23 / 2 x Sub-D, 9-pin	8.0000.6900.0001.0080

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Safety Modules

Safety-M Basic module Speed and position monitoring – MSP1 1 axis

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.

Bus modules
For standard field bus interface.



Overview inputs / outputs

14 x	safe digital inputs
2 x	relays outputs (safe due to redundant operation)
2 x	digital outputs LOSIDE / HISIDE (safe due to redundant operation)
2 x	messaging outputs

Technical data

General data	
Max. number of expansion modules	2 x EM, 1 x BM
Interface for expansion modules	T-bus connector for top hat rail mount
Safe digital input lines	14 incl. 8 OSSD
Safe digital output lines	2
Safe relay outputs	1
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]
Drive monitoring - number of axis	1 axis

Electrical characteristics	
Power supply	24 V DC / 2 A
Tolerance	-15 %, +20 %
Power consumption	2.4 W
Fuse on power supply	max. 2 A
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Rated data relay	24 V DC / 2 A or 230 V AC / 2 A
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ... +122°F]
Storage temperature	-10°C ... +70°C [+14°F ... +158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Mechanical characteristics	
Size w x h x d	67.5 x 99 x 114.5 mm [2.66 x 3.90 x 4.51"]
Weight	390 g [13.76 oz]
Mounting	snap-on mounting on standard head rail

Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	2.3 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Encoder interface front X31	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL
Frequency SinCos, TTL	max. 200 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 250 kHz
Data length SSI	10-28 bit

Encoder interface front X33	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL, Resolver
Frequency SinCos, TTL	max. 250 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 350 kHz
Data length SSI	10-28 bit
Resolver	Signal frequency max. 600 kHz Input voltage max. 8 Vpp Reference frequency 6 - 16 kHz Reference amplitude 8 - 28 Vpp Number of pole pairs 1 - 8 Transformation ratio 2:1, 3:1, 4:1 Phase fault max. 8°

Encoder interface terminal X23	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 10 kHz

Encoder interface terminal X27, X28	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 200 kHz

Safety Modules

Safety-M Basic module

Speed and position monitoring – MSP1

1 axis

Terminal assignment

X11		X12		X13		X14		X17	
1	2	1	2	1	2	1	2	1	2
Power supply module +24 V DC	U24 extern	Digital IN 13	DI 13 / E 0.13	Power supply encoder interface X31	U_ENC_1	Digital IN 01 (OSSD compatible)	DI 01 / E 0.1	Power supply encoder interface X33	U_ENC_3
Power supply module +24 V DC	U24 extern	Digital IN 14	DI 14 / E 0.14	Power supply encoder interface X31	GND_ENC_1	Digital IN 02 (OSSD compatible)	DI 02 / E 0.2	Power supply encoder interface X33	GND_ENC_3
Power supply module 0 V DC	GND extern	Pulse output P1	P1	Messaging and auxiliary output DO 0.1	DO 0.1 / A 0.1	Digital IN 03 (OSSD compatible)	DI 03 / E 0.3	Reference signal Res. f. encoder interf. X33	U_Ref_3
Power supply module 0 V DC	GND extern	Pulse output P2	P2	Messaging and auxiliary output DO 0.2	DO 0.2 / A 0.2	Digital IN 04 (OSSD compatible)	DI 04 / E 0.4	NC	NC

X21		X22		X23		X24		X27		X28	
1	2	1	2	1	2	1	2	1	2	1	2
HISIDE output 0	DO 0-HI / AD 0.0P	Relay output 1	K1.1 / AK 0.1	Digital IN 05 / Proximity switch 1	DI 05 / E 0.5	Digital IN 09 (OSSD compatible)	DI 09 / E 0.9	HTL input A f. encoder interface X33	HTL_A_1	HTL input B f. encoder interface X33	HTL_B_1
LOSIDE output 0	DO 0-LO / AD 0.0M	Relay output 1	K1.2 / AK 0.1	Digital IN 06 / Proximity switch 1	DI 06 / E 0.6	Digital IN 10 (OSSD compatible)	DI 10 / E 0.10	HTL input A f. encoder interface X33	HTL_A_2	HTL input B f. encoder interface X33	HTL_B_2
HISIDE output 1	DO 1-HI / AD 0.1P	Relay output 2	K1.1 / AK 0.2	Digital IN 07 / Proximity switch 2	DI 07 / E 0.7	Digital IN 11 (OSSD compatible)	DI 11 / E 0.11	HTL input A f. encoder interface X33	HTL_A_3	HTL input B f. encoder interface X33	HTL_B_3
LOSIDE output 1	DO 1-LO / AD 0.1M	Relay output 2	K1.2 / AK 0.2	Digital IN 08 / Proximity switch 2	DI 08 / E 0.8	Digital IN 12 (OSSD compatible)	DI 12 / E 0.12	NC	NC	NC	NC


Safety Modules

Safety-M Basic module	Speed and position monitoring – MSP1	1 axis
----------------------------------	---	---------------

Terminal assignment

Interface	Sub-D female connector											
Terminal X31/X32	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	-	C-	D+	D-	-	C+	+V	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH

Sub-D female connector, 9-pin




Interface	Sub-D female connector											
Terminal X33/X34	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	C+	-	D+	D-	C-	-	+V	\perp
		Resolver	R1	R2	R3	S1	S2	S4	R4	S3	RV	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / incremental output channel A
- B, \bar{B} : Sine signal / incremental output channel B
- C+, C-: Clock signal
- D+, D-: Data signal
- R1, R2: Reference output
- R3, R4: Reference input
- S1, S3: Cosine signal
- S2, S4: Sine signal
- RV: Reference power supply
- PH \perp : Plug connector housing (Shield)




HTL encoder interface A / B

without inverted signal




HTL encoder interface A, \bar{A} / B, \bar{B}

with inverted signal



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M
Basic module

Speed monitoring – MS2

2 axes



MS2 is a compact and modular safety control of the Safety-M family with integrated drive monitoring for 2 axes. This device is freely programmable for the safe processing of drive-related safety functions as well as of EMERGENCY STOP switches, two-hand operator controls, light barriers, operating mode selectors, etc. Complex motion monitoring tasks are also possible when both axes are combined.

The basic version allows 2 safe encoder connections to be implemented. 14 safe inputs, 3 safe shut-off channels and 2 safe analogue inputs (optional) are available.

1-encoder solutions (TTL/HTL, Resolver, SinCos, proximity switch) and to a limited extent also 2-encoder solutions (a combination of any encoder technologies) are supported for the safe speed and/or position detection.

- Extensive library of pre-configured safe sensors and command devices.
- Complete range of speed- and position-related safe drive monitoring functions as per DIN EN 61800 already integrated (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, SBC, EDM).
- Parameterizable encoder interface for TTL / SinCos / SSI on the front and proximity switch / HTL via terminal connection.
- Graphical programming interface by SafePLC software.

- Basic unit comes with 14 safe input lines and 3 safe shut-off channels, comprising 1 safe relay output and 2 messaging outputs.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Status monitoring by coded 7-segment-display and status LED's.
- Quit- / Start- / Reset-button on the front display.
- Extendable up to max. 65 safe I/O lines by means of an integrated backplane bus (connector for top hat rail mount).
- Optional field bus interface (bus modules for PROFIBUS DP, PROFINET IO, CANopen, EtherCAT, DeviceNet).
- 4 analogue inputs (optional).

Order code

8 . MS2 . XXX
a b c

The programming software SafePLC and the programming cable are required for programming. T-BUS connectors are required for connecting a BUS module or an expansion module.

a Analogue inputs
0 = without analogue inputs
A = with analogue inputs

b Analogue voltage measuring ¹⁾
0 = without
2 = 2 analogue voltage inputs (X25)
4 = 4 analogue voltage inputs (X25/X26)

c Analogue current measuring ¹⁾
0 = without
2 = 2 analogue current inputs (X26)
4 = 4 analogue current inputs (X25/X26)

¹⁾ 4 analogue inputs are available

Accessory		Order No.
T-bus connector		05.TBMS.000
Programming adapter		8.0010.9000.0020
Licence key SafePLC		05.SPLC.001
Connection technology		Order No.
Cordset, pre-assembled 1 m	for incremental encoders	cable with 1 x M23 / 1 x Sub-D, 9-pin 8.0000.6900.0001.0081
	for SSI signals, X31/X32	cable with 1 x M23 / 1 x Sub-D, 9-pin 8.0000.6900.0001.0068

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Safety Modules

Safety-M Basic module	Speed monitoring – MS2	2 axes
----------------------------------	-------------------------------	---------------

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.

Bus modules
For standard field bus / Ethernet interface.



Overview inputs / outputs

14 x	safe digital inputs
2 x	relays outputs (safe due to redundant operation)
2 x	digital outputs LOSIDE / HISIDE (safe due to redundant operation)
2 x	messaging outputs
4 x	analogue inputs (safe due to redundant operation) – optional

Technical data

General data	
Max. number of expansion modules	2 x EM, 1 x BM
Interface for expansion modules	T-bus connector for top hat rail mount
Safe digital input lines	14 incl. 8 OSSD
Safe digital output lines	2
Safe relay outputs	1
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]
Drive monitoring - number of axis	1 axis / 2 axes

Electrical characteristics	
Power supply	24 V DC / 2 A
Tolerance	-15 %, +20 %
Power consumption	2.4 W
Fuse on power supply	max. 2 A
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Rated data analogue inputs	±5 V DC / 0 - 10 V DC / 4 ... 20 mA
Rated data relay	24 V DC / 2 A or 230 V AC / 2 A
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Mechanical characteristics	
Size w x h x d	67.5 x 99 x 114.5 mm [2.66 x 3.90 x 4.51"]
Weight	390 g [13.76 oz]
Mounting	snap-on mounting on standard head rail

Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	2.3 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Encoder interface front X31 / X32	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL
Frequency SinCos, TTL	max. 200 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 250 kHz
Data length SSI	10-28 bit

Encoder interface terminal X23	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 10 kHz

Safety Modules


Safety-M Basic module

Speed monitoring – MS2

2 axes

Terminal assignment

X11		X12		X13		X14		X15	
1	2	1	2	1	2	1	2	1	2
Power supply module +24 V DC	U24 extern	Digital IN 13	DI 13 / E 0.13	Power supply encoder interface X31	U_ENC_1	Digital IN 01 (OSSD compatible)	DI 01 / E 0.1	Power supply encoder interface X32	U_ENC_2
Power supply module +24 V DC	U24 extern	Digital IN 14	DI 14 / E 0.14	Power supply encoder interface X31	GND_ENC_1	Digital IN 02 (OSSD compatible)	DI 02 / E 0.2	Power supply encoder interface X32	GND_ENC_2
Power supply module 0 V DC	GND extern	Pulse output P1	P1	Messaging and auxiliary output DO 0.1	DO 0.1 / A 0.1	Digital IN 03 (OSSD compatible)	DI 03 / E 0.3	NC	NC
Power supply module 0 V DC	GND extern	Pulse output P2	P2	Messaging and auxiliary output DO 0.2	DO 0.2 / A 0.2	Digital IN 04 (OSSD compatible)	DI 04 / E 0.4	NC	NC



X21		X22	
1	2	1	2
HISIDE output 0	DO 0-HI / AD 0.0P	Relay output 1	K1.1 / AK 0.1
LOSIDE output 0	DO 0-LO / AD 0.0M	Relay output 1	K1.2 / AK 0.1
HISIDE output 1	DO 1-HI / AD 0.1P	Relay output 2	K1.1 / AK 0.2
LOSIDE output 1	DO 1-LO / AD 0.1M	Relay output 2	K1.2 / AK 0.2

X23		X24	
1	2	1	2
Digital IN 05 / Proximity switch 1	DI 05 / E 0.5	Digital IN 09 (OSSD compatible)	DI 09 / E 0.9
Digital IN 06 / Proximity switch 1	DI 06 / E 0.6	Digital IN 10 (OSSD compatible)	DI 10 / E 0.10
Digital IN 07 / Proximity switch 2	DI 07 / E 0.7	Digital IN 11 (OSSD compatible)	DI 11 / E 0.11
Digital IN 08 / Proximity switch 2	DI 08 / E 0.8	Digital IN 12 (OSSD compatible)	DI 12 / E 0.12

optional (Type MS2.AXX)

X25		X26	
1	2	1	2
Analogue input AI1+	AI 1+	Analogue input AI3+	AI 3+
Analogue input AI1-	AI 1-	Analogue input AI3-	AI 3-
Analogue input AI2+	AI 2+	Analogue input AI4+	AI 4+
Analogue input AI2-	AI 2-	Analogue input AI4-	AI 4-

Type	AI1 + AI2	AI3 + AI4
MS2.A22	voltage	current
MS2.A40	voltage	voltage
MS2.A04	current	current


Safety Modules

Safety-M Basic module	Speed monitoring – MS2	2 axes
----------------------------------	-------------------------------	---------------

Terminal assignment

Interface	female connector											
Terminal X31/X32	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	-	C-	D+	D-	-	C+	+V	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH

Sub-D
female connector, 9-pin




- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / incremental output channel A
- B, \bar{B} : Sine signal / incremental output channel B

- C+, C- : Clock signal
- D+, D- : Data signal
- PH \perp : Plug connector housing (Shield)

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety Modules

Safety-M Basic module

Speed and position monitoring – MSP2

2 axes



MS2 is a compact and modular safety control of the Safety-M family with integrated drive monitoring for 2 axes. This device is freely programmable for the safe processing of drive-related safety functions as well as of EMERGENCY STOP switches, two-hand operator controls, light barriers, operating mode selectors, etc. Complex motion monitoring tasks are also possible when both axes are combined.

The basic version allows 4 safe encoder connections to be implemented. 14 safe inputs, 3 safe shut-off channels and 2 safe analogue inputs (optional) are available.

1-encoder solutions (TTL/HTL, Resolver, SinCos, proximity switch) and to a limited extent also 2-encoder solutions (a combination of any encoder technologies) are supported for the safe speed and/or position detection.

- Extensive library of pre-configured safe sensors and command devices.
- Complete range of speed- and position-related safe drive monitoring functions as per DIN EN 61800 already integrated (e.g. SS1, SS2, SOS, SLS, SDI, SLA, SSM, SCA, SBC, EDM, SLI, SLP).
- Parameterizable encoder interface for TTL / SinCos / SSI / Resolver on the front and proximity switch / HTL via terminal connection.
- Graphical programming interface by SafePLC software.

- Basic unit comes with 14 safe input lines and 3 safe shut-off channels, comprising 1 safe relay output and 2 messaging outputs.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.
- Status monitoring by coded 7-segment-display and status LED's.
- Quit- / Start- / Reset-button on the front display.
- Extendable up to max. 65 safe I/O lines by means of an integrated backplane bus (connector for top hat rail mount).
- Optional field bus interface (bus modules for PROFIBUS DP, PROFINET IO, CANopen, EtherCAT, DeviceNet).
- 4 analogue inputs (optional).

Order code

8 . MSP2 . XXX
a b c

The programming software SafePLC and the programming cable are required for programming. T-BUS connectors are required for connecting a BUS module or an expansion module.

a Analogue inputs

- 0 = without analogue inputs
- A = with analogue inputs

b Analogue voltage measuring ¹⁾

- 0 = without
- 2 = 2 analogue voltage inputs (X25)
- 4 = 4 analogue voltage inputs (X25/X26)

c Analogue current measuring ¹⁾

- 0 = without
- 2 = 2 analogue current inputs (X26)
- 4 = 4 analogue current inputs (X25/X26)

¹⁾ 4 analogue inputs are available

Accessory		Order No.	
T-bus connector		05.TBMS.000	
Programming adapter		8.0010.9000.0020	
Licence key SafePLC		05.SPLC.001	
Connection technology		Order No.	
Cordset, pre-assembled 1 m	for incremental encoders	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0081
	for SSI signals, X31/X32	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0068
	for SSI signals, X33/X34	cable with 1 x M23 / 1 x Sub-D, 9-pin	8.0000.6900.0001.0072
	for SinCos+SSI signals	cable with 1 x M23 / 2 x Sub-D, 9-pin	8.0000.6900.0001.0070
	for SinCos+SSI signals, SET/DIR separate	cable with 1 x M23 / 2 x Sub-D, 9-pin	8.0000.6900.0001.0080

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.

Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.

You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Safety Modules

Safety-M Basic module Speed and position monitoring – MSP2 2 axes

Modular construction

Basic module
Modular safety control system.

Expansion modules
For additional inputs and outputs.

Bus modules
For standard field bus / Ethernet interface.



Overview inputs / outputs

14 x	safe digital inputs
2 x	relays outputs (safe due to redundant operation)
2 x	digital outputs LOSIDE / HISIDE (safe due to redundant operation)
2 x	messaging outputs
4 x	analogue inputs (safe due to redundant operation) – optional

Technical data

General data	
Max. number of expansion modules	2 x EM, 1 x BM
Interface for expansion modules	T-bus connector for top hat rail mount
Safe digital input lines	14 incl. 8 OSSD
Safe digital output lines	2
Safe relay outputs	1
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]
Drive monitoring	2 axes

Electrical characteristics	
Power supply	24 V DC / 2 A
Tolerance	-15 %, +20 %
Power consumption	2.4 W
Fuse on power supply	max. 2 A
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Rated data analogue inputs	±5 V DC / 0 - 10 V DC / 4 ... 20 mA
Rated data relay	24 V DC / 2 A or 230 V AC / 2 A
Pulse output lines	max. 250 mA

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ... +122°F]
Storage temperature	-10°C ... +70°C [+14°F ... +158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Mechanical characteristics	
Size w x h x d	112.5 x 99 x 114.5 mm [4.43 x 3.90 x 4.51"]
Weight	520 g [18.34 oz]
Mounting	snap-on mounting on standard head rail

Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	2.3 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Encoder interface front X31 / X32	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL
Frequency SinCos, TTL	max. 200 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 250 kHz
Data length SSI	10-28 bit

Encoder interface front X33 / X34	
Type of connection	Sub-D, 9-pin
Signal	SSI, SinCos, TTL, Resolver
Frequency SinCos, TTL	max. 250 kHz
Clock frequency SSI	Mastermode 150 kHz Slavemode max. 350 kHz
Data length SSI	10-28 bit
Resolver	Signal frequency max. 600 kHz Input voltage max. 8 Vpp Reference frequency 6 - 16 kHz Reference amplitude 8 - 28 Vpp Number of pole pairs 1 - 8 Transformation ratio 2:1, 3:1, 4:1 Phase fault max. 8°

Encoder interface terminal X23	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 10 kHz

Encoder interface terminal X27, X28, X29, X30	
Type of connection	pluggable terminals, 4-pin
Signal	proximity switch, HTL
Frequency	max. 200 kHz

Safety-M Basic module

Speed and position monitoring – MSP2

2 axes

Terminal assignment


	1	2	3	4
Power supply module +24 V DC	U24 extern			
Power supply module +24 V DC	U24 extern			
Power supply module 0 V DC	GND extern			
Power supply module 0 V DC	GND extern			
Digital IN 13	DI 13 / E 0.13			
Digital IN 14	DI 14 / E 0.14			
Pulse output P1	P1			
Pulse output P2	P2			

	1	2	3	4
Power supply encoder interface X31	U_ENC_1			
Power supply encoder interface X31	GND_ENC_1			
Messaging and auxiliary output DO 0.1	DO 0.1 / A 0.1			
Messaging and auxiliary output DO 0.2	DO 0.2 / A 0.2			
Digital IN 01 (OSSD compatible)	DI 01 / E 0.1			
Digital IN 02 (OSSD compatible)	DI 02 / E 0.2			
Digital IN 03 (OSSD compatible)	DI 03 / E 0.3			
Digital IN 04 (OSSD compatible)	DI 04 / E 0.4			

	1	2	3	4
Power supply encoder interface X33	U_ENC_3			
Power supply encoder interface X33	GND_ENC_3			
Reference signal Res. f. encoder interf. X33	U_Ref_3			
NC	NC			

	1	2	3	4
Power supply encoder interface X34	U_ENC_4			
Power supply encoder interface X34	GND_ENC_4			
Reference signal Res. f. encoder interf. X34	U_Ref_4			
NC	NC			

	1	2	3	4
Power supply encoder interface X32	U_ENC_2			
Power supply encoder interface X32	GND_ENC_2			
Reference signal Res. f. encoder interf. X32	U_Ref_2			
NC	NC			



	1	2	3	4
HISIDE output 0	DO 0-HI / AD 0.0P			
LOSIDE output 0	DO 0-LO / AD 0.0M			
HISIDE output 1	DO 1-HI / AD 0.1P			
LOSIDE output 1	DO 1-LO / AD 0.1M			
Relay output 1	K1.1 / AK 0.1			
Relay output 1	K1.2 / AK 0.1			
Relay output 2	K1.1 / AK 0.2			
Relay output 2	K1.2 / AK 0.2			

	1	2	3	4
Digital IN 05 / Proximity switch 1	DI 05 / E 0.5			
Digital IN 06 / Proximity switch 1	DI 06 / E 0.6			
Digital IN 07 / Proximity switch 2	DI 07 / E 0.7			
Digital IN 08 / Proximity switch 2	DI 08 / E 0.8			
Digital IN 09 (OSSD compatible)	DI 09 / E 0.9			
Digital IN 10 (OSSD compatible)	DI 10 / E 0.10			
Digital IN 11 (OSSD compatible)	DI 11 / E 0.11			
Digital IN 12 (OSSD compatible)	DI 12 / E 0.12			

	1	2	3	4
HTL input A.f. encoder interface X33	HTL_A_1			
HTL input A.f. encoder interface X33	HTL_A_2			
HTL input A.f. encoder interface X33	HTL_A_3			
NC	NC			
HTL input B.f. encoder interface X33	HTL_B_1			
HTL input B.f. encoder interface X33	HTL_B_2			
HTL input B.f. encoder interface X33	HTL_B_3			
NC	NC			

	1	2	3	4
HTL input A.f. encoder interface X34	HTL_A_1			
HTL input A.f. encoder interface X34	HTL_A_2			
HTL input A.f. encoder interface X34	HTL_A_3			
NC	NC			
HTL input B.f. encoder interface X34	HTL_B_1			
HTL input B.f. encoder interface X34	HTL_B_2			
HTL input B.f. encoder interface X34	HTL_B_3			
NC	NC			

optional (Type MSP2.AXX)

Type	AI1 + AI2	AI3 + AI4
MSP2.A22	voltage	current
MSP2.A40	voltage	voltage
MSP2.A04	current	current

Safety Modules


Safety-M	Speed and position monitoring – MSP2	2 axes
Basic module		

Terminal assignment

Interface	Sub-D female connector											
Terminal X31/X32	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	-	C-	D+	D-	-	C+	+V	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH

Interface	Sub-D female connector											
Terminal X33/X34	Signal:	TTL	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SinCos	-	0 V	-	\bar{A}	B	\bar{B}	-	A	+V	\perp
		SSI	-	0 V	C+	-	D+	D-	C-	-	+V	\perp
		Resolver	R1	R2	R3	S1	S2	S4	R4	S3	RV	\perp
	Pin:		1	2	3	4	5	6	7	8	9	PH



Sub-D female connector, 9-pin



- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal / incremental output channel A
- B, \bar{B} : Sine signal / incremental output channel B
- C+, C-: Clock signal
- D+, D-: Data signal
- R1, R2: Reference output
- R3, R4: Reference input
- S1, S3: Cosine signal
- S2, S4: Sine signal
- RV: Reference power supply
- PH \perp : Plug connector housing (Shield)


HTL encoder interface A / B

without inverted signal





HTL encoder interface A, \bar{A} / B, \bar{B}

with inverted signal



Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M Expansion module	I/O expansion – EM3	Digital
--------------------------------------	----------------------------	----------------



Digital I/O expansion for the Safety-M basis modules.

The module is connected to the basic module via a backplane bus connector that snaps onto the standard top-hat rail.

The expansion module has 10 safe I/O optionally configurable as inputs or outputs, 12 safe inputs and 2 messaging outputs.

- 10 safe I/O – configurable as inputs or outputs.
- 12 safe inputs, incl. 8 OSSD compatible.
- 2 messaging outputs.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.	
EM3 I/O expansion, digital	8.EM3.000 T-BUS connectors are required for connecting basic modules.

Accessory	Order No.
T-bus connector	05.TBMS.000

Modular construction

Basic module Modular safety control system.	Expansion modules For additional inputs and outputs.	Bus modules For standard field bus / Ethernet interface.
MSx	EM3	BM

Overview inputs / outputs

12 x	safe digital inputs (8 x OSSD compatible)
10 x	safe digital inputs / outputs I/O
2 x	messaging outputs

Technical data

General data	
Interface for basic modules	T-bus connector for top hat rail mount
Safe digital input lines	12 incl. 8 OSSD
Safe digital I/O	10
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]

Mechanical characteristics	
Size w x h x d	45 x 99 x 114.5 mm [1.77 x 3.90 x 4.51"]
Weight	250 g [8.82 oz]
Mounting	snap-on mounting on standard head rail

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Electrical characteristics	
Power consumption	3.8 W
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Pulse output lines	max. 250 mA

Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH_d value	2.2 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Safety Modules

Safety-M Expansion module I/O expansion – EM3 Digital

Terminal assignment

X11		X12		X13		X14	
1	2	1	2	1	2	1	2
3	4	3	4	3	4	3	4
U24 extern	U24 extern	IO 01 / EA y.1	IO 02 / EA y.2	NC	NC	DI 01 / E x.1	DI 02 / E x.2
Power supply module +24 V DC	Power supply module +24 V DC	Digital I/O 1	Digital I/O 2	NC	NC	Digital IN 01 (OSSD compatible)	Digital IN 02 (OSSD compatible)
U24 extern	U24 extern	Pulse output P1	Pulse output P2	DO 0.1 / A x.1	DO 0.2 / A x.2	Digital IN 03 (OSSD compatible)	Digital IN 04 (OSSD compatible)
Power supply module 0 V DC	Power supply module 0 V DC			Messaging and auxiliary output DO 0.1	Messaging and auxiliary output DO 0.2	Digital IN 03 (OSSD compatible)	Digital IN 04 (OSSD compatible)
GND extern	GND extern						




x = 1 or 2, depending on the address of the expansion module.
y = 1 or 0, depending on whether selected as input or output.

X21		X22		X23		X24	
1	2	1	2	1	2	1	2
3	4	3	4	3	4	3	4
IO 03 / EA y.3	IO 04 / EA y.4	IO 03 / EA y.3	IO 04 / EA y.4	DI 05 / E x.5	DI 06 / E x.6	DI 09 / E x.9	DI 10 / E x.10
Digital I/O 3	Digital I/O 4	Digital I/O 7	Digital I/O 8	Digital IN 05	Digital IN 06	Digital IN 09 (OSSD compatible)	Digital IN 10 (OSSD compatible)
IO 05 / EA y.5	IO 06 / EA y.6	IO 05 / EA y.5	IO 10 / EA y.10	Digital IN 07	Digital IN 08	Digital IN 11 (OSSD compatible)	Digital IN 12 (OSSD compatible)
Digital I/O 5	Digital I/O 6	Digital I/O 9	Digital I/O 10				

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M Expansion module	I/O expansion – EM4	Relay
--------------------------------------	----------------------------	--------------



Digital I/O expansion for the Safety-M basis modules.

The module is connected to the basic module via a backplane bus connector that snaps onto the standard top-hat rail.


The expansion module has 2 safe I/O optionally configurable as inputs or outputs, 12 safe inputs, 2 messaging outputs as well as 4 safe relay outputs.

- 2 safe I/O – configurable as inputs or outputs.
- 12 safe inputs, incl. 8 OSSD compatible.
- 2 messaging outputs.
- 4 safe relay outputs.
- Cross-short-cut monitoring functionality.
- Contact multiplication or increase of power capability by external contactors in connection with the device-internal monitoring function for external contacts.
- Extensive diagnostic functionality integrated in FW.

Order No.	
EM4 I/O expansion, relay	8.EM4.000 T-BUS connectors are required for connecting basic modules.

Accessory	Order No.
T-bus connector	05.TBMS.000

Modular construction



Overview inputs / outputs

12 x	safe digital inputs (8 x OSSD compatible)
2 x	safe digital inputs / outputs I/O
8 x	relay outputs (safe due to redundant operation)
2 x	messaging outputs

Technical data

General data	
Interface for basic modules	T-bus connector for top hat rail mount
Safe digital input lines	12 incl. 8 OSSD
Safe digital I/O	10
Messaging outputs	2
Pulse output lines	2
Type of connection	pluggable terminals, coded
Max. terminal cross section	1.5 mm ² [AWG 15]

Mechanical characteristics	
Size w x h x d	90 x 99 x 114.5 mm [3.54 x 3.90 x 4.51"]
Weight	540 g [19.05 oz]
Mounting	snap-on mounting on standard head rail

Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178
EMC	acc. to EN 55011 and EN 61000-6-2

Electrical characteristics	
Power consumption	3.8 W
Rated data digital inputs	24 V DC / 20 mA, type 1 to EN 61131-2
Rated data digital outputs	24 V DC / 250 mA
Pulse output lines	max. 250 mA


Safety characteristics	
Relevant standards	EN ISO 13849-1 / EN 62061, EN 61508
Classification	PLe / SIL3
System structure	2 channel (Cat. 4 / HFT = 1)
PFH _d value	6.0 x 10 ⁻⁹ h ⁻¹
Proof-test intervall	20 years

Safety Modules

Safety-M Expansion module I/O expansion – EM4 Relay

Terminal assignment

X07		X08		X09		X10		X11		X12		X13		X14					
1	2	3	4	1	2	3	4	1	2	3	4	1	2	3	4	1	2	3	4
Read back contact relay 1	K1/11	Read back contact relay 3	K3/11	Read back contact relay 5	K5/11	Read back contact relay 7	K7/11	Power supply module +24 V DC	U24 extern	Digital I/O 1	IO 01 / EA y.1	NC	NC	Digital IN 01 (OSSD compatible)	D1/01 / E.x.1				
Read back contact relay 2	K1/12	Read back contact relay 4	K3/12	Read back contact relay 6	K5/12	Read back contact relay 8	K7/12	Power supply module +24 V DC	U24 extern	Digital I/O 2	IO 02 / EA y.2	NC	NC	Digital IN 02 (OSSD compatible)	D1/02 / E.x.2				
Read back contact relay 2	K2/11	Read back contact relay 3	K3/11	Read back contact relay 6	K6/11	Read back contact relay 8	K8/11	Power supply module 0 V DC	GND extern	Pulse output	P1	Messaging and auxiliary output DO 0.1	DO 0.1 / A.x.1	Digital IN 03 (OSSD compatible)	D1/03 / E.x.3				
Read back contact relay 2	K2/12	Read back contact relay 4	K4/11	Read back contact relay 6	K6/12	Read back contact relay 8	K8/12	Power supply module 0 V DC	GND extern	Pulse output	P2	Messaging and auxiliary output DO 0.2	DO 0.2 / A.x.2	Digital IN 04 (OSSD compatible)	D1/04 / E.x.4				




x = 1 or 2, depending on the address of the expansion module.
y = 1 or 0, depending on whether selected as input or output.

Relay output 1	K1.1 / AK x.1	Relay output 5	K5.1 / AK x.5	Digital IN 05	D1/05 / E.x.5
Relay output 1	K1.2 / AK x.1	Relay output 5	K5.2 / AK x.5	Digital IN 06	D1/06 / E.x.6
Relay output 2	K2.1 / AK x.2	Relay output 6	K6.1 / AK x.6	Digital IN 07	D1/07 / E.x.7
Relay output 2	K2.2 / AK x.2	Relay output 6	K6.2 / AK x.6	Digital IN 08	D1/08 / E.x.8
Relay output 3	K3.1 / AK x.3	Relay output 7	K7.1 / AK x.7	Digital IN 09 (OSSD compatible)	D1/09 / E.x.9
Relay output 3	K3.2 / AK x.3	Relay output 7	K7.2 / AK x.7	Digital IN 10 (OSSD compatible)	D1/10 / E.x.10
Relay output 4	K4.1 / AK x.4	Relay output 8	K8.1 / AK x.8	Digital IN 11 (OSSD compatible)	D1/11 / E.x.11
Relay output 4	K4.2 / AK x.4	Relay output 8	K8.2 / AK x.8	Digital IN 12 (OSSD compatible)	D1/12 / E.x.12

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M Bus module	Communication module – BM11	DeviceNet
----------------------------	------------------------------------	------------------



DeviceNet

The BM communication modules ensure data exchange between the Safety-M basic modules and non-safe controls. It is for example possible to send error and operating messages. In addition, they allow transmitting process and logic data such as the current position and/or speed, as well as the status of the inputs and outputs.

The communication modules are operated together with a basic module on a common backplane bus and thus take on the functionality of a gateway to the corresponding field bus.

- The binary or analogue input or output data, configured for each module by a safe PLC, are transmitted from and to the non-safe control via field bus.
- This connection allows for coordination of the non-safe and of the safe sections of the global system thanks to easily configurable functions.
- The communication modules BM are to be parameterised as slave elements.
- The communication modules permit a basic module to be connected to a field bus communication module via a common backplane.

DeviceNet

EDS files are available on the Safety-M software CD and online on our homepage.

The DeviceNet baud rates of 125 kbps, 250 kbps und 500 kbps can be set with the address switches on the front side.

Order No.		
BM11	BUS communication - DeviceNet	8.BM11.000

Accessory		Order No.
T-bus connector	to connect basic and expansion modules	05.TBMS.000
Connection technology		Order No.
Unprepared cable	DeviceNet cable	05.KABEL5723.XXX ¹⁾

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module	Expansion modules	Bus modules
Modular safety control system.	For additional inputs and outputs.	For standard field bus / Ethernet interface.
MSx	EM	BM11

¹⁾ Cable length in meters (xxx = length in m; e.g. 10 m = 010).

Safety Modules

Safety-M Bus module	Communication module – BM11	DeviceNet
----------------------------	------------------------------------	------------------

Technical data

Data interface	
Max. numbers of basic modules	1
Output data	max. 128 bit / basic module
Minimum operating time	> 8 ms
Timeout WD	adjustable, max. 400 ms


Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178

Electrical characteristics	
Power consumption	2.4 W
Power supply	5.7 V via backplane bus

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	110 g [3.88 oz]
Mounting	snap-on mounting on standard head rail

Connector pin assignment

Pin	Assignment
1	BUS_GND ¹⁾
2	CAN_L
3	CAN_GND
4	CAN_H
5	BUS_VDC ¹⁾




Address switches

Addr HIGH				Addr LOW				Baud rate	Node ID
B7	B6	B5	B4	B3	B2	B1	B0		
-	-	0	0	0	0	0	0	-	0
-	-	0	0	0	0	0	1	-	1
-	-	0	0	0	0	1	0	-	2
-	-	0	0	0	0	1	1	-	3
-	-	-	...
-	-	1	1	1	1	0	1	-	61
-	-	1	1	1	1	1	0	-	62
-	-	1	1	1	1	1	1	-	63
0	0	-	-	-	-	-	-	125 kbps	-
0	1	-	-	-	-	-	-	250 kbps	-
1	0	-	-	-	-	-	-	500 kbps	-
1	1	-	-	-	-	-	-	AutoBaud	not supported

Dimensions

Dimensions in mm [inch]



1) For supplying an external DeviceNet termination resistor.

Safety Modules

Safety-M Bus module	Communication module – BM21	CANopen
----------------------------	------------------------------------	----------------



The BM communication modules ensure data exchange between the Safety-M basic modules and non-safe controls. It is for example possible to send error and operating messages. In addition, they allow transmitting process and logic data such as the current position and/or speed, as well as the status of the inputs and outputs.

The communication modules are operated together with a basic module on a common backplane bus and thus take on the functionality of a gateway to the corresponding field bus.

- The binary or analogue input or output data, configured for each module by a safe PLC, are transmitted from and to the non-safe control via field bus.
- This connection allows for coordination of the non-safe and of the safe sections of the global system thanks to easily configurable functions.
- The communication modules BM are to be parameterised as slave elements.
- The communication modules permit 4 basic modules to be connected to a field bus communication module via a common backplane.

CANopen

EDS files are available on the Safety-M software CD and online on our homepage.

The CANopen baud rate of 500 kbps is fixed.

Order No.		
BM21	BUS communication - CANopen	8.BM21.000

Accessory		Order No.
T-bus connector	to connect basic and expansion modules	05.TBMS.000
	to connect several basic modules	05.TBFM.000

Connection technology		Order No.
Unprepared cable	CANopen cable	8.0000.6V00.XXX ¹⁾
Connector, self-assembly	Sub-D connector, 9-pin – angled 70°	8.0000.514A.0000

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module	Expansion modules	Bus modules
Modular safety control system.	For additional inputs and outputs.	For standard field bus / Ethernet interface.
MSx	EM	BM21

¹⁾ Cable length in meters (xxx = length in m; e.g. 10 m = 010).

Safety Modules

Safety-M Bus module	Communication module – BM21	CANopen
----------------------------	------------------------------------	----------------

Technical data

Data interface	
Max. numbers of basic modules	4
Input data	max. 32 bit / basic module
Output data (binary, analogue)	max. 128 bit / basic module
Minimum operating time	> 8 ms
Timeout WD	adjustable, max. 400 ms


Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178

Electrical characteristics	
Power consumption	2.4 W
Power supply	5.7 V via backplane bus

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	110 g [3.88 oz]
Mounting	snap-on mounting on standard head rail


Connector pin assignment

Pin	Assignment
1	-
2	CAN_L
3	-
4	-
5	CAN_GND
6	-
7	CAN_H
8	-
9	-
housing	SHIELD



DIP switches

Switch	Assignment
1	120 Ohm terminating resistor Backplane bus
2	120 Ohm terminating resistor Sub-D female connector CANopen




Address switches

B7	Addr HIGH				Addr LOW				Baud rate	Node ID
	B6	B5	B4	B3	B2	B1	B0			
-	0	0	0	0	0	0	0	-	0	
-	0	0	0	0	0	0	1	-	1	
-	0	0	0	0	0	1	0	-	2	
-	0	0	0	0	0	1	1	-	3	
-	-	...	
-	1	1	1	1	1	0	1	-	125	
-	1	1	1	1	1	1	0	-	126	
-	1	1	1	1	1	1	1	-	127	
0	-	-	-	-	-	-	-	500 kbps		
1	-	-	-	-	-	-	-	1000 kbps	not supported	

Dimensions

Dimensions in mm [inch]



Safety Modules

Safety-M Bus module	Communication module – BM31	PROFIBUS DP
----------------------------	------------------------------------	--------------------



The BM communication modules ensure data exchange between the Safety-M basic modules and non-safe controls. It is for example possible to send error and operating messages. In addition, they allow transmitting process and logic data such as the current position and/or speed, as well as the status of the inputs and outputs.

The communication modules are operated together with a basic module on a common backplane bus and thus take on the functionality of a gateway to the corresponding field bus.

- The binary or analogue input or output data, configured for each module by a safe PLC, are transmitted from and to the non-safe control via field bus.
- This connection allows for coordination of the non-safe and of the safe sections of the global system thanks to easily configurable functions.
- The communication modules BM are to be parameterised as slave elements.
- The communication modules permit 4 basic modules to be connected to a field bus communication module via a common backplane.

PROFIBUS DP

GSD files are available on the Safety-M software CD and online on our homepage.

The Profibus baud rate of 9.6 kBaud up to 12 Mbaud is recognised automatically.

Order No.		
BM31	BUS communication - PROFIBUS DP	8.BM31.000

Accessory		Order No.
T-bus connector	to connect basic and expansion modules	05.TBMS.000
	to connect several basic modules	05.TBFM.000

Connection technology		Order No.
Unprepared cable	Profibus cable	05.KABEL451.XXX¹⁾
Connector, self-assembly	Sub-D connector, 9-pin – angled 70°	8.0000.514A.0000

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module	Expansion modules	Bus modules
Modular safety control system.	For additional inputs and outputs.	For standard field bus / Ethernet interface.
MSx	EM	BM31

1) Cable length in meters (xxx = length in m; e.g. 10 m = 010).

Safety Modules

Safety-M Bus module	Communication module – BM31	PROFIBUS DP
----------------------------	------------------------------------	--------------------

Technical data

Data interface	
Max. numbers of basic modules	4
Output data (binary, analogue)	max. 128 bit/ basic module
Minimum operating time	> 8 ms
Timeout WD	adjustable, max. 400 ms


Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178

Electrical characteristics	
Power consumption	2.4 W
Power supply	5.7 V via backplane bus

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	110 g
Mounting	snap-on mounting on standard head rail


Connector pin assignment

Pin	Assignment
1	-
2	-
3	PB_B
4	-
5	BUS_GND ¹⁾
6	BUS_VDC ¹⁾
7	-
8	PB_A
9	-



DIP switches

Switch	Assignment
1	120 Ohm terminating resistor Backplane bus
2	120 Ohm terminating resistor Sub-D female connector PROFIBUS DP




Address switches

Addr HIGH				Addr LOW				Baud rate	Node ID
B7	B6	B5	B4	B3	B2	B1	B0		
0	0	0	0	0	0	0	0	-	0
0	0	0	0	0	0	0	1	-	1
0	0	0	0	0	0	1	0	-	2
0	0	0	0	0	0	1	1	-	3
-	-	...
1	1	1	1	1	1	0	1	-	253
1	1	1	1	1	1	1	0	-	254
1	1	1	1	1	1	1	1	-	255

Dimensions

Dimensions in mm [inch]



1) For supplying an external Profibus-DP termination resistor.

Safety Modules

Safety-M Bus module	Communication module – BMB1	EtherCAT
----------------------------	------------------------------------	-----------------



The BM communication modules ensure data exchange between the Safety-M basic modules and non-safe controls. It is for example possible to send error and operating messages. In addition, they allow transmitting process and logic data such as the current position and/or speed, as well as the status of the inputs and outputs.

The communication modules are operated together with a basic module on a common backplane bus and thus take on the functionality of a gateway to the corresponding field bus.

- The binary or analogue input or output data, configured for each module by a safe PLC, are transmitted from and to the non-safe control via field bus.
- This connection allows for coordination of the non-safe and of the safe sections of the global system thanks to easily configurable functions.
- The communication modules BM are to be parameterised as slave elements.
- The communication modules permit 4 basic modules to be connected to a field bus communication module via a common backplane.

EtherCAT

ESI files are available on the Safety-M software CD and online on our homepage.

The EtherCAT transmission rate is 100 Mbit/s in full-duplex mode.

Order No.		
BMB1	BUS communication - EtherCAT	8.BMB1.000

Accessory		Order No.
T-bus connector	to connect basic and expansion modules	05.TBMS.000
	to connect several basic modules	05.TBFM.000
Connection technology		Order No.
Unprepared cable	Ethernet cable	05.00.6031.1111.XXXM ¹⁾
Connector, self-assembly	RJ45 connector straight, IP20	05.VS-08-RJ45-5-Q/IP20

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction

Basic module	Expansion modules	Bus modules
Modular safety control system.	For additional inputs and outputs.	For standard field bus / Ethernet interface.
MSx	EM	BMB1

¹⁾ Cable length in meters (xxx = length in m; e.g. 10 m = 010)

Safety Modules

Safety-M Bus module	Communication module – BMB1	EtherCAT
--------------------------------	------------------------------------	-----------------

Technical data

Data interface	
Max. numbers of basic modules	4
Input data	max. 64 bit / basic module
Output data	max. 128 bit / basic module
Minimum operating time	> 8 ms
Timeout WD	adjustable, max. 400 ms


Environmental data	
Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Protection acc. to EN 60529	IP52
Climate class	3 acc. to DIN 50178

Electrical characteristics	
Power consumption	2.4 W
Power supply	5.7 V via backplane bus

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	110 g [3.88 oz]
Mounting	snap-on mounting on standard head rail


Connector pin assignment

Pin	Assignment	Colour
1	TxD+	white-orange
2	TxD-	orange
3	RxD+	white-green
4	-	blue
5	-	white-blue
6	RxD-	green
7	-	white-brown
8	-	brown



Dimensions

Dimensions in mm [inch]



X1: BUS Port OUT
X2: BUS Port IN

Safety Modules

Safety-M Bus module	Communication module – BMC1	PROFINET IO
----------------------------	------------------------------------	--------------------



The BM communication modules ensure data exchange between the Safety-M basic modules and non-safe controls. It is for example possible to send error and operating messages. In addition, they allow transmitting process and logic data such as the current position and/or speed, as well as the status of the inputs and outputs.

The communication modules are operated together with a basic module on a common backplane bus and thus take on the functionality of a gateway to the corresponding field bus.

- The binary or analogue input or output data, configured for each module by a safe PLC, are transmitted from and to the non-safe control via field bus.
- This connection allows for coordination of the non-safe and of the safe sections of the global system thanks to easily configurable functions.
- The communication modules BM are to be parameterised as slave elements.
- The communication modules permit 4 basic modules to be connected to a field bus communication module via a common backplane.

PROFINET IO

GSDML files are available on the Safety-M software CD and online on our homepage.

The PROFINET baud rate is 100 Mbit/s in full-duplex mode.


Order No.		
BMC1	BUS communication - PROFINET IO	8.BMC1.000

Accessory		Order No.
T-bus connector	to connect basic and expansion modules RJ45	05.TBMS.000
	to connect several basic modules	05.TBFM.000

Connection technology		Order No.
Unprepared cable	Ethernet cable	05.00.6031.1111.XXXM ¹⁾
Connector, self-assembly	RJ45 connector straight, IP20	05.VS-08-RJ45-5-Q/IP20

Further accessories can be found in accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Modular construction



¹⁾ Cable length in meters (xxx = length in m; e.g. 10 m = 010)

Safety Modules


Safety-M Bus module	Communication module – BMC1	PROFINET IO
--------------------------------	------------------------------------	--------------------

Technical data

Data interface		Environmental data	
Max. numbers of basic modules	4	Operating temperature	0°C ... +50°C [+32°F ...+122°F]
Input data	max. 92 bit / basic module	Storage temperature	-10°C ... +70°C [+14°F ...+158°F]
Output data (binary, analogue)	max. 128 bit / basic module	Protection acc. to EN 60529	IP52
Minimum operating time	> 8 ms	Climate class	3 acc. to DIN 50178
Timeout WD	adjustable, max. 400 ms		
Electrical characteristics		Mechanical characteristics	
Power consumption	2.4 W	Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Power supply	5.7 V via backplane bus	Weight	110 g [3.88 oz]
		Mounting	snap-on mounting on standard head rail


Connector pin assignment


Pin	Assignment	Colour
1	TxD+	white-orange
2	TxD-	orange
3	RxD+	white-green
4	-	blue
5	-	white-blue
6	RxD-	green
7	-	white-brown
8	-	brown



Dimensions

Dimensions in mm [inch]





Services

Advice		Page
Safety Services	Risk Assessment	216
	Safety Concept	217
	Start-up / Validation	218
	Safety Retrofit	219
Support		Page
Application	PreSales	220
Service	AfterSales	222

Advice	Safety Services	Risk Assessment
---------------	------------------------	------------------------



The Risk Assessment service package includes the following points:

- **Directives and standards research**
- **Analysis of the operating modes**
- **Risk assessment**
- **Documentation**

Operators of machines or plants can be exposed to increased hazard potentials. These potentials can be mitigated with suitable protective equipment and safety measures.

Safety Services by Kübler will support you with custom-tailored service packages during the whole service life cycle of your machine / plant.

Risk Assessment

The compliance with the applicable safety and health requirements is the cornerstone of a safe machine. Something that goes wrong already at the start, during risk assessment, can lead to expensive consequences at a later time. No one wants to have to add constructive measures or to modify totally the control concept because of missing safety technology. And, at the end, all steps need to be documented in a legally secure way.

This service package is based on a description of the machine, its processes and operating sequences.

Risk assessment pursuant to Annex I of the Machinery Directive, using standard EN ISO 12100.

Contents

- **Directives and standards research**
Inspection of the machine / plant according to the applicable international or national provisions.
- **Analysis of the operating modes**
Definition and evaluation of the different operating modes of the machine / plant.
- **Risk assessment**
Determination of the risks in all operating modes of the machine / plant.
- **Documentation**
Preparation of a customer documentation for an EC-compliant proof.

Order No.

Risk Assessment

8.DLSS.100

(Service Package)

Other Safety Services	Order No.
Safety Concept	8.DLSS.200
Start-up / Validation	8.DLSS.400
Safety Retrofit	8.DLSS.500
Further service packages on request	

Further information can be found on our website under www.kuebler.com/safety.

Advice	Safety Services	Safety Concept
---------------	------------------------	-----------------------



The Safety Concept service package includes the following points:

- **Analysis of the risks**
- **Selection of the components**
- **Documentation**

Operators of machines or plants can be exposed to increased hazard potentials. These potentials can be mitigated with suitable protective equipment and safety measures.

Safety Services by Kübler will support you with custom-tailored service packages during the whole service life cycle of your machine / plant.

<p>Safety Concept</p> <p>The best safety concepts are useless if they cannot be implemented; this is why the many years of know-how of this branch are requested when working out the concept. The safety concept turns the requirement of the risk assessments into actions. Constructive actions, technical actions or organisational actions can be defined here, always according to the state-of-the-art technology, for a long service life of the machine / plant.</p> <p>This service package is based on a risk assessment of the machine.</p> <p>Safety Concept pursuant to Annex I of the Machinery Directive, using standard EN ISO 12100.</p>	<p>Contents</p> <ul style="list-style-type: none"> • Analysis of the risks This analysis is based on a risk assessment for identifying all risks. • Selection of the components Selection of the suitable components with description of the respective tasks, and supply of the respective documentation. • Documentation Preparation of a customer documentation for an EC-compliant proof.
---	--

Order No.	
Safety Concept (Service Package)	8.DLSS.200

Other Safety Services	Order No.
Risk Assessment	8.DLSS.100
Start-up / Validation	8.DLSS.400
Safety Retrofit	8.DLSS.500
Further service packages on request	

Further information can be found on our website under www.kuebler.com/safety.

Advice	Safety Services	Start-up / Validation
---------------	------------------------	------------------------------



The Start-up / Validation service package includes the following points:

- **Installation of the components**
- **Functional test in the plant**
- **Acceptance of the components**
- **Documentation**

Operators of machines or plants can be exposed to increased hazard potentials. These potentials can be mitigated with suitable protective equipment and safety measures.

Safety Services by Kübler will support you with custom-tailored service packages during the whole service life cycle of your machine / plant.

Start-up / Validation

The selected components are commissioned by Kübler according to the requirements of the safety concept. The customer saves a thorough training in the software and in the handling. After the functional tests, the components are accepted and handed out to the customer. A comprehensive protocol is elaborated to serve as a documentation.

Acceptance with functional and system tests using standard EN ISO 13849-2.

Contents

- **Installation of the components**
Commissioning of the safety components according to the instructions.
- **Functional test in the plant**
Functional test of all safety functions and switching-off paths of the safety components.
- **Acceptance of the components**
Validation of the safety functions and integration in the documentation, on request also in cooperation with a certifying body.
- **Documentation**
Preparation of a customer documentation for an EC-compliant proof.

Order No.

Start-up / Validation
(Service Package)

8.DLSS.400

Other Safety Services	Order No.
Risk Assessment	8.DLSS.100
Safety Concept	8.DLSS.200
Safety Retrofit	8.DLSS.500
Further service packages on request	

Further information can be found on our website under www.kuebler.com/safety.

Advice	Safety Services	Safety Retrofit
---------------	------------------------	------------------------



The Safety Retrofit service package includes the following points:

- **Project management**
- **Working out a safety concept**
- **Components procurement**
- **Modification / Integration**
- **Commissioning / Acceptance**
- **Documentation**

Operators of machines or plants can be exposed to increased hazard potentials. These potentials can be mitigated with suitable protective equipment and safety measures.

Safety Services by Kübler will support you with custom-tailored service packages during the whole service life cycle of your machine / plant.

<p>Safety Retrofit</p> <p>The largest service package encompasses other service packages (Safety Concept and Start-up / Validation) and includes in addition the mechanical and electrical installation of the components. Optionally, the risk assessment can be carried out previously with the customer.</p> <p>Since modifications or integrations of new machine elements are mostly issues that are time-critical and involve complex safety technology, this service package ensures the customer an all-round „no-worry“ package allowing him to concentrate in a time-optimised manner on his core competencies. After the acceptance, the customer has a revised safe machine and a legally secure documentation describing the modification for his files.</p>	<p>Contents</p> <ul style="list-style-type: none"> • Project management A well-functioning project management is important for the coordination of the timeframes and a reliable planning. • Working out a safety concept Preparation of a safety concept that will result in the actions for risk minimisation. • Components procurement Definition and procurement of all necessary components. • Modification / Integration Mechanical and electrical modifications of the machine and plant. • Commissioning / Acceptance Commissioning and test of all safety components. • Documentation Preparation of a customer documentation for an EC-compliant proof.
--	--

Order No.	
Safety Retrofit (Service Package)	8.DLSS.500

Other Safety Services	Order No.
Risk Assessment	8.DLSS.100
Further service packages on request	

Further information can be found on our website under www.kuebler.com/safety.

Support	Application	PreSales
---------	-------------	----------



Kübler Hotline

An expert is always available for your questions, per phone or e-mail, on our Kübler Service hotline. Whatever the topic, general information or complex technical questions or problems: we react immediately and find the suitable solution to your request.

- Contact persons with technical training.
- Specialists with practical experience.
- Highly efficient processes and solutions.
- Quick response with immediate delivery of parts.
- Solution for applications involving third-party suppliers.
- Advice and choice of tailor-made products.
- Analysis and selection of a suitable device for the customer's task/application.



Web Service

Service at any time and anywhere. Kübler offers on line an elaborate all-round service program. We answer your questions – from planning, passing through design and programming up to maintenance – in a systematic, user-friendly and understandable way. Our service for continuous availability and lasting solutions.

- Technical data and drawings.
- Data sheets, operating instructions, catalogues, manuals.
- CAD data for mechanical design.
- ePlan macros for electrical design.
- Kübler webinars about many technical topics.
- Targeted product finder.



Application Engineering

Qualified application engineers are at your disposal to guide you from products overview with suitable product selection through project planning, mounting and integration, up to successfully and safely operating systems. With Kübler, you can rely on guaranteed safety – up to the Functional Safety technology.

- Support as from the first planning step.
- Experienced project engineers.
- Costs reduction thanks to fast commissioning.
- Reliable and safe functions.
- Adaptation and implementation.
- Support in case of malfunctions and troubleshooting.
- Comprehensive advice.



Tailor-made Solutions – Kübler Design System (KDS) OEM Products and Systems (OPS)

Together with our customers, we develop product and engineering solutions for customer-specific products, integrated drive solutions, up to complete systems (sensors, electronics and mechanics).

Support	Application	PreSales
---------	-------------	----------



Prototyping

Together with our customers, we turn ideas into parts that can be touched: regardless of whether they are sensors, electronic or mechanical parts. We develop engineering products ranging from integrated drive solutions to complete customer-specific systems.

- Technical and economic feasibility study.
- Upon release, delivery of a test sample of the customer-specific device including possibly necessary accessories and mounting parts.



Training

Long-term success with successful systems begins with the foundation: a comprehensive offer of product and topical trainings and seminars prepares you and your product for the future. The graded contents range - of course prepared accordingly - from the basics up to the refinements of sophisticated solutions.

- Product trainings in the customer's or in our premises.
- Topical training relating to field bus, safety, encoder basics and many others.
- Project and innovation workshops for new solutions.
- On-line training via remote connections.

Support	Service	AfterSales
 <p>Kübler Hotline</p> <p>An expert is always available for your questions, per phone or e-mail, on our Kübler Service Hotline.</p> <p>Whatever the topic, general information or complex technical questions or problems: we react immediately and find the suitable solution to your request.</p>		<ul style="list-style-type: none"> • Technical explanations. • Assistance for programming. • Support for connection and commissioning. • Problem and troubleshooting.
 <p>On-Site Service</p> <p>Kübler experts are working for you all over the world.</p>		<ul style="list-style-type: none"> • On-site as-is analysis in collaboration with the customer for error analysis and problem solving. • Direct communication during physical system analysis. • Customer maintenance personnel relief.
 <p>Commissioning Support</p> <p>Commissioning monitored by Kübler Service specialists saves time and costs. This ensures our customers a twofold benefit:</p> <p>Thanks to fast processes followed by long trouble-free operation. Everything works as planned.</p>		<ul style="list-style-type: none"> • Cost saving thanks to shorter commissioning. • Prevents consequential damage. • Proper parameterising of the Kübler components. • Safety thanks to test runs. • Plant integration. • Possibly necessary adaptations.
 <p>Repair Service</p> <p>Good to know: your product is in good hands with us.</p> <p>If it must be sent back for repair, we put it back in perfect condition according to a clear and systematic procedure. Our service is reliable and fast, our service technicians are conscientious and well-trained. Because we want everything to run smoothly for you.</p>		<ul style="list-style-type: none"> • Structured registration upon RMA (Return Material Authorisation). • Fast device analysis: max. 5 working days. • Repair report, test report, detailed failure description, cause analysis. • Estimated charges / Timetable.
 <p>48 h Express Service</p> <p>We manufacture your order within 48 hours; products on stock are shipped the same day.</p>		<ul style="list-style-type: none"> • Simplified orders. • Calculable delivery. • Flexible use of small batch sizes.

Support	Service	AfterSales
----------------	----------------	-------------------



Service Sites

Kübler has service sites all over the world for diagnostics, error analysis and repair, with qualified technicians who will be glad to support you.

- Germany – Villingen Schwenningen
- China – Beijing
- India – Pune
- USA – Charlotte



Service Centers / Technical Hotline


Kübler's technicians are available on site all over the world for advice, analysis or installation support.

Phone

Kübler Germany	+49 7720 3903 952
Kübler France	+33 3 89 53 45 45
Kübler Italy	+39 026 423 345
Kübler Poland	+48 61 84 99 902
Kübler Turkey	+90 216 999 9791
Kübler China	+86 10 5134 8680
Kübler India	+91 8600 147 280
Kübler USA	+1 855 583 2537


E-Mail

support_EN@kuebler.com
safetysupport@kuebler.com




Connection Technology




		Page
Cable	Unprepared, cut to length	226
M12 connection technology	Connectors, self-assembly	228
	Cordsets, pre-assembled	229
M23 connection technology	Connectors, self-assembly	231
	Cordsets, pre-assembled	233
Sub-D connection technology	Connectors, self-assembly	235
	Cordsets, pre-assembled	236
RJ45 connection technology	Connectors, self-assembly	243
	Cordsets, pre-assembled	244



Further connection technology you will find in our catalogue "Transmission Technology" or under:







www.kuebler.com/connection_technology



Cable		Unprepared, cut to length		
8 core + shield				
PUR trailing cable halogen-free, flame resistant 	Cross section Permanent working temp. range flexible installation secure installation Bending radius flexible installation secure installation Cable diameter	8 x 0.14 mm ² [AWG25] -20°C ... +80°C [-4°F ... +176°F] -40°C ... +80°C [-40°F ... +176°F] min. 65 mm [2.56"] min. 45 mm [1.77"] approx. 5.5 mm ±0.2 mm	suitable for: Limes, 365X, 368X SSI and analogue Safety-M	8.0000.6P00.XXXX ¹⁾
	Cross section Permanent working temp. range flexible installation secure installation Bending radius flexible installation secure installation Cable diameter	3 x 2 x 0.14 mm ² [AWG25] + 2 x 0.5 mm ² [AWG20] -40°C ... +90°C [-40°F ... +194°F] -50°C ... +90°C [-58°F ... +194°F] min. 111 mm [4.37"] min. 55 mm [2.17"] approx. 7.4 mm ±0.3 mm	suitable for: Limes, 365X, 368X SSI and analogue Safety-M	8.0000.6F00.XXXX ¹⁾
10 core + shield				
PUR electronic trailing cable halogen-free 	Cross section Permanent working temp. range flexible installation secure installation Bending radius flexible installation secure installation Cable diameter	4 x 2 x 0.25 mm ² [AWG23] + 2 x 1 mm ² [AWG17] -40°C ... +90°C [-40°F ... +194°F] -50°C ... +90°C [-58°F ... +194°F] min. 95 mm [3.74"] min. 40 mm [1.57"] approx. 7.9 mm ±0.7mm	suitable for: H100 with speed switch LA10, LA50 Safety-M	8.0000.6400.XXXX ¹⁾
	Cross section Permanent working temp. range flexible installation secure installation Bending radius flexible installation secure installation Cable diameter	10 x 0.14 mm ² [AWG25] + 2 x 0.5 mm ² [AWG20] -30°C ... +80°C [-22°F ... +176°F] -50°C ... +90°C [-58°F ... +194°F] min. 50 mm [1.97"] min. 35 mm [1.38"] approx. 6.9 mm ±0.3 mm	suitable for: robust incremental encoders	8.0000.6100.XXXX ¹⁾
12 core + shield				
PUR electronic trailing cable halogen-free 	Cross section Permanent working temp. range flexible installation secure installation Bending radius flexible installation secure installation Cable diameter	12 x 0.14 mm ² [AWG25] + 2 x 0.5 mm ² [AWG20] -5°C ... +70°C [+23°F ... +158°F] -30°C ... +80°C [-22°F ... +176°F] min. 100 mm [3.94"] min. 70 mm [2.76"] approx. 6.7 mm ±0.2 mm	suitable for: incremental encoders standard cable	8.0000.6200.XXXX ¹⁾
	Cross section Permanent working temp. range flexible installation secure installation drag chain operation Bending radius flexible installation secure installation Cable diameter	6 x 2 x 0.14 mm ² [AWG25] -30°C ... +90°C [-22°F ... +194°F] -40°C ... +90°C [-40°F ... +194°F] -25°C ... +60°C [-13°F ... +140°F] min. 50 mm [1.97"] min. 35 mm [1.38"] approx. 7.5 mm ±0.2 mm	suitable for: robust incremental encoders LA10	8.0000.6Y00.XXXX ¹⁾










1) XXX = cable length in meters (e.g. 10 m = 010)

Connection Technology

Cable		Unprepared, cut to length			Order No.
12 core + shield					
TPE electronic cable halogen-free 	Cross section Permanent working temp. range Bending radius Cable diameter	5 x 2 x 0.14 mm ² [AWG25] + 2 x 0.5 mm ² [AWG20] flexible installation secure installation flexible installation secure installation min. 90 mm [3.54"] min. 70 mm [2.76"] approx. 8.5 mm ±0.4 mm	suitable for: high temperatures or encoders with sine wave output	8.0000.6E00.XXXX¹⁾	
PVC electronic cable LiYCY 	Cross section Permanent working temp. range Bending radius Cable diameter	6 x 2 x 0.14 mm ² [AWG25] flexible installation secure installation flexible installation secure installation -5°C ... +70°C [+23°F ... +158°F] -30°C ... +80°C [-22°F ... +176°F] min. 110 mm [4.33"] min. 75 mm [2.95"] approx. 7.3 mm ±0.2 mm	suitable for: absolute encoders with SSI or 4 ... 20 mA analogue output, twisted pair conductors	8.0000.6900.XXXX¹⁾	
PROFIBUS DP - cable					
PUR outer jacket, PE wire insulation 	Cross section Permanent working temp. range Bending radius Cable diameter	2 x 0.34 mm ² [AWG22] flexible installation secure installation flexible installation secure installation -30°C ... +70°C [-22°F ... +158°F] -50°C ... +90°C [-58°F ... +194°F] min. 70 mm [2.76"] min. 50 mm [1.97"] approx. 7.6 mm ±0.2 mm	suitable for: all Profibus fieldbus encoders, Safety-M BM31, Safety-M modular SMBU and SMBS	05.KABEL451.XXX¹⁾	
DeviceNet - cable					
PUR outer jacket, PE wire insulation 	Cross section Permanent working temp. range Bending radius Cable diameter	2 x 0.52 mm ² [AWG24] + 2 x 1.04 mm ² [AWG17] flexible installation secure installation flexible installation secure installation -30°C ... +70°C [-22°F ... +158°F] -50°C ... +90°C [-58°F ... +194°F] min. 70 mm [2.76"] min. 50 mm [1.97"] approx. 8.4 mm ±0.2 mm	suitable for: all DeviceNet fieldbus encoders, Safety-M BM11	05.KABEL5723.XXX¹⁾	
CANopen - cable					
PVC electronic cable 	Cross section Permanent working temp. range Bending radius Cable diameter	3 x 2 x 0.25 mm ² [AWG23] flexible installation secure installation flexible installation secure installation -10°C ... +90°C [+14°F ... +194°F] -30°C ... +90°C [-22°F ... +194°F] min. 120 mm [4.72"] min. 40 mm [1.57"] approx. 6.2 mm ±0.2 mm	suitable for: all CANopen fieldbus encoders, Safety-M BM21, Safety-M modular SMBU	8.0000.6V00.XXXX¹⁾	
EtherCAT / PROFINET IO / EtherNet IP - cable					
PUR electronic cable 	Cross section Permanent working temp. range Bending radius Cable diameter	2 x 2 x 0.34 mm ² [AWG22] flexible installation secure installation flexible installation secure installation -30°C ... +70°C [-22°F ... +158°F] -40°C ... +80°C [-40°F ... +176°F] min. 50 mm [1.97"] min. 25 mm [0.98"] approx. 4.8 mm ±0.2 mm	suitable for: all EtherCAT / PROFINET IO encoders, Safety-M BMB1 and BMC1, Safety-M modular SMBU and SMBS	05.00.6031.1111.XXXM¹⁾	

1) XXX = cable length in meters (e.g. 10 m = 010)

Connection Technology

M12 connection technology		Connectors, self-assembly		Order No.
4 pin				
Female connector with coupling nut power supply, straight, IP67 Housing: plastic	A coded, screw connections, for cable \varnothing 4 ... 6 mm [0.16 ... 0.24"]	suitable for our series: 5858 / 5878 5868 / 5888 EMIO.S10.10xP		05.B8141-0
				
5 pin				
Male connector with external thread straight, IP67 Housing: metal / plastic	A coded, screw connections, for cable \varnothing 6 ... 8 mm [0.24 ... 0.32"]	suitable for our series: 9080 IS60 EMIO.S10.10xP		05.BS-8151-0/9
				
8 pin				
Female connector with coupling nut straight, IP67 Housing: metal	A coded, screw connections, for cable \varnothing 6 ... 8 mm [0.24 ... 0.32"]	suitable for our series: 3610 / 3620 5821 F3653 / F3673 5814 / 5834 F3663 / F3683 5853 / 5873 5000 / 5020 5863 / 5883 5006 / 5026 58x4FSx A020 / A02H 5876		05.CMB 8181-0
				
Male connector with external thread straight, IP67 Housing: metal	A coded, screw connections, for cable \varnothing 6 ... 8 mm [0.24 ... 0.32"]	suitable for: versions with cable outlet		05.CMBS 8181-0
				
Accessory		Working temperature range -25°C ... +90°C [-13F ... +194°F]		Order No.
Securing clip for M12 connectors EX zone 2/22 Material: plastic		suitable for use in areas with combustible dust acc. to EN 50281-1-1		8.0000.5000.0006
				

Connection Technology

M12 connection technology Cordsets, pre-assembled


With connector, 4-pin Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

Female connector with coupling nut straight, single-ended, IP67

Cable: PUR, 4 x 0.34 mm² [AWG22]
Housing: metal / plastic



A coded



suitable for our series:
EMIO.S10.10xP

Terminal assignment

Signal:	AS-i+	0 V	AS-i-	24 V	⊥
Pin female contacts:	1	2	3	4	PH 1)
Wire colour:	BN	WH	BU	BK	PH 1)

Cable length


2 m [6.56']	05.00.6061.6211.002M
5 m [16.40']	05.00.6061.6211.005M
10 m [32.81']	05.00.6061.6211.010M
15 m [49.21']	05.00.6061.6211.015M

Female connector with coupling nut + male connector with external thread straight, IP67

Cable: PUR/PVC, 4 x 0.34 mm² [AWG22]
Housing: metal / plastic



A coded



suitable for our series:
EMIO.S10.10xP

Terminal assignment

Signal:	AS-i+	0 V	AS-i-	24 V	⊥
Pin female contacts:	1	2	3	4	PH 1)
Pin male contacts:	1	2	3	4	PH 1)

Cable length

2 m [6.56']	05.00.6061.6462.002M
5 m [16.40']	05.00.6061.6462.005M
10 m [32.81']	05.00.6061.6462.010M
15 m [49.21']	05.00.6061.6462.015M


With connector, 5-pin Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

Male connector with external thread, straight, IP67, single-ended

Cable: PVC, 3 x 2 x 0.25 mm² [AWG23]
Housing: metal / plastic



A coded



suitable for our series:
EMIO.S10.10xP

Terminal assignment

Signal:	depending on the application					⊥
Pin male contacts:	1	2	3	4	5	PH 1)
Wire colour:	GY	BN	WH	GN	YE	PH 1)

Cable length

2 m [6.56']	05.00.6091.A411.002M
5 m [16.40']	05.00.6091.A411.005M
10 m [32.81']	05.00.6091.A411.010M
15 m [49.21']	05.00.6091.A411.015M

1) Shield on housing

M12 connection technology Cordsets, pre-assembled

With connector, 5-pin

Working temperature range -30°C ... +80°C [-22°F ... +176°F]


Order No.

Female connector with coupling nut + male connector with external thread, Bus in / out, straight, IP67

Cable: PUR, 4 x 0.34 mm² [AWG22]
Housing: metal / plastic



A coded



suitable for our series:

EMIO.S10.10xP

Terminal assignment

Cable length

Signal:	depending on the application					±
Pin female contacts:	1	2	3	4	5	PH ¹⁾
Pin male contacts:	1	2	3	4	5	PH ¹⁾

2 m [6.56']

05.00.6021.2422.002M

5 m [16.40']

05.00.6021.2422.005M

10 m [32.81']

05.00.6021.2422.010M

15 m [49.21']

05.00.6021.2422.015M

With connector, 8-pin

Working temperature range -30°C ... +80°C [-22°F ... +176°F]


Order No.

Female connector with coupling nut straight, IP67, single-ended

Cable: PVC, 8 x 0.25 mm² [AWG23]
Housing: metal / plastic



A coded



suitable for our series:

3610 / 3620 5821
F3653 / F3673 5814 / 5834
F3663 / F3683 5853 / 5873
5000 / 5020 5863 / 5883
5006 / 5026 58x4FSx
A020 / A02H 5876

Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	0	$\bar{0}$	±
Pin female contacts:	1	2	3	4	5	6	7	8	PH ¹⁾
Wire colour:	WH	BN	GN	YE	GY	PK	BU	RD	PH ¹⁾

2 m [6.56']

05.00.6041.8211.002M

5 m [16.40']

05.00.6041.8211.005M

10 m [32.81']

05.00.6041.8211.010M

15 m [49.21']


05.00.6041.8211.015M

Female connector with coupling nut right-angle, IP67, single-ended

Cable: PVC, 8 x 0.25 mm² [AWG23]
Housing: metal / plastic



A coded



suitable for our series:

3610 / 3620 5821
F3653 / F3673 5814 / 5834
F3663 / F3683 5853 / 5873
5000 / 5020 5863 / 5883
5006 / 5026 58x4FSx
A020 / A02H 5876

Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	0	$\bar{0}$	±
Pin female contacts	1	2	3	4	5	6	7	8	PH ¹⁾
Wire colour:	WH	BN	GN	YE	GY	PK	BU	RD	PH ¹⁾

2 m [6.56']

05.00.6041.8311.002M

5 m [16.40']

05.00.6041.8311.005M

10 m [32.81']

05.00.6041.8311.010M

15 m [49.21']

05.00.6041.8311.015M

+V: Encoder power supply +V DC

0 V: Encoder power supply ground GND (0 V)

A, \bar{A} : Incremental output channel A










B, \bar{B} : Incremental output channel B

0, $\bar{0}$: Reference signal

PH ±: Plug connector housing (Shield)

1) Shield on housing

Connection Technology

M23 connection technology		Connectors, self-assembly		Order No.									
12 pin													
<p>Male connector with external thread IP67</p> <p>Housing: metal</p> 	<p>pin assignment ccw, solder connections, for cable ø 5.5 ... 10.5 mm [0.22 ... 0.41"]</p> 	<p>suitable for: versions with cable outlet</p> 	<p>8.0000.5015.0001</p>										
<p>Male connector with external thread IP67, central fastening</p> <p>Housing: metal</p> 	<p>pin assignment ccw, solder connections, for cable ø 5.5 ... 10.5 mm [0.22 ... 0.41"]</p> 	<p>suitable for: versions with cable outlet</p> 	<p>8.0000.5015.0000</p>										
<p>Female connector with coupling nut IP67</p> <p>Housing: metal</p> 	<p>pin socket assignment cw, solder connections, for cable ø 5.5 ... 10.5 mm [0.22 ... 0.41"]</p> 	<p>suitable for our series:</p> <table border="0"> <tr> <td>5000 / 5020</td> <td>5814 / 5834</td> </tr> <tr> <td>580X / 582X</td> <td>585X / 587X</td> </tr> <tr> <td>586X / 588X</td> <td>58xxFSx</td> </tr> <tr> <td>9000</td> <td>908X</td> </tr> <tr> <td>A02X</td> <td></td> </tr> </table> 	5000 / 5020	5814 / 5834	580X / 582X	585X / 587X	586X / 588X	58xxFSx	9000	908X	A02X		<p>8.0000.5012.0000</p>
5000 / 5020	5814 / 5834												
580X / 582X	585X / 587X												
586X / 588X	58xxFSx												
9000	908X												
A02X													

Connection Technology

M23 connection technology Connectors, self-assembly

12 pin Order No.


Female connector with coupling nut
IP67, EX-Zone 2/22

Housing: metal

pin socket assignment cw,
 solder connections, for cable
 ø 5.5 ... 10.5 mm [0.22 ... 0.41"]

suitable for our series:
 5000 / 5020 5814 / 5834
 580X / 582X 585X / 587X
 586X / 588X 58xxFSx
 9000 908X
 A02X

8.0000.5012.0000.Ex



Connection Technology

M23 connection technology Cordsets, pre-assembled

With connector, 12 pin, for incremental encoders Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

Female connector with coupling nut + male connector with external thread IP67


Cable: PVC,
6 x 2 x 0.14 mm² [AWG25]
Housing: metal



pin assignment cw



pin assignment ccw



suitable for our series:

5000 / 5020 5803 / 5823
5804 / 5824 5805 / 5825
5814 / 5834 58x4FSx
A020 / A02H

Terminal assignment

Cable length

Signal:	0 V	+V	0 Vsens	+Vsens	A	\bar{A}	B	\bar{B}	0	$\bar{0}$	\perp
Pin female contacts:	10	12	11	2	5	6	8	1	3	4	PH ¹⁾
Pin male contacts:	10	12	11	2	5	6	8	1	3	4	PH ¹⁾
Wire colour:	WH	BN	GY-PK	RD-BU	GN	YE	GY	PK	BU	RD	PH ¹⁾

2 m [6.56']
5 m [16.40']
10 m [32.81']
15 m [49.21']

8.0000.6905.0002
8.0000.6905.0005
8.0000.6905.0010
8.0000.6905.0015

Female connector with coupling nut IP67, single-ended

Cable: PVC,
6 x 2 x 0.14 mm² [AWG25]
Housing: metal



pin assignment cw



suitable for our series:

5000 / 5020 5814 / 5834
580X / 582X 58x4FSx
9000
(with RS422 or SinCos output)

Terminal assignment

Cable length

Signal:	0 V	+V	0 Vsens	+Vsens	A	\bar{A}	B	\bar{B}	0	$\bar{0}$	\perp
Pin female contacts:	10	12	11	2	5	6	8	1	3	4	PH ¹⁾
Wire colour:	WH	BN	GY-PK	RD-BU	GN	YE	GY	PK	BU	RD	PH ¹⁾

2 m [6.56']
5 m [16.40']
10 m [32.81']
15 m [49.21']

8.0000.6901.0002
8.0000.6901.0005
8.0000.6901.0010
8.0000.6901.0015

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- 0 Vsens, +Vsens: Using the sensor outputs of the encoder, the voltage present can be measured and if necessary increased accordingly.
- A, \bar{A} : Incremental output channel A
- B, \bar{B} : Incremental output channel B
- 0, $\bar{0}$: Reference signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology

M23 connection technology Cordsets, pre-assembled

With connector, 12 pin, for absolute encoders Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

Female connector with coupling nut IP67, single-ended

Cable: PVC,
6 x 2 x 0.14 mm² [AWG25]
Housing: metal

pin assignment cw



suitable for our series:
5850 / 5870 5853 / 5873
5863 / 5883 5862 / 5882
58x3FSx 9081
(SSI or analogue output)



Terminal assignment

Cable length

Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
Pin female contacts:	1	2	3	4	5	6	7	8	9	10	11	12	PH ¹⁾
Wire colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	PH ¹⁾

2 m [6.56']	8.0000.6901.0002.0031
5 m [16.40']	8.0000.6901.0005.0031
10 m [32.81']	8.0000.6901.0010.0031
15 m [49.21']	8.0000.6901.0015.0031

Female connector with coupling nut + male connector with external thread IP67

Cable: PVC,
6 x 2 x 0.14 mm² [AWG25]
Housing: metal


pin assignment cw



suitable for our series:
5850 / 5870 5853 / 5873
5863 / 5883 5862 / 5882
58x3FSx 9081
(SSI output)



pin assignment ccw



Terminal assignment

Cable length

Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
Pin female contacts:	1	2	3	4	5	6	7	8	9	10	11	12	PH ¹⁾
Pin male contacts:	1	2	3	4	5	6	7	8	9	10	11	12	PH ¹⁾
Wire colour:	WH	BN	GN	YE	GY	PK	BU	RD	BK	VT	GY-PK	RD-BU	PH ¹⁾







2 m [6.56']	8.0000.6905.0002.0032
5 m [16.40']	8.0000.6905.0005.0032
10 m [32.81']	8.0000.6905.0010.0032
15 m [49.21']	8.0000.6905.0015.0032

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C- : Clock signal
- D+, D- : Data signal
- SET: SET input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology

Sub-D connection technology Connectors, self-assembly

9 pin		Order No.
<p>Male connector with cable outlet 70° Housing Sub-D: ABS, metallised</p>   <p>Shield on housing</p>	<p>solder contacts, self-assembly</p> <p>suitable for our series: MS1, MSP1, MS2, MSP2, BM21 (CANopen), BM31 (PROFIBUS DP) SMC1</p> 	<p>8.0000.514A.0000</p>
<p>Female connector with cable outlet 70° Housing Sub-D: ABS, metallised</p>   <p>Shield on housing</p>	<p>solder contacts, self-assembly</p> <p>suitable for our series: SMC1</p> 	<p>8.0000.514B.0000</p>

Connection Technology

Connection Technology

Sub-D connection technology Cordsets, pre-assembled

With Sub-D connector, 9 pin

Working temperature range -30°C ... +80°C [-22°F ... +176°F]

Order No.



Male connector with cable outlet 70°, single-ended

suitable for our series:

SMC1

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]

Housing Sub-D: ABS, metallised



Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	5	4	1	9	3	2	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X5

for SinCos signals

1 m [3.28']

2 m [6.56']

5 m [16.40']

8.0000.6V00.0001.0086

8.0000.6V00.0002.0086

8.0000.6V00.0005.0086

With M12 connector, 8 pin + Sub-D connector, 9 pin

Working temperature range -30°C ... +80°C [-22°F ... +176°F]

Order No.

M12 female connector with coupling nut, straight + Sub-D, male connector with cable outlet 70°

suitable for our series:


Sendix 58x4, 58x4FSx

SMC1

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]

Housing M12: metal / plastic

Housing Sub-D: ABS, metallised



Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	5	4	1	9	3	2	PH ¹⁾
Pin M12:	1	2	3	4	5	6	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X6, X7

for SinCos signals

1 m [3.28']

2 m [6.56']

5 m [16.40']

8.0000.6V00.0001.0084

8.0000.6V00.0002.0084

8.0000.6V00.0005.0084

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology


Sub-D connection technology Cordsets, pre-assembled

With M23 connector, 12 pin + Sub-D connector, 9 pin Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

M23 female connector with coupling nut + Sub-D, male connector with cable outlet 70°

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
 Housing M23: metal
 Housing Sub-D: ABS, metallised

suitable for our series:
 Sendix 58x4, 58x4FSx
 SMC1



pin socket assignment cw

Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	5	4	1	9	3	2	PH ¹⁾
Pin M23:	10	12	5	6	8	1	PH ¹⁾
Wire colour:	WH	BR	BK	VT	GY/PK	RD/BU	

Terminal X6, X7
 for SinCos signals

1 m [3.28']
 2 m [6.56']
 5 m [16.40']

8.0000.6V00.0001.0085
8.0000.6V00.0002.0085
8.0000.6V00.0005.0085

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology

Sub-D connection technology Cordsets, pre-assembled

With Sub-D connector, 9 pin



Working temperature range -30°C ... +80°C [-22°F ... +176°F]

Order No.

Male connector with cable outlet 70°, single-ended

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
Housing Sub-D: ABS, metallised

suitable for our series:
MS1, MSP1, MS2, MSP2



Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Wire colour:	WH	BR	BK	VT	GY/PK	RD/BU	

Terminal X31, X32, X33, X34	1 m [3.28']	8.0000.6900.0001.0076
for SinCos signals	2 m [6.56']	8.0000.6900.0002.0076
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0076

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X31, X32, X33, X34	1 m [3.28']	8.0000.6V00.0001.0082
for SinCos signals	2 m [6.56']	8.0000.6V00.0002.0082
(for incremental encoders)	5 m [16.40']	8.0000.6V00.0005.0082

Signal:	0 V	+V	C+	C-	D+	D-	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X31, X32	1 m [3.28']	8.0000.6900.0001.0075
for SSI signals	2 m [6.56']	8.0000.6900.0002.0075
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0075

Signal:	0 V	+V	C+	C-	D+	D-	\perp
Pin Sub-D:	2	9	3	7	5	6	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X33, X34	1 m [3.28']	8.0000.6900.0001.0078
for SSI signals	2 m [6.56']	8.0000.6900.0002.0078
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0078

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C- : Clock signal
- D+, D- : Data signal
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology



Sub-D connection technology Cordsets, pre-assembled

With 2 Sub-D connectors, 9 pin Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

Male connector with cable outlet 70°, single-ended

suitable for our series:
MSP1, MSP2

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
Housing Sub-D: ABS, metallised



Terminal assignment

Cable length

Signal:	0 V	+V	C+	C-	D+	D-	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D 1:	2	9	3	7	5	6	-	-	-	-	PH ¹⁾
Pin Sub-D 2:	-	-	-	-	-	-	8	4	5	6	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	BK	VT	GY/PK	RD/BU	

Terminal X31/X33, X32/X34	Cable length
for SSI and SinCos signals	1 m [3.28']
	2 m [6.56']
	5 m [16.40']

8.0000.6900.0001.0077
8.0000.6900.0002.0077
8.0000.6900.0005.0077

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Sub-D connection technology Cordsets, pre-assembled

With M23 connector, 12 pin + Sub-D connector, 9 pin


Working temperature range -30°C ... +80°C [-22°F ... +176°F]

Order No.

M23 female connector with coupling nut + Sub-D, male connector with cable outlet 70°

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
 Housing M23: metal
 Housing Sub-D: ABS, metallised

suitable for our series:
 Sendix 58x3, 58x3FSx
 Sendix 58x4, 58x4FSx
 MS1, MSP1, MS2, MSP2



pin socket assignment cw

Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Pin M23:	1	2	9	10	11	12	PH ¹⁾
Wire colour:	WH	BR	BK	VT	GY/PK	RD/BU	

Terminal X31, X32, X33, X34	1 m [3.28']	8.0000.6900.0001.0069
for SinCos signals	2 m [6.56']	8.0000.6900.0002.0069
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0069

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Pin M23:	1	2	9	10	11	12	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GR	PK	

Terminal X31, X32, X33, X34	1 m [3.28']	8.0000.6V00.0001.0081
for SinCos signals	2 m [6.56']	8.0000.6V00.0002.0081
(for incremental encoders)	5 m [16.40']	8.0000.6V00.0005.0081

Signal:	0 V	+V	C+	C-	D+	D-	\perp
Pin Sub-D:	2	9	8	4	5	6	PH ¹⁾
Pin M23:	1	2	3	4	5	6	
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X31, X32	1 m [3.28']	8.0000.6900.0001.0068
for SSI signals	2 m [6.56']	8.0000.6900.0002.0068
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0068

Signal:	0 V	+V	C+	C-	D+	D-	\perp
Pin Sub-D:	2	9	3	7	5	6	PH ¹⁾
Pin M23:	1	2	3	4	5	6	
Wire colour:	WH	BR	GN	YE	GY	PK	

Terminal X33, X34	1 m [3.28']	8.0000.6900.0001.0072
for SSI signals	2 m [6.56']	8.0000.6900.0002.0072
(for absolute encoders)	5 m [16.40']	8.0000.6900.0005.0072

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

Connection Technology


Sub-D connection technology Cordsets, pre-assembled

With M23 connector, 12 pin + 2 x Sub-D connector, 9 pin Working temperature range -30°C ... +80°C [-22°F ... +176°F] Order No.

**M23 female connector with coupling nut +
2 x Sub-D, male connector with cable outlet 70°**

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
Housing M23: metal
Housing Sub-D: ABS, metallised

suitable for our series:
Sendix 58x3, 58x3FSx
MSP1, MSP2



pin socket assignment cw

Terminal assignment

Cable length

Signal:	0 V	+V	C+	C-	D+	D-	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D 1:	2	9	3	7	5	6	-	-	-	-	PH ¹⁾
Pin Sub-D 2:	-	-	-	-	-	-	8	4	5	6	PH ¹⁾
Pin M23:	1	2	3	4	5	6	9	10	11	12	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	BK	VT	GY/PK	RD/BU	

Terminal X31/X33, X32/X34	Cable length	Order No.
for SSI and SinCos signals	1 m [3.28']	8.0000.6900.0001.0070
	2 m [6.56']	8.0000.6900.0002.0070
	5 m [16.40']	8.0000.6900.0005.0070

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Sub-D connection technology Cordsets, pre-assembled

With M23 connector, 12 pin + 2 x Sub-D connector, 9 pin with SET + DIR


Working temp. range -30°C ... +80°C [-22°F ... +176°F]

Order No.

**M23 female connector with coupling nut +
2 x Sub-D, male connector with cable outlet 70°**

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
Housing M23: metal
Housing Sub-D: ABS, metallised

suitable for our series:
Sendix 58x3, 58x3FSx
MSP1, MSP2



pin socket assignment cw

Terminal assignment

Cable length

Signal:	0 V	+V	C+	C-	D+	D-	SET	DIR	A	\bar{A}	B	\bar{B}	\perp
Pin Sub-D 1:	2	9	3	7	5	6	-	-	-	-	-	-	PH ¹⁾
Pin Sub-D 2:	-	-	-	-	-	-	-	-	8	4	5	6	PH ¹⁾
Pin M23:	1	2	3	4	5	6	7	8	9	10	11	12	PH ¹⁾
Wire colour:	WH	BR	GN	YE	GY	PK	BU	RD	BK	VT	GY/PK	RD/BU	

Terminal X31/X33, X32/X34
for SSI and SinCos signals

1 m [3.28']
2 m [6.56']
5 m [16.40']




8.0000.6900.0001.0080
8.0000.6900.0002.0080
8.0000.6900.0005.0080

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- C+, C-: Clock signal
- D+, D-: Data signal
- SET: SET input. The current position becomes defined as position zero.
- DIR: Direction input: If this input is active, output values are counted backwards (decrease) when the shaft is turning clockwise.
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology

RJ45 connection technology Cordsets, pre-assembled

RJ45 connector			Order No.
RJ45 straight, IP20 Housing RJ45: plastic	screw connections, for cable \varnothing 4.5 ... 8 mm [0.18 ... 0.32"]	suitable for our series: BMB1 (EtherCAT), BMC1 (PROFINET IO), SMBU, SMBS, SMBD	05.VS-08-RJ45-5-Q/IP20
			

Connection Technology

RJ45 connection technology Cordsets, pre-assembled

Mini-I/O connector, 8 pin + RJ45 connector Working temperature range -20°C ... +60°C [-4°F ... +140°F] Order No.

Mini-I/O and RJ45

Cable: PVC, 6 x 2 x 0.14 mm² [AWG 25]
 Housing: ABS, metallised

suitable for our series:

EMAA
 EMAS



Terminal assignment

Cable length

Signal:	0 V	+V	A	\bar{A}	B	\bar{B}	\perp
Pin Mini-I/O:	8	n.c.	5	6	2	1	PH ¹⁾
Pin RJ45:	2	1	4	5	7	8	PH ¹⁾
Wire colour:	OG	WH-OG	BU	WH-BU	WH-BN	BN	

Terminal ENC1, ENC2
 HTL, TTL, SinCos

1 m [3.28']

8.SMAS.C21.001M

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- PH \perp : Plug connector housing (Shield)

1) Shield on housing

Connection Technology

RJ45 connection technology Cordsets, pre-assembled

Ethernet patch cable with 2 x RJ45 connector Working temperature range -20°C ... +60°C [-4°F ... +140°F] Order No.

Ethernet adapter cable

Cable: PVC, planar cable black category 6 acc. to EN 50173-1
6 x 2 x 0.14 mm² [AWG 25], shielded twisted pairs
Housing RJ45: ABS, metallised

suitable for our series:
EMAA
EMAS



Terminal assignment

Cable length

Signal :	0 V	+V	A / C+	\bar{A} / C-	B	\bar{B}	D+	D-	\perp
Pin RJ45-1:	2	1	4	5	7	8	3	6	PH ¹⁾
Pin RJ45-2:	2	1	4	5	7	8	3	6	PH ¹⁾
Wire colour:	OG	WH-OG	BU	WH-BU	WH-BN	BN	WH-GN	GN	

Terminal ENC1, ENC2
HTL, TTL, SinCos, SSI

1 m [3.28']

8.SMAS.C22.001M

Ethernet parameterizing cable

Cable: PUR, grey/white
4 x 2 x 0.15 mm² [AWG 25], shielded
Housing RJ45: ABS, metallised

suitable for our series:
SMBD.32E
SMBU
SMBS



Terminal assignment

Cable length

Signal :	TX+	TX-	RX+	-	-	RX-	-	-	\perp
Pin RJ45-1:	1	2	3	4	5	6	7	8	PH ¹⁾
Pin RJ45-2:	1	2	3	4	5	6	7	8	PH ¹⁾
Wire colour:	WH-OG	OG	WH-GN	BU	WH-BU	GN	WH-BN	BN	

Ethernet terminal
Parameterizing interface

2 m [6.56']

5 m [16.40']

10 m [32.81']

05.00.60A1.7272.002M

05.00.60A1.7272.005M

05.00.60A1.7272.010M

- +V: Encoder power supply +V DC
- 0 V: Encoder power supply ground GND (0 V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- C+, C- : Clock signal
- D+, D- : Data signal
- TX+, TX-: Transmitter
- RX+, RX-: Receiver
- PH \perp : Plug connector housing (Shield)

1) Shield on housing



Accessories

Encoders		Page
Encoder mounting attachments	Fixing components for hollow shaft encoders	248
	Fixing components for shaft encoders	250
<hr/>		
Connection of motor and encoder	Bellows couplings (FS)	254
<hr/>		
General		255
<hr/>		
LED displays	SSI absolute encoder display – type 570	256
	SSI or incremental display – type 575	259
<hr/>		
Optical fibre transmitter, optical fibre receiver	SSI	262
<hr/>		
Safety modules		Page
Safety-M compact		264
<hr/>		
Safety-M modular		265
<hr/>		
Safety-M		270
<hr/>		

Encoders

Fixing components for hollow shaft encoders

Dimensions / Details

Dimensions in mm [inch]

Stator coupling



Scope of delivery:

- Stator coupling (stainless steel)
- 4 screws M3 x 6 mm [M3 x 0.24"] for fixing to the encoder

Connection to application:

- 4 screws (not supplied)

Max. permissible shaft connection tolerances:


- Axial offset <math>< \pm 0.25 \text{ mm } [0.01"]</math>
- Radial offset <math>< \pm 0.20 \text{ mm } [0.01"]</math>
- Angular offset <math>< 1^\circ</math>

suitable for our encoders:

- Sendix SIL 5834FSx
- Sendix SIL 5873FSx
- Sendix SIL 5883FSx

Order No.

8.0010.4048.00FS



Accessories

Encoders

Fixing components for shaft encoders

Dimensions / Details

Dimensions in mm [inch]

Adapter flange, ø 58 mm [2.28"]



This adapter flange allows converting a Kübler encoder clamping flange into a synchro flange.

Scope of delivery:

- Adapter flange (aluminium)
- 3 screws for fixing to the encoder

Connection to application:

- 3 screws (not supplied)



suitable for our encoders:

Sendix SIL 58xxFS

Order No.

8.0010.2180.0000

Adapter flange, ø 65 mm [2.56"]



This adapter flange allows replacing 65 mm diameter encoders from other manufacturers with pitch circle diameter 48 mm with 58 mm Kübler encoders.

Scope of delivery:

- Adapter flange (aluminium)
- 3 screws for fixing to the encoder

Connection to application:

- 3 screws (not supplied)



suitable for our encoders:

Sendix SIL 58xxFS

Order No.

8.0010.2230.0000

Accessories

Encoders Fixing components for shaft encoders

Dimensions / Details

Dimensions in mm [inch]

Adapter flange, ø 90 mm



This adapter flange allows replacing 90 mm diameter encoders from other manufacturers with pitch circle diameter 60 mm with 58 mm Kübler encoders.

Scope of delivery:

- Adapter flange
- 3 screws for fixing to the encoder

Connection to application:

- 6 screws (not supplied)



suitable for our encoders:
Sendix SIL 58xxFS

Order No.

8.0010.2270.0000

Adapter flange, ø 115 mm [4.53"], Euro flange (Euro RE0444)





This adapter flange allows replacing 115 mm diameter encoders from another manufacturer with pitch circle diameter 100 mm (Euro flange) with 58 mm or 70 mm Kübler encoders.

Scope of delivery:

- Adapter flange (Aluminium)
- 3 screws for fixing to the encoder

Connection to application:

- 6 screws (not supplied)



suitable for our encoders:
Sendix SIL 58xxFS
Sendix SIL 70xxFS

Order No.

8.0010.2160.0000

8.0010.2170.0000

Encoder type	D1	D2	D3	X	Y	B
58xx	48	36	58	11	1	DIN 74-BM3
70xx	51	12	42	11.5	7.5	DIN 74-BM4

- 1** countersunk DIN 74-Hm6
- B** see table

Encoders

Fixing components for shaft encoders

Dimensions / Details

Dimensions in mm [inch]


Adapter flange, square

Scope of delivery:

- Adapter flange (aluminium)
- 3 screws for fixing to the encoder

Connection to application:


- 4 screws (not supplied)



suitable for our encoders:
Sendix SIL 58xxFS


Order No.

8.0010.2100.0000




Order No.

8.0010.2120.0000



Order No.

8.0010.2600.0000



Order No.

8.0010.2800.0000

Accessories

Encoders Fixing components for shaft encoders

Dimensions / Details

Dimensions in mm [inch]


Angular flange

Scope of delivery:

- Angular flange (aluminium)
- 3 screws for fixing to the encoder

Connection to application:

- 2 screws (not supplied)



suitable for our encoders:
Sendix SIL 58xxFS

Order No.

8.0010.2300.0000

1 countersunk DIN 74-Hm6

Fastening eccentrics for encoders with synchro flange

- Suitable for Kübler encoders with synchro flange
- Material ACu Zn 39 Pb 3
- Surface finish: galvanised Ni

Scope of delivery:

- 3 eccentrics
- 3 screws


(Use at least three fastening eccentrics to mount the encoder)

suitable for our encoders:
Sendix SIL 58xxFS,
Sendix SIL 70xxFS

Order No.

8.0010.4100.0000

encoder type	d1	d2	d3	A	B	C
58xxFSx	9.6	6.5	3.2	5.6	2.9	1.2
70xxFSx	[0.38]	[0.26]	[0.13]	[0.22]	[0.11]	[0.047]



Accessories

Encoders	Connection of motor and encoder	Bellows couplings (FS)
-----------------	--	-------------------------------



Bellows couplings provide cost-effective connection of the motor and encoder. They are also able to correct any angular errors between the drive and encoder.

These bellows couplings (FS) are used for safe connection of applications and Sendix SIL encoders.

The safety-oriented bellows coupling has, in addition to the metallic bellows, internal claws that ensure the driving of the encoder in case of breakage of the bellows connection.

Order code	8.0000	. 1	X	FS	. XX	XX
Couplings	Type		a		b	c
a Type of coupling	5 = bellows coupling \varnothing 25 mm [0.98"]		b Bore diameter d1 (see technical data)		Example: d1 = 10 mm and d2 = 12 mm Order No. = 8.0000.15FS.1012	
			c Bore diameter d2 (see technical data)			

Accessory	Order No.
Screw retention Loctite 243, 5 ml	8.0000.4G05.0000


Technical data

Mechanical characteristics	
Max. speed	10000 min ⁻¹
Max. torque	200 Ncm
Max. shaft offset	radial \pm 0.3 mm axial \pm 0.45 mm angular \pm 3°
Torsion spring stiffness	183 Nm/rad
Radial spring stiffness	17.8 N/mm
Moment of inertia	9.1 gcm ²
Headless set screw tightening torque	min. 80 Ncm max. 100 Ncm

Working temperature range	-30°C ... +120°C [-22 ... +248°F]	
Weight approx.	54 g	
Material	flange	stainless steel 1.4104
	bellows	stainless steel 1.4571
Standard bore diameter	(d1 / d2)	10 / 10 mm [0.39 / 0.39"] 10 / 12 mm [0.39 / 0.47"] 12 / 12 mm [0.47 / 0.47"]
Insertion depth	min.	6 mm [0.24"]
	max.	11 mm [0.43"]


Dimensions

Dimensions in mm [inch]



Nut DIN 6885

nut width b	d1 / d2
3 [0.12]	10 [0.39]
4 [0.16]	12 [0.47]



Accessories

Encoders General

Dimensions / Details

Dimensions in mm [inch]

Screw retention Loctite 243 (5 ml)





Chemical basis: dimethacrylate ester
 Components: single-component (no mixing required)
 Viscosity: medium, thixotrope
 Cure: anaerobic
 Secondary cure: activator
 Use: screw retention
 Strength: medium

suitable for our series:
 Sendix SIL
 Safety-M compact
 Safety-M modular
 Safety-M

Order No.
8.0000.4G05.0000

EMC shield terminal

For an EMC-compliant installation of the encoder cable, top-hat rail mounting, Shield diameter 3.0 ... 6.0 mm, Clamp (spring steel, galvanised) Foot (spring steel)




suitable for our series:
 Sendix SIL
 Safety-M compact
 Safety-M modular
 Safety-M

Order No.
8.0000.4G06.0000

Stylus for the set key

For easy operation of the set key on the encoder
 Material POM (HKS8 orange)



suitable for our series:
 Sendix SIL
 5853FSx
 5863FSx
 5873FSx
 5883FSx

Order No.
8.0010.4052.0000

Encoders	SSI absolute encoder display	570
-----------------	-------------------------------------	------------



The fast SSI display type 570 is designed for absolute SSI encoders with a resolution up to 32 bits. It can be used as either a master or a slave display.

Thanks to simple bit assignment and bit blanking the display, which can be scaled and linearized, can also be cascaded, in order to extend the display range as desired. Output options include 2 limit values, analogue output or interface.



AC/DC 17...260V Power supply	SSI SSI Input	max. 1 MHz Count frequency	2 2 limit values	mA, V Analogue output	14 bit Resolution	RS 232/485 RS232/485 Interface	IP65 High protection level	POSITION Position display	DIN 96 x 48 DIN front bezel	123... 6 LED LED display
Prog Menu-driven programming	SSI Display linearization	Plug-in Plug-in screw terminal								

Characteristics

- Suitable for SSI-protocols from 8 up to 32 bits.
- Version with 2 optocoupler outputs to work as limit or preset values; also with programmable tracking preset.
- Version with scaleable analogue output, resolution 14 bits, 0 ... 10 V, -10 ... +10 V, 0 ... 20 mA or 4 ... 20 mA.
- Version with serial interface for reading data in and out (RS232 / RS485).
- Version with 2 relay outputs as limit values or presets; can also be programmed as tracking preset and with RS232 / RS485 interface.
- Gray or binary code.
- 96 x 48 mm DIN-housing, IP65.

Benefits

- AC and DC power supply in one unit.
- Master- or slave mode.
- Plug-in screw terminals.
- SSI-clock frequency from 100 Hz up to 1 MHz.
- Display may be adjusted using scaling- and offset-features.
- Large 15 mm high LED display, 6-digit, with adjustable brightness.
- Round-loop function.
- Linearization with teach option.
- Bit blanking.

Order specifications

Display with:	Order-No.	Delivery specification
2 optocoupler outputs ¹⁾	0.570.011.E00	- Display 570
Analogue output ¹⁾	0.570.012.E90	- Gasket
Serial interface RS232/485	0.570.012.E05	- Mounting kit
2 relay outputs and RS232/485	0.570.010.305	- Operating instruction German/English

Accessory

Accessory	Order No.
Mounting frame with cut-out 92 x 45 [3.62 x 1.77]	for snap-on mounting on 35 [1.38] top-hat DIN rail, for counters 96 x 48 [3.74 x 1.89] grey G300005

Suitable gaskets as well as further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.

1) Stock types

Accessories

Encoders SSI absolute encoder display 570

Technical data

General technical data	
Display	LED display, 15 mm high 6 decades
Operating temperature	0°C ... +45°C [+32°F ... +113°F] (non-condensing)
Storage temperature	-25°C ... +70°C [-13°F ... +158°F]
Altitude	up to 2000 m [6562']

Electrical characteristics	
Power supply	(0.570.01X.EXX) 17 ... 30 V DC and 115/230 V AC, ± 12.5 % (0.570.010.305) 17 ... 30 V DC
Current consumption DC	17 V 190 mA 24 V 150 mA 30 V 120 mA
Power consumption AC	7.5 VA
Sensor power supply (for encoder)	24 V DC ± 15%, 120 mA
EMC	Immunity to interference EN 55011 class B Emitted interference EN 61000-6-2
Device safety	Designed to EN 61010 part 1 Protection class 2 Application area Pollution level 2


Mechanical characteristics	
Protection acc. to EN 60529	IP65 (front side)
Weight	approx. 200 g [7.06 oz]

Inputs	
SSI data inputs	Differential RS422 input
Input frequency range	100 Hz ... 1 MHz
SSI clock output	Differential RS422 output
Output frequency range	100 Hz ... 1 MHz
Input reset	PNP or NPN, programmable 5.1 mA, 24 V DC R _i = 4.7 kOhm
Input level	LOW 0 ... 2 V HIGH 9 ... 35 V
Min. reset pulse time	min. 5 ms


Outputs	
Scaleable analogue output	(0.570.012.E90) 0 ... 10 V, -10 ... + 10 V or 0 ... 20 mA, 4 ... 20 mA
Resolution	14 bit + sign
Accuracy	0.1 %
Optocoupler output	(0.570.011.E00) 5 ... 35 V DC/150 mA reaction time approx. 5 ms
Interface	(0.570.012.E05 + 0.570.010.305) RS232 and RS485 acc. to ISO 1745 drivecom protocol or printer protocol
Relay output	(0.570.010.305) 2 changeover contacts max. 250 V AC / 1 A / 250 VA max. 100 V DC / 1 A / 100 W reaction time approx. 10 ms

Terminal assignment


Display with 2 optocoupler outputs (0.570.011.E00)




Display with analogue output (0.570.012.E90)



Display with serial interface RS232/485 (0.570.012.E05)



Display with 2 relay outputs, RS232/485 (0.570.010.305)





Encoders	SSI absolute encoder display	570
-----------------	-------------------------------------	------------

Dimensions

Dimensions in mm [inch]

Panel cut-out
92 x 45 [3.62 x 1.77]



Accessories

Encoders	LED SSI or incremental display	575
-----------------	---------------------------------------	------------



Counter series for demanding applications with two individually scalable encoder inputs, each SSI master / SSI slave or A, /A, B, /B, for count frequencies up to 1 MHz per channel.

Programmable operating modes include position or event counter, totaliser, difference counter.

 AC/DC 24/17...30V	 DIN 96 x 48	 IP65	 max. 1 MHz	 SSI	 TTL, HTL and RS422 input	 6/8 LED	 DC OUT 5 / 24 V	 mA, V	 4	 RS232
Power supply	DIN front bezel	High protection level	2 inputs	SSI input		LED display	2 x sensor power supply	Analogue output optional	Transistor output	Interface

Innovative

- 3 display values: counter 1, 2 as well as calculation-based display.
- 2 separate freely scalable count inputs: SSI master, SSI slave or TTL incremental (also with inverted inputs) max. input frequency 1 MHz/channel.
- Very bright LED display, 15 mm (6-digit) and 10 mm (8-digit) high.
- 4 freely programmable fast solid-state outputs, each with 350 mA output current.
- Step or tracking presets.
- Simple programming – with function codes, dependent on the operating mode selected.
- With 8 different fixed count functions, such as simple count, difference count and total count of both inputs, separate display of the inputs.

Compact and multifunctional

- One device caters for AC and DC power supplies.
- Simple programming with 4 keys and programmable dual functions.
- Can be used as counter or position display with limit values, where 2 values are monitored or calculated with respect to each other.
- 4 fast, programmable inputs with various functions, such as reset, gate, display memory (store), reference input or switching between the display values.
- Scalable analogue output 0/4 ... 20 mA, ±10 V or 0 ... 10 V.
- RS232 interface as standard, for parameter setting, readout of values or for modifications during operation.
- 2 auxiliary power supplies for sensors: 5.2 V DC and 24 V DC.

Order specifications

4 fast switch outputs and serial interface (RS232)	Order-No.	Delivery specification
6 digits	6.575.0116.D05	- Controller 575
6 digits, scalable analogue outputs	6.575.0116.D95	- Gasket
8 digits	6.575.0118.D05	- Fastening set
8 digits, scalable analogue outputs	6.575.0118.D95	- Instruction manual German/English

Accessory

Mounting frame

with cut-out 92 x 45 [3.62 x 1.77]



Dimensions in mm [inch]

For snap-on mounting on 35 [1.38] top-hat DIN rail, for counters 96 x 48 [3.78 x 1.89]

grey

Order No.

G300005

OS2 software for parameter setting

can be downloaded at www.kuebler.com

Suitable gaskets as well as further accessories can be found in the accessories section or in the accessories area of our website at: www.kuebler.com/accessories.

Accessories

Encoders LED SSI or incremental display 575

Technical data

General technical data		
Display	6 digits	LED display, 15 mm [0.59"]high
	8 digits	LED display, 10 mm [0.39"]high
Operating temperature	0°C ... +45°C [+32°F ... +113°F] (non-condensing)	
Storage temperature	-25°C ... +70°C [-13°F ... +158°F]	

Electrical characteristics		
Power supply	24 V AC, + 10% 24 (17 ... 30) V DC	
Current consumption DC	100 mA + current consumption encoder	
Connected load AC	15 VA	
Auxiliary power supply output for sensors	2 x 5.2 V DC, each 150 mA 2 x 24 V DC, each 120 mA	
EMC	Emitted interference	EN 61000-6-3
	Immunity to interference	EN 61000-6-2
Device safety	Designed to	EN 61010 part 1
	Protection class	2
	Application area	Pollution level 2


Mechanical characteristics		
Housing	Noryl UL94-V-0	
Screw terminal	Cable cross-section	max. 1.5 mm ² [AWG 25]
Protection acc. to EN 60529	IP65 (front side)	
Weight	approx. 250 g [8.82 oz]	

Inputs		
Universal SSI incremental encoder inputs		
Count frequency	RS422 and TTL with Inv.	1 MHz
(per encoder)	SSI master	1 MHz (max. 32 bit)
	SSI slave	1 MHz (max. 32 bit)
Control inputs HTL		
Ri (input resistor)		3.3 kOhm
Switching level	LOW	< 2.5 V
	HIGH	> 10 V
Min. pulse duration		50 µs


Outputs		
Switch outputs		
4 fast power transistors		5 ... 30 V DC, 350 mA
Reaction time		< 1ms ¹⁾
Inductive loads require a freewheeling diode		
Serial interface		RS232, 2400 ... 38400 Baud
Analogue outputs		
Current		0 / 4 ... 20 mA
Load		max. 270 Ohm
Voltage		0 ... +10 V (max. 3 mA)
Resolution		14 bit
Precision		0.1 %
Reaction time		< 1 m

Application examples


Total position display



Difference position display




Independent individual operation



1) Intensive serial communication can temporarily prolong the reaction time.


Encoders **LED SSI or incremental display** **575**

Terminal assignment




Connection examples

Example shows encoder with 5 V-supply and TTL / RS422-output



Dimensions

Dimensions in mm [inch]



Encoders **Optical fibre signal transmission – transmitter and receiver** **SSI**

eco plus

Cost advantage compared to conventional wiring over 150 m length*



Optical fibre transmission system for SSI absolute encoders

The system is made up of an optical fibre transmitter and an optical fibre receiver.

The optical fibre transmitter converts the electrical signals of a normal absolute encoder with Synchronous Serial Interface (SSI) into a light signal for transmission by means of an optical fibre. The receiving module converts the optical signal back into electrical signals.

Absolute signals can be transmitted safely through one glass fibre over distances of up to 1500 m. The resolution of 13 bit for a singleturn encoder or 25 bit for a multiturn encoder can be defined by means of a DIP-switch on the front side of the module.

Reliable transmission

- Safe signal transmission up to 1500 m.
- Resists extremely strong electro-magnetic fields.

Easy installation

- Signal transmission via a single glass fibre.
- Resolution of 13 bit or 25 bit can be set via DIP-switch.
- LED for monitoring of power supply, clock and data.
- DIN-rail mounting – requires min. installation space – only 22 mm wide.

Application areas

- Process control technology and automation technology.
- Applications sensitive to interference.
- High voltage plants.
- Plants with long transmission distances.
- Potential separation.
- Explosive areas.

Order code

Optical fibre transmitter / receiver

6.LWLX . AX

a
S = Optical fibre transmitter
E = Optical fibre receiver

b Supply voltage
1 = 10 ... 30 V DC
4 = 5 V DC

Scope of delivery:

- Optical fibre module
- Operating manual, dual language, German and English

Accessories

Simplex Patch cable
ST-ST - Multimode



Connector:
2 x ST/PC, Optical fibre:
1 x 50/125

Order No.

05.B09-B09-821-XXXX

XXXX = Length in m
Standard lengths: 2 m, 5 m,
8 m, 10 m, 15 m, 20 m, ...
(in 5 m steps)

ST Multimode coupling



Barrel: ceramic, slotted

05.LWLK.001

* Comparison of costs:
Costs per meter standard copper cable compared to costs per meter optical fibre signal cable + costs of transmitter + costs of receiver

Accessories

Encoders Optical fibre signal transmission – transmitter and receiver SSI

Technical data

General technical data	
Power supply	10 ... 30 DC V eg. 5 V DC $\pm 5\%$
Power consumption per module	+V = 10 ... 30 V DC max 1,6 W +V = 5 V DC max 0,8 W
Operating voltage reverse connection protection	available
Encoder inputs	opt. fibre transmitter C-, C+ and D-, D+
SSI clock rate	500 kHz fixed setting
Optical wavelength	820 nm (infrared)
Optical transmission rate	120 Mbit/s
Optical fibre connection	ST connector, \varnothing 9 mm [0.35] on the bottom side of the housing
Glass fibre	multimode fibre, 50/125 μ m, 62.5/125 μ m
Optical fibre transmission distance	max. 1500 m [4921.3']

Dimensions (W x L x H)	22.5 x 110.8 x 88.4 mm [0.89 x 4.36 x 3.48"]
Protection acc. to EN 60529	IP40, terminals IP20
Terminals	protected against contact max. conductor diameter 2,5 mm ² [AWG 23]
Temperature range	-10°C ... +60°C [+14°F ... +140°F]
Weight	ca. 100 g [3.53 oz]

EMC	
Standards	EN 55011 class B1:2009 / A1:2010 EN 61000-6-2: 2006

Connection diagram

Optical fibre transmitter


Pin	Signal
1	0 V (GND)
2	+V
3	C+
4	C-
5	D+
6	D-
7	0 V (GND)
8	+V

Optical fibre receiver




Pin	Signal	Connection
1	0 V (GND)	from power supply
2	+V	
3	D+	to controller
4	D-	
5	C+	from controller
6	C-	
7	emitter (-)	optocoupler output alarm output
8	collector (+)	

Dimensions







Dimensions in mm [inch]





Accessories

Safety modules	Safety-M compact		
<p>Control and diagnostic display</p> 	<p>Real value display for rotary speed and direction Parameterizing tool for changing device parameters</p> <p><i>Technical data:</i></p> <p>Ambient temperature 0°C ... +60°C [+32°F ... +140°F]</p> <p>Interface to the PC USB Mini-B (underside)</p> <p>Interface to the SMC1 8-pole pin strip (rear side)</p> <p>Dimensions (WxHxD) 50 x 70 x 15 mm [1.97 x 2.76 x 0.59"]</p> <p>Display OLED 128 x 64 pixels</p> <p>Weight appr. 50 g [1.76 oz]</p> <p>Conformity and standards EN 61326-1:2006 EN 61000-6-2:2006-03 EN 61000-6-3:2007-09</p>	<p>suitable for our safety modules Safety-M compact: SMC1</p>	<p><i>Order No.</i></p> <p>8.SMCB.000</p>
<p>Programming cable Safety-M compact</p> 	<p>Multi-USB-Adapter</p> <p><i>Scope of delivery:</i></p> <ul style="list-style-type: none"> • Retractable USB cable • Adapter for USB type A plug • Adapter for USB type A socket • Adapter for USB type B plug • Adapter for USB type B socket • Adapter for USB Mini B plug • Adapter for USB Mini B socket 	<p>suitable for our safety modules Safety-M compact: SMC1</p>	<p><i>Order No.</i></p> <p>05.C162RK1</p>
<p>SafeConfig software</p> 	<p>The SafeConfig software allows PC-based configuration of the Safety-M compact family.</p>	<p>suitable for our safety modules Safety-M compact: SMC1</p>	<p><i>Online on our homepage</i></p> <p>www.kuebler.com/software</p>

Accessories

Safety modules	Safety-M modular		
<p>Programming cable Safety-M modular (USB)</p> 	<p><i>Scope of delivery:</i> Mini USB cable Length 2 m [6.56']</p>	<p>suitable for our safety modules Safety-M modular: SMBD.420</p>	<p><i>Order No.</i> 05.68784.002M</p>
<p>Programming cable Safety-M modular (Ethernet)</p> 	<p>For programming Safety-M modular</p> <p>Cable: 2 x RJ45 PUR, grey 4 x 1 x 0.15 mm² [AWG 35], shielded Length 2 m [6.56']</p>	<p>suitable for our safety modules Safety-M modular: SMBD.32E SMBU SMBS</p>	<p><i>Order No.</i> 05.00.60A1.7272.002M</p>
<p>Ethernet crossover adapter</p> 	<ul style="list-style-type: none"> • Plug/Socket (RJ45) • Crossover assignment • For adapting a 1:1 patch cable as a crossover-patch cable • Unshielded • Assignment: 1/2 – 3/6 – 4/5 – 7/8 	<p>suitable for our safety modules Safety-M modular: SMBD.32E SMBU SMBS</p>	<p><i>Order No.</i> 05.CA.RJ45</p>
<p>USB Fast Ethernet adapter</p> 	<p>For easy programming of Safety-M modular using the Ethernet programming interface</p> <ul style="list-style-type: none"> • USB1.1/2.0 to 10/100 Fast Ethernet • Plug-and-Play • Supports Windows XP/7, Mac OS 5.0 or higher 	<p>suitable for our safety modules Safety-M modular: 8.SMBD.32E 8.SMBU.031 8.SMBU.0B1 8.SMBU.0C1 8.SMBU.0D1 8.SMBS.S31 8.SMBS.SC1</p>	<p><i>Order No.</i> 05.UA0144</p>
<p>Software SafeMonitor</p> 	<p>SafeMonitor programming software</p>	<p>suitable for our safety modules Safety-M modular</p>	<p><i>Online on our homepage</i> www.kuebler.com/software</p>
<p>Software license SafeMonitor</p> 	<p>Software license for the SafeMonitor programming software (including release code for download and registration)</p>	<p>suitable for the software SafeMonitor</p>	<p><i>Order No.</i> 8.SMSW.000</p>

Accessories

Safety modules	Safety-M modular		
<p>Chip card 32k</p> 	<p>Memory capacity Weight Dimensions</p>	<p>32 kBytes (256 kbits) appr. 1 g [0.035 oz] 25 x 15 x 1 mm [0.98 x 0.59 x 0.039"]</p>	<p>suitable for our safety modules Safety-M modular: SMBD EMAI EMAA EMIO</p> <p><i>Order No.</i> 8.SMCC.032</p>
<p>Chip card 128k</p> 	<p>Memory capacity Weight Dimensions</p>	<p>128 kBytes (1024 kbits) appr. 1 g [0.035 oz] 25 x 15 x 1 mm [0.98 x 0.59 x 0.039"]</p>	<p>suitable for our safety modules Safety-M modular: SMBU SMBS</p> <p><i>Order No.</i> 8.SMCC.128</p>

Accessories

Safety modules	Safety-M modular – SMAS.000	Encoder adapter module
-----------------------	------------------------------------	-------------------------------



Encoder adapter module for EMAI / EMAA axis expansion of the Safety-M modular product family.

With encoder input and output and splitted branching for the axis modules. All signal types (SSI, BiSS-C, Sin Cos, TTL / RS422, HTL / Push-Pull) can be connected thanks to passive splitting.



- Clear, EMC-compliant wiring possible.
- Passive signal splitting.
- Internally entirely shielded.
- Pin assignment switchable for EMAI / EMAA.
- For incremental and absolute encoders.

Order No.	
SMAS	Encoder expansion module
	8.SMAS.000

Accessory		Order No.
EMC terminal	for encoder cable shield, top hat rail installation	8.0000.4G06.0000
Connection technology		Order No.
Cordset, pre-assembled, 1 m [3.28']	RJ45 / RJ45	8.SMAS.C22.001M
Cordset, pre-assembled, 1 m [3.28']	RJ45 / Mini-IO	8.SMAS.C21.001M
Connection cable 5 m [16.40']	for encoder connection, Mini-IO – wire	8.SMAS.C01.005M

Further accessories can be found in the accessories area of our website at: www.kuebler.com/accessories.
 Additional connectors can be found in the connection technology section or in the connection technology area of our website at: www.kuebler.com/connection_technology.
 You will find an overview of our systems and components for Functional Safety under www.kuebler.com/safety.

Safety modules	Safety-M modular – SMAS.000	Encoder adapter module
-----------------------	------------------------------------	-------------------------------


Technical data

General data	
Type of connection	pluggable terminals
Max. terminal cross section	1.5 mm ² [AWG 15]
Environmental data	
Operating temperature	0°C ... +55°C [+32°F ...+131°F]
Storage temperature	-25°C ... +85°C [-13°F ...+185°F]
Protection acc. to EN 60529	IP20
Climate class	3 acc. to DIN 50178
EMC	
Relevant standards	EN 61000-6-2 :2005 / AC:2005 EN 61000-6-4 :2007 / A1:2011

Mechanical characteristics	
Size w x h x d	22.5 x 99 x 114.5 mm [0.89 x 3.90 x 4.51"]
Weight	160 g [5.64 oz]
Mounting	snap-on mounting on standard head rail
Input X47, X57, X67	
Type of connection	pluggable terminals
Number of encoders	max. 2
Type of signal	HTL / Push-pull TTL / RS422 SinCos SSI BiSS-C

Terminal assignment


X17	X27	X37	
1 2 3 4	1 2 3 4	1 2 3 4	
SET	/B	/D	
Encoder power supply +V	B	D	
Encoder ground 0V	/A	/C	
Cable shield PH	A	C	



X47	X57	X67	
1 2 3 4	1 2 3 4	1 2 3 4	
Input channel C	Input channel A	Cable shield	PH
/C	/A	Encoder ground	0V
D	B	Encoder power supply	+V
/D	/B	SET signal	SET

Terminal RJ45

Signal	0V	+V	A / C+	\bar{A} / C-	B	\bar{B}	D+	D-	\perp
Pin RJ45-1	2	1	4	5	7	8	3	6	PH ¹⁾




- +V: Encoder power supply +V DC
- 0V: Encoder power supply ground GND (0V)
- A, \bar{A} : Cosine signal
- B, \bar{B} : Sine signal
- C+, C-: Clock signal
- D+, D-: Data signal
- PH \perp : Plug connector housing (Shield)


Accessories

Safety modules **Safety-M modular – SMAS.000** **Encoder adapter module**

Switching




Passive signal splitting









Dimensions

Dimensions in mm [inch]



Accessories

Safety modules	Safety-M		
T Bus connector TBMS 	TBMS for connecting a basic module and expansion modules. The mounting rail bus connector is snapped on the top-hat rail. This allows simple forwarding of signals and supply voltages.	suitable for our safety modules Safety-M: MS1, MSP1, MS2, MSP2, EM3, EM4, BM11, BM21, BM31, BMB1, BMC1	<i>Order No.</i> 05.TBMS.000
T Bus connector TBFM 	TBFM for connecting several basic modules with each other for a bus module (without voltage pin). The mounting rail bus connector is snapped on the top-hat rail. This allows simple forwarding of signals.	suitable for our safety modules Safety-M: BM21, BM31, BMB1, BMC1	<i>Order No.</i> 05.TBFM.000
Programming adapter Safety-M 	Connection cable for connecting a laptop/PC to the Safety-M safety modules. The programming cable acts as an interface converter USB <-> RS422.	suitable for our safety modules Safety-M: MS1, MSP1, MS2, MSP2	<i>Order No.</i> 8.0010.9000.0020
Software SafePLC 	The SafePLC software allows comfortable graphic programming with function plan and block functions.	suitable for our safety modules Safety-M: MS1, MSP1, MS2, MSP2	<i>Online on our homepage</i> www.kuebler.com/software
Software license SafePLC 	The license dongle is a license key for the USB port. It activates the whole range of functions of the SafePLC programming software.	suitable for: SafePLC software	<i>Order No.</i> 8.SPLC.001
Software SafePMT 	The SafePMT software allows simple, license-free parameterizing of pre-defined safety values which have been previously programmed with SafePLC.	suitable for our safety modules Safety-M: MS1, MSP1, MS2, MSP2	<i>Online on our homepage</i> www.kuebler.com/software

Accessories

Accessories



Addresses

	Page
Kübler worldwide	276
Contact partners in Germany	278



Kübler worldwide

Kübler Group

Fritz Kübler GmbH, Germany

Schubertstraße 47
D-78054
Villingen-Schwenningen
Phone +49 7720 39 03-0
Fax +49 7720 21 56 4
info@kuebler.com
www.kuebler.com

Fritz Kübler SARL, France

2 rue de Grande Bretagne
F-68310 Wittelsheim
Phone +33 3 89 53 45 45
Fax +33 3 89 53 66 77
www.kuebler-sarl.com
www.kuebler.fr

Kübler Italia S.r.l., Italy

Viale F. Testi 287
I-20162 Milano
Phone +39 026 423 345
Fax +39 026 611 3843
info@kuebler.it
www.kuebler.it
as of 1.9.2014:
Viale Sarca, 96
I-20125 Milano MI

Kubler SP. Z O.O., Poland

I. Dabrowskiego 441
PL-60-451 Poznan
Phone +48 61 84 99 902
Fax +48 61 84 99 903
info@kubler.pl
www.kubler.pl

Kübler Turkey Otomasyon Ticaret Ltd. Sti., Turkey

Yeni mahalle Balikesir Cad.
Uprise Elit Residence C1 AB Blok
No:180 Soganlik
TR - 34880 Kartal/Istanbul
Phone: +90 216 999 9791
Fax: +90 216 999 9784
cengizhan.temurcin@kuebler.com
www.kuebler.com

Kuebler (Beijing) Automation Trading Co. Ltd., China

4404 Zhongyun Building-2
No. 208
Lize Zhongyuan Erqu Wangjing
New Industrial Park
Chaoyang District Beijing,
100102
Phone +86 10 5134 8680
Fax: +86 10 5134 8681
kuebler.china@kuebler.com
www.kuebler.cn

Kuebler Automation India Pvt. Ltd., India

Plot No 677, S.No. 269/3,
Paud Road, Bhugaon,
Pune 412 115,
Maharashtra
Phone +91 99 7065 5599
Tel. +91 20 6790 1-200/230/
214/202
Fax +91 20 6790 1232
info@kuebler.in
www.kuebler.in

Kuebler Korea (by F&B), South Korea

578, Kwaebop-dong, Sasang-ku
Pusan Industrial Supplies
Market 9-116
ROK-PUSAN
Phone +82 51 319 12 30
Fax +82 51 319 12 50
fnb@kuebler.co.kr
www.kuebler.kr

Kuebler Inc., USA

5245-3 Old Dowd Road
Charlotte, NC 28208
Phone +1-704-705-4711
Toll Free +1-855-KUEBLER (583-2537)
Fax +1-704-733-9170
usa@kuebler.com
www.kuebler.com/usa

Europe

Austria

Balluff GmbH
Industriestraße B16
A-2345 Brunn am Gebirge
Phone +43 22 36 3 25 21-0
Fax +43 22 36 3 25 21 46
sensor@balluff.at
www.balluff.at

Belarus

FEK Company
Pushkin Ave., 29B
BY-220015 Minsk
Phone +375 17 202 68 00
Fax +375 17 202 68 01
turck@fek.by
www.turck.by

Belgium

Multiprox N.V.
Lion d'Orweg 12
B-9300 Aalst
Phone +32 53 76 65 66
Fax +32 53 78 39 77
mail@multiprox.be
www.multiprox.be

Bulgaria

Sensomat Ltd.
Ul.Stratsin 4, vh.A, app.1
P.O.B. 116
BG-9300-Dobrich
Phone +359-888 403 570
Fax +359-58-603 033
info@sensomat.info
www.sensomat.info

Croatia

Bering d.o.o.
Naselje Tršinski 7b
HR-49210 Zabok
Phone +385 49 221 182
Fax +385 49 223 658
bering@email-t.com.hr
www.bering.hr

Czech Republic

TURCK s.r.o.
Na Brně 2065
CZ-500 06 Hradec Králové
Phone +420 - 4 95 51 87 66
Fax +420 - 4 95 51 87 67
turck-cz@turck.com
www.turck.cz

Denmark

Hans Følsgaard A/S
Theilgaardstr. 1
DK-4600 Køge
Phone + 45 43 20 86 00
Fax + 45 43 96 88 55
hf@hf.net
www.hf.net

Estonia

Standel AS
Kiisa 8
EE-11313 Tallinn
Phone +372 6 558 180
Fax +372 6 558 179
standel@standel.ee
www.standel.ee

Finland

Sähkölehto Oy
Holkitie 14
FIN-00880 Helsinki
Phone +358 9 774 6420
Fax +358 9 759 1071
office@sahkolehto.fi
www.sahkolehto.fi

France

Fritz Kübler S.à.r.l.
Compteurs et codeurs
industriels
2 rue de Grande Bretagne
F-68310 Wittelsheim
Phone +33 3 89 53 45 45
Fax +33 3 89 53 66 77
info@kuebler-sarl.com
www.kuebler.fr

Great Britain

OEM Automatic Ltd
Whiteacres, Cambridge Road
Whetstone
GB-Leicester LE8 6ZG
Phone +44 116 284 99 00
Fax +44 116 284 17 21
information@uk.oem.se
www.oem.co.uk

Greece

Industrial Automation
Systems
L.J. Skourgialos
241, El. Venizelou Ave.
GR-176 73 Kallithea - Athens
Phone +30 210 9510260
Fax +30 210 9511048
info@ias.gr
www.ias.gr

Hungary

Kvalix Automatika Kft.
Kiss Ernő u. 1-3
H-1046 Budapest
Phone +36 1 272 2242
Fax +36 1 272 2244
info@kvalix.hu
www.kvalix.hu

Iceland

Reykjafell Ltd.
Skipholt 35
IS-125 Reykjavik
Phone +354 5 88 60 00
Fax +354 5 88 60 88
reykjafell@reykjafell.is
www.reykjafell.is

Ireland

Kübler Group
Fritz Kübler GmbH
Schubertstr. 47
D-78054
Villingen-Schwenningen
Phone +49 7720 3903-0
Fax +49 7720 21564
info@kuebler.com
www.kuebler.com

Italy

Encoders:
Kübler Italia Srl.
Viale F. Testi 287
I-20162 Milano
Phone +39 026 423 345
Fax +39 026 611 3843
info@kuebler.it
www.kuebler.it
as of 1.9.2014:
Viale Sarca, 96
I-20125 Milano MI

Counters and process devices:

MAS AUTOMAZIONE S.R.L.
Via G. Galilei 20
I-20090 Segrate (MI)
Phone +39 02 26 92 20 90
Fax +39 02 26 92 16 87
info@masautomazione.it
www.masautomazione.it

Lithuania

UAB JML GROUP
Naugarduko g. 91-108,
LT-03160, Vilnius, Lietuva
Phone +370 700 01760
Phone +370 5 2133603
Fax + 3705 2159198
info@jml-group.lt
www.jml-group.lt

Netherlands

Duranmatic B.V.
Robijn 800
NL-3316 KE Dordrecht
Phone +31 78 631 05 99
Fax +31 78 613 11 33
info@duranmatic.nl
www.duranmatic.nl

Norway

ELTECO AS
Floodmyrveien 24
N-3946 Porsgrunn
Phone +47 35 56 20 70
Fax +47 35 56 20 99
firmapost@elteco.no
www.elteco.no

Poland

Kubler Sp. z o.o.
ul. Dabrowskiego 441
PL-60-451 Poznan
Phone +48 61 849 99 02
Fax +48 61 849 99 03
info@kubler.pl
www.kubler.pl

ASTAT sp. z o.o.

ul. Dabrowskiego 441
PL-60-451 Poznan
Phone +48 61 848 8871
Fax +48 61 848 8276
info@astat.com.pl
www.astat.com.pl

Electronic counters and process displays:

IMPOL-1 Sp.J.
ul. Krakowiaków 103
PL-02-255 Warszawa
Phone +48 22 886 56 02
Fax +48 22 886 56 04
biuro@impol-1.pl
www.impol-1.pl

Encoders:

OEM AUTOMATIC Sp. z o.o.
ul. Działkowa 121 A
PL-02-234 Warszawa
Phone +48 22 863 27 22
Fax +48 22 863 27 24
info@pl.oem.se
www.oemautomatic.pl

Portugal

LA2*P, Lda.
Rua Teófilo Braga, 156 A
Escrit. F - Edifício S. Domingos
Cabeço do Mouro
PT-2785 - 122 S. Domingos
de Rana
Phone +351 21 444 70 70
Fax +351 21 444 70 75
la2p@la2p.pt
www.la2p.pt

Romania

Syscom 18 SRL
Calea Plevnei 139B, Sector 6
RO-060011 Bucharest
Phone +40 21 310 26 78
Fax +40 21 316 91 76
syscom@syscom18.com
www.syscom.ro

Russia

Servotechnica ZAO
Klara Tsetkin str., 33/35
RUS-125130 Moscow
Phone +7 495 797 8866
Fax +7 495 450 0043
info@servotechnica.ru
www.servotechnica.ru

Sweden

OEM AUTOMATIC AB
Dalagatan 4, Box 1011
S-57328 Tranås
Phone +46 75-242 4100
Fax +46 75-242 4119
info@aut.oem.se
www.oemautomatic.se

Serbia

RAP Electronics d.o.o.
Dorda Stanojevic 11-17
SRB-11070 Novi Beograd
Phone +381 11 6300636
Fax +381 11 6300635
office@rapelectronics.co.rs

Slovakia

S.D.A. s. r. o.
Jána Bottu 4
SK-974 01 Banská Bystrica
Phone +421 48 472 34 11
Fax +421 48 472 343 69
sekretariat@s-d-a.sk
www.s-d-a.sk

Slovenia

SENZORJI SB d.o.o.
Livadna ulica 1
SLO-2204
Miklavž na Dravskem polju
Phone +386 2 6 29 03 00
Fax +386 2 6 29 03 02
senzorji.sb@siol.net
www.senzorji-sb.si

Spain

Elion, S.A.
Farell, 5
E-08014 Barcelona
Phone +34 93 298 20 00
Fax +34 93 431 18 00
elion@elion.es
www.elion.es

Switzerland

(French)
Fritz Kübler S.à.r.l.
2 rue de Grande Bretagne
F-68310 Wittelsheim
Phone +33 3 89 53 45 45
Fax +33 3 89 53 66 77
info@kuebler-sarl.com
www.kuebler.fr

(Italian)

Kübler Italia Srl.
Viale F. Testi 287
I-20126 Milano
Phone +39 0 26 42 33 45
Fax +39 0 26 61 13 843
info@kuebler.it
www.kuebler.it
as of 1.9.2014:
Viale Sarca, 96
I-20125 Milano MI

(German)

Fritz Kübler GmbH
Schubertstraße 47
D-78054
Villingen-Schwenningen
Phone +49 7720 39 03-58
Fax +49 7720 21 56 4
vedrana.sollic@kuebler.com
www.kuebler.com

Turkey

Kübler Turkey Otomasyon
Ticaret Ltd. Sti.
Yeni mahalle Balikesir Cad.
Uprise Elit Residence C1 AB Blok
No:180 Soganlik
TR - 34880 Kartal/Istanbul
Phone +90 216 999 9791
Fax: +90 216 999 9784
cengizhan.temurcin@kuebler.com
www.kuebler.com

Encoders, process devices and transmission technology:

Sanil Teknik
Elektrik San. ve Tic. Ltd. Sti.
Okçumusa Caddesi
Tusak Sokak
No: 27/5 Karaköy
TR-34420 Istanbul
Phone +90 212 256 94 28
Fax +90 212 256 94 04
sanil@sanil.com.tr
www.sanil.com.tr

Counters:

ERUZ Elektrik San. ve Tic. A.S.
Necatibey Caddesi
Sait Demirbag Han No.5 K.1
TR-34425 Istanbul
Phone +90 212 2 93 60 36
Fax +90 212 2 44 51 56
eruzelektrik@eruzelektrik.com.tr
www.eruzelektrik.com.tr

Ukraine

SV Altera Ltd.
4, Ivana Lepshe blvd
UA-03680 Kyiv
Phone +38 044 496-18-88
Fax +38 044 496-18-18
office@sv-altera.com
www.svaltera.ua

America, Asia, Australia, Africa

Catalogue distributors: (Europe)

Austria
Farnell GmbH
Birkenstrasse 2
A-5300 Salzburg/Hallwang
Phone +43 662 - 218 06 80
Fax +43 662 - 218 06 70
verkauf.at@farnell.com
www.farnell.at

RS Components
Albrechtser Straße 11
A-3950 Gmünd
Phone +43 28 52 505
Fax +43 28 52 53 223
www.rs-components.at

France
RS Components SAS
Rue Norman King BP 40453
F-60031 Beauvais CEDEX
Phone +33 3 44 10 16 48
Fax +33 3 44 10 16 44
www.radiospares.fr

Farnell France SAS
81-83 rue Henri Depagneux
BP 60426 Limas
F-69654 Villefranche sur
Saône
Cedex
Phone +33 4 74 68 99 99
Fax +33 4 74 68 99 90
ventes@farnell.com
www.farnell.fr

Great Britain
RS Components Ltd.
PO Box 99, Corby
GB-Northants NN17 9RS
Phone +44 84 58 50 99 00
Fax +44 15 36 40 56 78
www.rs-components.com

Farnell
Canal Road
GB-Leeds, LS12 2TU
Phone +44 8447 11 11 11
Fax +44 8447 11 11 13
sales@farnell.co.uk
www.farnell.co.uk

Italy
RS Components S.p.A.
Via De Vizzi 93/95
I-20092, Cinisello Balsamo,
Milano
Phone +39 02 660 581
Fax +39 02 660 580 51
www.rs-components.it

Distrelec Italia s.r.l.
Via Canova 40/42
I-20020 Lainate (Mi)
Phone +39 02 - 93 75 51
Fax +39 02 - 93 75 57 55
info-it@distrelec.com
www.distrelec.com

Switzerland
Distrelec AG
Grabenstraße 6
CH-8606 Nänikon
Phone +41- 44 9 44 99 11
Fax +41- 44 9 44 99 88
www.distrelec.com

Farnell AG
Brandschenkestr. 178
Postfach 1703
CH-8027 Zürich
Phone +41 1 - 204 64 64
Fax +41 1 - 204 64 54
verkauf.ch@farnell.com
www.farnell.ch

Micronor AG
Pumpwerkstraße 32
CH-8105 Regensdorf
Phone +41 44 843 40 20
Fax +41 44 843 40 39
sales@micronor.ch
www.micronor.ch

Argentina
AUMECON S.A.
Acassuso 4768
1605 Munro
Prov. de Buenos Aires
Phone +54 11 47 56 1251
Fax +54 11 47 62 63 31
ventas@amecon.com.ar
www.amecon.com.ar

Australia
Balluff Leuze Pty. Ltd.
12 Burton Court
Bayswater, Vic. 3153
Phone +61 3 97 20 41 00
Fax +61 3 97 38 26 77
sales@balluff.com.au
www.balluff.com.au

Brazil
Balluff Controles Elétricos Ltda.
Rua Francisco Foga 25,
Cx. Postal 189
CEP 13280-000 Vinhedo-SP
Phone +55 19 38 76 99 99
Fax +55 19 38 76 99 90
balluffbr@balluff.com.br.
www.balluff.com.br

Canada
Chartwell Automation Inc.
140 Duffield Drive
Markham, Ontario L6G 1B5
Phone +1 905 513 7100
Fax +1 905 513 7101
info@chartwell.ca
www.chartwell.ca

Chile
Electronica industrial
El Schädler y Cia. Ltda.
Casilla 189-9
Av. Antonio Varas 1871
Providencia
Santiago
6641545
Phone +56 2 274 74 30
Fax +56 2 204 93 38
info@schadler.com

China
Kuebler (Beijing) Automation
Trading Co. Ltd.
4404 Zhongyun
Building-2 No. 208
Lize Zhongyuan Erqu
Wangjing New Industrial Park
Chaoyang District
Beijing, 100102
Phone +86 10 5134 8680
Fax +86 10 5134 8681
beijing@kuebler.com
www.kuebler.cn

Egypt
AEE Advanced Electronic
Engineering Co.
3 Hassan El-Sheraie St.Off
El-Horiya St-Heliopolis
Cairo
Phone +20 2 2418 50 20
Fax +20 2 2415 92 65
hfarid@aecontrols.com
www.aeecontrols.com

Hong Kong
Po Kwong Electric (HK) Ltd.
Rm. 177-180, 1/F, Bk C,
Hang Wai Ind. Ctr.,
6 Kin Tai St., Tuen Mun, N.T
Phone +852 24 23 66 22
Fax +852 24 61 10 02
sales@pokwong.com
www.pokwong.com

India
Kuebler Automation India Pvt Ltd
Plot No 677, S. No. 269/3,
Paud Road, Bhugaon,
Pune 412 115,
Maharashtra
Phone +91 99 7065 5599
Tel. +91 20 6790 1-200 / 230 /
214 / 202
Fax +91 20 6790 1232
info@kuebler.in
www.kuebler.in

Rajdeep Automation Pvt. Ltd.
G3A, Anand Estate, Ground floor
Sane Guruji Marg, Mahalaxmi
Mumbai 400 011
Phone +91 22 23 00 28 37 / 8
Fax +91 22 23 00 2839
info@rajdeep.in
www.rajdeep.in

Indonesia
SUPRA Engineering
Jl. Pecenongan 17 D
RI-10120 Jakarta
Phone +62 21 345 73 55
Fax +62 21 345 73 18
astina@centrin.net.id
www.supra.co.id

Israel
Omega Engineering
P.o.Box 190
Ein Carmel 30860
Phone +972-4-9544993
Fax +972-4-9544992
info@omegae.net
www.omegae.net

Lebanon
Industrial Technologies S.A.L
(ITEC)
Blvd. Fouad Chehab
Point Center, Sin El Fil, Beirut
Phone +961 (1) 491161
Fax +961 (1) 491162
info@iteclb.com
www.iteclb.com

Malaysia
dpStar Thermo Electric Sdn. Bhd.
No. 37-G, Pusat
Perdagangan One Puchong
Jalan DP 1/2 Off Jalan . 47160
Puchong
Selangor
Malaysia
Phone +603 80 70 87 88
Fax +603 80 70 87 66
chrisliu@dpstar.com.my
www.dpstar.com.my

Mexico
Turck Mexico S.de R.L.de C.V.
Parque Industrial La Angostura
Zacatecas Km 4.5 Nave 8A
Saltillo, Coahuila 25315
Phone +52 844 411 6650
Toll Free: 01-800-01-TURCK
(Mexico only)
Fax +52 844 482 6926
mexico@turck.com
www.turck.com.mx

Morocco
r2i Consult SARL
109 rue Montaigne Val
Fleuri Maarif Casablanca
Maroc
Phone +212522986960
Fax +212522989537
info@r2imaroc.com
www.r2imaroc.com

New Zealand
Carrel-Electrade Ltd.
P.O. Box 11-078
Ellerslie
NZ-Auckland 1542
Phone +64 95251753
Fax +64 95251756
sales@carrel-electrade.co.nz
www.carrel-electrade.co.nz

Peru
Techpro SAC
Calle Alberto del Campo 414
Magdalena del Mar
Lima 17 - Peru
Phone +51 98943 58-54
Fax +51 17272 685
techpro.peru@techprocorp.net
www.techprocorp.net

Philippines
Technorand Sales Corporation
Wilshire Annapolis Plaza,
Annapolis Street
San Juan, Metro Manila 1500
Phone +63 2 9850705
Fax +63 2 172 65 986
technorand@gmail.com

Singapore
Raymond International Pte. Ltd.
Blk 219 Henderson Road #07-04
Henderson Industrial Park
Singapore 159556
Phone +65 62 76 37 38
Fax +65 62 76 37 39
sales@raymondcom.com
www.raymondcom.com

South Africa
Kübler Group
Fritz Kübler GmbH
Schubertstr. 47
78054 Villingen-Schwenningen
Phone +49 7720 3903-0
Fax +49 7720 21564
info@kuebler.com
www.kuebler.com

South Korea
Kuebler Korea (by F&B)
578, Kwaebop-dong, Sasang-ku
Pusan Industrial Supplies
Market 9-116
PUSAN
Phone +82 51 319 12 30
Fax +82 51 319 12 50
fnb@kuebler.co.kr
www.kuebler.kr

Taiwan, R.O.C.
• Encoders, transmission
technology:
E-Sensors & Automation Int'l Corp.
6F-2, No.109, Chien Kuo 1st Rd.
Kaohsiung 80284
Taiwan, R.O.C.
Phone +886-7-7220371
Fax +886-7-7718161
ez-corp@umail.hinet.net
www.e-sensors.com.tw

• Electronic counters and
process devices:
Canaan Electric Corp.
6F-5, No. 63, Sec. 2
Chang An East Road
Taipei
Phone +886 225 08 23 31
Fax +886 225 08 47 44
sales@canaan-elec.com.tw
www.canaan-elec.com.tw

Thailand
Technology Instruments Co., Ltd.
549/9 Onnut Road Kwaeng
Pravet, Khet Pravet
Bangkok 10250
Phone +662 74 388 88
Fax +662 74 388 43
marketing@tic.co.th
www.tic.co.th

Tunisia
H2M Technologies
13, Rue El Moutanabi
TN-2037 El Menzah 7 -Tunis
Phone +216 71 42 76 77
Fax +216 71 42 76 88
h2m.tech@planet.tn

U.S.A.
Kuebler Inc.
5245-3 Old Dowd Road
Charlotte, NC 28208
Phone +1-704-705-4711
Toll Free +1-855-KUEBLER (583-2537)
Fax +1-704-733-9170
usa@kuebler.com
www.kuebler.com/usa

• Counting and process
technology:
Global Industrial Products Inc.
8129 North Austin Ave
Morton Grove, IL 60053
Toll-free number:
1-800-951-8774
Phone 847 965 9808
Fax 847 901 9846
sales@globalepower.com
www.kueblerusa.com

United Arab Emirates
Baer Measurements LLC
P.O. Box 111393
Al Gaiht Tower 505,
Hamdan Street
Abu Dhabi - UAE
Phone +971 2 627 2097
Fax +971 2 627 2091
info@bml.ae
www.bml-international.com

Vietnam
GNN Co., Ltd
153, Nguyen Van Thu
Da Koa Ward, District 1
Ho Chi Minh City
Phone +84 8 3517 4923
Fax +84 8 3517 4924
contact@gnnvietnam.com
www.gnnvietnam.com

Contact partners in Germany

PLZ 01000 ... 09999
PLZ 15000 ... 15999
 Kübler Vertriebsbüro Süd-Ost
 Lars Meyer
 Durchfahrt 9
 09569 Oederan
 Phone +49 37292 283500
 Fax +49 37292 283501
 lars.meyer@kuebler.com

PLZ 10000 ... 14999
PLZ 16000 ... 19999
PLZ 20000 ... 32999
PLZ 38000 ... 39999
 Kübler Vertriebsbüro Nord
 Hermi Herrmann
 Mohnblumenweg 6
 28876 Oyten
 Phone +49 4207 6880-32
 Fax +49 4207 6880-34
 hermi.herrmann@kuebler.com

PLZ 33000 ... 33999
 Kübler Vertriebsbüro West
 Torsten Czubkowski
 Auf der Ümcke 11 a
 59757 Arnsberg
 Phone +49 2932 891898
 Fax +49 2932 53311
 torsten.czubkowski@kuebler.com

PLZ 34000 ... 37999
 Kübler Vertriebsbüro Mitte
 Stefan Heinigk
 Gartenstraße 10
 35759 Driedorf
 Phone +49 2775 578427
 Fax +49 2775 578428
 stefan.heinigk@kuebler.com

PLZ 40000 ... 47999
 Kübler Vertriebsbüro West
 Torsten Czubkowski
 Auf der Ümcke 11a
 59757 Arnsberg
 Phone +49 2932 891898
 Fax +49 2932 53311
 torsten.czubkowski@kuebler.com

PLZ 48000 ... 49999
 Kübler Vertriebsbüro Nord
 Hermi Herrmann
 Mohnblumenweg 6
 28876 Oyten
 Phone +49 4207 6880-32
 Fax +49 4207 6880-34
 hermi.herrmann@kuebler.com

PLZ 50000 ... 54999
PLZ 55300 ... 55999
PLZ 56500 ... 56999
PLZ 58000 ... 59999
 Kübler Vertriebsbüro West
 Torsten Czubkowski
 Auf der Ümcke 11a
 59757 Arnsberg
 Phone +49 2932 891898
 Fax +49 2932 53311
 torsten.czubkowski@kuebler.com

PLZ 55000 ... 55299
PLZ 56000 ... 56499
PLZ 57000 ... 57999
 Kübler Vertriebsbüro Mitte
 Stefan Heinigk
 Gartenstraße 10
 35759 Driedorf
 Phone +49 2775 578427
 Fax +49 2775 578428
 stefan.heinigk@kuebler.com

PLZ 60000 ... 65999
PLZ 67000 ... 67599
PLZ 68000 ... 69999
 Kübler Vertriebsbüro Mitte
 Stefan Heinigk
 Gartenstraße 10
 35759 Driedorf
 Phone +49 2775 578427
 Fax +49 2775 578428
 stefan.heinigk@kuebler.com

PLZ 66000 ... 66999
PLZ 67600 ... 67999
 Kübler Vertriebsbüro West
 Torsten Czubkowski
 Auf der Ümcke 11a
 59757 Arnsberg
 Phone +49 2932 891898
 Fax +49 2932 53311
 torsten.czubkowski@kuebler.com

PLZ 70000 ... 79999
 Kübler Vertriebsbüro Süd-West
 Philipp Lang
 Lembergstraße 6
 72119 Ammerbuch-Altingen
 Phone +49 7032 2293665
 Fax +49 7032 2993454
 philipp.lang@kuebler.com

PLZ 80000 ... 87999
PLZ 89200 ... 89499
 Kübler Vertriebsbüro Süd
 Bernhard Preißler
 Am Seeacker 8
 93326 Abensberg
 Phone +49 9443 9186926
 Fax +49 9443 9186974
 bernhard.preissler@kuebler.com

PLZ 88000 ... 89199
PLZ 89500 ... 89999
 Kübler Vertriebsbüro Süd-West
 Philipp Lang
 Lembergstraße 6
 72119 Ammerbuch-Altingen
 Phone +49 7032 2293665
 Fax +49 7032 2993454
 philipp.lang@kuebler.com

PLZ 90000 ... 93999
PLZ 95000 ... 95999
 Kübler Vertriebsbüro Süd-Ost
 Lars Meyer
 Durchfahrt 9
 09569 Oederan
 Phone +49 37292 283500
 Fax +49 37292 283501
 lars.meyer@kuebler.com

PLZ 94000 ... 94999
 Kübler Vertriebsbüro Süd
 Bernhard Preißler
 Am Seeacker 8
 93326 Abensberg
 Phone +49 9443 9186926
 Fax +49 9443 9186974
 bernhard.preissler@kuebler.com

PLZ 96000 ... 99999
 Kübler Vertriebsbüro Mitte
 Stefan Heinigk
 Gartenstraße 10
 35759 Driedorf
 Phone +49 2775 578427
 Fax +49 2775 578428
 stefan.heinigk@kuebler.com

Approved system partners/ distributors

22149 Hamburg
 Hermann Seidel GmbH
 Techn. Vertretungen
 Rahlstedter Str. 16
 Phone +49 40 675085-0
 Fax +49 40 675085-85
 info@seidel-gmbh.de
 www.seidel-gmbh.de

42499 Hückeswagen
 Fuhrmeister + Co. GmbH
 Industrie-Elektronik
 Stahlschmidtsbrücke 61
 Phone +49 2192 851122
 Fax +49 2192 851127
 info@fuhrmeister-gmbh.de
 www.fuhrmeister-gmbh.de

66287 Göttelborn
 Herbert Neundörfer
 GmbH & Co. KG
 Werksvertretungen
 Am Campus 5
 Phone +49 6825 9545-0
 Fax +49 6825 9545-99
 info@herbert-neundoerfer.de
 www.herbert-neundoerfer.de

82069 Hohenschäftlarn
 Bachmann
 Electronic GmbH
 Am Wagnerfeld 4
 Phone +49 8178-8676-0
 Fax +49 8178-8676-50
 info@bachmann-electronic.de
 www.bachmann-electronic.de


Catalogue distributors (Germany):

28359 Bremen
 Distrelec Schuricht GmbH
 Lise Meitner-Str. 4
 Phone +49 1805 2234-35
 Fax +49 1805 2234-36
 scc@distrelec.de
 www.distrelec.de

64546 Mörfelden-Walldorf
 RS Components GmbH
 Hessenring 13 b
 Phone +49 6105 401234
 Fax +49 6105 401100
 www.rs-components.de

82041 Oberhaching
 Farnell GmbH
 Keltenring 14
 Phone +49 89 61393939
 www.farnell.de


92240 Hirschau
 Conrad Electronic SE
 Klaus-Conrad-Straße 1
 Phone +49 9622-30-4145
 www.conrad.com





Kubler

www.kuebler.com




Position and Motion
Sensors



Functional Safety



Transmission
Technology



Counters and Process
Devices

Kübler Group
Fritz Kübler GmbH
Schubertstrasse 47
D-78054 Villingen-Schwenningen
Germany
Phone +49 7720 3903-0
Fax +49 7720 21564
info@kuebler.com
www.kuebler.com

■■■■ *pulses for automation*

R65001.0002 08 200 14 ES