

MDRIVE 34™ LINEAR SLIDE

MOTOR+DRIVER

Plus

FEATURES

- Screw driven slide offering exceptional linear speed, accurate positioning and long life at a compelling value
- High bidirectional repeatability of up to 50 micro-inches (1.25 microns)
- Positional lead accuracy of 0.0006"/in. – accuracies to 0.0001"/in. available
- Linear speeds not limited by critical screw speed
- Standard leads:
 - 0.10" travel per revolution
 - 0.20" travel per revolution
 - 0.50" travel per revolution
 - 1.00" travel per revolution
- Achieve speeds that exceed 60.0"/second while offering excellent repeatability, accuracy and axial stiffness
- Optional sensor flag kit available for home, limits and general purpose inputs
- Assembly includes a precision aluminum guide and carriage which is driven by a precision rolled stainless steel lead screw
- Sliding contact areas coated with TFE (Teflon) permanent lubrication to offer a low 0.09 coefficient of friction
- Exceptional torsional stiffness and stability
- Standard lengths from 12.0" to 42.0", longer sizes available upon request*
- Comes standard with wear-compensating, anti-backlash driven carriage
- Additional passive carriages or slides available to support cantilevered loads
- Easily mountable with provided mounting flange and holes
- Extrusions provided for sensor mounts

* Consult Factory for Availability.


LINEAR SLIDE SPECIFICATIONS

Screw Lead	Screw Efficiency	Nom. Screw Diam.	Inch Lead	Max Drag Torque	Life @ 1/4 Axial Design Load	Torque to Move Load	Axial Design Load	Screw Inertia
	%	inches (mm)	inches (mm)	oz inch (Nm)	inches (cm)	oz inch/lb (Nm/kg)	lbs (kg)	oz.in.sec ² /inch (Kg.m ² /m)
0.10"	40	0.625" (15.9)	0.100 (2.54)	5.0 (0.03)	100,000,000 (254,000,000)	1.3 (0.020)	100 (46)	14.2 x 10 ⁻⁵ (3.9 x 10 ⁻⁵)
0.20"	53	0.625" (15.9)	0.200 (5.08)	6.0 (0.04)	100,000,000 (254,000,000)	2.0 (0.031)	100 (46)	14.2 x 10 ⁻⁵ (3.9 x 10 ⁻⁵)
0.50"	76	0.625" (15.9)	0.500 (12.70)	7.0 (0.05)	100,000,000 (254,000,000)	3.0 (0.047)	100 (46)	14.2 x 10 ⁻⁵ (3.9 x 10 ⁻⁵)
1.00"	81	0.625" (15.9)	1.000 (25.40)	8.5 (0.06)	100,000,000 (254,000,000)	6.5 (0.101)	100 (46)	14.2 x 10 ⁻⁵ (3.9 x 10 ⁻⁵)

ORDER INFORMATION

Linear Slide R		Example: [MDrive P/N] - RA12 Adds a Linear Slide with a lead of 0.10"/rev, 12" long to a specified MDrive34Plus.	
Screw Lead (inches/rev) A = 0.10" C = 0.50" B = 0.20" D = 1.00"	Screw Length (in inches) 12, 18, 24, 36, 42		
Optional Kits Sensor Flag RSM10-K		Kit includes: flag for optical sensor, 3 - sensor holders, 6 - #2-56 X 1/4" long BHCS screws, 3 - #4-40 X 1/2" long SHCS screws, 2 - #6-32 X 1/2" long SHCS screws.	
Mounting Bracket RMB10-K		Kit includes: 2 - mounting brackets, 4 - #1/4-20 X 3/4" long SHCS screws	

LINEAR SLIDE SPEED-FORCE LIMITATIONS†



†Speed/Force correlating equations:

- $$\text{Axial Force} = F_{\text{friction}} + F_{\text{acceleration}} + F_{\text{gravity}}$$

$$F_{\text{friction}} = (\text{Weight})(0.09)$$



$$F_{\text{acceleration}} = (\text{Weight})(\text{Acceleration}) / \text{Accel. of gravity}$$

$$F_{\text{gravity}} = 0 \text{ for horizontal application and Weight for vertical application}$$
- $$\text{Torque} = \frac{(\text{Axial Force})(\text{Screw Lead})}{(0.393)(\text{Screw Efficiency})}$$

Force in lbs; Torque in oz-in; Lead in inches/rev
- $$\frac{\text{Full Steps}}{\text{Second}} = \frac{(200 \text{ Full Steps/Rev})(\text{Velocity})}{\text{Lead}}$$

Lead in inches/rev; Velocity in inches/second

MDRIVE SPEED-TORQUE CURVES




- A** Single Stack
- B** Double Stack
- C** Triple Stack


MECHANICAL SPECIFICATIONS

Dimensions in Inches (mm)


- 1 NEMA 34 Mounting Plate
- 2 Heli-Cal Coupling
- 3 Sunx P/N PM-L24 sensor or equivalent (*not supplied*)
- 4 Optional Sensor Flag for use with U-channel sensor (*details below*)
- 5 Optional Mounting Brackets (*details below*)



SIDE VIEW



TOP VIEW




Mounting Holes

Slide Length (L)	Max Hole Distance (D)	Extra Hole Sets (not shown)	Equal Space Between Holes
12"	10.5"	none	10.5"
18"	16.5"	1	8.25"
24"	22.5"	2	7.5"
36"	34.5"	2	11.5"
42"	40.5"	2	13.5"

Sensor Flag Kit Option

P/N RSM10-K Includes:


- A #2-56 X 1/4" Long BHCS (6)
- B Sensor Holder (3)
- C #4-40 X 1/2" Long SHCS (3)
- D Flag for Optical Sensor (1)
- E #6-32 X 1/2" Long SHCS (2)



Mounting Bracket Kit Option

P/N RMB10-K Includes:

- F Mounting Bracket (2)
- G #1/4-20 X 3/4" Long SHCS (4)



INTELLIGENT MOTION SYSTEMS, INC.

Excellence in Motion™

www.imshome.com

370 N. Main St., P.O. Box 457
Marlborough, CT 06447 U.S.A.
Phone: 860/295-6102
Fax: 860/295-6107
E-mail: info@imshome.com

TECHNICAL SUPPORT

Phone: 860/295-6102 (U.S.A.)
Fax: 860/295-6107
E-mail: etech@imshome.com

Germany/UK

Phone: +49/7720/995858-3
Fax: +49/7720/995858-9
E-mail: mweber@imshome.com

DISTRIBUTED BY:

IMS UK Ltd.

25 Barnes Wallis Road
Segensworth East
Fareham, Hampshire PO15 5TT
Phone: +44/O 1489-889825
Fax: +44/O 1489-889857
E-mail: mcheckley@imshome.com

IMS ASIA PACIFIC OFFICE

30 Raffles Pl., 23-00 Caltex House
Singapore 048622
Phone: +65/6233/6846
Fax: +65/6233/5044
E-mail: wlee@imshome.com

IMS EUROPE GmbH

Niedereschacher Strasse 54
78083 Dauchingen Germany
Phone: +49/7720/995858-0
Fax: +49/7720/995858-9
E-mail: info@imseuropehome.com

European Sales Management

4 Quai Des Etroits
69005 Lyon, France
Phone: +33/4 7256 5113
Fax: +33/4 7838 1537
E-mail: bmartinez@imshome.com

Germany Sales

Phone: +49/35205/4587-8
Fax: +49/35205/4587-9
E-mail: hruhland@imshome.com

Germany/UK Technical Support

Phone: +49/7720/995858-3
Fax: +49/7720/995858-9
E-mail: mweber@imshome.com

U.S.A. SALES OFFICES

Eastern Region

Phone: 973/661-1270
Fax: 973/661-1275
E-mail: jroake@imshome.com

Central Region

Phone: 260/402-6016
Fax: 419/858-0375
E-mail: dwaksman@imshome.com

Western Region

Phone: 602/578-7201
E-mail: dweisenberger@imshome.com