

Moving towards tomorrow

LS MECAPION

# L7 Series

Game Must Be Changed !



**LS** Mecapion

Products Collection Vol. 1.1

# L7 Drive

Designing your future with  
**LS Mecapion L7 Series.**

## Your reasonable selection for total solution

The wide range of LS Mecapion line up will satisfy your requirements for the motion system through optimal application and use of the products.

With the excellent functionality, high precision and high-speed control, LS Mecapion AC servo system is customer-friendly and cost-effective.



# **Moving towards tomorrow**

The Best Automation **Brand** in Korea  
The World Class Leader in Automation System

LS Mecapion has supplied not only the servo drives and servo motors of high quality and high efficiency but also rotary encoders and actuators for the Korean and Global Industries for the past 20 years.

We are making efforts to provide a variety of products to our customers all over the world to satisfy their requirements. We have provided cutting-edge technologies that consider the needs of our customers by adopting the best functionality as well as innovative ideas.

We have accumulated a deep and wide range of experiences in the field of the control system for years and are venturing into new possibilities to provide the technologies of a higher level to our customers.

We hope that you don't miss the opportunity to use the proven, **world-class products** from **LS Mecapion** to improve the performance and value of your equipment.

We hope that we can provide the best services and partnerships for our customers by utilizing our expertise and technologies.



# L7 SERIES SYSTEM

## Features of L7 Drive

### Compact Size

Capacity	400W			1kW			3.5kw		
	L7	VS	Competitor	L7	VS	Competitor	L7	VS	Competitor
L [mm]	38	80	40	58	88	60	88	137	90
W [mm]	169	187	168	169	210	168	169	256	168
H [mm]	173	132	170	198	195	195	198	225	195

Compared with VS

Slim up to  
52%  
More

Compared with a representative competitor

Slim up to  
5%  
More

### Ultra-thin 38 mm width (400 W)

Its small footprint allows flexible installation, reducing the size of the equipment.

■ 400W



■ 1kW




■ 3.5kW



### Easy to USE

#### • The automatic inertia detection function for easier gain adjustment.

- Fast and accurate inertia detection
- Off-line tuning
- Parameters for inertia detection (speed and distance) provided



#### • Encoder based on two-way high-speed serial communication

- Automatic recognition for motors and encoders
- BiSS protocol
- Wire-saving system (7-line) for encoder, resistant to noise

**BiSS**  
INTERFACE

#### • Support for various motors and encoders [L7NH and L7P Series]

- Support for standard BiSS encoders as well as other encoders

Motor	Encoder
Rotary	Quadrature / BiSS Interface
DD	Tamagawa serial absolute
Linear	EnDat 2.2 / Resolver


## Features of L7 Drive

### • Sufficient input/output contacts and various functions

- L7S: Digital input contacts: 10, output contacts: 8 / Analog input contacts: 2 and output contacts: 2
- L7N: Digital input contacts: 6, output contacts: 4 / Analog input contacts: 2 and output contacts: 2
- L7NH: Digital input contacts: 8, output contacts: 4 / Analog input contacts: 1 and output contacts: 2
- L7P: Digital input contacts: 16, output contacts: 8 / Analog input contacts: 2 and output contacts: 2
- PEGASUS: Digital input contacts: 4, output contacts: 2 / Analog input contacts: 1 and output contacts: 1
- Flexible assignment of input/output signals by parameters and contact setting based on the input/output contact type (N.O / N.C contacts)


### • Using the rotary switch to configure the drive node address [L7NH, L7P, and PEGASUS]

- Using the rotary switch to configure the drive node address conveniently
- L7NH: 0–99, L7P: 0–31, PEGASUS: 0–15



### • Various homing functions [L7NH, L7P, and PEGASUS]

- The drive provides the homing function.
- You can specify the speed, acceleration, offset, and homing method.




### • Easy firmware upgrade [L7NH, L7P, and PEGASUS]

- Supporting the USB OTG function to allow firmware download with a USB memory
- Useful where space is limited or environmentally unfavorable



### • Built-in regenerative braking resistance in the drive

- Drive installed inside to improve user convenience (100 W – 3.5 kW)
- Providing the connection for external installation
- Enhanced protection algorithm



### • Plug-in type power connector

- Expanded to 100 W – 3.5 kW for improved wiring convenience




# L7 SERIES SYSTEM

## Features of L7 Drive

### ■ Reliability

- Main capacitor quality improved
  - Long-life type capacitor applied (2.5 times improvement)
- Convenient DC reactor installable
  - Power connection to DC-link
  - Easier wiring and smaller size compared to 3-phase AC reactor
  - Connection for DC input (PI, N)
- Stable turn-off function based on the detection of the control power turn-off
- CE certification and RoHS certification
- Enhanced protection function
  - Triple protection function for the protection of power module
  - Detection of the main power phase loss
  - Temperature sensor installed in the drive and motor for the prevention of overheat
  - Alarm code grouping and dedicated output contacts (ALO0, ALO1, ALO2)
  - Warning function (Digital output WARN)



### ■ High Performance


- Serial encoder of high resolution (19 bit)
  - Stability improved during precision position control and low-speed operation
- Stable low-speed properties based on precise speed measurement
  - Stable speed measurement at low speed
- Calculation speed improved [L7NH, L7P, and PEGASUS]
  - FPU (Floating Point Unit) for reliable precision calculation
  - 16 kHz switching frequency for precision current control
  - 32 bit operation for increased synchronous command processing rate (MIPS)
- Dedicated PC program
  - L7S, and L7N: LIVE-I.C.E / L7NH, L7P, and PEGASUS: Drive CM
  - PC program for shortened equipment tuning time and debugging
  - Monitoring for speed, torque, current feedback, position values and positional error values and alarm occurrence time

## Features of L7 Drive

### ■ Intelligent Control


- Notch filter for resonance suppression

- 4-step notch filter
- 2-step vibration suppression filter at the load position
- FFT function for real-time frequency analysis



- Various gain switching modes for improved control performance

- P/PI auto-switching function to reduce overshooting during acceleration/deceleration
- Various Gain1 ↔ Gain2 switching modes



- Various dynamic brake control modes

- Configuring the operation mode at stop and after stop

### ■ Network Based – EtherCAT Network Type

- A wide range of products

- L7N: EtherCAT communication command type
- L7NH: All-in-one EtherCAT communication command type
- PEGASUS: Motor drive-integrated EtherCAT communication command type

Field Bus



- High performance

- Synchronization mechanism of high speed, high accuracy, and real-time communication
- Various Gain1 ↔ Gain2 switching modes

- Open network

- An international standard network with 1,600 members over the world

- Low cost


- Standard Ethernet connector and cabling supported and slave-master implemented at a low cost

- Easy to use

- Various topology types supported and easy diagnosis for devices

- L7 drive with a built-in EtherCAT interface

- 100BASE-TX (100 Mbps) real-time communication
- CiA402 (IEC61800-7) drive profile supported
- Connection with various masters and slaves
- Up to 100 m connection between nodes
- Precision synchronization mechanism of 1 us or less



# L7 SERIES SYSTEM

## Features of L7 Drive

### • Various operation modes

- L7N: Using the EtherCAT communication to support Cyclic (P/S/T) and Profile (P/S/T) modes
- L7NH and PEGASUS: Using the EtherCAT communication to support Cyclic & Profile (P/S/T) modes, EOE, COE, and FOE

### • Safe torque off function

- Torque-off forced by hardware signals without involvement of the drive CPU and FPGA (ASIC); international standards adopted (IEC61508)

### • Flexible I/O setup

- Mapping and level (A/B) setup by parameters

### • High-speed position capture


- Touch probe function (PROBE1 and PROBE2)

### • Adjustment function linked with XGT series from LSIS

- Inertia detection, position/speed gain manual adjustment, gain switching setup, etc.

### • EtherCAT drive compatibility

- Verified by CTT (Conformance Test Tool)






## Servo Setup Software

### ■ Software dedicated for Live-ICE / L7S and L7N Series


#### ● Monitoring function

- Monitoring for I/O input contact and I/O output contact
- Driving Information monitoring: Monitoring and displaying the parameter values
- Communication connection monitoring : Displaying the current communication connection status using animation in real time



#### ● Setup function

- Using the PC to read and write parameters
- Manual JOG function: Manual jog speed adjustment and forward/reverse test
- Automatic gain tuning
- Alarm history and alarm reset



#### ● Graph function

- Data Trace: Graphic presentation of pre-defined channels in real time
- Trigger Monitoring: Graphic presentation by the channel and trigger settings
- Alarm Trace: Graphic presentation of alarm history for channels




#### ● Download software

- OS Download: Firmware version upgrade software

# L7 SERIES SYSTEM


## Servo Setup Software

- Software dedicated for Drive CM / L7NH, L7P, and PEGASUS Series



### I/O CONFIG

- Setting the output function and its signal level for I/O input contacts and I/O output signal pins
- Limiting the analog input torque and using the analogue voltage to override the speed
- Analog monitoring output for the gain tuning or internal state variables of the drive





### Monitoring function

- Implementation of 4-channel tracer or trigger monitor
- Performing various operations, including Manual Jog, Program Jog, PTP Move, etc., and monitoring the operation state
- Monitoring Zoom or Pan / Mouse Wheel / Rollover or Cursor

### Setup function

- Configuring the data structure including parameters, state variables, commands, etc. inside the drive
- Using Manual Jog and Program Jog to carry out the test
- Using Offline Auto Tuning for one-touch adjustment
- Customer convenience functions such as PTP movement, homing, and touch probe



### Indexer setup [L7P only]

- Using Index Edit to enter/configure the index parameters
- Using Indexer Test to configure the operation and provide testing function

# INDEX

## Servo Drive

L7S Series \_ 13

L7N Series \_ 25

L7NH Series \_ 31

L7P Series \_ 44



## Servo Motor

S Series \_ 52

F Series \_ 68

MDM Series \_ 83

## Options

Servo motor cable \_ 93

Servo drive cable \_ 105

Other options \_ 107

## Integrated Servo System

PEGASUS Series \_ 110

# L7 SERIES SYSTEM

## Contents

### Servo Drive

## L7S Series

General Pulse Type, Analog Command Type

- Servo Drive Designation \_ 13
- Product Feature \_ 18
- External Dimensions \_ 20



## L7N Series

EtherCAT Communication Command Type

- Servo Drive Designation \_ 25
- Product Feature \_ 28
- External Dimensions \_ 29



## L7NH Series

All-in-one EtherCAT Communication Command Type

- Servo Drive Designation \_ 31
- Product Feature \_ 37
- External Dimensions \_ 39



## L7P Series

Indexer Function Type

- Servo Drive Designation \_ 44
- Product Feature \_ 48
- External Dimensions \_ 49



General Pulse Type, Analog Command Type

# L7S Series



## Servo Drive Designation

L7	S	A	004	B	AA
Model Name	Communication	Input Power Supply	Capacity	Encoder Type	Option
Servo Series	S : Standard I/O Type	A : 200VAC B : 400VAC	001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1.0kW 020 : 2.0kW 035 : 3.5kW 050 : 5.0kW 075 : 7.5kW 150 : 15.0kW	A : Quadrature (Pulse Type)  B : Serial (Communication Type)	Exclusive Option Code
<b>* Range</b>					
· 200V : 0.1kW~5.0kW					
· 400V : 1.0kW~15kW					

# L7 SERIES SYSTEM

## L7S Series

### Characteristic

#### • Easy to USE

- Easy Gain Tuning with Automatic Inertia Estimating Function
- Easy Setting Built-in Panel Operator
- Many I/O Contacts and Various Functions  
(Digital Input: 10 contacts, Digital Output: 8 contacts / Analog input, output : 2 contacts )


#### • Reliability for Protection Function

- CE, RoHS Certificated
- Drive Protection Function and Warning Function

#### • High Response for Precision Control

- High Resolutions Serial type Encoder(19Bit, BiSS)
- Improved Speed Response(= 1Khz) Frequency

### Identifying the Part of L7S



- ① Operation keys (Mode, Up, Down, Set)
- ② Charge Lamp
- ③ Main Power Connector (L1, L2, L3)
- ④ DC Reactor Connector(PO, PI)
  - Short-Circuit when not used
- ⑤ Regenerative resistance connector (B+, B, B<sub>I</sub>)
  - Short-Circuit B, B<sub>I</sub> terminals when standard type
  - Use B+, B terminals when using external resistor
- ⑥ Control Power Connector (C1, C2)
- ⑦ Front Cover
- ⑧ Motor Power Cable Connector (U, V, W)
- ⑨ Heat Sink
- ⑩ Display
- ⑪ CN5 : USB Connector
- ⑫ CN4 : RS-422 Communication Connector
- ⑬ CN3 : RS-422 Communication Connector
- ⑭ CN1 : Control Signal Connector
- ⑮ CN2 : Encoder Signal Connector
- ⑯ Ground

## L7S Drive Combination Table

### L7SA Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable	Power Cable			
							Quadrature Type	INC	For power	Power + Brake
3,000	5,000	□40	SAP3A	L7SA001A	2,048 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□KS		
			SAPSA	L7SA001A						
			SA01A	L7SA001A						
			S405A	L7SA002A						
			S801A	L7SA002A						
			S802A	L7SA002A						
			S804A	L7SA004A						
			S804A	L7SA004A						
			S806A	L7SA008A						
			S808A	L7SA008A						
			S810A	L7SA010A						
			S810A	L7SA008A						
			S812A	L7SA020A		APCS E□□□BS	APCS P□□□HS	APCS P□□□HS	APCS P□□□KS	
			S812A	L7SA020A						
			S813A	L7SA050A						
2,000	3,000	□80	SF30A	L7SA035A	3,000 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□KS		
			SF50A	L7SA050A						
			S8030	L7SA004A						
			S8050	L7SA008A						
			S8060	L7SA008A						
			S8070	L7SA008A						
			S8060	L7SA008A						
			S8110	L7SA010A		APCS P□□□HS	APCS P□□□NS	APCS P□□□NS	APCS P□□□KS	
			S8160	L7SA020A						
			S8220	L7SA020A						
			SF220	L7SA020A		APCS P□□□IS	APCS P□□□PB	APCS P□□□PB	APCS P□□□KS	
			LF350	L7SA035A						
			SF550	L7SA050A						
1,500	3,000	□180	SG220	L7SA020A	APCS E□□□BS	APCS P□□□AS	APCS P□□□GS	APCS P□□□KS		
			SG350	L7SA035A						
			SG550	L7SA050A						
			SE05G	L7SA008A						
			SE09G	L7SA010A						
			SE13G	L7SA020A						
			SE17G	L7SA020A						
			SF20G	L7SA035A		APCS P□□□IS	APCS P□□□PB	APCS P□□□PB	APCS P□□□KS	
			LF30G	L7SA035A						
			SF44G	L7SA050A						
			SG20G	L7SA020A	APCS P□□□JS	APCS P□□□US	APCS P□□□US	APCS P□□□KS		
			LG30G	L7SA035A						
			SG44G	L7SA050A						
1,000	2,000	□180	SE03M	L7SA004A	APCS E□□□BS	APCS P□□□AS	APCS P□□□GS	APCS P□□□KS		
			SE06M	L7SA008A						
			SE09M	L7SA010A						
			SE12M	L7SA020A						
			SF12M	L7SA020A		APCS P□□□IS	APCS P□□□PB	APCS P□□□PB	APCS P□□□KS	
			SF20M	L7SA035A						
			LF30M	L7SA035A						
			SF44M	L7SA050A	APCS P□□□JS	APCS P□□□US	APCS P□□□US	APCS P□□□KS		
			SG12M	L7SA020A						
			SG20M	L7SA035A						
			LG30M	L7SA035A	APCS P□□□JS	APCS P□□□US	APCS P□□□US	APCS P□□□KS		
			SG44M	L7SA050A						
			H801A	L7SA002A						
3,000	3,600	□180	H802A	L7SA002A	1,024 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□KS		
			H804A	L7SA004A						
			H809A	L7SA008A		APCS E□□□BS	APCS P□□□HS	APCS P□□□HS		
			H815A	L7SA020A						
			H820A	L7SA050A						

# L7 SERIES SYSTEM

## L7S Drive Combination Table

### L7SA Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable			
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake
3,000	5,000	□40	□40	FALPSA	L7SA0016	18bit Serial / M. Turn Abs	APCS E□□□ES	APCS E□□□ES1	APCS P□□□LS	APCS P□□□QS	
			□40	FAL01A	L7SA0016						
			□40	FAL05A	L7SA0028						
			□60	FBL01A	L7SA0016						
			□60	FBL02A	L7SA0028						
			□60	FBL04A	L7SA0048						
			□60	FCL04A	L7SA0048						
			□60	FCL06A	L7SA0088						
			□60	FCL08A	L7SA0088						
			□60	FCL10A	L7SA0108						
			□60	FB01A	L7SA0016						
			□60	FB02A	L7SA0028						
			□60	FB04A	L7SA0048						
			□60	FC04A	L7SA0048						
			□60	FC06A	L7SA0088						
			□60	FC08A	L7SA0088						
			□60	FG10A	L7SA0108						
			□100	FE09A	L7SA0108	APCS E□□□OS	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NS	APCS P□□□QS	
			□100	FE15A	L7SA0208						
			□100	FE22A	L7SA0208						
			□100	FE30A	L7SA0358						
			□100	FF30A	L7SA0358						
			□100	FF50A	L7SA0508						
			□60	FC03D	L7SA0048						
			□60	FC05D	L7SA0088						
			□60	FC06D	L7SA0088						
			□60	FC07D	L7SA0088						
2,000	3,000	□60	□60	FC03D	L7SA0048						
			□60	FO05D	L7SA0088						
			□60	FO06D	L7SA0088						
			□60	FO07D	L7SA0088						
			□100	FE06D	L7SA0088						
			□100	FE11D	L7SA0108						
			□100	FE16D	L7SA0208						
			□100	FE22D	L7SA0208						
			□100	FF22D	L7SA0208						
			□100	FF30D	L7SA0358						
1,500	3,000	□60	□100	FE05G	L7SA0088	18bit Serial / M. Turn Abs	APCS E□□□OS	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NS	APCS P□□□QS
			□100	FE09G	L7SA0108						
			□100	FE33G	L7SA0208						
			□100	FE17G	L7SA0208						
			□100	FF20G	L7SA0208						
			2,700	FF30G	L7SA0358						
			3,000	FF44G	L7SA0608						
			3,000	FG20G	L7SA0208						
			2,700	FG30G	L7SA0358						
			3,000	FG44G	L7SA0608						
1,000	2,000	□60	□100	FE03M	L7SA0048	18bit Serial / M. Turn Abs	APCS E□□□OS	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NS	APCS P□□□QS
			□100	FE06M	L7SA0088						
			□100	FE09M	L7SA0108						
			□100	FE12M	L7SA0208						
			□100	FE13M	L7SA0208						
			□100	FF20M	L7SA0208						
			1,700	FF30M	L7SA0358						
			1,700	FF44M	L7SA0508						
			2,000	FG12M	L7SA0208						
			2,000	FG20M	L7SA0208						
			1,700	FG30M	L7SA0358						
			2,000	FG44M	L7SA0508						

## L7S Drive Combination Table

### L7SB Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable			
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake
3,000	5,000	□130	FEP09A	L7SB0108	19Bit Serial / M.Turn Abs	APCS E□□□0S	APCF P□□□HS	APCF P□□□NB	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FEP16A	L7SB0208							
			FEP22A	L7SB0308							
			FEP30A	L7SB0308							
			FPP30A	L7SB0308							
			FPP50A	L7SB0508							
2,000	3,000	□130	FEP06D	L7SB0108	19Bit Serial / M.Turn Abs	APCS E□□□0S	APCF P□□□HS	APCF P□□□NB	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FEP10D	L7SB0108							
			FEP16D	L7SB0208							
			FEP22D	L7SB0208							
			FPP22D	L7SB0208							
			FPP30D	L7SB0308							
	2,500	□180	FPP50D	L7SB0508			APCF P□□□JS	APCF P□□□MS	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FPP75D	L7SB0758							
			FGP22D	L7SB0208							
			FGP35D	L7SB0308							
			FGP50D	L7SB0508							
			FGP75D	L7SB0758							
1,500	3,000	□130	FEP05G	L7SB0108	19Bit Serial / M.Turn Abs	APCS E□□□0S	APCF P□□□HS	APCF P□□□NB	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FEP09G	L7SB0108							
			FEP13G	L7SB0208							
			FEP17G	L7SB0208							
			FPP20G	L7SB0208							
			FPP30G	L7SB0308							
	2,500	□180	FPP44G	L7SB0508			APCF P□□□JS	APCF P□□□MS	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FPP60G	L7SB0758							
			FPP75G	L7SB0758							
			FGP20G	L7SB0208							
			FGP30G	L7SB0308							
			FGP44G	L7SB0508							
1,000	2,000	□130	FGP60G	L7SB0758	19Bit Serial / M.Turn Abs	APCS E□□□0S	APCF P□□□HS	APCF P□□□NB	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FGP75G	L7SB0758							
			FPP12M	L7SB0208							
			FPP20M	L7SB0208							
			FPP30M	L7SB0308							
			FPP44M	L7SB0508							
	2,000	□180	FPP60M	L7SB0758			APCF P□□□JS	APCF P□□□MS	APCF P□□□S	APCF P□□□PB	APCF P□□□JS
			FPP75M	L7SB0758							
			FPP44M	L7SB0508							
			FPP60M	L7SB0758							

L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

# L7 SERIES SYSTEM

## L7SA Drive Product Features

Item	Type Name	L7SA001□	L7SA002□	L7SA004□	L7SA008□	L7SA010□	L7SA020□	L7SA035□	L7SA050□
Input Power	Main Power Supply	3 Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Control Power Supply	Single Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Rated Current[A]	1.4	1.7	3.0	5.2	6.75	13.5	16.7	32
	Peak Current[A]	4.2	5.1	9.0	15.6	20.25	40.5	50.1	96
	Encoder Type	Quad. Type Incremental Line Driver Max 6000 [P/R] Serial Type : 18bit(FA type), 19bit, 20bit(MDM series)							
Control Performance	Speed Control	Speed Control Range	Maximum 1: 5000						
		Frequency Response	Maximum 1 [kHz] or above (When using 19bit Serial Encoder)						
		Speed Command	DC -10 [V]~+10 [V] (Reverse rotation in case of negative voltage)						
		Accel/Decel Time	Straight or S-curve acceleration/deceleration (0~10,000 [ms], possible to be set by one [ms] unit)						
		Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ± 10°C]						
Position/Torque Control	Position Control	Input Frequency	1[Mpps], Line Driver / 200[kpps], Open Collector						
		Input Pulse Type	Symbol + Pulse Series, CW+CCW, A/B Phase						
	Torque Control	Electric Gear Ratio	Four digital gear ratios can be set, selected and tuned.						
		Torque Command	DC -10~+10 [V] (Reverse direction torque in case of negative voltage)						
		Speed Limit	DC 0~10 [V], internal speed command within ±1[%]						
		Repetition accuracy	Within ±1[%]						
Input/Output Signal	Analog Input	Input Range	DC -10 ~ 10[V]						
		Resolution	12[bit]						
	Analog Output	Output Range	DC -10 ~ 10[V]						
		Resolution	12[bit]						
	Digital Input	Total 10 Input Channels(assignment available) SVON, SPD1, SPD2, SPD3, ALMRST, DIR, CCWLIM, CWLIM, EMG, STOP, EGEAR1, EGEAR2, PCON, GAIN2, P_CLR, T_LMT, MODE, ABS_RQ, ZCLAMP Above 19 functions can be used selectively for assignment Signal can be set as positive logic or negative logic							
	Digital Output	Total 5 Channels(assignment available), 3 Channels(set as alarm code) ALARM, READY, ZSPD, BRAKE, INPOS, TLMT, VLMT, INSPD, WARN Above 9 outputs can be used selectively for assignment Signal can be set as positive logic or negative logic							
Communication	RS422	Accessible to PC software and the RS422 server							
	USB	Status monitoring, JOG operation, parameter upload/download are available with PC Software							
Built-in Functions	Encoder	Serial BiSS encoder and quadrature encoder supported							
	Encoder Output Type	Random pre-scale output through FPGA (maximum 6.4 Mpps)							
	Dynamic Braking	Standard built-in (activated when the servo alarm goes off or when the servo is off)							
	Regenerative Braking	Both default built-in and external installation possible							
	Display	Seven segments (5 DIGIT)							
	Setting Function	Loader (SET, MODE, UP, and [DOWN] keys)							
	Additional Function	Auto gain tuning, phase Z detection, manual JOG operation, program JOG operation, automatic analog input calibration							
Environment	Protective Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheating(power module overheating, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem							
	Temperature	0 ~ 50[°C]							
	Humidity	Below 90[%]RH(avoid dew-condensation)							
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.							

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

## L7SB Drive Product Features


Item	Type Name	L7SB010□	L7SB020□	L7SB035□	L7SB050□	L7SB075□	L7SB150□
Input Power	Main Power Supply	3 Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Control Power Supply	Single Phase AC380 ~ 480[V](-15 ~ +10[%]), 50 ~ 60[Hz]					
	Rated Current[A]	3.7	8	10.1	17.5	22.8	39
	Peak Current[A]	11.1	24	30.3	52.5	57	97.5
	Encoder Type	Quad. Type Incremental Line Driver Max 6000 [P/R] Serial Type : 18bit(FA type), 19bit, 20bit(MDM series)					
Control Performance	Speed Control	Speed Control Range	Maximum 1: 5000				
		Frequency Response	Maximum 1 [kHz] or above (when the 19-bit serial encoder is applied)				
		Speed Command	DC -10 [V]~+10 [V] (Reverse rotation in case of negative voltage)				
		Accel/Decel Time	Straight or S-curve acceleration/deceleration (0~10,000 [ms], possible to be set by one [ms] unit)				
		Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ±10°C]				
	Position Control	Input Frequency	1[Mpps], Line Driver / 200[kpps], Open Collector				
		Input Pulse Type	Symbol + pulse series, CW+CCW, A/B phase				
	Torque Control	Electric Gear Ratio	Four digital gear ratios can be set, selected and tuned.				
		Torque Command	DC -10~+10 [V] (Reverse direction torque in case of negative voltage)				
		Speed Limit	DC 0~10 [V], internal speed command within ±1[%]				
Input/Output Signal	Analog Input	Input Range	DC 0 ~ 10[V]				
		Resolution	12[bit]				
	Analog Output	Output Range	DC 0 ~ 10[V]				
		Resolution	12[bit]				
	Digital Input	A total of 10 input channels (allocable) SVON, SPD1, SPD2, SPD3, ALMRST, DIR, CCWLIM, CWLIM, EMG, STOP, EGEAR1, EGEAR2, PCON, GAIN2, P_CLR, T_LMT, MODE, ABS_RQ, ZCLAMP You can selectively allocate a total of 19 functions. You can set the positive/negative logic of the selected signal.					
	Digital Output	A total of 5 channels (allocable), 3 channels (fixed with alarm codes) ALARM, READY, ZSPD, BRAKE, INPOS, TLMT, VLMT, INSPD, WARN You can selectively allocate a total of nine kinds of output. You can set the positive/negative logic of the selected signal.					
Communication	RS422	Accessible to PC software and the RS422 server					
	USB	Status monitoring through PC software, JOG operation, and parameter uploading/downloading are possible.					
	Encoder	Serial BISS encoder and quadrature encoder supported					
	Encoder Output Type	Random pre-scale output through FPGA (maximum 6.4 Mpps)					
Built-in functions	Dynamic Braking	Standard built-in (activated when the servo alarm goes off or when the servo is off)					
	Regenerative Braking	Both default built-in and external installation possible					
	Display	Seven segments (5 DIGIT)					
	Setting Function	Loader (SET, MODE, UP, and [DOWN] keys)					
	Additional Function	Auto gain tuning, phase Z detection, manual JOG operation, program JOG operation, automatic analog input calibration					
	Protective Function	Overcurrent, overload, overvoltage, voltage lack, main power input error, control power input error, overspeed, motor cable, heating error (power module heating, drive temperature error), encoder error, excessive regeneration, sensor error, communication error					
	Temperature	0 ~ 50[°C]					
Environment	Humidity	90[%] RH or lower (no condensation)					
	Environment	Indoors, a place free from corrosive gas or combustible gas, or a place without liquid or conductive dust.					

# L7 SERIES SYSTEM

## External Dimensions of L7SA Drive


■ L7SA001□ ~ L7SA004□ [Weight : 1.2kg]

\* Unit [mm]



■ L7SA008□ ~ L7SA010□ [Weight : 1.5kg(Fan-Cooling included)]


\* Unit [mm]



## External Dimensions of L7SA Drive


■ L7SA020□ ~ L7SA035□ [Weight : 2.5kg(Fan-Cooling included)]

\*Unit [mm]



■ L7SA050□ [Weight : 5.5kg(Fan-Cooling included)]

\*Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

F Series

MDM Series

Options


PEGASUS Series

# L7 SERIES SYSTEM

## External Dimensions of L7SB Drive


- L7SB010□ [Weight : 1.5kg(Fan-Cooling included)]

\* Unit [mm]



- L7SB020□ / L7SB035□ [Weight : 2.5kg(Fan-Cooling included)]


\* Unit [mm]



## External Dimensions of L7SB Drive


■ L7SB050□ [Weight : 5.5kg(Fan-Cooling included)]

\*Unit [mm]



■ L7SB075□ [Weight : 8.5kg(Fan-Cooling included)]

\*Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options


PEGASUS Series

# L7 SERIES SYSTEM

## External Dimensions of L7SB Drive

■ L7SB150□ [Weight : 15.5kg(Fan-Cooling included)]

\* Unit [mm]



L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

## EtherCAT Communication Command Type

# L7N Series



## Servo Drive Designation

L7	N	A	004	B	AA
Model Name	Communication	Input Power Supply	Capacity	Encoder Type	Option
Servo Series	Network Type	A : 200VAC	001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1,0kW 020 : 2,0kW 035 : 3,5kW 050 : 5,0kW	B : Serial (Communication Type)	Exclusive Option Code

L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

# L7 SERIES SYSTEM

## L7N Series

### Characteristic

#### • Real-time control by EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- 100BASE-TX(100Mbps) EtherNET based real-time communication


#### • Support Various Operation Mode

- Cyclic(P/S/T) Mode and Profile (P/S/T)Mode, Homming Mode

#### • High Response for Precision Control

- High Resolutions Serial type Encoder(19Bit, BiSS)
- Improved Speed Response(=1Khz) Frequency

### Identifying the Part of L7N Drive



- ① Operation keys (Mode, Up, Down, Set)
- ② Charge lamp
- ③ Main power connector (L1, L2, L3)
- ④ DC reactor connector(PO, PI)
  - Short circuit when not used
- ⑤ Regenerative Resistor Connector (B+, B, BI)
  - Short-Circuit B, BI terminals when standard type
  - Use B+, B terminals when using external resistor
- ⑥ Control Power Connector (C1, C2)
- ⑦ Front cover
- ⑧ Servo Motor Connecting Terminals (U, V, W)
- ⑨ Heat Sink
- ⑩ Display
- ⑪ Status LED
- ⑫ CN5:USB connector
- ⑬ CN4:EtherCAT Communication Port (IN)
- ⑭ CN3:EtherCAT Communication Port (OUT)
- ⑮ CN6 : STO Connector
- ⑯ CN1 : Control Signal Connector
- ⑰ CN2 : Encoder Signal Connector
- ⑱ Ground

## L7N Drive Combination Table

### L7N Serial Type

Rated Speed (rpm)	Maximum speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder Cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	1981 Serial / M Turn Abs	□40	FALRSA	L7NA0018	APCS E□□□ES	APCS P□□□LS	APCS P□□□QS	APCS P□□□NS	APCS P□□□NB
			□40	FAL01A	L7NA0018					
			□40	FAL016A	L7NA0028					
			□60	FBL01A	L7NA0018					
			□60	FBL02A	L7NA0028					
			□60	FBL04A	L7NA0048					
			□80	FCL01A	L7NA0048					
			□80	FCL06A	L7NA0088					
			□80	FCL08A	L7NA0088					
			□80	FCL10A	L7NA0108					
			□60	FB01A	L7NA0018	APCS E□□□FS	APCS P□□□FS	APCS P□□□QS	APCS P□□□NS	APCS P□□□NB
			□60	FB02A	L7NA0028					
			□60	FB04A	L7NA0048					
			□80	FC04A	L7NA0048					
			□80	FO06A	L7NA0088					
			□80	FC08A	L7NA0088					
			□80	FC10A	L7NA0108					
			□100	FE09A	L7NA0108					
			□100	FE05A	L7NA0208					
			□100	FE22A	L7NA0208					
2,000	3,000	1981 Serial / M Turn Abs	□80	FE30A	L7NA0358	APCS E□□□OS	APCS E□□□ES1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS
			□80	FF30A	L7NA0358					
			□80	FF50A	L7NA0508					
			□80	FCL03D	L7NA0048					
			□80	FCL05D	L7NA0088					
			□80	FCL06D	L7NA0088					
			□80	FCL07D	L7NA0088					
			□80	FO03D	L7NA0048					
			□80	FO05D	L7NA0088					
			□80	FO06D	L7NA0088	APCS E□□□FS	APCS E□□□ES1	APCS P□□□FS	APCS P□□□NB	APCS P□□□QS
			□80	FO07D	L7NA0088					
			□100	FE05D	L7NA0088					
			□100	FE10D	L7NA0108					
			□100	FE16D	L7NA0208					
			□100	FE22D	L7NA0208					
			□100	FF22D	L7NA0208					
			□100	FF35D	L7NA0358					
1,500	3,000	1981 Serial / M Turn Abs	□100	FF55D	L7NA0508	APCS E□□□OS	APCS E□□□ES1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS
			□220	FG22D	L7NA0208					
			□220	FG35D	L7NA0358					
			□220	FG55D	L7NA0508					
			□100	FE05G	L7NA0088					
			□100	FE09G	L7NA0108					
			□100	FE13G	L7NA0308					
			□100	FE17G	L7NA0208					
			□100	FF20G	L7NA0308					
			□100	FF30G	L7NA0358					
1,000	2,000	1981 Serial / M Turn Abs	□100	FF44G	L7NA0508	APCS E□□□OS	APCS E□□□ES1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS
			□220	FG20M	L7NA0208					
			□220	FG30M	L7NA0358					
			□220	FG44M	L7NA0508					
			□100	FE03M	L7NA0048					
			□100	FE09M	L7NA0088					
			□100	FE09M	L7NA0108					
			□100	FE10M	L7NA0208					
			□100	FF12M	L7NA0208					
			□100	FF20M	L7NA0308					
1,700	2,000	1981 Serial / M Turn Abs	□100	FF30M	L7NA0358	APCS E□□□OS	APCS E□□□ES1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS
			□100	FF44M	L7NA0508					
			□220	FG20M	L7NA0208					
			□220	FG30M	L7NA0358					
			□220	FG44M	L7NA0508					

# L7 SERIES SYSTEM

## L7N Drive Product Features

Item	Type Name	L7NA001B	L7NA002B	L7NA004B	L7NA008B	L7NA010B	L7NA020B	L7NA035B	L7NA050B
Input Power	Main Power Supply	3 Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
	Control Power Supply	Single Phase AC200 ~ 230[V](-15 ~ +10[%]), 50 ~ 60[Hz]							
Rated Current[A]		1.4	1.7	3.0	5.2	6.75	13.5	16.7	32
Peak Current[A]		4.2	5.1	9.0	15.6	20.25	40.5	50.1	96
Encoder Type		Serial Type : 18 bit(FA type), 19bit, 20bit(MDM series)							
Control Performance	Speed Control Range	Maximum 1: 5000							
	Frequency Response	Maximum 1 kHz or more (when the 19-bit serial encoder is applied)							
	Speed Variation Ratio	$\pm 0.01[\%]$ or lower(When the load changes between 0 and 100%) $\pm 0.1[\%]$ or less(Temperature of 25°C [ $\pm 10$ ])							
	Torque Control Repetition Accuracy	Within $\pm 1\%$							
Supported Drive Modes (CiA402)		Profile Position Mode Profile Velocity Mode Profile Torque Mode Interpolated Position Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode							
Digital Input/Output	Digital Input	Total 6 input channels (allocable) PCON, GAIN2, ALMRST, HOME, P-OT, N-OT Above 6 functions can be used selectively for assignment. Signal can be set as positive logic or negative logic.							
	Touch Probe Input	There are 2 input channels. Provides rising and falling edge detection functions for each channel.							
	Digital Output	Total 4 channels (allocable) ALARM, READY, ZSPD, BRAKE, INPOS, INSPD, WARN Above 7 outputs can be used selectively for assignment. Signal can be set as positive logic or negative logic.							
Additional Communication	USB	Program download is available with USB Communication.							
Built-in Functions	Dynamic Braking	Built-in type(operates when Servo alarm or Servo off)							
	Regenerative Braking	Built-in type, and also external connection is available							
	Display	7 segments(5DIGIT)							
	Setting Function	Loder(SET), (MODE)							
	Additional Function	Auto gain tuning function							
	Protective Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheating(power module overheating, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem							
Operation Environment	Temperature	0 ~ 50[°C]							
	Humidity	Below 90[%]RH(avoid dew-condensation)							
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.							

L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series


Options

PEGASUS Series

## External Dimensions of L7SN Drive


### L7NA001B ~ L7NA004B [Weight : 1.0kg]

\*Unit [mm]



### L7NA008B / L7NA010B [Weight : 1.5kg(Fan-Cooling included)]

\*Unit [mm]




# L7 SERIES SYSTEM

## External Dimensions of L7SN Drive


■ L7NA020B / L7NA035B [Weight : 2.5kg(Fan-Cooling included)]

\* Unit [mm]



■ L7NA050B [Weight : 5.5kg(Fan-Cooling included)]

\* Unit [mm]



All-in-one EtherCAT Communication Command Type

# L7NH Series



## Servo Drive Designation

L7	NH	A	004	B	AA
Model Name	Communication	Input Power Supply	Capacity	Encoder Type	Option
Servo Series	Network / All-in-One Type	A : 200VAC B : 400VAC	001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1,0kW 020 : 2,0kW 035 : 3,5kW 050 : 5,0kW 075 : 7,5kW 110 : 11kW 150 : 15kW	U : Universal	Exclusive Option Code
<b>* Range</b> · 200V : 0,1kW~3,5kW · 400V : 1,0kW~15kW					

# L7 SERIES SYSTEM

## L7NH Series

### Characteristic

#### Real-time control through EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- Improved EtherCAT communication speed(min. 250us, DC support)
- Supporting CoE, EoE and FoE
- Improved Speed Response(=1.6Khz) Frequency

#### Improved Control Performance


- Improved Control bandwidth
- Providing 4-step Notch-Filter
- Vibration control by Real-time FFT
- Real-time gain tuning function

#### Support various motor and Encoder drive

- Supporting Rotary, DD and Motor drive (supporting 3rd party motor)
- Quadrature, BiSS-C, Tamagawa serial abs, EnDat 2.2, Resolver

### Identifying the Part of L7NH Drive

[L7NH]



- Display
- State LED
- Charge Lamp
- Main Power Connector (L1, L2, L3)
- DC Reactor Connector (PO, PI)
- Regenerative Resistance Connector (B+, B, BI)
  - Short-Circuit B, BI terminals when standard type
  - Use B+, B terminals when using external resistor
- Control Power Connector (C1, C2)
- Servo Motor Connecting Terminal (U,V,W)
- Connector for Analog Monitor
- Node Address Setting Switch
- USB Connector
- EtherCAT Communication Port (IN)
- EtherCAT Communication Port (OUT)
- Safety Connector (STO)
- Input / Output signal /Connector
- Encoder Connector (ENCODER)
- Ground Terminal

## L7NHA Drive Combination Table

### L7NHA Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable		
					Quadrature Type		INC	For power	Power+Brake
3000	5,000	□40	SAP3A	L7NHA001U	2,048 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□KB	
			SAP5A	L7NHA001U					
			SA01A	L7NHA001U					
			SA015A	L7NHA003U					
		□60	SE01A	L7NHA003U	3,000 P/R	APCS E□□□BS	APCS P□□□HS	APCS P□□□NS	
			SE02A	L7NHA003U					
			SE04A	L7NHA004U					
			SC04A	L7NHA004U					
		□80	SC06A	L7NHA008U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			SC08A	L7NHA008U					
			SC10A	L7NHA010U					
			SE09A	L7NHA008U					
		□130	SE15A	L7NHA020U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			SE22A	L7NHA020U					
			SE30A	L7NHA035U					
			SC03D	L7NHA0104U					
2,000	3,000	□80	SC05D	L7NHA008U	APCS E□□□AS	APCS P□□□GS	APCS P□□□QS		
			SC08D	L7NHA008U					
			SC07D	L7NHA008U					
			SE06D	L7NHA008U					
		□100	SE10D	L7NHA010U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			SE16D	L7NHA020U					
			SE22D	L7NHA020U					
			SE22D	L7NHA035U					
		□180	SG22D	L7NHA020U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			LG35D	L7NHA035U					
			SE05G	L7NHA008U					
			SE09G	L7NHA010U					
1,500	3,000	□100	SE10G	L7NHA020U	APCS E□□□BS	APCS P□□□GS	APCS P□□□QS		
			SE17G	L7NHA020U					
			SF20G	L7NHA035U					
			LF30G	L7NHA035U					
		□220	SG20G	L7NHA020U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			LG30G	L7NHA035U					
		□180	SE03M	L7NHA0104U	APCS E□□□BS	APCS P□□□GS	APCS P□□□QS		
			SE08M	L7NHA008U					
			SE09M	L7NHA010U					
			SE12M	L7NHA020U					
1,000	2,000	□100	SP04M	L7NHA020U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			SP20M	L7NHA035U					
			LF30M	L7NHA035U					
			SG20M	L7NHA035U					
		□220	SG20M	L7NHA035U	APCS P□□□HS	APCS P□□□NS	APCS P□□□PB		
			LG30M	L7NHA035U					
		□180	HE01A	L7NHA003U	APCS E□□□AS	APCS P□□□GS	APCS P□□□QS		
			HE02A	L7NHA002U					
			HE04A	L7NHA004U					
			HE09A	L7NHA008U					
3,000	3,500	□180	HE15A	L7NHA020U	2,048 P/R	APCS E□□□BS	APCS P□□□HS	APCS P□□□QS	

# L7 SERIES SYSTEM

## L7NHA Drive Combination Table

### L7NHA Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	□40	FAL05A	L7NHA001U	10bit Serial / M. Turn Abs	APCS E□□□□S	APCS E□□□□S1	APCS P□□□LS	APCS P□□□QS	APCS P□□□QS
			FAL01A	L7NHA001U						
			FAL05A	L7NHA002U						
			FBL01A	L7NHA001U						
			FBL02A	L7NHA002U						
			FBL04A	L7NHA004U						
			FCL04A	L7NHA004U						
			FCL05A	L7NHA008U						
			FCL08A	L7NHA008U						
			FCL10A	L7NHA010U						
			FB01A	L7NHA001U						
			FB02A	L7NHA002U						
			FB04A	L7NHA004U						
			FC04A	L7NHA004U						
			FC06A	L7NHA008U						
			FC08A	L7NHA008U						
			FC10A	L7NHA010U						
			FE09A	L7NHA010U						
			FE15A	L7NHA020U						
			FE22A	L7NHA020U						
			FE30A	L7NHA035U						
			FF30A	L7NHA035U						
2,000	3,000	□80	FCL03D	L7NHA004U	10bit Serial / M. Turn Abs	APCS E□□□□S	APCS E□□□□S1	APCS P□□□LS	APCS P□□□QS	APCS P□□□QS
			FCL05D	L7NHA008U						
			FCL06D	L7NHA008U						
			FCL07D	L7NHA008U						
			FO03D	L7NHA004U						
			FO05D	L7NHA008U						
			FO06D	L7NHA008U						
			FO07D	L7NHA008U						
			FE06D	L7NHA008U						
			FE11D	L7NHA010U						
			FE16D	L7NHA020U						
			FE22D	L7NHA020U						
1,500	3,000	□130	FE05G	L7NHA008U	APCS E□□□□S	APCS E□□□□S1	APCS P□□□LS	APCS P□□□QS	APCS P□□□QS	APCS P□□□QS
			FE09G	L7NHA010U						
			FE13G	L7NHA020U						
			FE17G	L7NHA020U						
			FF20G	L7NHA020U						
			FF30G	L7NHA035U						
			FG20G	L7NHA020U						
			FG30G	L7NHA035U						
			FE06M	L7NHA004U						
			FE09M	L7NHA008U						
1,000	2,000	□130	FE09M	L7NHA010U	APCS E□□□□S	APCS E□□□□S1	APCS P□□□LS	APCS P□□□QS	APCS P□□□QS	APCS P□□□QS
			FE12M	L7NHA020U						
			FF13M	L7NHA030U						
			FF20M	L7NHA020U						
			FF30M	L7NHA035U						
			FG12M	L7NHA020U						
			FG20M	L7NHA020U						
			FG30M	L7NHA035U						

## L7NHB Drive Combination Table

### L7NHB Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable			
							Quadrature Type	INC	For power	Power + Brake
3,000	5,000	□130	SEP09A	L7NH8010U			APCF P□□□HS	APCF P□□□NB		
		□130	SEP15A	L7NH8010U						
		□130	SEP22A	L7NH8020U						
		□130	SEP30A	L7NH8030U						
		□180	SPP30A	L7NH8030U						
		□180	SPP50A	L7NH8050U						
2,000	3,000	□130	SEP06D	L7NH8010U			APCF P□□□HS	APCF P□□□NB		
		□130	SEP10D	L7NH8010U						
		□130	SEP16D	L7NH8020U						
		□130	SEP22D	L7NH8020U						
		□180	SFP22D	L7NH8020U						
		□180	SFP30D	L7NH8030U						
		□180	SFP50D	L7NH8050U						
		□220	SGP22D	L7NH8020U			APCF P□□□HS	APCF P□□□NB		
		□220	SGP30D	L7NH8030U						
		□220	SGP50D	L7NH8050U						
		□220	SGP75D	L7NH8075U						
1,500	3,000	□130	SEP05G	L7NH8010U			APCF P□□□HS	APCF P□□□NB		
		□130	SEP09G	L7NH8010U						
		□130	SEP13G	L7NH8020U						
		□130	SEP17G	L7NH8020U						
		□180	SPP20G	L7NH8020U						
		□180	SPP30G	L7NH8050U						
		□180	SPP44G	L7NH8050U						
		□180	SPP60G	L7NH8075U						
	2,500	□180	SFP75G	L7NH8075U			APCF P□□□HS	APCF P□□□NB		
		□220	SGP20G	L7NH8020U						
		□220	SGP30G	L7NH8050U						
		□220	SGP44G	L7NH8050U						
1,000	3,000	□220	SGP60G	L7NH8075U			APCF P□□□HS	APCF P□□□NB		
		□220	SGP80G	L7NH8150U						
		□220	SGP10G	L7NH8150U						
		□220	SGP15G	L7NH8150U						
		□130	SEP03M	L7NH8010U						
		□130	SEP06M	L7NH8010U						
	2,000	□130	SEP09M	L7NH8010U			APCF P□□□HS	APCF P□□□NB		
		□130	SEP12M	L7NH8020U						
		□180	SPP20M	L7NH8020U						
		□180	SPP20M	L7NH8020U						
1,000	1,700	□180	SFP30M	L7NH8030U			APCF P□□□HS	APCF P□□□NB		
		□180	SFP44M	L7NH8050U						
		□220	SGP20M	L7NH8020U						
		□220	SGP30M	L7NH8050U						
	2,000	□220	SGP44M	L7NH8050U			APCF P□□□HS	APCF P□□□NB		
		□220	SGP60M	L7NH8075U						
		□220	SGP80M	L7NH8050U						
		□220	SGP10M	L7NH8050U						
		□220	SGP15M	L7NH8075U						
		□220	SGP20M	L7NH8075U						

# L7 SERIES SYSTEM

## L7NHB Drive Combination Table

### L7NHB Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable			
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake	Brake
3,000	5,000		□130	FEP09A	L7NH8010U				APCF P□□□HS	APCF P□□□NS	
			□130	FEP15A	L7NH8020U				APCF P□□□HS	APCF P□□□PS	
			□130	FEP22A	L7NH8035U				APCF P□□□HS	APCF P□□□LS	
			□130	FEP30A	L7NH8035U				APCF P□□□HS	APCF P□□□NS	
			□160	FPP30A	L7NH8035U				APCF P□□□HS	APCF P□□□PS	
			□160	FPP50A	L7NH8050U				APCF P□□□HS	APCF P□□□LS	
2,000	3,000		□130	FEP060	L7NH8010U	18bit Serial / M. Turn Abs	APCS E□□□D6	APCS E□□□D6I	APCF P□□□HS	APCF P□□□NS	APCF P□□□S8
			□130	FEP110	L7NH8010U						
			□130	FEP160	L7NH8020U						
			□130	FEP220	L7NH8020U						
			□160	FPP220	L7NH8020U						
			□160	FPP350	L7NH8035U						
			□160	FPP550	L7NH8050U						
	2,500		□160	FPP750	L7NH8075U						
	3,000		□220	FGP220	L7NH8020U						
1,500	3,000		□130	FGP350	L7NH8035U						APCF P□□□S8
			□130	FGP550	L7NH8050U						
			□220	FGP750	L7NH8075U						
			□220	FGP1100	L7NH8150U						
			□130	FEP05G	L7NH8010U						
			□130	FEP08G	L7NH8010U						
			□130	FEP10G	L7NH8020U						
	2,500		□130	FEP17G	L7NH8020U						
			□160	FPP20G	L7NH8020U						
			□160	FPP30G	L7NH8050U						
			□160	FPP44G	L7NH8050U						
			□160	FPP60G	L7NH8075U						
			□160	FPP75G	L7NH8075U						
			□220	FGP20G	L7NH8020U						
1,000	2,000		□220	FGP30G	L7NH8035U						APCF P□□□S8
			□220	FGP44G	L7NH8050U						
			□220	FGP60G	L7NH8075U						
			□220	FGP85G	L7NH8150U						
			□220	FGP110G	L7NH8150U						
			□220	FGP160G	L7NH8150U						
	1,700		□130	FEP03M	L7NH8010U						APCF P□□□S8
			□130	FEP06M	L7NH8010U						
			□130	FEP09M	L7NH8010U						
			□130	FEP10M	L7NH8020U						
800	2,000		□160	FPP12M	L7NH8020U						APCF P□□□S8
			□160	FPP20M	L7NH8020U						
			□160	FPP30M	L7NH8035U						
			□160	FPP44M	L7NH8050U						
			□160	FPP60M	L7NH8075U						
	2,000		□220	FGP12M	L7NH8020U						APCF P□□□S8
			□220	FGP20M	L7NH8020U						
			□220	FGP30M	L7NH8050U						
			□220	FGP44M	L7NH8050U						
			□220	FGP60M	L7NH8075U						

## L7NHA Drive Product Features

Item	Type Name	L7NHA001U	L7NHA002U	L7NHA004U	L7NHA008U	L7NHA010U	L7NHA020U	L7NHA035U
Input Power	Main Power Supply	3-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]						
	Control Power Supply	Single-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]						
Rated Current[A]		1.4	1.7	3.0	5.2	6.75	13.5	16.7
Peak Current[A]		4.2	5.1	9.0	15.6	20.25	40.5	50.1
Encoder Type		Quadrature (Incremental) BiSS-B, BiSS-C(Absolute, Incremental) Tamagawa Serial (Absolute, Incremental) EnDat 2.2						
Control Performance	Speed Control Range	Maximum 1: 5000						
	Frequency Response	Maximum 1[kHz] or above(When the 19-bit Serial Encoder is applied)						
	Speed Variation Ratio	±0.01[%] or lower(When the load changes between 0 and 100%) ±0.1[%] or less(Temperature of 25°C[±10])						
	Torque Control Repetition Accuracy	Within ±1%						
EtherCAT Communication Specifications	Communication Standard	FoE (Firmware download) EcE (Parameter setting by UDP, Tuning, Secondary function, Parameter copy) CoE (IEC 61158 Type12, IEC 61800-7 CIA 402 Drive profile)						
	Physical Layer	100BASE-TX(IEEE802.3)						
	Connector	RJ45 x 2						
	Communication distance	Within connection between nodes 100[m]						
	DC (Distributed Clock)	By DC mode synchronism, minimum DC cycle: 250[us]						
	LED Display	LinkAct IN, LinkAct OUT, RUN, ERR						
	Cia402 Drive Profile	Profile Position Mode Profile Velocity Mode Profile Torque Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode						
Digital Input/Output	Digital Input	Input Voltage range : DC 12[V] ~ DC 24[V] Total 8 input channels (allocable) Above 12 functions can be used selectively for assignment, (*POT, *NOT, *HOME, *STOP, *PCON, *GAIN2, *P_CL, *N_CL, PROBE1, PROBE2, EMG, A_RST) *Basic allocation signal						
	Digital Output	Service rating: DC 24[V] ±10%, 120[mA] Total 4 input channels (allocable) Above 11 functions can be used selectively for assignment. (*BRAKE±, *ALARM±, *READY±, *ZSPD±, INPOS±, TLMT±, VLMT±, INSPD±, WARN±, TGON±, INPOS2±) *Basic allocation signal						
	Analog Monitor	There are 2 input channels. Above 15 functions can be used selectively for assignment.						
Safety Function		2 Input Channels (STO1, STO2), 1 Output Channels (EDM±)						
USB Communication	Function	Firmware download, Parameter setting, Tuning, Secondary function, Parameter copy						
	Communication Standard	USB 2.0 Full Speed (applies standard)						
	Connect	PC or USB storing medium						
Internal Function	Dynamic Braking	Standard built-in brake (activated when the servo alarm goes off or when the servo is off).						
	Regenerative Braking	Both the default built-in brake and an externally installed brake are possible.						
	Display Function	7 segments(5DIGIT)						
	Self-setting Function	The [MODE] key changes the content displayed in 7 segments.						
	Additional Function	Auto gain tuning function						
	Protection Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheated(power module overheated, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem						
Environment	Temperature	0 ~ +50[°C] / -20 ~ +70[°C]						
	Humidity	Below 90[%]RH(avoid dew-condensation)						
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.						

L7S Series

L7NH Series

L7P Series

S Series

MDM Series

Options

# L7 SERIES SYSTEM


## L7NHB Drive Product Features

Item	Type Name	L7NHB010U	L7NHB020U	L7NHB035U	L7NHB050U	L7NHB075U	L7NHB150U
Input Power	Main Power Supply	3-Phase AC 380~480 [V] (-15~10[%]), 50~60 [Hz]					
	Control Power Supply	Single-Phase AC 380~480 [V] (-15~10[%]), 50~60 [Hz]					
	Rated Current[A]	3.7	8	10.1	17.5	22.8	39
	Peak Current[A]	11.1	24	30.3	47.25	57	97.5
	Encoder Type	Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2					
Control Performance	Speed Control Range	Maximum 1: 5000					
	Frequency Response	Maximum 1[kHz] or above(When the 19-bit Serial Encoder is applied)					
	Speed Variation Ratio	± 0.01[%] or lower(When the load changes between 0 and 100%) ± 0.1[%] or less(Temperature of 25°C [±10])					
	Torque Control Repetition Accuracy	Within ±1%					
EtherCAT Communication Specifications	Communication Standard	FoE (Firmware download) EoE (Parameter setting by UDP, Tuning, Secondary function, Parameter copy) CoE (IEC 61158 Type12, IEC 61800-7 CIA 402 Drive profile)					
	Physical Layer	100BASE-TX(IEEE802.3)					
	Connector	RJ45 x 2					
	Communication distance	Within connection between nodes 100[m]					
	DC (Distributed Clock)	By DC mode synchronism, minimum DC cycle: 250[us]					
	LED Display	LinkAct IN, LinkAct OUT, RUN, ERR					
Digital Input/Output	Cia402 Drive Profile	Profile Position Mode Profile Velocity Mode Profile Torque Mode Cyclic Synchronous Position Mode Cyclic Synchronous Velocity Mode Cyclic Synchronous Torque Mode Homing Mode					
	Digital Input	Input Voltage range : DC 12[V] ~ DC 24[V] Total 8 input channels (allocable) Above 12 functions can be used selectively for assignment. (*POT, *NOT, *HOME, *STOP, *PCON, *GAIN2, *P_CL, *N_CL, PROBE1, PROBE2, EMG, A_RST) *Basic allocation signal					
	Digital Output	Service rating: DC 24[V] ±10%, 120[mA] Total 4 input channels (allocable) Above 11 functions can be used selectively for assignment. (*BRAKE±, *ALARM±, *READY±, *ZSPD±, INPOS±, TLMT±, VLMT±, INSPD±, WARN±, TGON±, INPOS2±) *Basic allocation signal					
	Analog Monitor	There are 2 input channels. Above 15 functions can be used selectively for assignment.					
USB Communication	Safety Function	2 Input Channels (STO1, STO2), 1 Output Channels (EDM±)					
	Function	Firmware download, Parameter setting, Tuning, Secondary function, Parameter copy					
	Communication Standard	USB 2.0 Full Speed (applies standard)					
USB Communication	Connect	PC or USB storing medium					
	Dynamic Braking	Standard built-in brake (activated when the servo alarm goes off or when the servo is off).					
	Regenerative Braking	Both the default built-in brake and an externally installed brake are possible.					
	Display Function	7 segments(5DIGIT)					
	Self-setting Function	Possible to set the drive node address by using Rotary Switch					
Operation Environment	Additional Function	Auto gain tuning function					
	Protection Function	Overcurrent, overload, overvoltage, insufficient voltage, main power input problem, control power input problem, overspeed, motor cable, overheat(power module overheat, abnormal drive operation's temp), encoder problem, over-regenerative, sensor problem, communication problem					
	Temperature	0 ~ +50[°C] / -20~ +70[°C]					
	Humidity	Below 90[%]RH(avoid dew-condensation)					
	Other	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust.					

## External Dimensions of L7NHA Drive


### L7NHA001U ~ L7NHA004U [Weight : 1.0kg]

\*Unit [mm]



### L7NHA008U / L7NHA010U [Weight : 1.5kg(Fan-Cooling included)]

\*Unit [mm]




# L7 SERIES SYSTEM

## External Dimensions of L7NHA Drive

■ L7NHA020U / L7NHA035U [Weight : 2.5kg(Fan-Cooling included)]


\* Unit [mm]



## External Dimensions of L7NHB Drive


### L7NHB010U [Weight : 1.5kg(Fan-Cooling included)]

\*Unit [mm]



### L7NHB020U / L7NHB035U [Weight : 2.5kg(Fan-Cooling included)]

\*Unit [mm]




# L7 SERIES SYSTEM

## External Dimensions of L7NHB Drive


■ L7NHB050U [Weight : 5.5kg(Fan-Cooling included)]

\* Unit [mm]



■ L7NHB075U [Weight : 8.5kg(Fan-Cooling included)]


\* Unit [mm]



## External Dimensions of L7NHB Drive

■ L7NHB150U [Weight : 15.5kg(Fan-Cooling included)]

\*Unit [mm]



L7S Series

L7N Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

# L7 SERIES SYSTEM

Indexer Function Type

## I L7P Series



### ■ Servo Drive Designation

L7	P	A	004	B	AA
Model Name Servo Series	Communication Stand I/O & Index Type	Input Power Supply A : 200VAC	Capacity 001 : 100W 002 : 200W 004 : 400W 008 : 750W 010 : 1,0kW 020 : 2,0kW 035 : 3,5kW	Encoder Type U : Universal	Option Exclusive Option Code


## L7P Series

### Characteristic

- Providing Program Function built-in single axis position determination module
  - Supporting position control mode by pulse input
  - Position control mode
  - Possible to use without upper controller
  - Modbus RTU Protocol (RS-422)
- Improved Control Performance
  - Improved Control bandwidth
  - Providing 4-step Notch-Filter
  - Vibration control by Real-time FFT
  - Real-time gain tuning function
- Support various motor and Encoder drive
  - Supporting Rotary, DD and Motor drive (supporting 3rd party motor)
  - Quadrature, BiSS-C, Tamagawa serial abs, EnDat 2.2, Resolver

### Identifying the Part of L7P Drive

#### [L7P]



- ① Display
- ② Status LED
- ③ Charge Lamp
- ④ Main Power Connector (L1, L2, L3)
- ⑤ DC Reactor Connector(PO, PI) Short-Circuit When Not used
- ⑥ Regenerative Resistor Connector (B+, B, BI)
  - Short-Circuit B, BI terminals when standard type
  - Use B+, B terminals when using external resistor
- ⑦ Control Power connector (C1, C2)
- ⑧ Motor power connector(U, V, W)
- ⑨ Connector for analogue monitor
- ⑩ Switch for nod address setting
- ⑪ USB connector (USB)
- ⑫ RS-422 communication connector (CN3, CN4)
- ⑬ Control signal connector (I/O)
- ⑭ Encoder Connector (ENCODER)
- ⑮ Ground

# L7 SERIES SYSTEM

## L7P Drive Combination Table

### L7P Incremental Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable	Power Cable			
							Quadrature Type	INC	For power	Power + Brake
3,000	5,000	□40	SAP3A	L7PA001U	2,048 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□MS		
			SAP5A	L7PA001U						
			SA01A	L7PA001U						
			S4016A	L7PA002U						
		□60	SE01A	L7PA002U	3,000 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□MS		
			SE02A	L7PA002U						
			SE04A	L7PA004U						
			SC04A	L7PA004U						
		□80	SC06A	L7PA008U	APCS E□□□BS	APCS P□□□HS	APCS P□□□NS			
			SC08A	L7PA008U						
			SC10A	L7PA010U						
			SE09A	L7PA008U						
		□100	SE15A	L7PA020U	APCS P□□□BS	APCS P□□□HS	APCS P□□□NS			
			SE22A	L7PA020U						
			SF30A	L7PA035U						
			SC03D	L7PA004U						
2,000	3,000	□80	SC05D	L7PA008U	3,000 P/R	APCS E□□□AS	APCS P□□□GS	APCS P□□□MS		
			SC06D	L7PA008U						
			SC07D	L7PA008U						
			SE06D	L7PA008U						
		□100	SE11D	L7PA010U	APCS P□□□HS	APCS P□□□NS				
			SE16D	L7PA020U						
			SE22D	L7PA030U						
			SF22D	L7PA030U						
		□160	LF35D	L7PA035U	APCS P□□□IS	APCS P□□□HS	APCS P□□□NS			
			SG22D	L7PA020U						
1,500	3,000	□100	SE05G	L7PA008U	APCS E□□□BS	APCS P□□□HS	APCS P□□□NS			
			SE09G	L7PA010U						
			SE13G	L7PA020U						
			SE17G	L7PA030U						
			SF20G	L7PA035U						
		□160	LF30G	L7PA035U	APCS P□□□IS	APCS P□□□HS	APCS P□□□NS			
			SG20G	L7PA020U						
		□220	LG30G	L7PA035U	APCS P□□□BS	APCS P□□□HS	APCS P□□□NS			
			SE03M	L7PA004U						
			SE06M	L7PA008U						
1,000	2,000	□100	SE09M	L7PA010U	APCS E□□□BS	APCS P□□□HS	APCS P□□□NS			
			SE12M	L7PA020U						
			SF12M	L7PA020U						
			SF20M	L7PA035U						
			LF30M	L7PA035U						
		□220	SG20M	L7PA020U	APCS P□□□IS	APCS P□□□HS	APCS P□□□NS			
			SG20M	L7PA035U						
		□220	LG30M	L7PA035U	APCS E□□□AS	APCS P□□□HS	APCS P□□□NS			
			HE01A	L7PA002U						
			HE02A	L7PA002U						
3,000	3,500	□60	HE04A	L7PA004U	1024 P/R	APCS E□□□AS	APCS P□□□GS			
			HE09A	L7PA008U						
		□100	HE16A	L7PA020U	2,048 P/R	APCS E□□□BS	APCS P□□□HS			
		□100	HE22A	L7PA035U						
		□100	HE30A	L7PA035U						

## L7P Drive Combination Table

### L7P Serial Type

Rated Speed (rpm)	Maximum Speed (rpm)	Flange Size	Applicable Motor	Applicable Drive	Standard Encoder Type	Encoder cable		Power Cable		
						Serial Type	Single Turn	Multi Turn	For power	Power + Brake
3,000	5,000	1981 Serial / M. Turn Abs	□40	FALR5A	L7PA001U	APCS E□□□ES	APCS E□□□ES1	APCS P□□□LS	APCS P□□□QS	APCS P□□□QS
			□40	FAL01A	L7PA001U					
			□40	FAL015A	L7PA002U					
			□60	FBL01A	L7PA001U					
			□60	FBL02A	L7PA002U					
			□60	FBL04A	L7PA004U					
			□60	FCL04A	L7PA004U					
			□60	FCL06A	L7PA008U					
			□60	FCL08A	L7PA008U					
			□60	FCL10A	L7PA010U					
2,000	3,000	1981 Serial / M. Turn Abs	□60	FB01A	L7PA001U	APCS E□□□ES	APCS E□□□ES1	APCS P□□□FS	APCS P□□□QS	APCS P□□□QS
			□60	FB02A	L7PA002U					
			□60	FB04A	L7PA004U					
			□60	FC04A	L7PA004U					
			□60	FC06A	L7PA008U					
			□60	FC08A	L7PA008U					
			□60	FC10A	L7PA010U					
			□130	FE09A	L7PA010U					
			□130	FE15A	L7PA020U					
			□130	FE22A	L7PA020U					
1,500	3,000	APCS E□□□OS	□130	FE30A	L7PA030U	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS	APCS P□□□QS
			□60	FCL030	L7PA004U					
			□60	FCL050	L7PA008U					
			□60	FCL060	L7PA008U					
			□60	FCL070	L7PA008U					
			□60	FC030	L7PA004U					
			□60	FC050	L7PA008U					
			□60	FC060	L7PA008U					
			□60	FC070	L7PA008U					
			□60	FE060	L7PA008U					
1,000	2,000	APCS E□□□OS	□130	FE10	L7PA010U	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS	APCS P□□□QS
			□130	Fe160	L7PA020U					
			□130	FE220	L7PA020U					
			□130	FF220	L7PA020U					
			□130	FG350	L7PA035U					
			□220	FG220	L7PA020U					
			□220	FG350	L7PA035U					
			□130	FE05G	L7PA008U					
			□130	FE09G	L7PA010U					
			□130	FE13G	L7PA020U					
1,700	2,700	APCS E□□□OS	□130	FE17G	L7PA020U	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS	APCS P□□□QS
			□130	FF20G	L7PA020U					
			□130	FF30G	L7PA035U					
			□220	FG20G	L7PA020U					
			□220	FG30G	L7PA035U					
			□130	FE03M	L7PA004U	APCS E□□□OS1	APCS P□□□HS	APCS P□□□NB	APCS P□□□QS	APCS P□□□QS
			□130	FE06M	L7PA008U					
			□130	FE09M	L7PA010U					
			□130	FE12M	L7PA020U					
			□130	FF12M	L7PA020U					
1,700	1,700	APCS E□□□OS	□130	FF20M	L7PA020U	APCS P□□□S	APCS P□□□PB	APCS P□□□SB	APCS P□□□SB	APCS P□□□SB
			□220	FG12M	L7PA020U					
			□220	FG20M	L7PA020U					
			□220	FG30M	L7PA035U					

# L7 SERIES SYSTEM


## L7P Drive Product Features

Item	Type Name	L7PA001U	L7PA002U	L7PA004U	L7PA008U	L7PA010U	L7PA020U	L7PA035U
Input Power	Main Power Supply	3-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]						
	Control Power Supply	Single-Phase AC 200~230 [V] (-15~10[%]), 50~60 [Hz]						
	Rated Current[A]	1.4	1.7	3.0	5.2	6.75	13.5	16.7
	Peak Current[A]	4.2	5.1	9.0	15.6	20.25	40.5	50.1
	Encoder Type	Quadrature(Incremental) BISS-B, BISS-C(Absolute, Incremental) Tamagawa Serial(Absolute, Incremental) EnDat 2.2						
Control Performance	Speed Control Range	Maximum 1: 5000						
	Frequency Response	Maximum 1 [kHz] or above (When using 19bit Serial Encoder)						
	Speed Variation Ratio	±0.01 [%] or lower [when load changes between 0 and 100%] ±0.1[%] or lower [temperature 25 ±10°C]						
	속도 가감속시간	Straight or S-curveacceleration/deceleration (0~10,000[ms], 0~1,000[ms] Unitconfigurable)						
	입력주파수	1[Mpps], line drive / 200[kpps], Open Collectorpr						
	입력펄스 방식	Symbol + Pulse Series, CW+CCW, A/B Phase						
RS422 Communication Specifications	Communication Specifications	ANSI/TIA/EIA-422 StandardSpecifications						
	Communication Protocol	MODBUS-RTU						
	Connector	RJ45 x 2						
	Synchro Method	Asynchronous						
	Transmission Speed	9600 /19200/38400/57600 [bps] Can be configured at [0x3002]						
	Transmission Distance	Maximum 200 [m]						
	Power Consumption	100[mA] 이하						
	Terminating Resistance	Dip S/W(On/Off), Built-In 120Ω						
Input/Output Signal	Digital Input	Input voltage range: DC 12[V] ~ DC 24[V] Total 16 input channel (allocatable) 32 function inputs can be selectively allocated (*SV_ON, *POT, *NOT, *A-RST, *START, *STOP, *REGT, *EMG, *HOME, *HSTART, *ISEL0, *ISEL1, *ISEL2, *ISEL3, *ISEL4, *ISEL5, PCON, GAIN2, P_CL, N_CL, MODE, PAUSE, ABSRQ, JSTART, JDIR, PCLR, AOVR, SPD1/LVSF1, SPD2/LVSF2, SPD3, PROBET, PROBE2) * Basic allocationsignal.						
	Digital Output	Use rating: DC 24[V] ±10%, 120[mA] Total 8 input channel (allocatable) 19 function inputs can be selectively allocated (*ALARM±, *READY±, *BRAKE±, *INPOS1±, *ORG±, *EOS±, *TGON±, *TLMT±, VLMT±, INSPD± ZSPD±, WARN±, INPOS2±, IOUT0±, IOUT1±, IOUT2± IOUT3±, IOUT4±, IOUT5±) * Standard Allocationsignal						
Analog Input/output	Analog input	Total 2 channels analog speedoverrideinput(-10[V] ~ +10[V]) analog torquecommand input(-10[V] ~ +10[V])						
	Analog output	Total 2 channels 15 function inputs can be selectively allocated						
USB Communication	Protection	Firmware download, parametersetting, tuning, auxiliary function,parametercopy						
	Communication Specifications	Complies with USB 2.0 Full Speed Specifications						
	Connection Device	PC or USB storage media						
Built-in functions	Dynamic Braking	Standard built-in(activated by servoalarm or servo OFF)						
	Regenerative Braking	Built-in, external brake attachable						
	Display	7 Segment(5 DIGIT)						
	Setting Function	Drive node address can be set using rotary switch						
	Additional Function	Gaituning, alarm history, JOG operation, origin search						
	Protective Function	Excessive current, overload, excessive current limit, overheating, excessive voltage, low voltage, excessive speed, encoder fail, position following fail, current sensing fail						
Environment	Temperature	0 ~ 50[°C] / -20 ~ 65 °C						
	Humidity	Below 90[%]RH(avoid dew-condensation)						
	Environment	Indoor, Avoid corrosive, inflammable gas or liquid, and electrically conductive dust,						

## External Dimensions of L7P Drive


### L7PA001U ~ L7PA004U [Weight : 1.0kg(Fan-Cooling included)]

\*Unit [mm]



### L7PA008U / L7PA010U [Weight : 1.5kg(Fan-Cooling included)]

\*Unit [mm]




# L7 SERIES SYSTEM

## External Dimensions of L7P Drive

■ L7PA020U / L7PA035U [Weight : 2.5kg(Fan-Cooling included)]

\* Unit [mm]



Contents

■ Servo Motor

## S Series

Solid/Hollow Type Roatating Servo Motor

- Servo Drive Designation \_ 52
- Product Feature \_ 53
- External Dimensions \_ 63



## F Series

Flat Type Roatating Servo Motor

- Servo Drive Designation \_ 68
- Product Feature \_ 69
- External Dimensions \_ 79



## MDM Series

Direct-Drive Motor

- Servo Drive Designation \_ 83
- Product Feature \_ 87
- External Dimensions \_ 89




# L7 SERIES SYSTEM

Solid/Hollow Type Rotating Servo Motor

## I S Series



### Servo Motor Designation



## S Series Motor Characteristics (200V)

### Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)		SAR5A	SA01A	SA015A	SB01A	SB02A	SB04A	SC04A	SC06A	SC08A	SC10A				
Applicable Drive (L7□A□□)		L7□A001		L7□A002		L7□A004		L7□A008		L7□A010					
Flange Size(□)		□40				□60				□80					
Rated Output	[kW]	0.05	0.1	0.15	0.1	0.2	0.4	0.4	0.6	0.8	1				
Rated Torque	[N·m]	0.16	0.32	0.48	0.32	0.64	1.27	1.27	1.91	2.55	3.19				
Max. Instantaneous	[N·m]	0.48	0.96	1.43	0.96	1.91	3.82	3.82	5.73	7.64	9.56				
Max. Instantaneous	[kgf·cm]	4.87	9.74	14.62	9.74	19.48	38.96	38.96	58.47	77.95	97.43				
Rated Current	[A]	1.2	1.38	1.73	1.65	1.63	2.89	2.82	3.58	4.83	5.37				
Max. Current	[A]	3.6	4.14	5.19	4.95	4.89	8.67	8.46	10.74	14.49	16.11				
Rated Speed	[r/min]	3000													
Max. Speed	[r/min]	5000													
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	0.02	0.05	0.06	0.11	0.18	0.32	0.67	1.09	1.51	1.93				
	[gf·cm×s <sup>2</sup> ]	0.02	0.05	0.07	0.12	0.19	0.33	0.69	1.11	1.54	1.97				
Allowable Load Inertia Ratio	30 times of motor inertia			20 times of motor inertia				15 times of motor inertia							
Rated Power Rate	[kW/s]	10.55	23.78	35.34	8.89	22.26	50.49	24.05	33.39	43.02	52.57				
Speed/Position Detector	Standard(Note1)	Quad. Type Incremental 2048[P/R]													
	Option	Serial Type 18[Bit]													
Specifications & Features	Structure	Fully closed · Self cooling IP55 Note1)						Fully closed · Self cooling IP65 Note1)							
	Rated Time	Continuous													
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]													
	Ambient Humidity	20 ~ 80[%] (avoid dew-condensation)													
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.													
Weight	E/N	Elevation/vibration 49[m/s <sup>2</sup> ](5G)													
	[kg]	0.38	0.5	0.7	0.82	1.08	1.58	1.88	2.52	3.15	3.8				

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM


## S Series Motor Characteristics (200V)

### Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	SE09A	SE15A	SE22A	SE30A	SF30A	SF50A	HB01A	HB02A	HB04A	HE09A	HE15A	HE30A							
Applicable Drive (L7□A□□)	L7□A008	L7□A020	L7□A050	L7□A035	L7□A050	L7□A002	L7□A004	L7□A008	L7□A020	L7□A050									
Range Size(□)	□130				□180				□60										
Rated Output [kW]	0.9	1.5	2.2	3	3	5	0.1	0.2	0.4	0.9	1.5	3							
Rated Torque [N·m]	2.86	4.77	7	9.55	9.55	15.91	0.32	0.64	1.27	2.86	4.77	9.55							
	[kgf·cm]	29.23	48.72	71.45	97.43	162.38	3.25	6.49	12.99	29.23	48.72	97.43							
Max. Instantaneous	[N·m]	8.59	14.32	21.01	28.64	47.74	0.96	1.91	3.82	8.59	14.32	28.64							
	[kgf·cm]	87.69	146.15	214.35	292.29	487.15	9.74	19.48	38.96	87.69	146.15	292.29							
Rated Current [A]	4.95	8.23	11.98	17.16	16.7	27.4	1.65	1.63	2.89	4.95	8.23	17.16							
Max. Current [A]	14.85	24.69	35.94	51.48	50.1	82.2	4.95	4.89	8.67	14.85	24.69	51.48							
Rated Speed [r/min]	3000																		
Max. Speed [r/min]	5000						3500												
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	6.66	12	17.34	22.68	30.74	52.13	0.27	0.33	0.46	19.56	22.27	31.81						
	[gf·cm×s <sup>2</sup> ]	6.8	12.24	17.69	23.14	31.37	53.19	0.27	0.34	0.47	19.96	22.72	32.46						
Allowable Load Inertia Ratio	10 times of motor inertia				5 times of motor inertia				20 times of motor inertia										
Rated Power Rate [kW/s]	12.32	18.99	28.28	40.20	29.66	48.58	3.34	11.98	34.47	4.10	10.01	22.03							
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]						Quad, Type Incremental 1024[P/R]											
	Option	Serial Type 19[Bit]						X											
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1)						Fully closed · Self cooling IP55 Note1)											
	Rated Time	Continuous																	
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]																	
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)																	
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,																	
	E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)																	
Weight [kg]	5.5	7.5	9.7	11.8	12.4	17.7	0.9	1.2	1.7	5.8	7.4								

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked. It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## S Series Motor Characteristics (200V)









### Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	SC03D	SC05D	SC06D	SC07D	SE06D	SE11D	SE16D	SE22D
Applicable Drive (L7□A□□)	L7□A004		L7□A008		L7□A008	L7□A010		L7□A020
Flange Size(□)		□80				□130		
Rated Output [kW]	0.3	0.45	0.55	0.65	0.6	1.1	1.6	2.2
Rated Torque [N·m]	1.43	2.15	2.83	3.1	2.86	5.25	7.84	10.5
[kgf·cm]	14.61	21.92	26.79	31.66	29.23	53.59	77.94	107.17
Max, Instantaneous [N·m]	4.3	6.45	7.88	9.31	8.59	15.75	22.92	31.51
[kgf·cm]	43.84	65.77	80.38	94.98	87.69	160.76	233.83	321.52
Rated Current [A]	2.59	3.23	3.82	4.42	3.97	6.28	9.23	12.37
Max. Current [A]	7.77	9.69	11.46	13.26	11.91	18.84	27.69	37.11
Rated Speed [r/min]				2000				
Max. Speed [r/min]				3000				
Inertia [kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	0.67	1.09	1.51	1.93	6.66	12	17.34	22.68
[gf·cm×s <sup>2</sup> ]	0.69	1.11	1.54	1.97	6.8	12.24	17.69	23.14
Allowable Load Inertia Ratio		15 times of motor inertia				10 times of motor inertia		
Rated Power Rate [kW/s]	30.43	42.27	45.69	49.97	12.32	22.98	33.65	48.64
Speed/Position Detector	Standard(Note1)				Quande, Type Incremental 3000[P/R]			
Option					Serial Type 19[Bit]			
Specifications & Features	Structure				Fully closed · Self cooling IP65 Note1)			
	Rated Time				Continuous			
	Ambient Temp				Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]			
	Ambient Humidity				90[%]RH Below (avoid dew-condensation)			
	Atmosphere				Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,			
	E/V				Elevation/vibration 49[m/s <sup>2</sup> ](5G)			
Weight [kg]	1.9	2.5	3.2	3.9	5.5	7.5	9.7	11.8

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM


## S Series Motor Characteristics (200V)

### Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)		SF22D	LF35D	SF55D	SF75D	SG22D	LG35D	SG55D	SG75D
Applicable Drive (L7□A□□)		L7□A020	L7□A035	L7□A050	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075
Range Size(□)			□180				□220		
Rated Output	[kW]	2.2	3.5	5.5	7.5	2.2	3.5	5.5	7.5
Rated Torque	[N·m]	10.5	16.71	26.26	35.81	10.5	16.71	26.26	35.81
	[kgf·cm]	107.17	170.5	267.93	365.38	107.2	170.52	267.9	365.4
Max. Instantaneous	[N·m]	31.51	50.13	78.77	89.51	31.51	50.13	78.77	89.51
	[kgf·cm]	321.52	511.51	803.8	913.41	321.52	511.51	803.8	913.4
Rated Current	[A]	13.5	15.85	30.25	34.6	12.3	16.05	30.25	38
Max. Current	[A]	40.5	47.55	90.75	86.5	36.9	48.15	90.75	102
Rated Speed	[r/min]				2000				
Max. Speed	[r/min]		3000		2500		3000		2500
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91
	[gf·cm·s <sup>2</sup> ]	31.35	53.16	85.31	123.74	52.47	81.99	135.11	176.44
Allowable Load Inertia Ratio					5 times of motor inertia				
Rated Power Rate	[kW/s]	35.88	53.56	82.56	105.75	21.45	34.75	52.07	74.15
Speed/Position Detector	Standard(Note1)				Quande, Type Incremental 3000[P/R]				
	Option				Serial Type 19[Bit]				
Specifications & Features	Structure				Fully closed · Self cooling IP65 Note1)				
	Rated Time				Continuous				
	Ambient Temp				Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]				
	Ambient Humidity				90[%]RH Below (avoid dew-condensation)				
	Atmosphere				Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,				
	E/V				Elevation/vibration 49[m/s <sup>2</sup> ](5G)				
Weight	[kg]	12.4	17.7	26.3	35.6	17	22	30.8	37.5

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked. It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## S Series Motor Characteristics (200V)


### ■ Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)		SE05G	SE09G	SE13G	SE17G	SF20G	LF30G	SF44G	SF60G	SG20G	LG30G	SG44G	SG60G
Applicable Drive (L7□A□□)		L7□A008	L7□A010	L7□A020		L7□A035	L7□A050	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075	L7□A075
Flange Size(□)		□130				□180				□220			
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	1.8	2.9	4.4	6
Rated Torque	[N·m]	2.86	5.41	8.28	10.82	11.46	18.46	28.01	38.19	11.46	18.46	28.01	38.19
Max. Instantaneous	[kgf·cm]	29.23	55.21	84.44	110.42	116.92	188.37	285.8	389.7	116.92	188.37	285.8	389.7
Max. Instantaneous	[N·m]	8.59	16.23	24.83	32.46	34.37	55.38	84.02	95.48	34.47	55.38	84.02	95.48
Max. Current	[A]	3.97	6.47	10	12.75	14.7	15.92	31.75	38	13.1	16.19	31.5	38
Max. Current	[A]	11.91	19.41	30	38.25	44.1	47.64	95.25	102	39.3	48.57	94.5	102
Rated Speed	[r/min]	1500											
Max. Speed	[r/min]	3000				3000	2700	3000	2500	3000	2700	3000	2500
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	6.66	12	17.34	22.68	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91
	[gf·cm×s <sup>2</sup> ]	6.8	12.24	17.69	23.14	31.37	53.19	85.31	123.83	52.47	81.99	135.11	176.44
Allowable Load Inertia Ratio		10 times of motor inertia				5 times of motor inertia							
Rated Power Rate	[kW/s]	12.32	24.4	39.49	51.63	42.71	65.37	93.83	120.21	25.53	42.41	59.24	84.36
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]											
	Option	Serial Type 19[Bit]											
Specifications & Features	Structure	Fully closed · Self cooling IP65 <b>Note1</b>											
	Rated Time	Continuous											
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]											
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)											
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.											
E/V		Elevation/vibration 49[m/s <sup>2</sup> ][5G]											
Weight	[kg]	5.5	7.5	9.7	11.8	12.4	17.7	26.3	35.6	17	22	30.8	37.52

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### ■ Speed-Torque Characteristics



# L7 SERIES SYSTEM


## S Series Motor Characteristics (200V)

### Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)	SE03M	SE06M	SE09M	SE12M	SF12M	SF20M	LF30M	SF44M	SG12M	SG20M	LG30M	SG44M	SG60M
Applicable Drive (L7□A□□□)	L7□A004	L7□A008	L7□A010	L7□A020		L7□A035		L7□A050	L7□A020	L7□A035		L7□A050	L7□A075
Flange Size(□)				□130			□180					□220	
Rated Output [kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque [N·m]	2.86	5.73	8.59	11.46	11.46	19.1	28.64	42.01	11.46	19.1	28.64	42.01	57.29
[kgf·cm]	29.23	58.46	87.69	116.92	116.92	194.86	292.29	428.69	116.92	194.86	292.29	428.69	584.6
Max. Instantaneous [N·m]	8.59	17.19	25.78	34.37	34.37	57.29	85.93	126.04	34.37	57.29	85.93	126.04	171.87
[kgf·cm]	87.69	175.3	263.06	350.75	350.75	584.58	876.88	1286.08	350.75	584.58	876.88	1286.08	1,753.80
Rated Current [A]	2.51	4.15	5.78	7.63	8.4	14.4	15.99	31.24	8.87	15.02	16.04	31.83	38
Max. Current [A]	7.53	12.45	17.34	22.89	25.2	43.2	47.97	93.72	26.61	45.06	48.12	95.49	102
Rated Speed [r/min]								1000					
Max. Speed [r/min]				2000				1700	2000	1700	2000		
Inertia [kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	6.66	12	17.34	22.68	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91	291.38
[gf·cm×s <sup>2</sup> ]	6.8	12.24	17.69	23.14	31.37	53.19	85.31	123.83	52.47	81.99	135.11	176.44	297.31
Allowable Load Inertia Ratio	10 times of motor inertia							5 times of motor inertia					
Rated Power Rate [kW/s]	12.32	27.35	42.59	57.89	42.71	69.95	98.15	145.45	25.53	45.39	61.97	102.08	112.65
Speed/Position Detector	Standard(Note1)							Quad, Type Incremental 3000[P/R]					
Option								Serial Type 19[Bit]					
Specifications & Features	Structure							Fully closed	Self cooling IP65 Note1)				
	Rated Time								Continuous				
	Ambient Temp							Operating : 0 ~ 40[°C]	Storage : -10 ~ 60[°C]				
	Ambient Humidity							90[%]RH Below (avoid dew-condensation)					
	Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.					
	E/V							Elevation/vibration 49[m/s <sup>2</sup> ](5G)					
Weight [kg]	5.5	7.5	9.7	11.8	12.4	17.7	26.3	35.6	17	22	30.8	37.5	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked. It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## S Series Motor Characteristics (400V)







### ■ Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)		SEP09A	SEP15A	SEP22A	SEP30A	SFP30A	SFP50A		
Applicable Drive (L7□A□□)		L7□B010	L7□B020		L7□B035		L7□B050		
Flange Size(□)		□130				□180			
Rated Output	[kW]	0.9	1.5	2.2	3	3	5		
Rated Torque	[N·m]	286	477	7	9.55	9.55	15.92		
	[kgf·cm]	29.23	48.72	71.46	97.44	97.44	162.4		
Max. Instantaneous	[N·m]	8.59	14.32	21.01	28.65	28.65	39.79		
	[kgf·cm]	87.7	146.16	214.37	292.33	292.33	406.01		
Rated Current	[A]	2.97	4.89	7.17	9.78	9.37	15.49		
Max. Current	[A]	8.62	14.2	20.84	28.41	27.38	45.27		
Rated Speed	[r/min]	3000							
Max. Speed	[r/min]	5000							
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	6.659	11.999	17.339	22.679	30.74	52.13		
	[gf·cm×s <sup>2</sup> ]	6.795	12.244	17.893	23.142	31.367	53.194		
Allowable Load Inertia Ratio		10 times of motor inertia				5 times of motor inertia			
Rated Power Rate	[kW/s]	12.32	19.00	28.28	40.21	42.71	65.37		
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]							
	Option	Serial Type 19[Bit]							
Specifications & Features	Structure	Fully closed · Self cooling IP65 <b>Note1</b>							
	Rated Time	Continuous							
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]							
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)							
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.							
E/V		Elevation/vibration 49[m/s <sup>2</sup> ](5G)							
Weight	[kg]	5.5	7.54	9.68	11.78	12.4	17.7		

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### ■ Speed-Torque Characteristics



# L7 SERIES SYSTEM


## S Series Motor Characteristics (400V)

### Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	SEP06D	SEP11D	SEP16D	SEP22D	SFP22D	SFP35D	SFP55D	SFP75D	SGP22D	SGP35D	SGP55D	SGP75D	SGP110D
Applicable Drive (L7□A□□)	L7□B010		L7□B020		L7□B035	L7□B050	L7□B075	L7□B020	L7□B035	L7□B050	L7□B075	L7□B150	
Flange Size(□)		□130			□180							□220	
Rated Output [kW]	0.6	1.1	1.6	2.2	2.2	3.5	5.5	7.5	2.2	3.5	5.5	7.5	11
Rated Torque [N·m]	2.86	5.25	7.64	10.5	10.5	16.71	26.26	35.81	10.50	16.71	26.26	35.81	52.52
[kgf·cm]	29.23	53.59	77.95	107.19	107.19	170.52	267.96	365.41	107.19	170.52	267.96	365.41	535.93
Max. Instantaneous [N·m]	8.59	15.76	22.92	31.51	31.51	50.13	85.65	89.52	31.51	50.13	78.78	89.52	131.30
[kgf·cm]	87.7	160.78	233.86	321.56	321.56	511.57	669.91	913.52	321.56	511.57	803.89	913.52	1,339.82
Rated Current [A]	1.78	3.27	4.79	6.54	6.56	10.07	15.82	21.36	6.27	10.03	15.66	18.42	27.41
Max. Current [A]	5.18	9.5	13.92	19	19.17	29.43	38.64	52.16	18.43	29.51	46.08	45.25	67.33
Rated Speed [r/min]							2000						
Max. Speed [r/min]							3000					2500	
Inertia [kg·m²×10⁻⁴]	6.659	11.999	17.339	22.679	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91	291.36
[gf·cm²×10⁻³]	6.795	12.244	17.693	23.142	31.367	53.194	85.306	123.827	52.47	81.99	135.11	176.44	297.10
Allowable Load Inertia Ratio	10 times of motor inertia							5 times of motor inertia					
Rated Power Rate [kW/s]	12.32	22.99	48.64	91.96	35.89	53.57	82.49	105.67	21.46	34.76	52.08	74.16	94.65
Speed/Position Detector	Standard(Note1)							Quad, Type Incremental 3000[P/R]					
Option								Serial Type 19[Bit]					
Specifications & Features	Structure							Fully closed · Self cooling IP65 Note1)					
	Rated Time							Continuous					
	Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]					
	Ambient Humidity							90[%]RH Below (avoid dew-condensation)					
	Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,					
	E/V							Elevation/vibration 49[m/s²](5G)					
Weight [kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked. It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## S Series Motor Characteristics (400V)


### Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)		SEP05G	SEP09G	SEP13G	SEP17G	SFP20G	SFP30G	SFP44G	SFP60G	SFP75G	SGP20G	SGP30G	SGP44G	SGP60G	SGP85G	SGP110G	SGP150G
Applicable Drive (L7□A□□)		L7□B010	L7□B020	L7□B020	L7□B020	L7□B050	L7□B075	L7□B150	L7□B20	L7□B20	L7□B050	L7□B075	L7□B075	L7□B150			
Flange Size(□)		□130				□180								□220			
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6	8.5	11	15
Rated Torque	[N·m]	2.86	5.41	8.28	10.82	11.46	18.46	28.01	38.2	47.75	11.46	18.46	28.01	38.2	54.11	70.03	95.49
	[kgf·cm]	29.23	55.22	84.45	110.43	116.93	188.39	285.83	389.77	487.21	116.93	188.39	285.83	389.77	552.17	714.57	974.42
Max. Instantaneous	[N·m]	8.59	16.23	24.83	32.47	34.38	55.39	70.03	95.49	119.37	34.38	55.39	70.03	95.49	135.28	175.07	219.6
	[kgf·cm]	87.7	165.65	253.35	331.3	350.79	565.16	745.7	974.42	1218.02	350.79	565.16	745.7	974.42	1380.43	1786.43	2240
Rated Current	[A]	1.78	3.37	5.19	6.74	7.15	11.12	16.87	22.78	28.13	6.84	11.08	16.71	19.65	28.24	28.28	35.71
Max. Current	[A]	5.18	9.79	15.07	19.58	20.91	165.9	41.21	55.64	65.7	20.11	33	49.15	48.23	69.37	68.83	87.7
Rated Speed	[r/min]	1500															
Max. Speed	[r/min]	3000				2500				3000				2500			
Inertia	[kg·m <sup>2</sup> × 10 <sup>-4</sup> ]	6.659	11.999	17.339	22.679	30.74	52.13	83.6	121.35	143.82	51.42	80.35	132.41	172.91	291.36	291.36	385.54
	[gf·cm×s <sup>2</sup> ]	6.795	12.244	17.693	23.142	31.367	53.194	85.306	123.827	146.755	52.47	81.99	135.11	176.44	297.31	297.31	393.14
Allowable Load Inertia Ratio	10 times of motor inertia				5 times of motor inertia												
Rated Power Rate	[kW/s]	12.32	24.4	57.08	97.61	42.72	65.38	93.86	120.23	158.51	25.531	42.41	59.25	84.36	100.5	168.3	214.8
Speed/Position Detector	Standard (Note1)	Quad Type Incremental 3000[P/R]															
	Option	Serial Type 19[Bit]															
Specifications & Features	Structure	Fully closed Self cooling IP65 Note1															
	Rated Time	Continuous															
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]															
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)															
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.															
	E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)															
Weight	[kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	39.4	16.95	21.95	30.8	37.52	66.2	66.3	92.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM


## S Series Motor Characteristics (400V)

### Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)		SEP03M	SEP06M	SEP09M	SEP12M	SFP12M	SFP20M	SFP30M	SFP44M	SGP12M	SGP20M	SGP30M	SGP44M	SGP60M
Applicable Drive (L7□A□□)		L7□B010		L7□B035		L7□B020		L7□B050		L7□B020		L7□B050		L7□B150
Flange Size(□)		□130				□180				□220				
Rated Output	[kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque	[N·m]	2.86	5.73	8.59	11.46	11.46	19.1	28.65	42.02	11.46	19.1	28.65	42.02	57.3
	[kgf·cm]	29.23	58.47	87.7	116.93	116.93	194.88	292.33	428.74	116.93	194.88	292.33	428.74	584.65
Max. Instantaneous	[N·m]	8.59	17.19	25.78	34.38	34.38	57.3	71.62	105.04	34.38	57.3	85.94	105.04	143.24
	[kgf·cm]	87.7	175.4	263.09	350.79	350.79	584.65	730.81	1,071.86	350.79	584.65	876.98	1,071.86	1,461.63
Rated Current	[A]	1.26	2.42	3.62	4.8	4.77	7.88	11.92	17.15	4.72	7.84	11.73	17.29	23.58
Max. Current	[A]	3.65	7.04	10.51	13.95	13.94	23.03	29.12	41.88	13.87	23.06	34.51	50.87	57.92
Rated Speed	[r/min]	1000												
Max. Speed	[r/min]	2000												
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	6.659	11.989	17.339	22.679	30.74	52.13	83.6	121.35	51.42	80.35	132.41	172.91	291.36
	[gf·cm×s <sup>2</sup> ]	6.795	12.244	17.693	23.142	31.367	53.194	85.306	123.827	52.47	81.99	135.11	176.44	297.31
Allowable Load Inertia Ratio	10 times of motor inertia				5 times of motor inertia									
Rated Power Rate	[kW/s]	12.32	27.36	42.6	57.9	42.72	69.97	98.17	145.48	25.53	45.39	61.97	102.08	112.64
Speed/Position Detector	Standard(Note1)	Quad, Type Incremental 3000[P/R]												
	Option	Serial Type I9[Bit]												
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1												
	Rated Time	Continuous												
	Ambient Temp.	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]												
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)												
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,												
E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)													
Weight	[kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked. It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## External Dimensions of S Series Motor

### SA Series

#### Plug Specifications

[Power]

Spec. 172167.1  
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground

(Power Connector Pin Table)


[Brake]

Spec. 172165.1  
(Made by AMP)

Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)


[Encoder]



Spec. 172171.1(Made by AMP)

Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	A	10	V
3	B	11	W
4	B	12	W
5	Z	13	+5V
6	Z	14	0V
7	U	15	SHIELD
8	U		

(Parallel Encoder Connector Pin Table)



Model	External Dimensions				Weight(kg)
	L	LM	LC	CB	
SAR3A	101.3(137.6)	76.3(112.6)	42.5(42.4)	66.3(102.3)	0.32(0.57)
SAR5A	108.3(144.6)	83.3(119.6)	49.5(49.4)	73.3(109.3)	0.38(0.73)
SA01A	125.3(161.6)	100.3(136.6)	66.5(66.4)	90.3(126.6)	0.5(0.85)
SA015A	145.3	120.3	86.5	110.3	0.7

### SB Series

#### Plug Specifications

[Power]

Spec. 172167.1  
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W

(Power Connector Pin Table)


[Brake]

Spec. 172165.1  
(Made by AMP)

Pin No.	Signal
1	BK+
2	BK-

(Brake Connector Pin Table)


[Encoder]



Spec. 172171.1(Made by AMP)

Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	A	10	V
3	B	11	W
4	B	12	W
5	Z	13	+5V
6	Z	14	0V
7	U	15	SHIELD
8	U		

(Parallel Encoder Connector Pin Table)



Model	External Dimensions				Weight(kg)
	L	LM	LC	CB	
SB01A	122(162)	92(132)	52.5(52.3)	59.5(99.5)	0.82(1.4)
SB02A	136(176)	106(146)	66.5(66.3)	73.5(113.5)	1.08(1.66)
SB04A	164(204)	134(174)	94.5(94.3)	101.5(141.5)	1.58(2.16)

# L7 SERIES SYSTEM

## External Dimensions of S Series Motor

### SC Series

#### Plug Specifications

[Power]		Pin No.	Color	Signal
		1	Red	U
		2	White	V
		3	Black	W
		4	Green	Ground

(Power Connector Pin Table)

[Brake]		Pin No.	Signal
		1	BK+
		2	BK-


(Brake Connector Pin Table)

[Encoder]		Pin No.	Signal	Pin No.	Signal
		1	A	9	V
		2	Ā	10	V̄
		3	B	11	W
		4	B̄	12	W̄
		5	Z	13	+5V
		6	Z̄	14	0V
		7	U	15	SHIELD
		8	Ū		

(Parallel Encoder Connector Pin Table)

- Note1)** Use DC[24V] for brake input power supply.  
**Note2)** The ( ) is for brake-attached type.  
**Note3)** For external dimensions for oil-sealed type. Please kindly contact us separately.  
**Note4)** Refer to page 24 for serial encoder pin table.



Model	External Dimensions					Weight(kg)
	L	LM	LC	CB	S	
SC04A, SC03D	158.5(199.8)	118.5(158.8)	79(78.8)	86(126.3)	14	1.88(2.92)
SC06A, SC05D	178.5(218.8)	138.5(178.8)	99(98.8)	106(146.3)	16	2.52(3.56)
SC08A, SC06D	198.5(238.8)	158.5(198.8)	119(118.8)	126(166.3)	16	3.15(4.22)
SC10A, SC07D	218.5(258.8)	178.5(218.8)	139(138.8)	146(186.3)	16	3.80(4.94)

### SE, SEP Series

#### Plug Specifications

[Power]		Pin No.	Signal
		A	U
		B	V
		C	W
		D	Ground

(Standard)

[Power]		Pin No.	Signal	Pin No.	Signal
		A	U	D	Ground
		B	V	E	BK+
		C	W	F	BK-


(Brake-attached type)

[Encoder]		Pin No.	Signal	Pin No.	Signal
		A	A	M	V
		B	Ā	N	V̄
		C	B	P	W
		D	B̄	R	W̄
		E	Z	H	+5V
		F	Z̄	G	0V
		K	U	J	SHIELD
		L	Ū		

(Parallel Encoder Connector Pin Table)

- Note1)** Use DC[24V] for brake input power supply.  
**Note2)** The ( ) is for brake-attached type.  
**Note3)** For external dimensions for oil-sealed type. Please kindly contact us separately.  
**Note4)** Refer to page 24 for serial encoder pin table.




Model	External Dimensions					Key	Weight(kg)
	L	LM	LC	S	T		
SE04A, SE06D, SE05G, SE03M, SEP04A, SEP06D, SEP05G, SEP03M	201.3(239.3)	143.3(181.3)	93.8(93.6)			5,5(7.04)	
SE15A, SE11D, SE09G, SE06M, SEP15A, SEP11D, SEP09G, SEP06M	225.3(263.3)	167.3(205.3)	117.8(117.6)	19	5	5	7.54(9.08)
SE22A, SE16D, SE13G, SE09M, SEP22A, SEP16D, SEP13G, SEP09M	249.3(287.3)	191.3(229.3)	141.8(141.6)				9.68(11.22)
SE30A, SE22D, SE17G, SE12M, SEP30A, SEP22D, SEP17G, SEP12M	273.3(311.3)	215.3(253.3)	165.8(165.6)	22	6	6	11.78(13.32)

## External Dimensions of S Series Motor


### SF, LF, SFP Series

#### Plug Specifications



(Power)	Pin No.	Signal
	A	U
	B	V
	C	W
	D	Ground

Spec. : MS3102A22 22P (Standard)




(Power)	Pin No.	Signal	Pin No.	Signal
	A	U	D	Ground
	B	V	E	BK+
	C	W	F	BK-

Spec. : MS3102A24 10P (Brake-attached type)


#### Encoder

(Incremental type)



(Encoder)	Pin No.	Signal	Pin No.	Signal
	A	A	M	V
	B	A	N	V
	C	B	P	W
	D	B	R	W
	E	Z	H	+5V
	F	Z	G	0V
	K	U	J	SHIELD
	L	U		


Spec. : MS3102A20 29P (Parallel Encoder Connector Pin Table)



Model	External Dimensions				Key					Weight(kg)
	L	LM	LC	LR	S	QW	T	W	U	
SF30A, SF2D, SP2G, SP1M, SF30A, SF22D, SF20G, SF12M	261.5(312.9)	182.5(233.9)	133(132.7)							12.4(19.2)
SF50A, LF35D, LF30G, SF20M, SF50A, SF22M	295.5(346.9)	216.5(267.9)	167(166.7)	79	35 <sup>0.01</sup>	60	8	10	5	17.7(24.9)
SF6D, SF44G, LF30M, SF55D, SF44G	345.5(396.9)	266.5(317.9)	217(216.7)							26.3(33.4)
SF7D, SF80G, SF44M, SF73D, SF80G, SF44M	405.5(456.9)	326.5(377.9)	277(276.7)							35.6(42.8)
SF75G, SF75G	457.5	344.5	295	113	42 <sup>0.01</sup>	96	8	12	5	39.4

### SG, LG, SGP Series

#### Plug Specifications




(Power)	Pin No.	Signal
	A	U
	B	V
	C	W
	D	Ground

Spec. : MS3102A22 22P (Standard)

#### Brake

(Brake-attached type)



(Brake)	Pin No.	Signal
	C	BK+
	D	BK-
	B	NC

Spec. : MS3102A24 7P (Brake-attached type)


#### Encoder

(Incremental type)



(Encoder)	Pin No.	Signal	Pin No.	Signal
	A	A	M	V
	B	A	N	V
	C	B	P	W
	D	B	R	W
	E	Z	H	+5V
	F	Z	G	0V
	K	U	J	SHIELD
	L	U		

Spec. : MS3102A20 29P (Parallel Encoder Connector Pin Table)



Model	External Dimensions				Key					Power Connector		
	L	LM	LC	LR	LF	LQ	S	GK	T	W	U	
SG2D, SG30G, SG32M, SF2D, SF30G, SF32M	236.5(302.7)	171.5(237.7)	122(121.2)								16.95(20.78)	
LG30G, LG32M, SF30G, SF32M	256.5(322.7)	191.5(257.7)	142(142.2)	65	19	56.4 (122.6)	35 <sup>0.01</sup>	55	8	10	5	21.95(25.7)
SG30D, SG44G, LG32M, SF35G, SF44G	292.5(358.7)	227.5(293.7)	178(177.2)								30.84(44.94)	
SG75G, SG80G, SG34M, SF35G, SF44G	320.5(386.7)	265.5(321.7)	209(205.2)								37.52(50.94)	
SG10D, SG30G, SG32M, SF44G, SF55G	418.5(484.7)	353.5(419.7)	304(303.2)	65	21	86 (132.2)	45 <sup>0.01</sup>					66.28(2.6)
SG10G, SG11G	469	354	304	116	21	86 (132.2)	42 <sup>0.01</sup>	96	10	12	5	66.3
SG15G, SG150G	575	459	409	116	35	55 <sup>0.01</sup>	55 <sup>0.01</sup>	96	10	16	6	92.2

Note1) In case of SG, use DC(90V) for brake input power supply.

Note2) The ( ) is for brake-attached type.

Note3) For external dimensions for oil-sealed type. Please kindly contact us separately.

Note4) Refer to page 24 for serial encoder pin table.

Note5) Use MS3102A32-17 for SG60M Power connector.

# L7 SERIES SYSTEM

## External Dimensions of S Series Motor

### HB Series [Hollow Shaft type]

#### Plug Specifications

[Power]




Spec. T72107.1  
(Made by AMP)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
4	Green	Ground

(Power Connector Pin Table)


[Encoder]



Spec. T72171 (Made by AMP)

Pin No.	Signal	Pin No.	Signal
1	A	9	V
2	A	10	V
3	B	11	W
4	B	12	W
5	Z	13	+5V
6	Z	14	0V
7	U	15	SHIELD
8	U		

(Parallel Encoder Connector Pin Table)




Weight(kg)

Model	External Dimensions					
	L	LM	LC	CB	Hollow Shaft	
HB01A	140.5	103.5	68.5	24	15	0.89
HB02A	154.5	117.5	82.5	38	15	1.16
HB04A	182.5	140.5	105.5	66	15	1.69

### HE Series [Hollow Shaft type]

#### Plug Specifications

[Power]




Spec. MS3102A20\_4P  
(Standard)

Pin No.	Signal
A	U
B	V
C	W
D	Ground

(Power Connector Pin Table)


[Encoder]



Spec. MS3102A20\_29P

Pin No.	Signal	Pin No.	Signal
A	A	M	V
B	A	N	V
C	B	P	W
D	B	R	W
E	Z	H	+5V
F	Z	G	0V
K	U	J	SHIELD
L	U		

(Parallel Encoder Connector Pin Table)



Weight(kg)

Model	External Dimensions				
	L	LM	LC	Hollow Shaft	
HE09A	207	150	111.5	40	5.82
HE15A	231	174	135.5	40	7.43
HE30A	279	222	183.5	40	

## Brake and Heat Sink Specification

### Electric Brake Specifications

Applicable Motor Series	APM-SA,FAL	APM-SB,FB,FBL	APM-SC, FC,FCL	APM-SE,SEP,FE,FEP	APM-SF,SFP,FF,FFF	APM-SG,SGP,FG,FGP
Purpose	Maintenance					
Input voltage [V]	DC 24V	DC 24V	DC 24V	DC 24V	DC 24V	DC 90V
Static friction torque [N · m]	0.32	1.47	3.23	10.4	40	74
Capacity [W]	6	6.5	9	19.4	25	32
Coil resistance [ $\Omega$ ]	96	89	64	29.6	23	327
Rated current [A]	0.25	0.27	0.38	0.81	1.04	0.28
Braking mechanism	Spring brake					
Insulation grade	Grade F					

Note1) For the Electronic Brake that is attached to our Servo Motor, the same specifications are to be applied as per the series.

Note2) Do not use it for braking purpose because the electronic brake is only for maintaining the stopped condition.

Note3) The characteristics of electronic brake is measured at 20°C

Note4) Please make sure to always check the voltage specification on the motor because indicated brake specifications are subject to change.


### Heat Sink Specifications

Type	Dimensions(mm)	Materials
AP04	250x250x6	Aluminum
AP06	250x250x6	
AP08	250x250x12	
AP13	350x350x20	
AP18	550x550x30	
AP22	650x650x35	

NOTE 1) The data on the product features is measured when those heat sinks are applied.

### S Series Encoder Pin Map

#### | SA, SB, SC Series |



Plug Specification :  
172169-1  
(AMP)

Single Turn (N)		Multi Turn (M)	
Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	MA	2	MA
3	SLO	3	SLO
4	SLO	4	SLO
5	-	5	VOD_B
6	-	6	GND_B
7	+5V	7	+5V
8	0V	8	0V
9	SHIELD	9	SHIELD

(Serial Encoder Connector Pin Table)

#### | SE, SF, SG Series |



17 Pole Plug  
(MS3102A20-29P)

Single Turn (N)		Multi Turn (M)	
Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	MA
L	-	-	-

(Serial Encoder Connector Pin Table)


# L7 SERIES SYSTEM

## Flat Type Servo Motor

### I F Series



#### Servo Motor Designation



## F Series Motor Characteristics (200V)

### Motor Specifications [Rated 3000r/min, 2000r/min]

Servo Motor (APM-□□□□)	FALR5A	FAL01A	FAL015A	FBL01A	FBL02A	FBL04A	FCL04A	FCL06A	FCL08A	FCL10A	FCL03D	FCL05D	FCL06D	FCL07D									
Applicable Drive	L7DA001	L7DA002	L7DA001	L7DA002	L7DA004	L7DA004	L7DA004	L7DA008	L7DA010	L7DA004	L7DA008												
Flange Size(□)	□40			□60							□80												
Rated Output	[kW]	0.05	0.1	0.15	0.1	0.2	0.4	0.4	0.6	0.75	1	0.3	0.45	0.55									
Rated Torque	[N·m]	0.16	0.32	0.48	0.32	0.64	1.27	1.27	1.91	2.39	3.18	1.43	2.15	2.63									
	[kgf·cm]	1.62	3.25	4.87	3.25	6.49	12.99	12.99	19.49	24.36	32.48	14.62	21.92	26.8									
Max. Instantaneous	[N·m]	0.48	0.96	1.43	0.96	1.91	3.82	3.82	5.73	7.16	9.55	4.3	6.45	7.88									
	[kgf·cm]	4.87	9.74	14.62	9.74	19.48	38.96	38.98	58.47	73.08	97.44	43.85	65.77	80.39									
Rated Current	[A]	0.95	1.25	1.76	0.95	1.45	2.6	2.58	3.81	5.02	5.83	2.5	3.05	3.83									
Max. Current	[A]	2.85	3.75	5.28	2.85	4.35	7.8	7.75	11.42	15.07	17.5	7.51	9.16	9.18									
Rated Speed	[r/min]						3000						2000										
Max. Speed	[r/min]						5000						3000										
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	0.023	0.042	0.063	0.091	0.147	0.248	0.53	0.897	1.264	1.632	0.53	0.897	1.264									
	[g·cm <sup>2</sup> ×s <sup>2</sup> ]	0.024	0.043	0.065	0.093	0.15	0.253	0.541	0.915	1.29	1.665	0.541	0.915	1.29									
Allowable Load Inertia Ratio	30 times of motor inertia				20 times of motor inertia						15 times of motor inertia												
Rated Power Rate	[kW/s]	10.55	23.78	35.34	11.09	27.6	27.57	30.6	40.66	45.09	62.08	38.73	51.47	54.56									
Speed/Position Detector	Standard (Note1)	Serial Multi-Turn Built-in Type (8bit)				Serial Multi-Turn Built-in Type (16bit)																	
	Option	X																					
Specifications & Features	Structure	Fully closed / Self cooling IP67 (Note1)																					
	Rated Time	Continuous																					
	Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]																					
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)																					
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.																					
	E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)																					
Weight	[kg]	0.31	0.45	0.61	0.56	0.74	1.06	1.52	2.14	2.68	3.3	1.26	2.12	2.66									

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM

## F Series Motor Characteristics (200V)


### Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	FB01A	FB02A	FB04A	FC04A	FC06A	FC08A	FC10A	FE09A	FE15A	FE22A	FE30A	FF30A	FF50A
Applicable Drive	L7□A001	L7□A002	L7□A004	L7□A004	L7□A008	L7□A010	L7□A010	L7□A020	L7□A035	L7□A035	L7□A050	L7□A050	L7□A050
Flange Size(□)	□80	□80	□80	□80	□80	□80	□130	□130	□130	□130	□130	□130	□180
Rated Output [kW]	0.1	0.2	0.4	0.4	0.6	0.75	1	0.9	1.5	2.2	3	3	5
Rated Torque [N·m]	0.32	0.64	1.27	1.27	1.91	2.39	3.18	2.86	4.77	7	9.55	9.55	15.91
[kgf·cm]	3.25	6.5	12.99	13	19.5	24.36	32.5	29.2	48.7	71.4	97.4	97.4	162.3
Max, Instantaneous [N·m]	0.98	1.91	3.82	3.82	5.73	7.16	9.55	8.59	14.32	21.01	28.65	28.65	47.74
[kgf·cm]	9.74	19.49	38.98	38.98	58.47	73.08	97.44	87.7	146.1	214.3	292.2	292.3	487
Rated Current [A]	0.95	1.45	2.6	2.58	3.81	5.02	6.7	6.45	9.15	13.24	16.09	15.26	26.47
Max, Current [A]	2.86	4.35	7.79	7.75	11.42	15.07	20.09	19.35	27.45	39.72	48.27	45.78	79.41
Rated Speed [r/min]							3000						
Max, Speed [r/min]							5000						
Inertia [kg·m <sup>2</sup> × 10 <sup>-4</sup> ]	0.09	0.15	0.25	0.5	0.88	1.25	1.62	5.66	10.18	14.62	19.04	27.96	46.56
[gf·cm <sup>2</sup> × s <sup>2</sup> ]	0.09	0.15	0.25	0.51	0.89	1.27	1.65	5.77	10.39	14.92	19.43	28.53	47.51
Allowable Load Inertia Ratio	20 times of motor inertia				15 times of motor inertia			10 times of motor inertia			5 times of motor inertia		
Rated Power Rate [kW/s]	11.38	27.95	65.9	32.62	41.69	45.78	62.74	14.47	22.38	33.59	47.85	32.59	54.33
Speed/Position Detector	Standard (Note1)						Serial Type 19[bit]						
Option							X						
Structure							Fully closed · Self cooling IP65 (Note1)						
Rated Time							Continuous						
Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]						
Ambient Humidity							90[%]RH Below (avoid dew-condensation)						
Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,						
E/V							Elevation/vibration 49[m/s <sup>2</sup> ][5G]						
Weight [kg]	0.7	0.9	1.3	1.6	2.2	2.7	3.8	5	6.7	8.5	10.1	12.5	17.4

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics




## F Series Motor Characteristics (200V)

### Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FC03D	FC05D	FC06D	FC07D	FE06D	FE11D	FE16D	FE22D
Applicable Drive	L7□A004			L7□A008		L7□A010	L7□A020	
Flange Size(□)		□80				□130		
Rated Output	[kW]	0.3	0.45	0.55	0.65	0.6	1.1	1.6
Rated Torque	[N·m]	1.43	2.15	2.6	3.1	2.86	5.25	7.63
	[kgf·cm]	14.6	21.9	26.8	31.7	29.20	53.6	77.9
Max. Instantaneous	[N·m]	4.3	6.45	7.88	9.31	8.59	15.75	22.92
	[kgf·cm]	43.8	65.8	80.4	95	87.7	160.7	233.8
Rated Current	[A]	2.5	3.05	3.06	3.83	4.56	6.47	10.98
Max. Current	[A]	7.51	9.16	9.18	11.5	13.68	19.41	32.94
Rated Speed	[r/min]				2000			
Max. Speed	[r/min]				3000			
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	0.5	0.88	1.25	1.62	5.66	10.18	14.62
	[gF·cm×s <sup>2</sup> ]	0.51	0.89	1.27	1.65	5.77	10.39	14.92
Allowable Load Inertia Ratio		15 times of motor inertia				10 times of motor inertia		
Rated Power Rate	[kW/s]	41.28	52.76	55.39	59.64	14.49	27.08	39.89
Speed/Position Detector	Standard(Note1)				Serial Multi-Turn Built-in Type(9bit)			
	Option				X			
	Structure				Fully closed · Self cooling IP65 Note1)			
	Rated Time				Continuous			
Specifications & Features	Ambient Temp				Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]			
	Ambient Humidity				90[%]RH Below (avoid dew-condensation)			
	Atmosphere				Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.			
	E/V				Elevation/vibration 49[m/s <sup>2</sup> ](5G)			
Weight	[kg]	1.6	2.2	2.7	3.8	5	6.7	8.5
								10.1

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.  
It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM


## F Series Motor Characteristics (200V)

### ■ Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FF22D	FF35D	FF55D	FF75D	FG22D	FG35D	FG55D	FG75D
Applicable Drive	L7□A020	L7□A035	L7□A050	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075
Flange Size(□)		□180				□220		
Rated Output [kW]	2,2	3,5	5,5	7,5	2,2	3,5	5,5	7,5
Rated Torque [N·m]	10,5	16,7	26,25	35,81	10,5	16,71	26,25	35,81
[kgf·cm]	107,1	170,4	267,8	365,4	107,1	170,4	267,8	365,4
Max, Instantaneous [N·m]	31,5	50,1	78,76	89,53	31,51	50,12	78,78	89,53
[kgf·cm]	321,3	511,4	803,4	913,5	321,3	511,3	803,4	913,5
Rated Current [A]	13,07	16,48	28,78	32,95	10,25	14,67	29,74	30,17
Max Current [A]	39,21	49,44	86,34	98,85	30,75	44,01	89,22	90,51
Rated Speed [r/min]				2000				
Max. Speed [r/min]		3000		2500	3000	2700	3000	2500
Inertia [kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	27,96	46,56	73,85	106,7	41,13	71,53	117,72	149,4
[gf·cm×s <sup>2</sup> ]	28,53	47,51	75,36	108,9	41,97	72,99	120,12	152,45
Allowable Load Inertia Ratio				5 times of motor inertia				
Rated Power Rate [kW/s]	39,43	59,89	93,27	120,15	26,78	38,99	58,51	85,83
Speed/Position Detector	Standard (Note1)				Serial Type 19[bit]			
Option					X			
Structure					Fully closed · Self cooling IP65 (Note1)			
Rated Time					Continuous			
Ambient Temp					Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]			
Ambient Humidity					90[%]RH Below (avoid dew-condensation)			
Atmosphere					Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,			
E/V					Elevation/vibration 49[m/s <sup>2</sup> ](5G)			
Weight [kg]	12,5	17,4	25,12	33,8	15,4	20,2	28,12	33,45

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.  
It can be satisfied protection grade when you use private cable only.

### ■ Speed-Torque Characteristics




## F Series Motor Characteristics (200V)

### Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□)	FE05G	FE09G	FE13G	FE17G	FF20G	FF30G	FF44G	FF60G	FF75G	FG20G	FG30G	FG44G	FG60G	
Applicable Drive	L7□A008	L7□A010	L7□A020	L7□A020	L7□A035	L7□A050	L7□A075	L7□A075	L7□A075	L7□A020	L7□A035	L7□A050	L7□A075	
Flange Size(□)	□130				□180					□220				
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6
Rated Torque	[N·m]	2.86	5.41	8.27	10.82	11.45	18.46	28	38.2	47.7	11.5	18.5	28	38.2
	[kgf·cm]	29.22	55.19	84.41	110.38	116.9	188.3	285.7	389.8	487.2	116.9	188.4	285.8	389.7
Max. Instantaneous	[N·m]	8.59	16.23	24.82	32.46	34.35	55.38	84.03	95.5	143.2	34.4	55.4	84	96.5
	[kgf·cm]	87.66	165.57	253.23	331.14	350.6	564.9	857.1	974.9	1462	350.8	565.1	857.4	974.3
Rated Current	[A]	4.56	6.67	11.9	13.36	12.16	15.98	30.7	35.14	35.26	11.18	16.21	31.72	32.18
Max. Current	[A]	13.68	20.01	35.7	40.08	36.48	47.94	92.1	105.42	105.78	33.54	48.63	95.16	96.54
Rated Speed	[r/min]							1500						
Max. Speed	[r/min]		3000		3000	2700	3000	2500	2200	3000	2700	3000	2500	
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	5.66	10.18	14.62	19.04	27.96	46.56	73.85	106.7	131.3	14.13	71.53	117.72	149.4
	[gf·cm <sup>2</sup> s <sup>2</sup> ]	5.77	10.39	14.92	19.43	28.53	47.51	75.36	108.9	134	41.97	72.99	120.12	152.45
Allowable Load Inertia Ratio		10 times of motor inertia								5 times of motor inertia				
Rated Power Rate	[kW/s]	14.49	28.74	46.81	61.46	46.92	73.14	106.15	136.73	173.63	31.91	47.66	66.64	97.63
Speed/Position Detector	Standard(Note1)							Serial Type 19 [bit]						
	Option							X						
	Structure							Fully closed · Self cooling IP65 Note1)						
	Rated Time							Continuous						
Specifications & Features	Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]						
	Ambient Humidity							90[%]RH Below (avoid dew-condensation)						
	Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.						
	E/V							Elevation/vibration 49[m/s <sup>2</sup> ](5G)						
Weight	[kg]	5.0	6.7	8.5	10.1	12.5	17.4	25.2	33.8	38.5	15.4	20.2	28	33.45

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.  
It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM

## F Series Motor Characteristics (200V)

### Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)	FE03M	FE06M	FE09M	FE12M	FF12M	FF20M	FF30M	FF44M	FG12M	FG20M	FG30M	FG44M	FG60M
Applicable Drive	L7□A004	L7□A008	L7□A010	L7□A020	L7□A020	L7□A035	L7□A050	L7□A020	L7□A035	L7□A050	L7□A075		
Flange Size(□)	□130				□180				□220				
Rated Output [kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6
Rated Torque [N·m]	2.86	5.72	8.59	11.46	11.46	19.09	28.64	42.02	11.5	19.1	28.6	42	57.29
[kgf·cm]	29.22	58.4	87.7	116.9	116.9	194.8	292.2	428.7	116.9	194.9	292.3	428.7	584.6
Max. Instantaneous [N·m]	8.59	17.18	25.77	34.22	34.38	57.29	85.94	126.1	34.4	57.3	86.9	126	171.87
[kgf·cm]	87.66	175.3	262.9	349.1	350.7	584.4	876.6	128.6	350.8	584.6	876.9	128.61	1,793.80
Rated Current [A]	2.73	4.56	6.18	10.67	11.01	12.96	16.58	30.6	11.28	13.1	15.52	27.26	38
Max. Current [A]	8.19	13.68	18.54	32.01	33.03	38.88	49.74	91.8	33.84	39.3	46.56	81.78	102
Rated Speed [r/min]									1000				
Max. Speed [r/min]					2000				1700	2000	1700	2000	
Inertia [kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	5.66	10.18	14.62	19.04	27.96	46.56	73.85	106.7	41.13	71.53	117.72	149.4	291.36
[gf·cm×s <sup>2</sup> ]	5.77	10.39	14.92	19.43	28.53	47.51	75.36	108.9	41.97	72.99	120.12	152.45	297.31
Allowable Load Inertia Ratio					10 times of motor inertia					5 times of motor inertia			
Rated Power Rate [kW/s]	14.49	32.22	50.48	68.91	46.94	78.27	111.04	165.38	31.91	51	69.7	118.14	112.65
Speed/Position Detector	Standard (Note1)						Serial Type 19 [bit]						
Option							X						
Structure							Fully closed · Self cooling IP65 (Note1)						
Rated Time							Continuous						
Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]						
Ambient Humidity							90[%]RH Below (avoid dew-condensation)						
Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,						
E/V							Elevation/vibration 49[m/s <sup>2</sup> ](5G)						
Weight [kg]	5	6.7	8.5	10.1	12.5	17.4	25.2	33.8	15.4	20.2	28	33.5	66.2

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics









## F Series Motor Characteristics (400V)

### ■ Motor Specifications [Rated 3000r/min]

Servo Motor (APM-□□□□)	FEP09A	FEP15A	FEP22A	FEP30A	FFP30A	FFP50A
Applicable Drive	L7□B010□	L7□B020□		L7□B035□		L7□B050□
Flange Size(□)			□30			□80
Rated Output	[kW]	0.9	1.5	2.2	3.0	5.0
Rated Torque	[N·m]	2.86	4.77	7.0	9.55	15.92
	[kgf·cm]	29.23	48.72	71.46	97.44	162.4
Max. Instantaneous	[N·m]	8.59	14.32	21.01	28.65	39.79
	[kgf·cm]	87.7	146.16	214.37	292.33	406.01
Rated Current	[A]	3.47	6.68	9.12	9.94	16.07
Max. Current	[A]	10.4	20.03	27.35	29.81	48.22
Rated Speed	[r/min]			3000		
Max. Speed	[r/min]			5000		
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	5.659	10.179	14.619	19.04	27.96
	[gf·cm×s <sup>2</sup> ]	5.774	10.387	14.917	19.429	28.531
Allowable Load Inertia Ratio				10 times of motor inertia		5 times of motor inertia
Rated Power Rate	[kW/s]	14.5	22.4	33.55	47.89	32.61
Speed/Position Detector	Standard(Note1)			Serial Type 19 [bit]		
	Option			X		
	Structure			Fully closed · Self cooling IP65 Note1)		
	Rated Time			Continuous		
Specifications & Features	Ambient Temp			Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]		
	Ambient Humidity			90[%]RH Below (avoid dew-condensation)		
	Atmosphere			Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.		
	E/V			Elevation/vibration 40[m/s <sup>2</sup> ](5G)		
Weight	[kg]	5.5	7.54	9.68	11.78	12.4
						17.7

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.  
It can be satisfied protection grade when you use private cable only.

### ■ Speed-Torque Characteristics



# L7 SERIES SYSTEM

## F Series Motor Characteristics (400V)


### Motor Specifications [Rated 2000r/min]

Servo Motor (APM-□□□□)	FEP06D	FEP11D	FEP16D	FEP22D	FFP22D	FFP35D	FFP55D	FFP75D	FGP22D	FGP35D	FGP55D	FGP75D	FGP110D
Applicable Drive	L7□B010□		L7□B020□		L7□B035□	L7□B050□	L7□B075□	L7□B020□	L7□B035□	L7□B050□	L7□B075□	L7□B150□	
Flange Size(□)	□130				□180				□220				
Rated Output [kW]	0.6	1.1	1.6	2.2	2.2	3.5	5.5	7.5	2.2	3.5	5.5	7.5	11
Rated Torque [N·m]	2.86	5.25	7.64	10.5	10.5	16.71	26.26	35.81	10.5	16.71	26.26	35.81	52.52
[kgf·cm]	29.23	53.59	77.95	107.19	107.19	170.52	267.96	365.41	107.19	170.52	267.96	365.41	535.93
Max. Instantaneous [N·m]	8.59	15.76	22.92	31.51	31.51	50.13	65.65	89.52	31.51	50.13	78.78	89.52	131.30
[kgf·cm]	87.7	160.78	233.86	321.56	321.56	511.57	669.91	913.52	321.56	511.57	803.89	913.52	1339.82
Rated Current [A]	3.28	3.4	4.97	6.80	6.93	9.09	14.70	18.97	7.12	8.73	16.04	19.10	27.41
Max. Current [A]	9.83	10.19	14.92	20.4	20.8	27.26	44.1	47.42	21.35	26.2	48.11	47.76	67.33
Rated Speed [r/min]							2000						
Max. Speed [r/min]					3000			2500	3000	2700	3000		2500
Inertia [ $\text{kg} \cdot \text{m}^2 \times 10^{-4}$ ]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	106.73	41.13	71.53	117.72	149.4	291.36
[gf·cm $\times$ s $^2$ ]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	41.67	72.99	120.12	152.45	297.31
Allowable Load Inertia Ratio				10 times of motor inertia						5 times of motor inertia			
Rated Power Rate [kW/s]	14.5	27.1	39.92	57.95	39.46	59.98	93.38	120.15	26.83	39.04	58.58	85.83	94.65
Speed/Position Detector	Standard (Note1)						Serial Type 19 [bit]						
Option							X						
Structure							Fully closed · Self cooling IP65 Note1)						
Rated Time							Continuous						
Ambient Temp							Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]						
Ambient Humidity							90[%]RH Below (avoid dew-condensation)						
Atmosphere							Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,						
E/V							Elevation/vibration 49[m/s $^2$ ](5G)						
Weight [kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



## F Series Motor Characteristics (400V)


### Motor Specifications [Rated 1500r/min]

Servo Motor (APM-□□□□□)		FEPO5G	FEPO9G	FEPI3G	FEPI7G	FFP20G	FFP30G	FFP44G	FFP60G	FFP75G	FGP20G	FGP30G	FGP44G	FGP60G	FGP85G	FGP110G	FGP150G	
Applicable Drive		L7□B010□		L7□B020□		L7□B030□		L7□B060□		L7□B075□		L7□B020□		L7□B030□		L7□B030□		L7□B150□
Flange Size(□)		□130				□180				□220								
Rated Output	[kW]	0.45	0.85	1.3	1.7	1.8	2.9	4.4	6	7.5	1.8	2.9	4.4	6	8.5	11	15	
Rated Torque	[N·m]	2.86	5.41	8.28	10.82	11.46	18.46	28.01	38.2	47.75	11.46	18.46	28.01	38.2	54.11	70.03	95.49	
	[kgf·cm]	29.23	55.22	84.45	110.43	116.93	188.39	285.83	389.77	487.21	116.93	188.39	285.83	389.77	552.17	714.57	974.42	
Max. Instantaneous	[N·m]	8.59	16.23	24.83	32.47	34.38	55.39	84.03	95.49	119.37	34.38	55.39	84.03	95.49	135.28	175.07	238.73	
	[kgf·cm]	87.7	165.65	252.35	331.3	350.79	565.16	857.49	974.42	1218.02	350.79	565.16	857.49	974.42	1380.43	1786.43	2436.05	
Rated Current	[A]	3.28	3.50	5.39	7.01	7.56	10.04	15.68	20.23	20.01	7.76	9.65	17.11	20.38	28.24	28.28	35.71	
Max. Current	[A]	9.83	10.5	16.16	21.02	22.69	30.12	47.04	50.58	50.03	23.29	28.95	51.32	50.95	69.37	69.83	87.7	
Rated Speed	[r/min]	1500																
Max. Speed	[r/min]	3000				2700	3000	2500	2200	3000	2700	3000	2500	2000				
Inertia	[kg·m <sup>2</sup> ×10 <sup>-4</sup> ]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	108.73	131.29	51.42	80.35	132.41	172.91	291.36	51.42	424.5	
	[g·cm <sup>2</sup> ×10 <sup>3</sup> ]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	133.969	52.47	81.99	135.11	176.44	297.31	52.47	433.2	
Allowable Load Inertia Ratio		10 times of motor inertia				5 times of motor inertia												
Rated Power Rate	[kW/s]	14.5	28.77	46.85	61.52	46.96	73.21	108.25	136.7	173.64	25.53	45.39	61.97	102.08	100.5	168.3	214.8	
Speed/Position Detector	Standard(Note1)	Serial Type 19 [bit]																
	Option	X																
Specifications & Features	Structure	Fully closed · Self cooling IP65 Note1)																
	Rated Time	Continuous																
	Ambient Temp	Operating : 0 ~ 40[°C] · Storage : -10 ~ 60[°C]																
	Ambient Humidity	90[%]RH Below (avoid dew-condensation)																
	Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust.																
	E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)																
Weight	[kg]	5.5	7.54	9.88	11.78	12.4	17.7	28.3	35.6	39.4	16.95	21.95	30.8	37.52	66.2	66.3	92.2	

Note1) Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.

It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM


## F Series Motor Characteristics (400V)

### Motor Specifications [Rated 1000r/min]

Servo Motor (APM-□□□□)	FEP03M	FEP06M	FEP09M	FEP12M	FFP12M	FFP20M	FFP30M	FFP44M	FGP12M	FGP20M	FGP30M	FGP44M	FGP60M	
Applicable Drive	L7□B010□				L7□B020□				L7□B050□				L7□B020□	
Flange Size(□)	□130				□180				□220					
Rated Output [kW]	0.3	0.6	0.9	1.2	1.2	2	3	4.4	1.2	2	3	4.4	6	
Rated Torque [N·m]	2.86	5.73	8.59	11.46	11.46	19.1	28.65	42.02	11.46	19.1	28.65	42.02	57.3	
[kgf·cm]	29.23	58.47	87.7	116.93	116.93	194.88	292.33	428.74	116.93	194.88	292.33	428.74	584.65	
Max. Instantaneous [N·m]	8.59	17.19	25.78	34.38	34.38	57.3	85.94	126.05	34.38	57.3	85.94	126.05	143.24	
[kgf·cm]	87.7	175.4	263.09	350.79	350.79	584.65	876.98	1286.23	350.79	584.65	876.98	1,071.86	1,461.63	
Rated Current [A]	3.28	3.28	3.33	4.87	4.83	7.94	11.9	16.69	4.75	7.88	11.74	17.39	23.58	
Max. Current [A]	9.83	9.83	9.99	14.6	14.5	23.83	35.7	50.08	14.24	23.64	35.22	52.18	57.92	
Rated Speed [r/min]	1000													
Max. Speed [r/min]	2000							1700	2000					
Inertia [ $\text{kg} \cdot \text{m}^2 \times 10^{-4}$ ]	5.659	10.179	14.619	19.04	27.96	46.56	73.85	106.73	51.42	80.35	132.41	172.91	291.36	
[gf·cm×s <sup>2</sup> ]	5.774	10.387	14.917	19.429	28.531	47.51	75.357	108.908	52.47	81.99	135.11	176.44	297.31	
Allowable Load Inertia Ratio	10 times of motor inertia							5 times of motor inertia						
Rated Power Rate [kW/s]	14.5	32.25	50.53	68.97	46.96	78.38	111.13	185.41	25.53	45.39	61.97	102.08	112.64	
Speed/Position Detector	Standard (Note1) Serial Type 19 [bit]													
Option	X													
Structure	Fully closed Self cooling IP65 Note1)													
Rated Time	Continuous													
Ambient Temp	Operating : 0 ~ 40[°C] Storage : -10 ~ 60[°C]													
Ambient Humidity	90[%]RH Below (avoid dew-condensation)													
Atmosphere	Avoid direct sunlight, no corrosive gas, inflammable gas, oil mist, or dust,													
E/V	Elevation/vibration 49[m/s <sup>2</sup> ](5G)													
Weight [kg]	5.5	7.54	9.68	11.78	12.4	17.7	26.3	35.6	16.95	21.95	30.8	37.52	66.2	

**Note1)** Except for axis penetration, when you attach reducer to the motor, we don't guarantee IP for reducer. If you bend over specification designated in cable standard, it is difficult to guarantee IP marked.  
It can be satisfied protection grade when you use private cable only.

### Speed-Torque Characteristics




## External Dimensions of Servo Motor

### FAL Series

#### Plug Specifications

[Power]




Pin No. Color Signal

1	Red	U
2	White	V
3	Black	W
PE	Green	Ground

(Power Connector Pin Table)

[Brake]




Pin No. Signal

1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]



Multi Turn (M)

Pin No.	Signal
1	MA
2	SLO
3	GND_B
4	0V
5	SHIELD
6	MA
7	SLO
8	VDD_B
9	+5V


(Encoder Connector Pin Table)

Note1) Use DC(24V) for brake input power supply.

Note2) The ( ) is for brake-attached type.

Note3) For external dimensions for oil-sealed type.


Please kindly contact us separately.



### FBL Series

#### Plug Specifications

[Power]




Pin No. Color Signal

1	Red	U
2	White	V
3	Black	W

(Power Connector Pin Table)

[Brake]




Pin No. Signal

1	BK+
2	BK-

(Brake Connector Pin Table)

[Encoder]



Multi Turn (M)

Pin No.	Signal
1	MA
2	SLO
3	GND_B
4	0V
5	SHIELD
6	MA
7	SLO
8	VDD_B
9	+5V


(Encoder Connector Pin Table)

Note1) Use DC(24V) for brake input power supply.

Note2) The ( ) is for brake-attached type.

Note3) For external dimensions for oil-sealed type.

Please kindly contact us separately.




# L7 SERIES SYSTEM

## External Dimensions of Servo Motor

### FCL Series

#### Plug Specifications


[Power]



(Power Connector Pin Table)

Pin No.	Color	Signal
1	Red	U
2	White	V
3	Black	W
PE	Green	Ground


[Brake]



(Brake Connector Pin Table)

Pin No.	Signal
1	BK+
2	BK-

[Encoder]




(Encoder Connector Pin Table)

Pin No.	Signal
1	MA
2	SLO
3	GND_B
4	0V
5	SHIELD
6	MA
7	SLO
8	VDD_B
9	+5V

Note① Use DC[24V] for brake input power supply.

Note② The ( ) is for brake-attached type.

Note③ For external dimensions for oil-sealed type. Please kindly contact us separately.




Model	External Dimensions							Weight (kg)
	L	LM	LC	S	H	T	W	
FCL04A/FCL03D	138.7(179.5)	98.7(139.5)	70(69.8)	14	-0.018	5	5	3 1.52(2.32)/1.26(2.06)
FCL06A/FCL05D	156.7(197.5)	116.7(157.5)	88(87.8)	19	-0.021	6	6	3.5 2.14(2.94)/2.12(2.92)
FCL08A/FCL06D	174.7(215.5)	134.7(175.5)	106(105.8)	19	-0.021	6	6	3.5 2.68(3.46)/2.66(3.46)
FCL10A/FCL07D	192.7(233.5)	152.7(193.5)	124(123.8)	19	-0.021	6	6	3.5 3.30(4.10)/2.78(3.58)

### FB Series

#### Plug Specifications


[Power]



(Power Connector Pin Table)

Pin No.	Color	Signal
1	Black	W
2	White	V
3	Red	U
4	Green	Ground


[Brake]



(Brake Connector Pin Table)

Pin No.	Signal
1	BK+
2	BK-

[Encoder]




(Encoder Connector Pin Table)

Pin No.	Signal
1	MA
2	SLO
3	GND_B
4	0V
5	SHIELD
6	MA
7	SLO
8	VDD_B
9	+5V

Note① Use DC[24V] for brake input power supply.

Note② The ( ) is for brake-attached type.

Note③ For external dimensions for oil-sealed type. Please kindly contact us separately.




Model	External Dimensions			Weight (kg)
	L	LM	LC	
FB01A	109(149.2)	79(119.2)	43.5(43)	0.72(1.3)
FB02A	120(160.2)	90(130.2)	54.5(54)	0.94(1.49)
FB04A	140(180.2)	110(150.2)	74.5(74)	1.32(1.87)

## External Dimensions of Servo Motor

### FC Series

#### Plug Specifications

##### [Power]




##### [Pin No.] [Color] [Signal]

1	Black	W
2	White	V
3	Red	U
4	Green	Ground

(Power Connector Pin Table)

##### [Brake]




##### [Pin No.] [Signal]

1	BK+
2	BK-

(Brake Connector Pin Table)


##### [Encoder]



##### [Single Turn (N)] [Multi Turn (M)]

Pin No.	Signal	Pin No.	Signal
1	MA	1	MA
2	SLO	2	SLO
3	-	3	GND_B
4	OV	4	OV
5	SHIELD	5	SHIELD
6	~MA	6	~MA
7	SLO	7	SLO
8	-	8	VDD_B
9	+5V	9	+5V


(Encoder Connector Pin Table)

**Note1)** Use DC[24V] for brake input power supply.**Note2)** The ( ) is for brake-attached type.**Note3)** For external dimensions for oil-sealed type, Please kindly contact us separately.

### FE, FEP Series

#### Plug Specifications

##### [Power]



##### [Pin No.] [Signal]

A	U
B	V
C	W
D	Ground


Spec.: MS3102A20\_4P  
(Standard)

##### [Pin No.] [Signal] [Pin No.] [Signal]

A	U	D	Ground
B	V	E	BK+
C	W	F	BK-
D	SLO	R	-

Spec.: MS3102A20\_15P  
(Brake-attached type)

##### [Encoder]



##### [Single Turn (N)]

A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	OV
K	-	J	SHIELD
L	-	I	-

(Single Turn Encoder Connector Pin Table)

A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	OV
K	-	J	SHIELD
L	-	I	-


(Multi Turn Encoder Connector Pin Table)

A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	OV
K	-	J	SHIELD
L	-	I	-

(Multi Turn Encoder Connector Pin Table)

A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	OV
K	-	J	SHIELD
L	-	I	-

(Multi Turn Encoder Connector Pin Table)

**Note1)** Use DC[24V] for brake input power supply.**Note2)** The ( ) is for brake-attached type.


# L7 SERIES SYSTEM

## External Dimensions of Servo Motor

### FF, FFP Series

#### Plug Specifications

[Power]



Spec.: MS3102A22 22P  
(Standard)

Pin No.	Signal
A	U
B	V
C	W
D	Ground

Pin No.	Signal	Pin No.	Signal
A	U	D	Ground
B	V	E	BK+
C	W	F	BK-

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

Single Turn Encoder Connector Pin Table			
Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	VOD_B	H	+5V
F	GND_B	G	0V
K	-	J	SHIELD
L	-		

(Multi Turn Encoder Connector Pin Table)			
Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

[Encoder]




Spec.: MS3102A20 20P  
(Serial type)

(Single Turn Encoder Connector Pin Table)			
Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

(Multi Turn Encoder Connector Pin Table)			
Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

Note①) FF30M or above models have eye bolts.  
Note②) Use DC[24V] for brake input power supply.  
Note③) The ( ) is for brake-attached type.  
Note④) Use MS3102A32-17 for FF75G Power connector.



Model	External Dimensions				Key				Weight (kg)
	L	LM	LC	LR	S	QW	T	W	
FF30, FF22, FF20G, FF20M, FPP30A, FPP22D, FPP20G, FPP20M	257.5(308.9)	178.5(229.9)	129(128.7)						12.5(19.7)
FF50A, FF50, FF30G, FF20M, FPP50A, FPP50D, FPP30G, FPP20M	287.5(338.9)	208.5(259.9)	159(158.7)	79	35 <sup>+0.01</sup> <sub>0</sub>	60		10	17.4(24.6)
FF50D, FPP44G, FF30M, FPP50D, FPP44M, FPP30M	331.5(382.9)	252.5(303.9)	203(202.7)			8		5	25.2(32.4)
FF75D, FPP60G, FPP44M, FPP75D, FPP60M, FPP44M	384.5(435.9)	305.5(356.9)	256(255.7)		42 <sup>+0.01</sup> <sub>0.06</sub>			12	33.8(41.0)
FF75G, FPP75G	439.5	326.5	277	113	96				38.5(45.7)

### FG, FGP Series

#### Plug Specifications

[Power]



Spec.: MS3102A22 22P  
(Standard)

Pin No.	Signal
A	U
B	V
C	W
D	Ground

Pin No.	Signal
A	BK+
B	BK+
C	NC

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

[Encoder]




Spec.: MS3102A20 20P  
(Serial type)

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

Pin No.	Signal	Pin No.	Signal
A	MA	M	-
B	MA	N	-
C	SLO	P	-
D	SLO	R	-
E	-	H	+5V
F	-	G	0V
K	-	J	SHIELD
L	-		

Note①) In case of SG, use DC[90V] for brake input power supply.  
Note②) The ( ) is for brake-attached type.




Model	External Dimensions				Key				Weight (kg)
	L	LM	LC	LR	S	QW	T	W	
FG22D, FG20G, FG12M, FGP22D, FGP20G, FGP12M	229.5(285.7)	164.5(230.7)	115(114.2)						15.42(29.23)
FG35D, FGP30G, FG20M, FGP35D, FGP30G, FGP20M	250.5(316.7)	185.5(251.7)	136(135.2)	8	35 <sup>+0.01</sup> <sub>0</sub>			10	20.22(34.03)
FG55D, FG44G, FG30M, FGP55D, FGP44G, FGP30M	282.5(348.7)	217.5(283.7)	168(167.2)					5	28.02(41.83)
FG75D, FGP60G, FG44M, FGP75D, FGP60G, FGP44M	304.5(370.7)	239.5(305.7)	190(189.2)	42 <sup>+0.01</sup> <sub>0.06</sub>				12	33.45(47.26)
FG80M, FGP80M	418.5(484.7)	353.5(419.7)	304(303.2)	45 <sup>+0.01</sup> <sub>0.05</sub>				10	66.2(82.6)

#### Direct-Drive motor



#### ■ Direct-Drive Designation



# L7 SERIES SYSTEM

## Features of Mecapion Direct-Drive Motor

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series


MDM Series

Options

PEGASUS Series

- Using the own technologies to produce motors, drives and encoders domestically

- Optimized for low-speed, high-torque and high-precision operation
  - Providing Power connection for the connection of DC-Link Terminal
  - Compact Size and Easy Wring (Compared with 3 phase AC Reactor)
  - Providing Connection for DC Input (PI, N)




- Reduced cogging torque and optimized torque design
  - Optimal ratio of the permanent magnet and coil / slot selected through electromagnetic analysis
  - Using multiple permanent magnets to reduce torque ripple and to maximize torque
  - Using a permanent magnet of high-energy rare earth elements (Nd-Fe-B)

- Using the high-performance rotary optical encoder that adopts the Biss protocol
  - Resolution of 1,048,576 CPR (Single turn Absolute)
  - Using our own encoder technology to reduce the cost and shorten the delivery time

- Compatible with our L7 Series AC Servo Drive (3phase AC 220V)
  - Both standard I/O type (serial communication supported) and network type (EtherCAT) applicable

### Direct Drive Structure

- No backlash impact
- High-precision operation and shortened installation time
- Smooth rotary motion
- Reduced noise



- Hollow type that is efficient for wiring and piping

[ Speed Reducer + Servo Motor ]

[ DD Motor ]

### A wide range of products

- Rated output: 63W~25kW
- Rated torque: 3.0N.m~160N.m (the instantaneous maximum torque should be 3 times the rated torque)
- Rated speed: 150RPM~200RPM
- Frame diameter: 135mm, 175mm, 230mm, 290mm, and 360mm (13 models)

## DD Motor Specifications

### Ratings and Specifications

- Insulation class : Class B
- Protection class: IP 40
- Cooling type : Fully enclosed self-cooling
- Vibration class : V15
- Insulation resistance : 500 VDC, 10[MΩ] or higher
- Insulation internal voltage: 1800 VAC, 1 second
- Operating voltage: 200 VAC
- Operating temperature : 0 – 40[°C] / Storage temperature: -10~60[°C]
- Ambient humidity : 20 – 80% RH (no condensation)
- Installation location : Place with no toxic substances, such as corrosive and combustible gasses, cutting oil, metal dust, grease or direct sunlight

### Line-up Table

Maximum Torque[Nm]			9	18	27	36	54	66	102	120	180	330	480	
Rated speed 200[rpm]	Maximum speed 500[rpm]	Φ135	DB03D	DB06D	DB09D									
		Φ175		DC06D		DC12D								
		Φ230				DD12D								
	Maximum speed 400[rpm]	Φ175					DC18D							
		Φ230						DD22D	DD34D					
	Maximum speed 300[rpm]	Φ290								DE40D	DE60D			
Rated speed 150[rpm]	Maximum speed 250[rpm]	Φ360										DFA1D	DFA6D	

L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

# L7 SERIES SYSTEM

## Motor Designation

### Applicable drive to motor

Rated Speed (RPM)	Maximum Speed (RPM)	External Diameter of Motor(Φ)	Applicable Motor	Applicable Drive	encoder type
200	500	Φ135	DB03D	L7□A001□	20 bit single turn serial encoder (Biss/Absolute)
		Φ135	DB06D	L7□A002□	
		Φ135	DB09D	L7□A004□	
	500	Φ175	DC06D	L7□A002□	
		Φ175	DC12D	L7□A004□	
	400	Φ175	DC18D	L7□A008□	
	500	Φ230	DD12D	L7□A004□	
	400	Φ230	DD22D	L7□A008□	
	400	Φ230	DD34D	L7□A010□	
	300	Φ290	DE40D	L7□A010□	
150	250	Φ290	DE60D	L7□A020□	
		Φ360	DFA1G	L7□A020□	
		Φ360	DFA6G	L7□A035□	

### Appearances of Motor





## Features of Direct Drive Motor

Motor Designation	MDM-DB□□D□H			MDM-DC□□D□H				
	03	06	09	06	12	18		
Applicable Drive (L7□-A□□□□)	L7□A001□	L7□A002□	L7□A004□	L7□A002□	L7□A004□	L7□A008□		
Flange Size	mm	Φ135		Φ175				
Rated Output	W	63	126	188	126	251		
Rated Torque	N·m	3	6	9	6	12		
Max Torque	N·m	9	18	27	18	36		
Rated Current	Arms	1.12	1.46	2.63	1.48	2.41		
Max Current	Arms	3.36	4.38	7.89	4.44	7.23		
Rated Speed	rpm	200			200			
Max Speed	rpm	500	500	500	500	400		
Constant of Torque	N·m/Arms	2.76	4.25	3.57	4.18	5.13		
Inertia	kg·m <sup>2</sup> ×10 <sup>-4</sup>	5.74	8.67	11.5	27.32	38.9		
Rated Power Rate	kW/s	15.68	42.35	70.43	13.18	52.71		
Angular acceleration	rad/s <sup>2</sup>	191.2	141.6	127.7	455.08	323.9		
positioning accuracy	arc-sec	±15						
positioning repeatability	arc-sec	±1.3						
Axial run-out	mm	0.015						
Radial run-out	mm	0.03						
Allowable Thrust Load	N	1500		3300				
Max. Instantaneous	N·m	40		70				
Encoder Type	20-bit single turn serial encoder (Biss/Absolute)							
Weight (Approx.)	kg	6.3	7.2	9.2	8.7	10.6		
Working Environment	Ambient Temp	operating : 0~40[°C] / storage : -20~60[°C]						
	Ambient Humidity	20~80[%] RH(avoid dew-condensation)						
	Atmosphere	Avoid direct sunlight, No corrosive gas, Inflammable gas, Oil mist, or Dust						

\* In case of allowable load inertia ratio, please apply within 30 times of rotator inertia.

### Speed-Torque Characteristics



# L7 SERIES SYSTEM

## Features of Direct Drive Motor

Motor Designation	MDM-DD□□D□H			MDM-DE□□D□H		MDM-DF□□G□H	
	12	22	34	40	60	A1	A6
Applicable Drive (L7□-A□□□□)	L7□A004□	L7□A008□	L7□A010□	L7□A010□	L7□A020□	L7□A020□	L7□A035□
Flange Size	mm	$\Phi 230$		$\Phi 290$		$\Phi 360$	
Rated Output	W	251	461	712	838	1,257	1,728
Rated Torque	N·m	12	22	34	40	60	110
Max Torque	N·m	36	66	102	120	180	330
Rated Current	Arms	2.58	3.33	5.72	5.3	8.33	9.48
Max Current	Arms	7.74	9.99	17.16	15.9	24.99	28.44
Rated Speed	rpm	200		200		150	
Max Speed	rpm	500	400	400	300	300	250
Constant of Torque	N·m/Arms	4.8	6.81	6.13	7.77	7.42	11.95
Inertia	$\text{kg}\cdot\text{m}^2 \times 10^{-4}$	54.14	68.15	82.16	311.55	371.71	1410.2
Rated Power Rate	kW/s	26.6	71.02	140.7	51.36	96.68	85.9
Angular acceleration	$\text{rad/s}^2$	450.9	309.6	241.5	778.35	619.1	1281.13
positioning accuracy	arc-sec			$\pm 15$			
positioning repeatability	arc-sec			$\pm 1.3$			
Axial run-out	mm			0.015			
Radial run-out	mm			0.03			
Allowable Thrust Load	N	4000		11000		15000	
Max. Instantaneous	N·m	93		250		350	
Encoder Type	20-bit single turn serial encoder (Biss/Absolute)						
Weight (Approx.)	kg	17.3	19.6	21.9	28.2	35	54
Working Environment	Ambient Temp	operating : 0~40[°C] / storage : -20~60[°C]					
	Ambient Humidity	20~80[%] RH (avoid dew-condensation)					
	Atmosphere	Avoid direct sunlight, No corrosive gas, Inflammable gas, Oil mist, or Dust					


\* In case of allowable load inertia ratio, please apply within 30 times of rotator inertia

## Speed-Torque Characteristics




## External Dimensions of Direct-Drive Rotary Motor

### ■ MDM-DB03D, MDM-DB06D, MDM-DB09D



### ■ MDM-DC06D, MDM-DC12D, MDM-DC18D



# L7 SERIES SYSTEM

## External Dimensions of Direct-Drive Rotary Motor

### ■ MDM-DD12D, MDM-DD22D, MDM-DD34D

**POWER CONNECTOR**

Signal	Line color	PIN NO.
LEAD WIRE	U Red	A
V White	B	C
W Black	C	D
PG Green	D	

**ENCODER CONNECTOR**

DD SERVO ENCODER CABLE			
No.	Encoder Signal	No.	Encoder Signal
1	MV	9	+5V
2	SLO	10	-
3	-	11	-
4	IV	12	-
5	SIGD	13	-
6	MV	14	-
7	SLO	15	-
8	-	16	-

**Encoder Cable, Power Cable**

**External Dimensions**

Motor Series	External Dimensions		Weight(kg)
	L	W	
MDM-DD12D	82.5	26	17.3
MDM-DD22D	100.5	33	19.6
MDM-DD34D	118.5	38	21.9

**Dimensions:**

- MDM-DD12D: Ø138 [0.06] x 82.5
- MDM-DD22D: Ø190 [0.06] x 100.5
- MDM-DD34D: Ø250 [0.06] x 118.5

### ■ MDM-DE40D, MDM-DE60D

**POWER CONNECTOR**

Signal	Line color	PIN NO.
LEAD WIRE	U Red	A
V White	B	C
W Black	C	D
PG Green	D	

**ENCODER CONNECTOR**

DD SERVO ENCODER CABLE			
No.	Encoder Signal	No.	Encoder Signal
1	MV	9	+5V
2	SLO	10	-
3	-	11	-
4	IV	12	-
5	SIGD	13	-
6	MV	14	-
7	SLO	15	-

**Encoder Cable, Power Cable**

**External Dimensions**


Motor Series	External Dimensions		Weight(kg)
	L	W	
MDM-DE40D	95.4	26	28.2
MDM-DE60D	113.4	33	35

**Dimensions:**

- MDM-DE40D: Ø193 [0.06] x 95.4
- MDM-DE60D: Ø250 [0.06] x 113.4

## External Dimensions of Direct-Drive Rotary Motor

### ■ MDM-DFA1G, MDM-DFA6G



L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series

## Contents

### ■ Options

## *Servo motor options*

- Signal cable \_ 93
- Power cable \_ 96

## *Servo drive options*

- Signal cable \_ 105
- Connector \_ 106

## *Other options*

- Braking resistance \_ 107

## Servo Motor Option

### ■ Signal Cable [Incremental]

Type	Product Type	Model Name <sup>(1)</sup>	Applicable Drive	Applicable Motor	Specifications																																																																									
For Signal	Parallel Encoder Cable (Small Capacity)	APCS-E□□AS	L7SA□□□A L7NH□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<p>Motor Side Connector</p> <table border="1"> <tr><th>PIN No.</th><th>Encoder Signal</th><th>PIN No.</th><th>Encoder Signal</th></tr> <tr><td>1</td><td>A</td><td>9</td><td>V</td></tr> <tr><td>2</td><td>Ā</td><td>10</td><td>Ā</td></tr> <tr><td>3</td><td>B</td><td>11</td><td>W</td></tr> <tr><td>4</td><td>Ā</td><td>12</td><td>W</td></tr> <tr><td>5</td><td>Z</td><td>13</td><td>+5V</td></tr> <tr><td>6</td><td>Ā</td><td>14</td><td>0V</td></tr> <tr><td>7</td><td>U</td><td>15</td><td>SHIELD</td></tr> <tr><td>8</td><td>Ā</td><td></td><td></td></tr> </table> <p>(Motor Side Connector)</p> <p>Drive Side Connector(CN2)</p> <table border="1"> <tr><th>PIN No.</th><th>Encoder Signal</th><th>PIN No.</th><th>Encoder Signal</th></tr> <tr><td>1</td><td>W</td><td>8</td><td>Z</td></tr> <tr><td>2</td><td>Ā</td><td>9</td><td>Ā</td></tr> <tr><td>3</td><td>V</td><td>10</td><td>Ā</td></tr> <tr><td>4</td><td>Ā</td><td>11</td><td>B</td></tr> <tr><td>5</td><td>U</td><td>12</td><td>Ā</td></tr> <tr><td>6</td><td>Ā</td><td>13</td><td>A</td></tr> <tr><td>7</td><td>0V</td><td>14</td><td>+5V</td></tr> <tr><td>8</td><td></td><td></td><td></td></tr> </table> <p>(Driver Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	A	9	V	2	Ā	10	Ā	3	B	11	W	4	Ā	12	W	5	Z	13	+5V	6	Ā	14	0V	7	U	15	SHIELD	8	Ā			PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	W	8	Z	2	Ā	9	Ā	3	V	10	Ā	4	Ā	11	B	5	U	12	Ā	6	Ā	13	A	7	0V	14	+5V	8				<ol style="list-style-type: none"> <li>1. Motor Side Connector           <ol style="list-style-type: none"> <li>a. Cap Spec.(15 Position) : 172163-1(AMP)</li> <li>b. Socket Spec. : 170361-1(AMP)</li> </ol> </li> <li>2. Driver Side Connector(CN2)           <ol style="list-style-type: none"> <li>a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone)</li> <li>b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</li> </ol> </li> <li>3. Cable Spec. : 7P×0.2SQ or 7P×AWG24</li> </ol>
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	A	9	V																																																																											
2	Ā	10	Ā																																																																											
3	B	11	W																																																																											
4	Ā	12	W																																																																											
5	Z	13	+5V																																																																											
6	Ā	14	0V																																																																											
7	U	15	SHIELD																																																																											
8	Ā																																																																													
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	W	8	Z																																																																											
2	Ā	9	Ā																																																																											
3	V	10	Ā																																																																											
4	Ā	11	B																																																																											
5	U	12	Ā																																																																											
6	Ā	13	A																																																																											
7	0V	14	+5V																																																																											
8																																																																														
For Signal	Parallel Encoder Cable (Middle Capacity)	APCS-E□□BS	L7S□□□A L7NH□□□U L7PA□□□U	All Models of APM-SE, SEP APM-SF, SFP APM-APM-SG, SGP APM-LF APM-LG APM-HE SERIES	<p>Motor Side Connector</p> <table border="1"> <tr><th>PIN No.</th><th>Encoder Signal</th><th>PIN No.</th><th>Encoder Signal</th></tr> <tr><td>A</td><td>A</td><td>M</td><td>V</td></tr> <tr><td>B</td><td>Ā</td><td>N</td><td>Ā</td></tr> <tr><td>C</td><td>B</td><td>P</td><td>W</td></tr> <tr><td>D</td><td>Ā</td><td>R</td><td>Ā</td></tr> <tr><td>E</td><td>Z</td><td>H</td><td>+5V</td></tr> <tr><td>F</td><td>Ā</td><td>G</td><td>0V</td></tr> <tr><td>K</td><td>U</td><td>J</td><td>SHIELD</td></tr> <tr><td>L</td><td>Ā</td><td></td><td></td></tr> </table> <p>(Motor Side Connector)</p> <p>Drive Side Connector(CN2)</p> <table border="1"> <tr><th>PIN No.</th><th>Encoder Signal</th><th>PIN No.</th><th>Encoder Signal</th></tr> <tr><td>1</td><td>W</td><td>8</td><td>Z</td></tr> <tr><td>2</td><td>Ā</td><td>9</td><td>Ā</td></tr> <tr><td>3</td><td>V</td><td>10</td><td>Ā</td></tr> <tr><td>4</td><td>Ā</td><td>11</td><td>B</td></tr> <tr><td>5</td><td>U</td><td>12</td><td>Ā</td></tr> <tr><td>6</td><td>Ā</td><td>13</td><td>A</td></tr> <tr><td>7</td><td>0V</td><td>14</td><td>+5V</td></tr> <tr><td>8</td><td></td><td></td><td></td></tr> </table> <p>(Driver Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	A	A	M	V	B	Ā	N	Ā	C	B	P	W	D	Ā	R	Ā	E	Z	H	+5V	F	Ā	G	0V	K	U	J	SHIELD	L	Ā			PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	W	8	Z	2	Ā	9	Ā	3	V	10	Ā	4	Ā	11	B	5	U	12	Ā	6	Ā	13	A	7	0V	14	+5V	8				<ol style="list-style-type: none"> <li>1. Motor Side Connector(MS : Military Standard)           <ol style="list-style-type: none"> <li>a. Plug Spec. : MS3108B20-29S</li> </ol> </li> <li>2. Drive Side Connector(CN2)           <ol style="list-style-type: none"> <li>a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone)</li> <li>b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</li> </ol> </li> <li>3. Cable Spec. : 7P×0.2SQ or 7P×AWG24</li> </ol>
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
A	A	M	V																																																																											
B	Ā	N	Ā																																																																											
C	B	P	W																																																																											
D	Ā	R	Ā																																																																											
E	Z	H	+5V																																																																											
F	Ā	G	0V																																																																											
K	U	J	SHIELD																																																																											
L	Ā																																																																													
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																											
1	W	8	Z																																																																											
2	Ā	9	Ā																																																																											
3	V	10	Ā																																																																											
4	Ā	11	B																																																																											
5	U	12	Ā																																																																											
6	Ā	13	A																																																																											
7	0V	14	+5V																																																																											
8																																																																														

Note① □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Signal Cable [Serial]

Type	Product Type	Model Name <sup>Note1)</sup>	Applicable Drive	Applicable Motor	Specifications																																																														
For Signal	S Series Motor S-turn Encoder Cable (Small Ca- pacity)	APCS- E□□□CS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC SERIES	<p>1. Motor Side Connector</p> <ul style="list-style-type: none"> <li>a. Cap Spec.(9 Position) : 172161-1(AMP)</li> <li>b. Socket Spec. : 170361-1(AMP)</li> </ul> <p>2. Drive Side Connector(CN2)</p> <ul style="list-style-type: none"> <li>a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone)</li> <li>b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</li> </ul> <p>3. Cable Spec. : 3P×0.2SQ or 3P×24AWG</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>MA</td> <td>8</td> <td>-</td> </tr> <tr> <td>2</td> <td>MA</td> <td>9</td> <td>-</td> </tr> <tr> <td>3</td> <td>SLO</td> <td>10</td> <td>-</td> </tr> <tr> <td>4</td> <td>SLO</td> <td>11</td> <td>-</td> </tr> <tr> <td>5</td> <td>-</td> <td>12</td> <td>-</td> </tr> <tr> <td>6</td> <td>-</td> <td>13</td> <td>-</td> </tr> <tr> <td>7</td> <td>+5V</td> <td>14</td> <td>+5V</td> </tr> <tr> <td>8</td> <td>0V</td> <td>PLATE</td> <td>SHIELD</td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	MA	8	-	2	MA	9	-	3	SLO	10	-	4	SLO	11	-	5	-	12	-	6	-	13	-	7	+5V	14	+5V	8	0V	PLATE	SHIELD																										
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																
1	MA	8	-																																																																
2	MA	9	-																																																																
3	SLO	10	-																																																																
4	SLO	11	-																																																																
5	-	12	-																																																																
6	-	13	-																																																																
7	+5V	14	+5V																																																																
8	0V	PLATE	SHIELD																																																																
For Signal	S Series Motor M-turn Encoder Cable (Small Ca- pacity)	APCS- E□□□CSI	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC SERIES	<p>1. Motor Side Connector</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>MA</td> </tr> <tr> <td>2</td> <td>MA</td> </tr> <tr> <td>3</td> <td>SLO</td> </tr> <tr> <td>4</td> <td>SLO</td> </tr> <tr> <td>5</td> <td>VDD_B</td> </tr> <tr> <td>6</td> <td>GND_B</td> </tr> <tr> <td>7</td> <td>+5V</td> </tr> <tr> <td>8</td> <td>0V</td> </tr> <tr> <td>9</td> <td>SHIELD</td> </tr> </table> <p>2. Drive Side Connector(CN2)</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>-</td> <td>8</td> <td>-</td> </tr> <tr> <td>2</td> <td>-</td> <td>9</td> <td>-</td> </tr> <tr> <td>3</td> <td>MA</td> <td>10</td> <td>-</td> </tr> <tr> <td>4</td> <td>MA</td> <td>11</td> <td>-</td> </tr> <tr> <td>5</td> <td>SLO</td> <td>12</td> <td>-</td> </tr> <tr> <td>6</td> <td>SLO</td> <td>13</td> <td>-</td> </tr> <tr> <td>7</td> <td>0V</td> <td>14</td> <td>+5V</td> </tr> <tr> <td>8</td> <td>PLATE</td> <td>SHIELD</td> <td>-</td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p> <p>3. Battery Connector Spec. : 5267-02A(MOLEX)</p> <p>4. Battery Connector Spec. : 5267-02A(MOLEX)</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>1</td> <td>BATTERY (MOD_B)</td> </tr> <tr> <td>2</td> <td>BATTERY (GND_B)</td> </tr> </table> <p>(Battery Connector)</p>	PIN No.	Encoder Signal	1	MA	2	MA	3	SLO	4	SLO	5	VDD_B	6	GND_B	7	+5V	8	0V	9	SHIELD	PIN No.	Encoder Signal	PIN No.	Encoder Signal	1	-	8	-	2	-	9	-	3	MA	10	-	4	MA	11	-	5	SLO	12	-	6	SLO	13	-	7	0V	14	+5V	8	PLATE	SHIELD	-	PIN No.	Encoder Signal	1	BATTERY (MOD_B)	2	BATTERY (GND_B)
PIN No.	Encoder Signal																																																																		
1	MA																																																																		
2	MA																																																																		
3	SLO																																																																		
4	SLO																																																																		
5	VDD_B																																																																		
6	GND_B																																																																		
7	+5V																																																																		
8	0V																																																																		
9	SHIELD																																																																		
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																
1	-	8	-																																																																
2	-	9	-																																																																
3	MA	10	-																																																																
4	MA	11	-																																																																
5	SLO	12	-																																																																
6	SLO	13	-																																																																
7	0V	14	+5V																																																																
8	PLATE	SHIELD	-																																																																
PIN No.	Encoder Signal																																																																		
1	BATTERY (MOD_B)																																																																		
2	BATTERY (GND_B)																																																																		
For Signal	S/F Series Mo- tor S-turn Encoder Cable (Middle Capacity)	APCS- E□□□DS	L7S□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SE, FE, SEP, FEP APM-SF, FF SFP, FFP APM-SG, FG SGP, FGP APM-LF APM-LG SERIES	<p>1. Motor Side Connector(MS : Military Standard)</p> <ul style="list-style-type: none"> <li>a. Plug Spec. : MS3108B20-29S</li> </ul> <p>2. Drive Side Connector(CN2)</p> <ul style="list-style-type: none"> <li>a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone)</li> <li>b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone)</li> </ul> <p>3. Cable Spec. : 3P×0.2SQ or 3P×24AWG</p> <table border="1"> <tr> <td>PIN No.</td> <td>Encoder Signal</td> <td>PIN No.</td> <td>Encoder Signal</td> </tr> <tr> <td>A</td> <td>MA</td> <td>M</td> <td>-</td> </tr> <tr> <td>B</td> <td>MA</td> <td>N</td> <td>-</td> </tr> <tr> <td>C</td> <td>SLO</td> <td>P</td> <td>-</td> </tr> <tr> <td>D</td> <td>SLO</td> <td>R</td> <td>-</td> </tr> <tr> <td>E</td> <td>-</td> <td>H</td> <td>+5V</td> </tr> <tr> <td>F</td> <td>-</td> <td>G</td> <td>0V</td> </tr> <tr> <td>K</td> <td>-</td> <td>J</td> <td>SHIELD</td> </tr> <tr> <td>L</td> <td>-</td> <td>-</td> <td>-</td> </tr> </table> <p>(Motor Side Connector) (Drive Side Connector)</p>	PIN No.	Encoder Signal	PIN No.	Encoder Signal	A	MA	M	-	B	MA	N	-	C	SLO	P	-	D	SLO	R	-	E	-	H	+5V	F	-	G	0V	K	-	J	SHIELD	L	-	-	-																										
PIN No.	Encoder Signal	PIN No.	Encoder Signal																																																																
A	MA	M	-																																																																
B	MA	N	-																																																																
C	SLO	P	-																																																																
D	SLO	R	-																																																																
E	-	H	+5V																																																																
F	-	G	0V																																																																
K	-	J	SHIELD																																																																
L	-	-	-																																																																

**Note1)** □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

## Servo Motor Option

## ■ Signal Cable [Serial]

Type	Product Type	Model Name(Kind)	Applicable Drive	Applicable Motor	Specifications
For Signal	S/F Series Motor M-turn Encoder Cable (Middle Capacity)	APCS-E□□□DS1	L7S□□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-SE, FE SEP,FEP APM-SF, FF SFP,FPP APM-SG, FG, SGP,FGP APM-HF APM-LG SERIES	<p>1. Motor Side Connector(MS : Military Standard) a. Plug Spec. : MS3108B20-29S 2. Drive Side Connector(CN2) a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 4P×0.25Q or 4P×24AWG 4. Battery Connector Spec. : 5267-02A(MOLEX)</p>
For Signal	F Series Motor S-turn Encoder Cable (Small Capacity)	APCS-E□□□ES-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-FAL APM-FB, FBL APM-FC, FCL SERIES	<p>1. Motor Side Connector a. Cap Spec. : 2201825-(Tyco) b. Socket Spec. : 2174065-4(Tyco) 2. Drive Side Connector(CN2) a. Case Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 3P×0.25Q or 3P×24AWG</p>
For Signal	F Series Motor M-turn Encoder Cable (Small Capacity)	APCS-E□□□ES1-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-FAL APM-FB, FBL APM-FC, FCL SERIES	<p>1. Motor Side Connector a. Cap Spec. : 2201825-(Tyco) b. Socket Spec. : 2174065-4(Tyco) 2. Drive Side Connector(CN2) a. Cap Spec. : 10314-52A0-008(3M) or SM-14J(Suntone) b. Connector Spec. : 10114-3000VE(3M) or SM-14J(Suntone) 3. Cable Spec. : 4P×0.25Q or 4P×24AWG 4. Battery Connector Spec. : 5267-02A(MOLEX)</p>

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).  
(Front Type : No mark, Rear Type : -R)

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Power Cable [200V]

Type	Product Type	Model Name <sup>Note1)</sup>	Applicable Drive	Applicable Motor	Specifications										
For Power	S Series Power Cable (Small Capacity)	APCS-P□□□GS	L7SA□□□A L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>U</td> </tr> <tr> <td>2</td> <td>V</td> </tr> <tr> <td>3</td> <td>W</td> </tr> <tr> <td>4</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector  a. Cap Spec.(4 Position) : 172159-1(AMP)  b. Socket Spec. : 170362-1(AMP)</p> <p>2. Drive Side Connector(U, V, W, FG)  a. U, V, W Pin Spec. : 1512  b. FG Pin Spec. : 1.54x4(Ring Terminal)</p> <p>3. Cable Spec. : 4C X 0.75SQ or 4C X 18AWG</p>	PIN No.	Signal	1	U	2	V	3	W	4	Ground
PIN No.	Signal														
1	U														
2	V														
3	W														
4	Ground														
For Power	S Series Brake Cable (Small Capacity)	APCS-P□□□KB	L7SA□□□A L7NHA□□□U L7PA□□□U	All Models of APM-SA APM-SB APM-SC APM-HB SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>BK+</td> </tr> <tr> <td>2</td> <td>BK-</td> </tr> </table> <p>1. Motor Side Connector  a. Cap Spec.(2 Position) : 172157-1(AMP)  b. Socket Spec. : 170362-1(AMP)</p> <p>2. Drive Side Connector  a. Connecting terminal Spec. : 1.5x3(Ring Terminal)</p> <p>3. Cable Spec. : 2C X 0.75SQ or 2C X 18AWG</p>	PIN No.	Signal	1	BK+	2	BK-				
PIN No.	Signal														
1	BK+														
2	BK-														
For Power	F Series Power Cable (Small Capacity)	APCS-P□□□FS-□	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-FB APM-FC SERIES	<table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>W</td> </tr> <tr> <td>2</td> <td>V</td> </tr> <tr> <td>3</td> <td>U</td> </tr> <tr> <td>4</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector  a. Plug Spec. : KN5FT04SJ1(JAE)  b. Socket Spec. : ST-KN-S-C1B-3500(JAE)</p> <p>2. Drive Side Connector(U, V, W, FG)  a. U, V, W Pin Spec. : 1512  b. FG Pin Spec. : 1.5X4(Ring Terminal)</p> <p>3. Cable Spec. : 4C X 0.75SQ or 4C X 18AWG</p>	PIN No.	Signal	1	W	2	V	3	U	4	Ground
PIN No.	Signal														
1	W														
2	V														
3	U														
4	Ground														



**Note1)** □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

**Note2)** In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).  
(Front Type : No mark, Rear Type : -R)

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

## Servo Motor Option

### ■ Power Cable [200V]

Type	Product Type	Model Name(Kind)	Applicable Drive	Applicable Motor	Specifications										
For Power	L Series Power Cable (Small Capacity)	APCS-P□□□LS-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APMC-FAL APMC-FBL APMC-FCL SERIES	<p>Motor Side Connector</p>  <p>Drive Side Connector</p>  <p>1. Motor Side Connector      a. Plug Spec. : SM-JN8FT04(Suntone)      b. Socket Spec. : SMS-201(Suntone)</p> <p>2. Drive Side Connector (U,V,W,FG)      a. U, V, W Pin Spec. : 1512(Ferrule)      b. FG Pin Spec. : 1.5x4 (Ring Terminal)</p> <p>3. Cable Spec. : 4Cx0.75SQ or 4Cx18AWG</p> <p>4. In case of FAL products,      Please install Power Cable first before connecting Encoder Cable.</p>										
For Power	Brake Cable for Flat Motor (Small Capacity)	APCS-B□□□QS-□	L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-FAL APM-FBL APM-FC. FCL SERIES	<p>Motor Side Connector</p>  <p>Brake Power side Connector</p>  <p>Front Direction      Rear Direction</p> <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>1</td> <td>U</td> </tr> <tr> <td>2</td> <td>V</td> </tr> <tr> <td>3</td> <td>W</td> </tr> <tr> <td>FG</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector      a. Plug Spec. : KN5FT02SJ1      b. Socket Spec. : ST-KN-S-C1B-3500</p> <p>2. Drive Side Connector      a. Connecting terminal Spec. : 1.5X3(Ring Terminal)</p> <p>3. Cable Spec. : 2Cx0.75SQ or 2Cx18AWG</p>	PIN No.	Signal	1	U	2	V	3	W	FG	Ground
PIN No.	Signal														
1	U														
2	V														
3	W														
FG	Ground														
For Power	Power Cable (Middle Capacity)	APCS-P□□□HS	L7SA□□□A L7SA□□□B L7NA□□□B L7NH□□□U L7PA□□□U	All Models of APM-SE APM-FE APM-HE SERIES	<p>Motor Side Connector</p>  <p>Drive Side Connector</p>  <table border="1"> <tr> <th>PIN No.</th> <th>Signal</th> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector      a. Plug Spec. : MS3108B20-4S(MS)</p> <p>2. Drive Side Connector      a. U, V, W Pin Spec. : 2512      b. FG Pin Spec. : 2.5X4(Ring Terminal)</p> <p>3. Cable Spec. : 4Cx2.5SQ or 4Cx14AWG</p>	PIN No.	Signal	A	U	B	V	C	W	D	Ground
PIN No.	Signal														
A	U														
B	V														
C	W														
D	Ground														

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of □ marked product, the connector can draw in a direction of Front(load) / Rear(half load).  
 (Front Type : No mark, Rear Type : -R)

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Power Cable [200V]





Type	Product Type	Model Name <sup>(1)</sup>	Applicable Drive	Applicable Motor	Specifications
For Power	Power Cable (Brake Type)	APCS-P□□□NB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All Models of APM-SE APM-FE SERIES	<p>1. Motor Side Connector a. Plug Spec. : MS3108B20-15S(MS) 2. Drive Side Connector a. U, V, W Pin Spec. : 2012 b. Cable Spec. : 4C×2.5SQ or 4C×14AWG c. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Brake Power side Connector a. BK Pin Spec. : 1.5×3(Ring Terminal) b. Cable Spec. : 2C×0.75SQ or 2C×18AWG</p>
For Power	Power Cable (Middle Capacity)	APCS-P□□□S	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF30A SF22D, LF35D SF20G, LF30G SF12M, SF20M LF30M, SG22D LG35D, SG20G LG30G, SG12M SG20M, LG30M FF30A, FF22D FF35D, FF20G FF30G, FF12M FF20M, FF30M FG22D, FG35D FG20G, FG30G FG12M, FG20M FG30M	<p>1. Motor Side Connector a. Plug Spec. : MS3108B22-22S(MSA) 2. Drive Side Connector a. U, V, W Pin Spec. : 2512 b. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Cable Spec. : 4C×2.5SQ or 4C14AWG</p>
For Power	Power Cable (Brake Type)	APCS-P□□□PB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	APM-SF30A SF22D, LF35D SF20G, LF30G SF12M, SF20M LF30M, FF30A FF22D, FF35D FF20G, FF30G FF12M, FF20M FF30M	<p>1. Motor Side Connector a. PLUG Spec. : MS3108B24-10S(MS) 2. Drive Side Connector a. U, V, W Pin Spec. : 2512 b. Cable Spec. : 4C×2.5SQ or 4C×14AWG c. FG Pin Spec. : 2.5×4(Ring Terminal) 3. Brake Power side Connector a. BK Pin Spec. : 1.5×3(Ring Terminal) b. Cable Spec. : 2C×0.75SQ or 2C×18AWG</p>

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

## Servo Motor Option

### ■ Power Cable [200V]

Type	Product Type	Model Name <sup>(1)</sup>	Applicable Drive	Applicable Motor	Specifications
For Power	Power Cable (Middle Capacity)	APCS-P□□□US	L7SA□□□A L7SA□□□B L7NA□□□B L7NHAD□□U L7PA□□□U	APM-SF50A SF55D, SF75D SF44G, SF60G SF44M, SG55D SG75D, SG44G SG60G, SG44M FF50A, FF55D FF75D, FF44G FF60G, FF44M FG55D, FG75D FG44G, FG60G FG44M	 <p>1. Motor Side Connector a. Plug Spec. : MS3108B22-22S(MS) 2. Drive Side Connector a. Connecting terminal Spec. : 6X5(Ring Terminal) 3. Cable Spec. : 4C×6SQ or 4C×10AWG</p>
For Power	Power Cable (Brake Type)	APCS-P□□□LB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHAD□□U L7PA□□□U	APM-SF50A SF55D, SF75D SF44G, SF60G SF44M, FF50A FF50D, FF75D FF44G, FF60G FF40M	 <p>1. Motor Side Connector a. Plug Spec. : MS3108A24-10S(MS) 2. Drive Side Connector a. Connecting terminal Spec. : 6X5(Ring Terminal) b. 4C×6SQ or 4C×10AWG 3. Brake Power side Connector a. Connecting terminal Spec. : 125X3(Ring Terminal) b. Cable Spec. : 2C×0.75SQ or 2C×8AWG</p>
For Power	Power Cable (Middle Capacity)	APCS-P□□□MS	L7SA□□□A L7SA□□□B L7NA□□□B L7NHAD□□U L7PA□□□U	APM-SG60M SP75G, FF75G	 <p>1. Motor Side Connector a. Plug Spec. : MS3108B32-17S(MS) 2. Drive Side Connector a. Connecting terminal Spec. : 10X8(Ring Terminal) 3. Cable Spec. : 4C×10SQ or 4C×8AWG</p>
For Power	Brake Cable	APCS-P□□□SB	L7SA□□□A L7SA□□□B L7NA□□□B L7NHAD□□U L7PA□□□U	All Models of APM-SG APM-LG APM-FG SERIES	 <p>1. Motor Side Connector a. Plug Spec. : MS3108B 14S-7S(MS) 2. Drive Side Connector a. Connecting terminal Spec. : 1.5X3(Ring Terminal) 3. Cable Spec. : 2C×0.75SQ or 2C×10AWG</p>







Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
General Cable(N)	N03	N05	N10	N20
Robotic Cable(F)	F03	F05	F10	F20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Power Cable [400V]

Type	Product Type	Model Name <sup>(1)</sup>	Applicable Drive	Applicable Motor	Specifications															
For Power	Power Cable	APCF-P□□□HS	L7SB□□□B L7NHB□□□U	All Models of APM-SEP APM-FEP SERIES	  <table border="1"> <tr><th>Pin No.</th><th>Signal</th></tr> <tr><td>A</td><td>U</td></tr> <tr><td>B</td><td>V</td></tr> <tr><td>C</td><td>W</td></tr> <tr><td>D</td><td>Ground</td></tr> </table> <p>1. Motor Side Connector  a. Plug Spec. : MS3108A 20-4S(MS)  2. Drive Side Connector (U,V,W,FG)  a. U, V, W Pin Spec. : 1512(Ferrule)  b. FG Pin Spec. : 1.5x4(Ring Terminal)  3. Cable Spec. : 4Cx1.5SQ or 4Cx15AWG</p>		Pin No.	Signal	A	U	B	V	C	W	D	Ground				
Pin No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
For Power (Brake Type)	Power Cable	APCF-P□□□NB	L7SB□□□B L7NHB□□□U	All Models of APM-SEP APM-FEP SERIES	  <table border="1"> <tr><th>Pin No.</th><th>Signal</th></tr> <tr><td>A</td><td>U</td></tr> <tr><td>B</td><td>V</td></tr> <tr><td>C</td><td>W</td></tr> <tr><td>D</td><td>Ground</td></tr> <tr><td>E</td><td>BK+</td></tr> <tr><td>F</td><td>BK-</td></tr> </table> <p>1. Motor Side Connector  a. Plug Spec. : MS3108A 20-15S(MS)  2. Drive Side Connector  a. U, V, W Pin Spec. : 1512(Ferrule)  b. FG Pin Spec. : 1.5 x 4(Ring Terminal)  3. Power Cable Spec. : 4Cx1.5SQ or 4Cx15AWG  4. Brake Power side Connector  a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal)  5. Brake Cable Spec. : 20x0.75SQ or 20x19AWG</p>		Pin No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
Pin No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			
E	BK+																			
F	BK-																			
For Power	Power Cable	APCF-P□□□IS	L7SB□□□B L7NHB□□□U	APM-[S/F]FP30A [S/F]FP22D, [S/F]FP35D [S/F]FP20G, FFP30G [S/F]FP12M, [S/F]FP20M [S/F]GP22D, [S/F]GP35D [S/F]GP20G, FGP30G [S/F]GP12M, [S/F]GP20M	  <table border="1"> <tr><th>Pin No.</th><th>Signal</th></tr> <tr><td>A</td><td>U</td></tr> <tr><td>B</td><td>V</td></tr> <tr><td>C</td><td>W</td></tr> <tr><td>D</td><td>Ground</td></tr> </table> <p>1. Motor Side Connector  a. Plug Spec. : MS3108A 22-22S(MS)  2. Drive Side Connector (U,V,W,FG)  a. U, V, W Pin Spec. : 2512(Ferrule)  b. FG Pin Spec. : 2.5x4 (Ring Terminal)  3. Cable Spec. : 4Cx2.5SQ or 4Cx14AWG</p>		Pin No.	Signal	A	U	B	V	C	W	D	Ground				
Pin No.	Signal																			
A	U																			
B	V																			
C	W																			
D	Ground																			




Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

## Servo Motor Option

### ■ Power Cable [400V]

Type	Product Type	Model Name <sup>(*)</sup>	Applicable Drive	Applicable Motor	Specifications														
For Power	Power Cable (Brake Type)	APCF-P□□□PB	L7SB□□□B L7NHB□□□U	APM-[S/F]FP30A [S/F]FP2D, [S/F]FP35D [S/F]FP20G, FFP30G [S/F]FP12M, [S/F]FP20M [S/F]GP22D, [S/F]GP35D [S/F]GP20G, FGP30G [S/F]GP12M, [S/F]GP20M	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table> <ol style="list-style-type: none"> <li>1. Motor Side Connector           <ol style="list-style-type: none"> <li>a. Plug Spec. : MS3108A 24-10S(MS)</li> </ol> </li> <li>2. Drive Side Connector           <ol style="list-style-type: none"> <li>a. U, V, W Pin Spec. : 2512(Ferrule)</li> <li>b. FG Pin Spec. : 2.5 x 4(Ring Terminal)</li> </ol> </li> <li>3. Power Cable Spec. : 4Cx2.5SQ or 4Cx14AWG</li> <li>4. Brake Power side Connector           <ol style="list-style-type: none"> <li>a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal)</li> </ol> </li> <li>5. Brake Cable Spec. : 2Cx0.75SQ or 2Cx19AWG</li> </ol>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
E	BK+																		
F	BK-																		
For Power	Power Cable (Middle Capacity)	APCF-P□□□QS	L7SB□□□B L7NHB□□□U	APM-[S/F]FP50A [S/F]FP55D, [S/F]FP75D SFP30G, [S/F]FP44G [S/F]FP60G, [S/F]FP30M [S/F]FP44M, [S/F]GP55D [S/F]GP75D, SGP30G [S/F]GP44G, [S/F]GP60G [S/F]GP30M, [S/F]GP44M	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <ol style="list-style-type: none"> <li>1. Motor Side Connector           <ol style="list-style-type: none"> <li>a. Plug Spec. : MS3108A 22-22S(MS)</li> </ol> </li> <li>2. Drive Side Connector (U,V,W,FG)           <ol style="list-style-type: none"> <li>a. U, V, W Pin Spec. : 4.0x 5(Ring Terminal)</li> </ol> </li> <li>3. Cable Spec. : 4Cx4.0SQ or 4Cx11AWG</li> </ol>	PIN No.	Signal	A	U	B	V	C	W	D	Ground				
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
For Power	Power Cable (Brake Type)	APCF-P□□□LB	L7SB□□□B L7NHB□□□U	APM-[S/F]FP50A [S/F]FP55D, [S/F]FP75D SFP30G, [S/F]FP44G [S/F]FP60G, [S/F]FP30M [S/F]FP44M	 <p>Motor Side Connector</p> <p>Drive Side Connector</p> <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> <tr> <td>E</td> <td>BK+</td> </tr> <tr> <td>F</td> <td>BK-</td> </tr> </table> <ol style="list-style-type: none"> <li>1. Motor Side Connector           <ol style="list-style-type: none"> <li>a. Plug Spec. : MS3108A 24-10S(MS)</li> </ol> </li> <li>2. Drive Side Connector           <ol style="list-style-type: none"> <li>a. U, V, W Pin Spec. : 4.0X5(Ring Terminal)</li> </ol> </li> <li>3. Power Cable Spec. : 4Cx4.0SQ or 4Cx11AWG</li> <li>4. Brake Power side Connector           <ol style="list-style-type: none"> <li>a. Connecting terminal Spec. : 1.5 x 3(Ring Terminal)</li> </ol> </li> <li>5. Brake Cable Spec. : 2Cx0.75SQ or 2Cx19AWG</li> </ol>	PIN No.	Signal	A	U	B	V	C	W	D	Ground	E	BK+	F	BK-
PIN No.	Signal																		
A	U																		
B	V																		
C	W																		
D	Ground																		
E	BK+																		
F	BK-																		

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.




Note2) In case of 400V products, you can use Robotic Cable only.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Power Cable [400V]

Type	Product Type	Model Name <sup>(1)</sup>	Applicable Drive	Applicable Motor	Specifications											
For Power	Power Cable (Middle Capacity)	APCF-P□□□MS	L7SB□□□B L7NHB□□□U	APM-[S/F]FP75G [S/F]GP110D, [S/F]GP85G [S/F]GP10G, [S/F]GP150G [S/F]GP60M	 <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>A</td> <td>U</td> </tr> <tr> <td>B</td> <td>V</td> </tr> <tr> <td>C</td> <td>W</td> </tr> <tr> <td>D</td> <td>Ground</td> </tr> </table> <p>1. Motor Side Connector a. PLUG Spec. : MS3108A 32-17S(MS) 2. Drive Side Connector(U,V,W,FG) a. U, V, W Pin Spec. : 10x5(Ring Terminal) 3. Cable Spec. : 4Cx10SQ or 4Cx7AWG</p>		PIN No.	Signal	A	U	B	V	C	W	D	Ground
PIN No.	Signal															
A	U															
B	V															
C	W															
D	Ground															
For Power	Brake Cable (same with 200V)	APCS-P□□□SB	L7SB□□□B L7NHB□□□U	All Models of APM-SGP APM-FGP SERIES	 <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> </tr> <tr> <td>1</td> <td>BK+</td> </tr> <tr> <td>2</td> <td>BK-</td> </tr> </table> <p>1. Motor Side Connector a. Plug Spec. : MS3108B 14-7S(MS) 2. Brake Power side Connector a. Connecting terminal Spec. : 1.5x3(Ring Terminal) 3. Cable Spec. : 2Cx0.75SQ or 2Cx19AWG</p>		PIN No.	Signal	1	BK+	2	BK-				
PIN No.	Signal															
1	BK+															
2	BK-															
Battery For Encoder	Battery Ass'y	APCS-BATT36	All L7 Drives for M-turn	All Model of APM-F Series	 <table border="1"> <tr> <td>PIN No.</td> <td>Signal</td> <td>Color</td> </tr> <tr> <td>1</td> <td>+</td> <td>Red</td> </tr> <tr> <td>2</td> <td>-</td> <td>Black</td> </tr> </table> <p>1. PLUG Spec. : 5264-02 (Molex) 2. PLUG Pin Spec. : 5263PBT (Molex) 3. Battery Spec. : ER6V/3.6V, 2000mAh (TOSHIBA)</p>		PIN No.	Signal	Color	1	+	Red	2	-	Black	
PIN No.	Signal	Color														
1	+	Red														
2	-	Black														


Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Note2) In case of 400V products, you can use Robotic Cable only.



Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20

## Servo Motor Option

### ■ DDMotor Signal Cable

Type	Product type	Model Name (Note)	Applicable Motor	Specifications	Specifications																																																			
For Signal	L7 Encoder Cable	APCS-E□□ZS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	All models of DD motor	 <p>D-D SERVO SIGNAL CABLE</p> <p>Encoder Connector:</p> <table border="1"> <tr><td>No.</td><td>Pin No.</td><td>Function</td></tr> <tr><td>1</td><td>MA</td><td>9 +5V</td></tr> <tr><td>2</td><td>SLO</td><td>10 GND</td></tr> <tr><td>3</td><td>1</td><td>10 GND</td></tr> <tr><td>4</td><td>OV</td><td>2</td></tr> <tr><td>5</td><td>Shield</td><td>3</td></tr> <tr><td>6</td><td>MA</td><td>4 MA</td></tr> <tr><td>7</td><td>SLO</td><td>5 GND</td></tr> </table> <p>Driver Connector:</p> <table border="1"> <tr><td>No.</td><td>Pin No.</td><td>Function</td></tr> <tr><td>1</td><td>9</td><td>5V</td></tr> <tr><td>2</td><td>8</td><td>GND</td></tr> <tr><td>3</td><td>MA</td><td>10 MA</td></tr> <tr><td>4</td><td>MA</td><td>11 MA</td></tr> <tr><td>5</td><td>SLO</td><td>12 SLO</td></tr> <tr><td>6</td><td>OV</td><td>13 GND</td></tr> <tr><td>7</td><td>MA</td><td>14 +5V</td></tr> <tr><td>8</td><td>Shield</td><td>15 GND</td></tr> </table> <p>(Motor Connector)      (Driver Connector)</p> <p>1. Motor Side Connector      a. Connector(D-SUB) : DA-15PF-N(Female connector)      b. Connector CASE(D-SUB) : SK-15H-1A</p> <p>2. Drive Side Connector      a. CASE Spec. : 10314-52A0-008(3M)      b. Connector Spec. : 10114-3000VE(3M)</p> <p>3. Cable Spec. : 3P×0.2SQ</p>	No.	Pin No.	Function	1	MA	9 +5V	2	SLO	10 GND	3	1	10 GND	4	OV	2	5	Shield	3	6	MA	4 MA	7	SLO	5 GND	No.	Pin No.	Function	1	9	5V	2	8	GND	3	MA	10 MA	4	MA	11 MA	5	SLO	12 SLO	6	OV	13 GND	7	MA	14 +5V	8	Shield	15 GND
No.	Pin No.	Function																																																						
1	MA	9 +5V																																																						
2	SLO	10 GND																																																						
3	1	10 GND																																																						
4	OV	2																																																						
5	Shield	3																																																						
6	MA	4 MA																																																						
7	SLO	5 GND																																																						
No.	Pin No.	Function																																																						
1	9	5V																																																						
2	8	GND																																																						
3	MA	10 MA																																																						
4	MA	11 MA																																																						
5	SLO	12 SLO																																																						
6	OV	13 GND																																																						
7	MA	14 +5V																																																						
8	Shield	15 GND																																																						

### ■ DDMotor Power Cable

Type	Product type	Model Name (Note)	Applicable Motor	Specifications	Specifications
For Signal	L7 Power Cable	APCS-P□□YS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	DB03D DB06D DB09D DC06D DC12D DC18D DD12D DD22D DD34D DE40D DE60D	 <p>1. Motor Side Connector      a. PLUG Spec. : NJC-24-4-ADF(Female connector)</p> <p>2. Drive Side Connector      a. U, V, W Pin PG Pin Spec. : UA-F2012(Seal)      b. FG Spec. : 1.5×4</p> <p>3. Cable Spec. : 4C×1.5SQ, LAPP Cable(P/N : 00257001)</p> <p>(Drive side connector)</p> <p>Motor Side Connector      Item      Lead Wire      Pin No.      Color      U      1      Red      V      2      White      W      3      Black      Ground      4      Green</p>
For Signal	L7 Power Cable	APCS-P□□ZS	L7SA□□□B L7NA□□□B L7NHA□□□U L7PA□□□U	DFA1G DFA6G	 <p>1. Motor Side Connector      a. PLUG Spec. : NJC-24-4-ADF(Female connector)</p> <p>2. Drive Side Connector      a. U, V, W Pin PG Pin Spec. : UA-F2012(Seal)      b. FG Spec. : 2.5×4</p> <p>3. Cable Spec. : 4C×2.5SQ, LAPP Cable(P/N : 00257011)</p> <p>(Drive side connector)</p> <p>Motor Side Connector      Item      Lead Wire      Pin No.      Color      U      1      Red      V      2      White      W      3      Black      Ground      4      Green</p>

Note1) □□□ of Model Name indicates the kind and length of cable. And the declaration is as below.

Cable Length(m)	3	5	10	20
Robotic Cable(F)	F03	F05	F10	F20
General Cable(N)	N03	N05	N10	N20

# L7 SERIES SYSTEM

## Servo Motor Option

### ■ Signal Cable

Type	Product type	Model Name <sup>(Note)</sup>	Applicable Motor	Specifications	
For Signal	CN1 Cable	APC-CN1□□A	L7S SERIES L7P SERIES	[Upper Controller]	[Drive Connection Side CN1] Indicates Pin No
		(Pin No. Display)			
For Signal	CN1 Cable	APCS-CN1□□A	L7N SERIES L7NH SERIES	[Upper Controller]	[Drive Connection Side CN1] Indicates Pin No
		(Pin No. Display)			
For Power	Communication Cable	APCS-CN5L7U	All Models of L7 SERIES	[PC – USB Port]	[Servo Drive – CN5] 




**Note1)** □□ of Model Name indicates the kind and length of cable And the designation is as below.

Cable Length(m)	1	2	3	5
General Cable(N)	01	02	03	05

CN1 cable : 1m, 2m, 3m and 5m are available.

## Servo Drive Option

### ■ Signal Cable / Connector

Type	Product Type	Model Name (Note)	Applicable Drive	Specifications
T/B	CN1 T/B	APC-VSCN1T -□□	L7S SERIES	 <p>1. Extended CN1 T/B for VS/L7S      2. Available Cable Length : 0.5[m], 1[m], 1.5[m], 2[m], 3[m]</p>
T/B	CN1 T/B	APCS-L7NCN1T -□□	L7N SERIES	 <p>1. Extended CN1 T/B for L7N      2. Available Cable Length : 0.5[m], 1[m], 1.5[m], 2[m]</p>
CN	CN1 Connector	APC-CN1NNA	L7S SERIES	 <p>1. Case Spec. : 10350-52A0-008(3M)      2. Connector Spec. : 10150-3000VE(3M)</p>

Note) □□ of Model Name indicates the kind and length of cable. And the declaration is as below.

\*APC-VSCN1T

\*APCS-L7NCN1T





Cable Length(m)	0.5	1	1.5	2	3
Declaration	None	01	015	02	03

Cable Length(m)	0.5	1	1.5	2
Declaration	None	01	015	02

# L7 SERIES SYSTEM

## Servo Drive Option




### ■ Connector

Type	Product Type	Model Name	Applicable Drive	Specifications																															
CN	CN1 Connector	APC-CN2NNA	L7NA□□□B L7NH□□□U	 <p>1. Case Spec. : 10320-52A0-008(3M) 2. Connector Spec. : 10120-3000VE(3M)</p>																															
CN	CN2 Connector	APC-CN3NNA	All Models of L7 SERIES	 <p>1. Case Spec. : 10314-52A0-008(3M) 2. Connector Spec. : 10114-3000VE(3M)</p>																															
CN	CN3 CN4 EtherCAT Connector	APCS-CN4NNA	L7NA□□□B L7NH□□□U	 <table border="1"> <thead> <tr> <th>PIN No.</th> <th>Signal</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>TX/RXD Plus</td> <td>White/Orange</td> </tr> <tr> <td>2</td> <td>TX/RXD Minus</td> <td>Orange</td> </tr> <tr> <td>3</td> <td>TX/RXI Plus</td> <td>White/Orange</td> </tr> <tr> <td>4</td> <td>TX/RXI Minus</td> <td>Blue</td> </tr> <tr> <td>5</td> <td>TX/RX2 Plus</td> <td>White/Blue</td> </tr> <tr> <td>6</td> <td>TX/RX2 Minus</td> <td>Green</td> </tr> <tr> <td>7</td> <td>TX/RX3 Plus</td> <td>White/Brown</td> </tr> <tr> <td>8</td> <td>TX/RX3 Minus</td> <td>Brown</td> </tr> <tr> <td>Plate</td> <td></td> <td>SHIELD</td> </tr> </tbody> </table> <p>Note) EtherCAT use only 4wires(1, 2, 3, 6)</p>	PIN No.	Signal	Color	1	TX/RXD Plus	White/Orange	2	TX/RXD Minus	Orange	3	TX/RXI Plus	White/Orange	4	TX/RXI Minus	Blue	5	TX/RX2 Plus	White/Blue	6	TX/RX2 Minus	Green	7	TX/RX3 Plus	White/Brown	8	TX/RX3 Minus	Brown	Plate		SHIELD	
PIN No.	Signal	Color																																	
1	TX/RXD Plus	White/Orange																																	
2	TX/RXD Minus	Orange																																	
3	TX/RXI Plus	White/Orange																																	
4	TX/RXI Minus	Blue																																	
5	TX/RX2 Plus	White/Blue																																	
6	TX/RX2 Minus	Green																																	
7	TX/RX3 Plus	White/Brown																																	
8	TX/RX3 Minus	Brown																																	
Plate		SHIELD																																	
CN	STO Cable	APCS-STO□□A	L7NA□□□B L7NH□□□U	 <table border="1"> <thead> <tr> <th>PIN No.</th> <th>KI Signal</th> <th>Color</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>NC</td> <td></td> </tr> <tr> <td>2</td> <td>NC</td> <td></td> </tr> <tr> <td>3</td> <td>HWE1 Minus</td> <td>Orange</td> </tr> <tr> <td>4</td> <td>HWE1 Plus</td> <td>Orange</td> </tr> <tr> <td>5</td> <td>HWE2 Minus</td> <td>Yellow</td> </tr> <tr> <td>6</td> <td>HWE2 Plus</td> <td>Yellow</td> </tr> <tr> <td>7</td> <td>EDM Plus</td> <td>White</td> </tr> <tr> <td>8</td> <td>EDM Minus</td> <td>White</td> </tr> </tbody> </table> <p>1. Cable Length Only 0.3[m], 1[m], 3[m] of Cable is available to use. 2. Connector Model Name : APCS-STO00A * Caution During assembly of connector, It can be broken easily without guaranty of LS Mecapion.</p>	PIN No.	KI Signal	Color	1	NC		2	NC		3	HWE1 Minus	Orange	4	HWE1 Plus	Orange	5	HWE2 Minus	Yellow	6	HWE2 Plus	Yellow	7	EDM Plus	White	8	EDM Minus	White				
PIN No.	KI Signal	Color																																	
1	NC																																		
2	NC																																		
3	HWE1 Minus	Orange																																	
4	HWE1 Plus	Orange																																	
5	HWE2 Minus	Yellow																																	
6	HWE2 Plus	Yellow																																	
7	EDM Plus	White																																	
8	EDM Minus	White																																	

## Other Options

## ■ 200V Braking Resistor

\* Option braking resistors are selectable items for user's need.

Type	Product Type	Model Name <small>(Note)</small>	Applicable Drive	Specifications
Resistor	Braking Resistor	APCS-140R50	L7□A001□ L7□A002□ L7□A004□	 <p>IRH 140W 50ohm</p>
Resistor	Braking Resistor	APCS-300R30	L7□A008□ L7□A010□	 <p>IRV 300W 30ohm</p>
Resistor	Braking Resistor	APC-600R30	L7□A020□ L7□A035□	
		APC-600R28	L7□A050□ (4P)	<p>IRV 600S 30ohm      I RV 600S 28ohm            * L7□A020□ – 2pcs      * L7□A050□ – 4pcs            (Parallel Connection)      (Parallel Connection)            L7□A035□ – 3pcs      Note) I RV 600S 30ohm and 600S 28ohm have the            (Parallel Connection)      same external dimensions.</p>

**Note1)** L7 Series 100W~7.5kW has the internal basic braking resistor. If the machine requires short deceleration time frequently, refer to table above and apply the appropriate braking resistor.

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Pegasus Series





Options

# L7 SERIES SYSTEM

## Other Options

### ■ 400V Braking Resistor

\* Option braking resistors are selectable items for user's need.

Type	Product Type	Model Name (Note)	Applicable Drive	Specifications
Resistor	Braking Resistor	APCS-300R82	L7□B010□	 IRV 300W 82ohm
Resistor	Braking Resistor	APCS-600R140	L7□B020□ L7□B035□	 IRV 600W 140ohm
Resistor	Braking Resistor	APCS-600R75	L7□B075□	 IRV 600W 75ohm (3PCS Parallel connection)
Resistor	Braking Resistor	APC-2000R13R4	L7□B150□	 IRM 2000W 13.4ohm

**Note1)** L7 Series 100W~7.5kW has the internal basic braking resistor. If the machine requires short deceleration time frequently, refer to table above and apply the appropriate braking resistor.

## Servo Drive Option

### ■ Noise Filter

Type	Product Type	Model Name	Applicable Drive	Specifications
Resistor Filter	APCS-TB6-B010LBEI	L7□A 001□ L7□A 002□ L7□A 004□ L7□A 008□ L7□A 010□ L7□B 010□		
		APCS-TB6-B020NBDC	L7□B 020□ L7□B 035□	
		APCS-TB6-B030NBDC	L7□A 020□ L7□A 035□ L7□B 050□	
	APCS-TB6-B040AS	L7□A 050□ L7□B 075□		
		APCS-TB6-B060LAS	L7□B 150□	

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

# L7 SERIES SYSTEM

## Contents

### ■ Integrated Servo System

## PEGASUS Series

Integrated Servo System (EtherCAT)

- Servo Drive Designation \_ 110
- Product Feature \_ 112
- External Dimensions \_ 114




Integrated Servo System (EtherCAT)

# | PEGASUS Series



## ■ Servo Drive Designation



L7S Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

PEGASUS Series  
Options

# L7 SERIES SYSTEM

## PEGASUS Series

L7S Series

L7N Series

L7NH Series

L7P Series

S Series

F Series

MDM Series

Options

PEGASUS Series

### Characteristic

#### • Enhanced efficiency integrated servo system

- Cost effective from installation by integrated system of motor, encoder cable and drive
- Maximization for useful space when installed at limited and small space
- High effectiveness for application of multi axis because there is no limitation for space of installation

#### • Real-time control through EtherCAT

- High speed, Real-time capability and Synchronization mechanism
- Improved EtherCAT communication speed
- Supporting CoE, EoE and FoE

### Identifying the Part of PEGASUS Series



#### ① Input / Output Signal Connector (CN1)

- This Connector is for Sequence

Input / Output Signals

#### ② EtherCAT Communication Output Port (OUT)

#### ③ Status LED

- It Indicates the current state of Ether CAT Communication

#### ④ Power Connector (CN3)

#### ⑤ USB Connector (CN5, Mini B type)

- This Connector is to Communicate With a PC

#### ⑥ Node Address Setting Switch

- This Switch is to set the node address of the drive You can set the node addresses from 0 to 15

#### ⑦ EtherCAT Communication Input Port (IN)

#### ⑧ Safety Connector (CN2)

- This Connector connects Safety Devices

## Specifications of PEGASUS Series

### ■ Rated Values of Servo Drive

Rated values for servo drive	□40 50W	□40 100W	□60 100W	□60 200W	□60 300W
Continuous output current [Arms]	1.77	2.38	3.62	5	6.8
Maximum output current [Arms]	3.54	3.57	7.24	10	13.6
Input voltage	DC 48V ~ DC 60V				

### ■ Basic Specifications

Category		Details	
Use conditions	Control method	PWM controlled sine wave current driving method	
	Operating temperature / storage temperature	0~+40[°C] / -20~ +60[°C]	
	Operating humidity / storage humidity	Below 80% RH / Below 90% RH (no freeze or condensation)	
	Vibration-/impact-resistance	TBD	
	Degree of protection / degree of pollution	TBD	
	Altitude	1000 m or lower	
Performance	Other		To be free from electrostatic noise, strong electrolysis, or radiation.
	Speed variation	Load variation	At 0 to 100% load: ± 3% (at rated speed)
		Voltage variation	Rated voltage ± 10%: 0% (at rated speed)
		Temperature variation	25°C: ± 0.1% or less (at rated speed)
Input/output signal	Input signal		Input voltage range: DC 12 V – DC 30 V The 4-channel input signal can be assigned to 12 functions: POT, NOT, HOME, STOP, PCON, GAIN2, PCL, NCL, PROBE1, PROB2, EMG, and ARS1.
	Output signal		Rated voltage and current: DC 24 V ± 10%, 120 [mA] The 2-channel output signal can be assigned to 11 functions: BRAKE, ALARM, RDY, ZSPD, INPOS1, TLMT, VLMT, INSPD, WARN, TGON, and INPOS2.
Analog Monitor		Number of channels: 1 Output voltage range: ±4V Angular resolution: 12 bits Stabilization time: 15 us	
USB communication	Connecting device	PC or USB storage medium	
	Communication standard	Conform to the USB 2.0 Full Speed Standard.	
	Function	Firmware download, parameter setting, adjustment, auxiliary functions, and parameter copy function.	
Dynamic brake (three-phase short-circuit)		Activates when servo alarm, servo OFF, or Emergency stop (POT, NOT and EMG) is input.	
Protection functions		Overcurrent, overload, current limit, overheat, overvoltage, undervoltage, overspeed, encoder error, position follow error, etc.	
Auxiliary functions		Gain adjustment, alarm history, JOG drive, programmed JOG drive, etc.	
Safety functions	Input	STO1 and STO2	
	Compatible standard	TBD	

# L7 SERIES SYSTEM

## Specifications of PEGASUS Series

### EtherCAT Communication Specification

Category		Details
Communication standard	FoE	Firmware download
	EoE	Parameter setting, adjustment, auxiliary functions, and parameter copy through UDP.
	CoE	IEC 61158 Type12, IEC 61800-7 CiA 402 drive profile
Physical layer		100BASE-TX (IEEE802.3)
Connector		RJ45 x 2
Distance		Within 100 m between nodes
DC (Distributed Clock)		Sync by DC mode
LED Display		L/A0(Link/Act IN) L/A1(Link/Act OUT) RUN ERR
CiA402 drive Profile		Supports CSP, CSV, CST, PP, PV, PT, and HM Modes.

### Motor Specification


Model	Unit	SAR5A-8	SA01A-8	SB01A-6	SB02A-9	SB03A-9
Frame Size	[mm]	40	40	60	60	60
Rated Power	[W]	50	80	100	200	300
Rated Torque	[N m]	0.16	0.32	0.32	0.64	0.95
	[Kgf cm]	1.62	3.25	3.25	6.5	9.74
Rated Speed	[rpm]	3,000	2,400	3,000	3,000	3,000
Inertia	[g cm s <sup>2</sup> ]	0.02	0.0435	0.114	0.186	0.328
	[Kg m <sup>2</sup> × 10 <sup>-4</sup> ]	0.02	0.0426	0.116	0.182	0.321
Rated Voltage	[Vdc]	Input Power : 48VDC				
Encoder Type	-	Magnetic Encoder (12bit)				

**Note1)** SA01A-8 can be operated at 3000rpm(100w) with 60Vdc of input power( instead of 48Vdc)

## External Dimensions of PEGASUS Series


### ■ PEGA-AR5A

\* Unit [mm]



### ■ PEGA-A01A

\* Unit [mm]



L7S Series

L7N Series

L7P Series

S Series

F Series

MDM Series

Options


PEGASUS Series

# L7 SERIES SYSTEM

## External Dimensions of PEGASUS Series


### ■ PEGA-B01A

\*Unit [mm]



### ■ PEGA-B02A


\*Unit [mm]



## External Dimensions of PEGASUS Series


### ■ PEGA-B03A

\* Unit [mm]



### ■ Accessory Kit


#### CN1 : I/O Connector



51004-1100 (MOLEX)

Pin Number	Direction	Name	Signals	Descriptions
1	VCC	+24V	+24V INPUT	+24V Voc Input
2	Input	POT	Positive Over-Travel	
3	Input	NOT	Negative Over Travel	Limit Sensor Input
4	Input	HOME	Home Sensor	Home Sensor Input for Homing
5	Input	STOP	Stop Input	Stop Command Input
6	Output	BRAKE+	BRAKE	Output Brake Control Signal
7	Output	BRAKE-		
8	Output	ALARM+	Alarm Output	Servo Alarm Output
9	Output	ALARM-		
10	Output	MONITOR1	Analog Monitor	Analog Monitor Output(0V~5V)
11	GND	AGND	AGND(0V)	Analog Signal Ground


#### CN2 : Safe Torque Off Connector



43645-3 (MOLEX)

Pin Number	Name	Descriptions
1	HWBB1	Safe Torque Off(STO) Input signals
2	HWBB2	
3	COMMON	DC 24V GND

#### CN3 : Power Connector


MC\_1.5-3-STF-3.5  
(PHOENIX CONTACT)

Pin Number	Name	Descriptions
1	FG	Frame Ground
2	N(DC 0V)	DC 0V GND
3	VCC(DC 48V)	DC 48V Input

**MEMO**



**MEMO**



**MEMO**



**MEMO**





[www.lsmechapion.com](http://www.lsmechapion.com)



Safety Instructions

- For your safety, please read user's manual thoroughly before operating.
- Contact the nearest authorized service facility for examination, repair, or adjustment.
- Please contact qualified service technician when you need maintenance.  
Do not disassemble or repair by yourself!
- Any maintenance and inspection shall be performed by the personnel having expertise concerned.

## LS Mecapion Co., Ltd

### Head Office & Plant

(Hightech Industrial Park) 8-4, Hosandong-ro 12-9,  
Dalseo-Gu, Daegu, Korea 704-240  
T:+82-53-593-0066 F:+82-53-591-8614

### Kyungin Center

104-605, SK-Ventilum, Gasan-ro 166,  
Gupo, Gyeonggi-Do, Korea 435-775  
T:+82-31-436-0600 F:+82-31-436-0604

### China Factory

204-1, Xida Road, Meicun Industrial Center,  
Xinqu, Wuxi, Jiangsu, China  
T:+86-510-8295-3000 F:+86-510-8295-3019